STATE OF DELAWARE

DEPARTMENT OF TRANSPORTATION



PLANS AND SPECIFICATIONS FOR

CONTRACT NUMBER: T201600901 FEDERAL AID PROJECT NUMBER: ESTP-2015(31)

OPEN-END CONSTRUCTION SERVICES, SUSSEX COUNTY



RECOMMENDED:

Assistant Director

Project Development South

No. 8567

No. 8567

No. 8567

APPROVED:

Chief Engineer

Transportation Solutions

CONTRACT DESCRIPTION


The purpose of this contract is to construct road projects in accordance with applicable standards. The location of work is limited to sites within Sussex County. Individual locations will vary in their context from within existing roadway and on virgin ground.


The work activities include, but are not limited to, the following:


- Clearing and grubbing
- Excavation
- Grading
- Placing all materials for curbing, sidewalk and roadway construction
- Construction of both open and closed drainage systems
- Placement of erosion and sediment controls
- Maintenance of traffic
- Signing and striping
- Signal system, lighting work, ITMS
- Guardrail placement/replacement
- Site amenities
- Modular block wall and/or retaining wall


Several work sites for this contract have been identified and are listed below. The state reserves the right to add additional Tasks to this contract as additional locations become available. Note that sites are not limited to and not guaranteed for this contract.

- Task 1 HEP SC, US 113 at Ennis Road/North Street
- Task 2 HRRRP SC, US 13 at SR 30/Dorothy Road/Whitesville Road
- Task 3 HEP SC, US 113 at Millsboro Towne Square/1st Street









PROJECT NOTES

- 1. Construction of this contract shall be performed in accordance with the Delaware Department of Transportation Standard Specifications dated August 2001 (as amended by the Supplemental Specifications) and DelDOT Standard Construction Details, including all revisions up to the date of advertisement.
- 2. This is an open-end Task driven contract, with some known and other not yet determined locations, to make general improvements to roads, trails, or pedestrian/bicycle facilities located within the boundaries of Sussex County. The work shall be issued as the Engineer provides individual Tasks. The Delaware Department of Transportation (hereinafter referred to as the Department) reserves the right to prioritize, substitute, add, or delete locations at anytime during the contract term.
- 3. <u>Contract Term</u>: this contract shall be for a period of three (3) years from the date of initial "Notice to Proceed."
- 4. The location listing indicates estimated quantities for the original specified Tasks as well as probable items and quantities to be used on future Tasks. During the bidding period, any questions pertaining to locations shall be directed to Contract Administration. After the award, such questions shall be referred to Construction Group 3.
- 5. Depending on fund availability, the Department reserves the right to increase or decrease the quantities of the items specified in this contract. Such additions or deletions shall not be cause for an increase or decrease in any contract unit bid prices.
- 6. The work will be scheduled by issuance of Tasks to the Contractor from the Department. Each Task will represent an independent construction location. Tasks will be issued upon design completion and receipt of necessary statements & permits for the individual sites. It is anticipated that each individual Task will obtain the necessary plan approvals prior to issuance. Field personnel representing the Department are not authorized to revoke, alter, or waive any requirements of the plans or specifications.
- 7. The scope of each Task will be defined by a fully engineered set of construction drawings. In addition to the drawings and notes the estimated quantities, property owner notification requirements, allowable time to perform the work and any additional specifications and construction guidance needed for the specific Task will also be provided.
- 8. Payment will be monthly for the completed pay estimates as outlined in Section 109.07.
- 9. Prosecution and progress of work:

DELAWARE DEPARTMENT OF TRANSPORTATION

CONTRACT NO: T201600901

OPEN-END CONSTRUCTION SERVICES, SUSSEX COUNTY

- a. The Contractor shall commence work indicated on the Task no later than thirty (30) days after issuance of Notice to Proceed for each Task unless the required materials are not available. Non-availability of materials shall be verified by at least three (3) independent sources, with the verification formally presented in writing by the Contractor to the Department within four (4) working days of being issued a new Task.
- b. Issuance of each Task does not constitute authorization to begin the work described on the Task. The Contractor shall not commence any work on a Task until a Notice to Proceed for the Task has been issued by the Department.
- c. If work does not commence, or non-availability of materials is not presented in the allotted time, default or termination of the Contract may occur as provided in the Standard Specifications. If there is a verified non-availability of materials, time charges shall commence on the first (1st) calendar day following the delivery date of said materials.
- d. Failure to complete the Task in the specified time shall subject the Contractor to liquidated damages as outlined in Subsection 108.08 of the Standard Specifications. Each Task is to be completed within the specified time as specified in the Notice to Proceed for Each location. Additional contract time may be added to any Task as needed at the discretion of the Engineer, provided an extension of time is submitted per Subsection 108.07 of the Standard Specifications. If the work on a specific Task is not completed within the assigned time, liquidated damages will be assessed in accordance with Subsection 108.09 of the Standard Specifications based on the total value of that particular Task.
- e. The Contractor **may** have up to three (3) active Tasks at a time until all assigned work has been substantially completed. The Contractor is required to have enough resources to work on all Tasks issued. Each Task start date shall be determined by the Engineer.
- 10. A semi-final inspection will be performed on each Task after the Department determines that substantial completion has been achieved. All work must meet the Department's specifications and the requirements as outlined in these notes. The Contractor must complete all punchlist work within thirty (30) calendar days of the issuance of the semi-final inspection punch list provided, unless the Engineer approves otherwise.
 - All work is subject to a final inspection upon each Task completion of the semi-final punch list. The Contractor will have forty-five (45) days to complete all punch list work from the final inspection letter date, unless the Engineer approves otherwise.
- 11. All additional work shall be performed by contract unit prices. In the case where contract prices are not available, prices are to be negotiated or performed by force account procedures as outlined in the Standard Specifications.
- 12. Proper disposal of construction related wastes shall be the sole responsibility of the Contractor, and

shall be performed in accordance with all applicable state regulations.

- 13. Trash, rubbish, debris or brush that hampers repair / maintenance work in this contract (as determined by the Engineer) shall be removed within the project limits, and shall be incidental to Pay Item 763000 (Initial Expense).
- 14. Clearing and grubbing of trees and shrubs less than six (6) inches in diameter shall be incidental to the Item 202000 Excavation and Embankment. Grubbing activities performed in wetland areas require environmental permit approvals. Other clearing and grubbing will be negotiated or performed by Force Account procedures.
- 15. Grass and soil areas that have been damaged by the Contractor's equipment during this contract shall be restored with topsoil, seed and mulch at the Contractor's expense, and in accordance with the requirements of Section 908 Soil Stabilization Practices.
- 16. The Contractor shall not trespass on private property unless the Department has acquired a "Temporary Trespass Agreement" from the property owner. If the work is within an easement, permanent or temporary, the work shall not begin until the adjacent property owners (if affected) have been notified. Prior to starting work on temporary or permanent easements, the Contractor shall notify affected property owners of the proposed work dates. The Contractor shall provide all residents who live adjacent to the work zone with a minimum seven (7) days prior written notice for the start of construction work unless directed otherwise in the site specific documentation. This notification shall include the scope of work, working hours, anticipated start and completion dates, Contractor name and address, and DelDOT contact name and numbers. Failure to give proper notice will result in a suspension of work requiring notice, until proper notice is provided.
- 17. No environmental permits are required for this work provided no jurisdictional wetlands or waters are impacted. If there is any question as to whether or not a water or wetland is jurisdictional or if permits are required, contact South Construction who will coordinate with the DelDOT Environmental Section at 302-760-2264.
- 18. A Notice to Proceed for a specific task will not be issued until the administration section receives any required clearance or permits from the **DelDOT Environmental Studies Office**. Any special conditions may be part of an assigned Task, such as environmental clearance for stockpile area.
- 19. Underground utilities may be present at all locations. Therefore, all standard practices and procedures regarding utilities shall be followed, see Subsection 105.09 of the Standard Specifications. The Contractor shall contact Miss Utility of Delaware prior to starting each task. The Contractor is responsible for the support and protection of all utilities when excavating. The Contractor is responsible for ensuring proper clearances, including safety clearances, from overhead utilities for construction equipment. The Contractor is advised to check the site for access purposes for his equipment.

- 20. Any known utility relocations will be identified in the plans. Should any unidentified conflicts be encountered during construction requiring adjustment and/or relocation of the agencies' existing facilities, the necessary relocation work shall be accomplished by the respective agencies' forces, as directed by the District Engineer. Any adjustments and/or relocations of municipally owned facilities shall be done by the State's contractor in accordance with the respective agencies' standard specifications as directed by the District Engineer.
- 21. All work shall be performed within the existing state Right-Of-Way or easement areas unless otherwise noted on the Task. Right-of-way information shall be available upon request from the DelDOT Engineer. Should the need occur to trespass onto private property; it will be the responsibility of the project manager to secure such trespass needs. Should the need occur to trespass onto railroad property, including the highway-rail crossing; it will be the responsibility of the Project Manager to contact the railroad chief engineer and obtain written authorization before entering.
- 22. Seasonal restrictions may exist at select locations to be performed under this Contract. The Department will notify the Contractor upon issuance of a new Task of any restrictions.
- 23. At the end of each work day, the Contractor shall correct all pavement edge drop offs in accordance with the current Delaware Manual on Uniform Traffic Control Devices. Any corrective measures taken by the contractor shall be incidental to the MOT items.
- 24. All Portland Cement Concrete must be received from an approved production plant unless otherwise approved by the Engineer. Only calibrated volumetric concrete trucks will be permitted to provide on-site mixtures. This pertains to both work occurring during normal working hours and nighttime restricted work.
- 25. The Construction Project Manager shall be responsible for coordinating with the Traffic Section relating to any impacts to Traffic Section facilities (including but not limited to traffic loops, junction wells etc.) at least 4 weeks in advance of the start of the activity. Prior to initiating any work on this contract (or sites), the Project Manager shall be responsible for preparing and submitting for approval of the Safety Section, a Maintenance of Traffic Plan. Sufficient time shall be provided for the review and approval of the plan. The Maintenance of Traffic Plan shall include proposed time restrictions on the closure of travel lanes subject to the approval of the Safety Section.
- 26. The Project Manager is responsible for ensuring any required documents and analysis as part of the adopted Work Zone Safety and Mobility Procedures and Guidelines has been completed prior to any work starting on this contract.


MAINTENANCE OF TRAFFIC PROJECT NOTES

- 1. The Contractor and all others shall perform all work in a manner that shall ensure the least practical obstruction to all road users, including vehicular, pedestrian, and bicycle traffic, and shall be consistent with safety standards, and shall comply with the requirements specified in the latest version of the "Delaware Manual On Uniform Traffic Control Devices" (MUTCD) Part 6, herein referred to as the "Traffic Control Manual" (including revisions in effect at the time of advertisement for bids).
- 2. The Contractor and all others shall review and follow project specific maintenance of traffic (MOT) and detour plans. If there is any conflict between the project specific mot plans and general notes in this section, the project specific mot plans will supersede. If the Contractor should wish to deviate from the proposed mot and detour plans then he shall seek approval from the engineer. No MOT or detour changes will be allowed without written approval from the Engineer prior starting any task.
- 3. No lane closures will be permitted on holidays or holiday weekdays, unless approved by the Engineer. This requirement applies to all roads impacted in this contract.
- 4. No lane closures will be permitted unless applicable work activity is taking place.
- 5. The Contractor shall prepare and submit a Traffic Control Plan, including the necessary NCHRP 350 certificate for all devices that will be utilized for each location prior to the pre-construction meeting, for approval ten (10) working days prior to the start of assigned tasks, and for each project site. Written approval for the Contractor's Traffic Control Plan and NCHRP 350 submittals must be received from the Department Safety Officer prior to the start of work at each and every location. Costs for preparation of traffic control plans for each site shall be included in the bid price for Pay Item 743000 (Maintenance of Traffic). The Traffic Control Plan must clearly indicate orientation of traffic control devices to be used for each site. The plan must be approved by DelDOT Safety Officer and DelDOT Engineer prior to commencement of work at each site.
- 6. For locations requiring a flagging operation, the flagger will be paid per Items 743052 & 743064 (Sussex County), respectively.
- 7. All flaggers utilized by the Contractor for this Contract shall be American Traffic Safety Services Association (ATSSA) certified. All flaggers shall have their certification cards with them while working. Absence of a certification card will be justification for flagger dismissal from the site and corresponding suspension of work. All construction and Contractor vehicles and equipment shall be equipped with an operating roof mounted amber flashing strobe light. All workers shall wear a retro-reflective ANSI Class 2 or equivalent safety vest while they are within the right-of-way or adjacent to it.

- 8. The Contractor shall have an ATSSA certified supervisor assigned to this project. The Contractor's general superintendent for this project or another ATSSA certified member of the Contractor's project staff may be the ATSSA supervisor.
- 9. If required, the DelDOT safety section must be notified a minimum of three (3) weeks in advance of the work in order to determine the type of and prepare a Transportation Management Plan (TMP) for the location. Should a Type "B" TMP be required, all restrictions given in the TMP will be followed.
- 10. Any deviation from the MOT plans must be approved by the DelDOT Project Manager and Safety Officer. If a Contractor requests a detour, the Contractor shall submit a proposed detour plan to the DelDOT Project Manager and Safety Officer for approval. Payment for detour plan preparation shall be included in the bid price for Item 743000 (Maintenance Of Traffic). The Contractor shall also coordinate the closure with the Department. The Department will coordinate with the safety section and be responsible for the necessary emergency notifications. The detour route requires approval by the Department prior to closure. The Contractor shall be responsible for furnishing and maintaining the maintenance of traffic apparatus at the closure (i.e. Type III Barricade, Road Closed Signs, etc.) and all advance-warning signs. The Contractor shall be responsible for placement of detour trailblazers. Payment for detour trailblazers shall be under Item 743024, Temporary Warning Signs & Plaques.
- 11. If the construction activity results in a vertical difference or drop-off along, adjacent to or across a travel way, the Contractor shall eliminate or remedy the hazard by the methods detailed in Section (6G.20, table 6G-1) of the Traffic Control Manual as directed by the Engineer. The construction safety fence, tie wire, etc. shall be incidental to the work it protects. At the end of each workday, the Contractor shall correct all pavement edge drop-offs in accordance with the Delaware MUTCD. This corrective work shall be accomplished with Temporary Road Material (TRM) unless otherwise noted in the plans. All ruts and potholes shall be filled with TRM as soon as possible, but no later than by the end of each workday. Placement of TRM shall be completed in accordance with the applicable sections of the Delaware Standard Specifications. If temporary elimination of a drop-off hazard cannot be accomplished, then the area shall be properly marked and protected with additional temporary barriers, barricades, warning signs, etc. as required by the Delaware MUTCD, and as approved by the Engineer. Payment for all work described in this Project Note shall be incidental to applicable maintenance of traffic pay items in the contract. There shall be no additional compensation provided to the Contractor for this work.
- 12. All traffic control devices shall be provided and placed in accordance with the Delaware MUTCD (Traffic Control Manual).
- 13. Payment for relocation and re-positioning of traffic control devices shall be incidental to the respective unit price pay items for maintenance of traffic included in this Contract. There shall be no additional compensation for relocation or re-positioning of traffic control devices.

- 14. The safety measures outlined within this Contract and the Delaware MUTCD are not necessarily sufficient in every instance to guarantee the protection of the traveling public or persons working on this project. Therefore, the provisions of this Contract do no relieve the Contractor of the sole responsibility for the safety of all persons working within or traveling through the work zone throughout the duration of the project. The Contractor shall implement any additional safety measures that are not expressly required by the Contract and are necessary to ensure the safety of all persons. The Contractor shall submit to the Engineer justification for deviations from the Traffic Control Plan or Transportation Management Plan. Final approval of the deviations or additions shall rest with the Engineer. All costs for this work shall be incidental to the applicable maintenance of traffic pay items as listed in the original Contract.
- 15. The Department reserves the right to stop the Contractor's operations, if in the opinion of the Engineer the Contractor's operations are not in compliance with the Delaware MUTCD, the specifications, or the plans. The Department also reserves the right to stop the Contractor's operations if the Engineer deems the operation unsafe.
- 16. The Department will not make payment to the Contractor for any and all temporary traffic control devices where the Contractor sets up temporary traffic control to perform work, but fails to perform any work.
- 17. If the Contractor does not complete the Contract work within the contract completion time as listed on the Task (including approved time extensions), the Contractor shall be responsible for providing the necessary temporary traffic control devices that are required to complete any remaining work. The cost of such temporary traffic control shall be borne by the Contractor. No additional payment will be made to the Contractor to maintain traffic in accordance with the Delaware MUTCD, specification, or these project notes. Temporary traffic control items shall include, but not be limited to, warning signs, barricades, plastic drums, P.C.C. safety barrier, flaggers, traffic officers, arrow panels, message boards, portable light assemblies, and portable impact attenuators.
- 18. All equipment shall be removed from the job sites on a daily basis, except when allowed by the DelDOT approved Traffic Safety Plan, or as approved by the Engineer.
- 19. All required maintenance of traffic warning signs will be paid under Item 743024, Temporary Warning Signs & Plaques, as determined by the duration of construction. All temporary traffic control devices used on all highways open to the public in this state shall be in new or refurbished condition and shall be crashworthy in accordance with the National Cooperative Highway Research Program (NCHRP) Report 350 and the memorandum issued August 28, 1998 by the USDOT Federal Highway Administration Information: Crash Tested Work Zone Traffic Control Devices. It is the requirement of the Department that such certification be submitted for traffic control devices used on all projects, not just those involving the National Highway System.
- 20. No separate payment shall be made for the use of traffic cones. Traffic cones and/or work associated with their use, such as set up, removal, cleaning, etc., shall be incidental to the work for which they protect. Cones shall not be used for traffic control during any night time operations.

- 21. A truck mounted attenuator; Type I (Item 743009) and or Type II (Item 743010) shall be required on roads for shoulder work, travel lane work and for other operations as outlined in the DelDOT Traffic Control Manual, or as directed by the Engineer.
- 22. Any erroneous pavement markings will not be paid for and shall be corrected immediately at the Contractor's expense. Erroneous markings or shadows that exceed one (1) inch in width shall be removed by either sand or water blasting. No other removal methods will be allowed. A flat black paint or driveway sealer shall be applied in the area of the removed marking to mask the repair. Any damage to the pavement caused by removal of erroneous markings shall be repaired / replaced to the satisfaction of the Engineer at the Contractor's expense.
- 23. At the end of each day's operation and before traffic is returned to unrestricted roadway use, temporary striping shall be utilized at locations that require permanent striping per the latest version of the permanent marking section of the Traffic Control Manual. Temporary pavement markings shall be paid at the applicable contract unit price.
- 24. Pedestrian Maintenance of Traffic: this work shall consist of providing and maintaining an accessible pedestrian route throughout the project's limits in accordance with the Americans With Disabilities Act Of 1990 (ADA) Title II, Paragraph 35.130. The Contractor shall be required to review each curb ramp location and submit the appropriate maintenance of traffic detail and devices to the Engineer for each location at least two (2) weeks before construction for review, comment, and approval. The following considerations shall be taken into account when addressing accessible pedestrian maintenance of traffic:
 - a. All pedestrians, including persons with disabilities, shall be provided with a reasonably safe, convenient and accessible path that replicates, as much as practicable, the existing pedestrian facilities.
 - b. Maintain access to all businesses and residences at all times.
 - c. Provide pedestrian access through or around the work zone. If a detour is chosen the Contractor must submit the detour route to the Engineer for review and approval. The detour route must meet or exceed the current conditions.
 - d. Work should be phased so that all areas of an intersection/sidewalk path are not under construction at the same time unless a clear pedestrian path is provided and identified.
 - e. Traffic control devices and other construction materials and features shall not intrude into the usable width of the sidewalk, temporary pathway or other pedestrian facility.
 - f. Signs and other devices mounted lower than 7 feet above the temporary pedestrian pathway shall not project more than 4 inches into accessible pedestrian route.
 - g. A smooth, continuous hard surface shall be provided throughout the entire length and width of the pedestrian route throughout construction. There shall be no curbs or vertical elevation changes greater than ¼ inch in grade or terrain that could cause tripping or be a barrier to wheelchair use.



YEAR: 2040

YEAR: 2040

NAME & DATE

BRIAN MCC

COSTER

No. 8567

SOONAL ENG

SEAL

EXISTING SYMBOLS

	DRAINAGE
—— aa ———	DITCH OR STREAM CENTERLINE
	DIRECTIONAL STREAM FLOW ARROW
C.B. D.I.	DRAINAGE INLET
J.B. DRAINAGE JUNCTION BOX	
DRAINAGE MANHOLE	
SIZE/TYPE LABEL DRAINAGE PIPE AND FLOW ARROW	
DRAINAGE PIPE HEADWALL	
	RIPRAP - AREA FEATURE
<i>○</i> ‰	RIPRAP - LINEAR FEATURE

	711 1771 21112711 71271 9112
MANN	IADE ROADSIDE FEATURES
0	BOLLARD - STEEL POLE
\boxtimes	BOLLARD - WOOD POST
(TYPE LABEL)	CURB
(TYPE LABEL)	CURB AND GUTTER
—-х	FENCE - CHAINLINK OR STRANDED
—-a——	FENCE - STOCKADE OR SPLIT RAIL
FP	FLAG POLE
_n	GUARDRAIL - STEEL BEAM
_0	GUARDRAIL - WIRE ROPE
LAMP ©	LAMP AND POST - RESIDENTIAL
МВ П	MAILBOX
PM ®	PARKING METER AND POST
	PAVEMENT - FLEXIBLE
	PAVEMENT - RIGID
	PILE - BRIDGE
0	PILLAR OR MISCELLANEOUS POST
4	TRAFFIC SIGN AND POST
	WALL - BRICK OR BLOCK
9000	WALL - STONE

NATURAL ROADSIDE FEATURES		
	GRASS LAWN	
acacacaca	HEDGEROW OR THICKET	
	MARSH BOUNDARY LINE	
*	TREE - CONIFEROUS	
	TREE - DECIDUOUS	
£	TREE STUMP	
©	SHRUBBERY	
WL	DELINEATED WETLAND BOUNDARY LINE	
	WOODS LINE BOUNDARY	

	RIGHT-OF-WAY SYMBOLS
C.M.	PROPERTY MARKER - CONCRETE MON.
I.P.	PROPERTY MARKER - IRON PIPE
100+00	HISTORIC RIGHT-OF-WAY BASELINE
	EXISTING RIGHT-OF-WAY
—— p ——	EXISTING PROPERTY LINE
EASEMENT TYPE	EXISTING EASEMENT
——— DA ———	EXISTING DENIAL OF ACCESS
—— R/W-DA ——	EXISTING R/W & DENIAL OF ACCESS

SURVEY CONTROL & MONUMENTATION SURVEY BENCHMARK LOCATION T.P. SURVEY TIE POINT LOCATION

Δ	SURVEY TRAVERSE POINT	
0	POINT OF CURVATURE OR TANGENCY	
0	POINT OF INTERSECTING TANGENTS	
	UTILITY	
•	SOIL BORING LOCATION	
•	UTILITY TEST HOLE LOCATION	
ī	CABLE TV DISTRIBUTION BOX	
(E)	ELECTRIC MANHOLE	
EM	ELECTRIC METER	
E	ELECTRIC TRANSFORMER	
	POLE MOUNTED LUMINAIRE	
©	GAS MANHOLE	
G _. M.	GAS METER	
G.V.	GAS VALVE	
G.P.	GAS PUMP - SERVICE STATION	
<u> </u>	RAILROAD TRACKS	
\$	SANITARY SEWER MANHOLE	
S.V.	SANITARY SEWER VALVE	
VENT	SANITARY SEWER VENT OR CLEANOUT	
[SEPTIC DRAIN FIELD	
B	TELEPHONE BOOTH	
T)	TELEPHONE MANHOLE	
T	TELEPHONE TEST POINT	
J.W.	TRAFFIC - CONDUIT JUNCTION WELL	
©	TRAFFIC - LIGHT POLE AND BASE	
©	TRAFFIC - PEDESTRIAN POLE & BASE	
9	TRAFFIC - SIGNAL CABINET & BASE	
⊗	TRAFFIC - SIGNAL POLE AND BASE	
U	UTILITY BOX	
0→	UTILITY POLE GUY WIRE ANCHOR	
×	UTILITY POLE	
F.H.	WATER - FIRE HYDRANT	
W _. M.	WATER METER	
w.v.	WATER VALVE	
WELL	WELL HEAD	
?	MANHOLE - UNDETERMINED OWNER	

UTILIT	Y COMPANY FAC <mark>ILITIE</mark> S
CU-G	CHESAPEAKE UTILITY - GAS
EX-SIG	DELDOT SIGNAL CO <mark>nduit</mark>
VER-C	VERIZON

PROPOSED SYMBOLS

×——BFS——× | BIOFILTRATION SWALE

100÷00

———*CSF*———

—— *CZ* ——

 \circ

X X X

_____ R/W _____

100+00

BRICK PATTERNED SURFACE

GUARDRAIL END TREATMENT, TYPE 1

GUARDRAIL END TREATMENT, TYPE 2

GUARDRAIL END TREATMENT, TYPE 3

PAVEMENT PATCH

-----LOC----- LIMIT OF CONSTRUCTION

MAILBOX

MANHOLE

PAVEMENT REMOVAL - TOPSOIL, SEED AND MULCH

UNDERDRAIN

---- PE--- PROPOSED PERMANENT EASEMENT

UNDERDRAIN OUTLET

PIPE & DIRECTIONAL FLOW ARROW

RIGHT-OF-WAY SYMBOLS

PROPOSED DENIAL OF ACCESS

PROPOSED RIGHT-OF-WAY

--- TCE --- TEMPORARY CONSTRUCTION EASEMENT

NOT TO SCALE

PROPOSED RIGHT-OF-WAY MONUMENT

PROPOSED RIGHT-OF-WAY BASELINE

P.C.C. SIDEWALK -USE ITEM 705005 - P.C.C. SIDEWALK, 8" USE ITEM 705530 - TRIANGULAR

CHANNELIZING ISLANDS

_ i i i i i i i i GUARDRAIL, TYPE 2

CONSTRUCTION		IDENTIFIERS
CONCRETE SAFETY BARRIER - PERMANENT	(A)	ADJUST BY CONTRACTOR
BIOFILTRATION SWALE	Â	ADJUST BY OTHERS
BRICK PATTERNED SURFACE	B	CONCRETE SAFETY BARRIER
BUTT JOINT	©	CURB OR CURB & GUTTER
CONSTRUCTION BASELINE	<u>CJB</u>	CONVERT TO JUNCTION BOX
CONSTRUCTION SAFETY FENCE	<u>CM</u>	CONVERT TO DRAINAGE MANHOLE
CURB, TYPE 1 & TYPE 3	Ĉ _O	CURB OPENING
CURB, TYPE 2	<u>CR</u>	CURB RAMP / TYPE
CURB & G <mark>UTTE</mark> R, TYPE 1	(CR-N)	CURB RAMP / TYPE - WITHOUT SIDEWALK SURFACE DETECTABLE WARNING SYSTEM
CURB & GUTTER, TYPE 2	(S)	CONSTRUCTION SAFETY FENCE
CURB & GUTTER, TYPE 3	(a)	DRAINAGE INLET
CURB & GUTTER, TYPE 4	(DND)	DO NOT DISTURB
CURB OPENING	€D .	ENERGY DISSIPATOR
CLEAR ZONE	(F)	FENCE
DRAINAGE INLET	(ES)	FLARED END SECTION
DITCH	FFC	FILL WITH FLOWABLE FILL
FENCE - METAL		FILTRATION STRUCTURE
FENCE - WOOD	<u>©R</u>	GUARDRAIL
FLARED END SECTION	<i>JB</i>	JUNCTION BOX
GUARDRAIL, TYPE 1	MH)	MANHOLE
GUARDRAIL, TYPE 2	<u> </u>	MONUMENT - RIGHT-OF-WAY
GUARDRAIL, TYPE 3	P	PIPE
GUARDRAIL END ANCHORAGE	R C	RELOCATE BY CONTRACTOR
GUARDRAIL END TREATMENT, TYPE 1	R O	RELOCATE BY OTHERS
GUARDRAIL END TREATMENT, TYPE 2	RMC	REMOVE BY CONTRACTOR
GUARDRAIL END TREATMENT, TYPE 3	RM	REMOVE BY OTHERS
IMPACT ATTENUATOR		UNDERDRAIN / LENGTH
JUNCTION BOX - DRAINAGE		UN <mark>DERD</mark> RAIN OUTLET PIPE
LATERAL OFFSET		

LANDSCAPING		
(IS)	LANDSCAPE PLANTINGS	
	SHRUBBERY	
\otimes	CONIFEROUS TREE	
\odot	DECIDUOUS TREE	

TRAFFIC		
ITMS-CON	ITMS CONDUIT	
SIG-CON	SIGNAL CONDUIT	
•	CONDUIT JUNCTION WELL	
	LUMINAIRE	
→	PAVEMENT MARKINGS	
	PAVEMENT STRIPING	
	TRAFFIC SIGN	

PAVEMENT SECTION(S)

8" GABC, TYPE B - ITEM 302007

RECONSTRUCTED PAVEMENT 2" BITUMINOUS CONCRETE, TYPE C, 160 GYRATIONS, PG 70-22, (NON-CARBONATE STONE) - ITEM 401830 3" BITUMINOUS CONCRETE, TYPE B, 160 GYRATIONS, PG 70-22 - ITEM 401813 S" BITUMINOUS CONCRETE BASE COURSE, 160 GYRATIONS, PG 64-22 - ITEM 401819

	DECIDUOUS TREE
	TRAFFIC
—— ITMS-CON ——	ITMS CONDUIT
SIG-CON	SIGNAL CONDUIT
	CONDUIT JUNCTION WELL
	LUMINAIRE
→	PAVEMENT MARKINGS
	PAVEMENT STRIPING
•	TRAFFIC SIGN

DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

TASK 1 – HEP SC, US 113 AT ENNIS ROAD/NORTH STREET

CONTRACT	BRIDGE NO.	NA	
T201600901	DECIGNED DV:	A N I N 4	
COUNTY	DESIGNED BY: ANM		
SUSSEX	CHECKED BY:	JLC	

GENERAL NOTES

1. THIS PROJECT IS TO BE CONSTRUCTED IN ACCORDANCE WITH THE DELAWARE DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS", DATED AUGUST 2001 AND THE DELAWARE DEPARTMENT OF TRANSPORTATION "STANDARD CONSTRUCTION DETAILS", DATED 2001, INCLUDING ALL REVISIONS UP TO THE DATE OF ADVERTISEMENT.

2.		
∠.	EROSION POTENTIAL FOR THIS PROJECT	CONTRACTOR ESC SUPERVISOR REQUIREMENT
	() INSIGNIFICANT	NONE
	(X) MINOR	CONTRACTOR TRAINING PROGRAM, AS DEFINED IN SECTION 6.2 OF THE DELAWARE SEDIMENT AND STORMWATER REGULATIONS.
	() MEDIUM	CONTRACTOR TRAINING PROGRAM, AS DEFINED IN SECTION 6.2 OF THE DELAWARE SEDIMENT AND STORMWATER REGULATIONS.
	() MAJOR	CERTIFIED CONSTRUCTION REVIEWER (CCR), AS DEFINED IN SECTION 6.3 OF THE DELAWARE SEDIMENT AND STORMWATER REGULATIONS.

3. ELECTRONIC PROJECT FILES THAT WILL BE MADE AVAILABLE TO THE AWARDED CONTRACTOR, INCLUDE:

()	NONE
(X)	ASCII DATA FILES WITH COORDINATES AND ELEVATIONS FOR PROPOSED POINTS AS SELECTED BY THE ENGINEER.
(X)	ALL PLAN SHEETS, IN PDF FORMAT.
()	EXISTING DIGITAL TERRAIN MODEL, IN .DTM FILE FORMAT, COMPATIBLE WITH SOFTWARE CURRENTLY USED BY DELDOT.
()	PROPOSED DIGITAL TERRAIN MODEL, IN .DTM FILE FORMAT <mark>, COMP</mark> ATIBLE WITH SOFTWA <mark>RE CU</mark> RRENTLY U <mark>SED</mark> BY DELDOT.
()	DESIGN FILE, IN .DGN FILE FORMAT, CONTAINING ONLY THE P <mark>ROPOSED 3D TRIANGLES O</mark> F THE PROPOS <mark>ED DI</mark> GITAL TERRAIN MODEL (DTM).

NOTE: THE DOCUMENT ENTITLED "RELEASE FOR DELIVERY OF DOCUMENTS IN ELECTRONIC FORM TO A CONTRACTOR" MUST BE SIGNED BY ALL PARTIES PRIOR TO THE DELIVERY OF ANY ELECTRONIC PROJECT FILES.

4. PROJECT FILES THAT WILL BE MADE AVAILABLE TO THE CONTRACTOR, INCLUDE:

()	CROSS SECTIONS (WILL BE MADE AVAILABLE TO THE AWARDED CONTRACTOR)
()	RIGHT-OF-WAY PLANS (WILL BE MADE AVAILABLE TO THE AWARDED CONTRACTOR)

5. AMERICAN TRAFFIC SAFETY SERVICES ASSOCIATION (ATSSA) CERTIFIED TRAFFIC CONTROL SUPERVISOR REQUIREMENT FOR THIS PROJECT.

()	THE CONTRACTOR SHALL NOT BE REQUIRED TO HAVE AN ATSSA SUPE <mark>RVISOR</mark> ASSIGNED TO THIS PROJECT.
(X)	THE CONTRACTOR SHALL HAVE AN ATSSA SUPERVISOR ASSIGNED TO THIS PROJECT. THE CONTRACTOR'S GENERAL SUPERINTENDENT FOR THIS PROJECT OR ANOTHER ATSSA CERTIFIED MEMBER OF THE CONTRACTOR'S PROJECT STAFF MAY BE THE ATSSA SUPERVISOR. PAYMENT FOR ATSSA SUPERVISOR IS INCIDENTAL TO ITEM 743000.
()	THE CONTRACTOR SHALL HAVE AN ATSSA SUPERVISOR ASSIGNED TO THIS PROJECT. THE ATSSA SUPERVISOR'S SOLE JOB SHALL BE SUPERVISION OF THE INSTALLATION, OPERATION AND MAINTENANCE OF TRAFFIC CONTROL DEVICES FOR THIS PROJECT. THE CONTRACTOR'S GENERAL SUPERINTENDENT FOR THIS PROJECT SHALL NOT BE THE ATSSA SUPERVISOR. PAYMENT FOR ATSSA SUPERVISOR SHALL BE PAID FOR UNDER ITEM 743031.

- 6. THE DISTURBED AREA FOR THIS PROJECT IS 1.85 ACRES.
- THE SEDIMENT AND STORMWATER MANAGEMENT PLANS HAVE BEEN APPROVED BY DELDOT'S STORMWATER ENGINEER UNDER DELDOT'S DELEGATED AUTHORITY. THE SEDIMENT AND STORMWATER MANAGEMENT PLANS ARE VALID FOR A THREE YEAR PERIOD, BEGINNING ON THE DATE THE STORMWATER ENGINEER SIGNED THE CONSTRUCTION TITLE SHEET. IF THE FINAL ACCEPTANCE OF THE PROJECT IS ANTICIPATED TO EXTEND BEYOND THE THREE YEARS, THE CONTRACTOR WILL INFORM THE ENGINEER THREE MONTHS PRIOR TO THE EXPIRATION OF THE APPROVED SEDIMENT AND STORMWATER MANAGEMENT PLANS. THE STORMWATER ENGINEER WILL REVIEW THE CURRENT SEDIMENT AND STORMWATER MANAGEMENT PLAN AND ISSUE AN EXTENSION WITH ANY APPROPRIATE MODIFICATIONS.

PROJECT NOTES

SECTION 100

1. ANY DAMAGE TO ITEMS NOTED TO BE RELOCATED OR RESET BY THE CONTRACTOR, AT THE DISCRETION OF THE ENGINEER, SHALL BE REPAIRED AND/OR REPLACED IN KIND AT THE CONTRACTOR'S EXPENSE.

SECTION 200

- 2. THE CONTRACTOR SHALL REMOVE AND RESET ALL MAILBOXES TO MAINTAIN MAIL SERVICE AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL RELOCATE MAILBOXES AS REQUIRED BY THE PROPOSED GEOMETRICS AND AS DIRECTED BY THE ENGINEER. WHEN RELOCATING MAILBOXES IN CURBED SECTIONS, THE FACE OF THE MAILBOX SHALL BE FLUSH WITH THE BACK EDGE OF CURB. WHEN RELOCATING MAILBOXES IN OPEN SECTIONS, THE FACE OF THE MAILBOX SHALL SET BACK 8 INCHES FROM THE EDGE OF THE PAVED SHOULDER. THE BOTTOM OF THE MAILBOX SHALL BE SET 46 INCHES ABOVE THE ROADWAY SURFACE. MAILBOXES LOCATED AT DRIVEWAY ENTRANCES SHALL BE PLACED ON THE FAR SIDE OF THE DRIVEWAY IN THE DIRECTION OF TRAVEL. POSTS BEING RESET IN CONCRETE SIDEWALK SHALL BE PLACED IN AN APPROPRIATE SIZE PVC SLEEVE. COST FOR ALL WORK AND MATERIALS SHALL BE PAID UNDER ITEM 202000 EXCAVATION AND EMBANKMENT.
- 3. THE ENGINEER MAY REQUIRE THE CONTRACTOR TO EXCAVATE TEST PITS ALONG PROPOSED DRAINAGE RUNS, AT POINTS OF POSSIBLE UTILITY CONFLICTS, TO DETERMINE IF A CONFLICT EXISTS. ANY CONFLICTS SHALL BE COORDINATED BY THE CONTRACTOR, WITH THE ENGINEER AND THE UTILITY COMPANY INVOLVED. THE ENGINEER SHALL ULTIMATELY DETERMINE THE SOLUTION TO THE UTILITY CONFLICT. TEST HOLES SHALL BE MEASURED AND PAID FOR IN ACCORDANCE WITH ITEM 202000-EXCAVATION AND EMBANKMENT, BUT ONLY TO THE ACTUAL DEPTH EXCAVATED.

SECTION 300

- 4. A. THE CONTRACTOR MAY ELECT TO USE ANY OF THE FOLLOWING MATERIALS TO MEET THE REQUIREMENTS OF ITEM 302007

 GRADED AGGREGATE BASE COURSE, TYPE 'B':
 - a. CRUSHED STONE (PER STANDARD SPECIFICATION 821)
 - b. CRUSHED CONCRETE (PER STANDARD SPECIFICATION 821)
 - c. HOT-MIX MILLINGS (PER SPECIAL PROVISION 302514 MILLED HOT-MIX BASE COURSE)

THE CONTRACTOR WILL NOT BE ALLOWED TO MIX DIFFERENT MATERIALS (OR SIMILAR MATERIALS FROM DIFFERENT SOURCES) TO MEET THE REQUIREMENTS OF ITEM 302007 - GRADED AGGREGATE BASE COURSE, TYPE 'B'.

ALL OF THE ABOVE LISTED MATERIALS ARE PERMITTED FOR USE ON THE JOB, PROVIDED THEY ARE SEPARATED INTO APPROVED AREAS, EACH AREA OF BASE COURSE MUST BE CONSTRUCTED USING MATERIALS FROM A SINGULAR SOURCE, FULL DEPTH, IN ORDER THAT PROPER TESTING MAY BE ACCOMPLISHED. THE CONTRACTOR AND ENGINEER SHALL AGREE ON THE LIMITS OF EACH SOURCE OF MATERIAL PRIOR TO PLACEMENT.

- B. THE QUANTITY USED FOR BASE OF EACH OF THE ABOVE LISTED MATERIALS WILL BE THE CONTRACTOR'S CHOICE, WITH
 THE TOTAL BEING EQUAL TO THE ACTUAL QUANTITY USED UNDER ITEM 302007 GRADED AGGREGATE BASE COURSE, TYPE 'B'.
- C. THE CONTRACTOR MAY ALSO ELECT TO RECYCLE MILLINGS FOR USE IN HOT-MIX AS PERMITTED BY THE STANDARD SPECIFICATIONS. THE CHOICE OF THE QUANTITY OF MILLINGS USED FOR THIS PURPOSE, OR FOR BASE COURSE, LIES WITH THE CONTRACTOR. ALL EXCESS MILLING MATERIAL SHALL BECOME PROPERTY OF THE CONTRACTOR.
- D. HOT-MIX MILLINGS MAY BE GENERATED FROM THE FOLLOWING SOURCES:
 - a. MATERIAL MADE AVAILABLE WHEN MILLED ON THIS CONTRACT UNDER ITEM 760507.
 - b. MATERIAL MILLED ON THIS CONTRACT AT THE CONTRACTOR'S CHOICE UNDER ITEM 202000.
- c. MILLED MATERIAL FURNISHED ON THE JOB FROM THE CONTRACTOR'S YARD OR OTHER OUTSIDE SOURCE.

 ALL MILLED MATERIALS SHALL MEET THE MATERIAL REQUIREMENTS OF ITEM 302514 MILLED HOT-MIX BASE COURSE.

E. PAYMENT CLARIFICATION:

- a. SHOULD THE CONTRACTOR ELECT TO MILL PORTIONS OF HOT-MIX SHOWN ON THE PLANS TO BE REMOVED UNDER ITEM 202000 EXCAVATION AND EMBANKMENT THE COST OF MILLING THIS HOT-MIX WILL BE PAID AS ITEM 202000 EXCAVATION AND EMBANKMENT. THE MILLINGS GENERATED MAY BE RECYCLED INTO HOT-MIX, UTILIZED FOR BASE COURSE, OR DISPOSED OF TO AN APPROVED SITE. HAULING COSTS FOR DISPOSAL AND/OR RECYCLING ARE INCIDENTAL TO ITEM 202000 EXCAVATION AND EMBANKMENT.
- b. MILLINGS GENERATED UNDER ITEM 760502 PAVEMENT MILLINGS, TAPERCUT MAY BE RECYCLED INTO HOT-MIX,
 UTILIZED FOR BASE COURSE OR DISPOSED OF BY THE CONTRACTOR TO AN APPROVED SITE. NO SEPARATE PAYMENT
 WILL BE MADE FOR TRANSPORTING MILLINGS ON SITE OR TO AN APPROVED DISPOSAL SITE.
- c. SHOULD THE CONTRACTOR ELECT TO TEMPORARILY STOCKPILE MILLINGS ON THE JOB SITE FOR LATER USE, ALL COSTS FOR STOCKPILING AND SUBSEQUENT REHANDLING SHALL BE INCIDENTAL TO ITEM 202000 EXCAVATION AND EMBANKMENT.
- d. MILLINGS USED FOR BASE COURSE SHALL BE PLACED IN ACCORDANCE WITH THE REQUIREMENTS OF SPECIAL PROVISION 302514 MILLED HOT-MIX BASE COURSE, NO SEPARATE PAYMENT WILL BE MADE TO FURNISH MILLINGS FROM AN OUTSIDE SOURCE OR TRANSPORT MILLINGS WITHIN THE PROJECT LIMITS, MILLINGS USED FOR BASE COURSE WILL BE PAID FOR AT THE UNIT BID PRICE FOR ITEM 302007 GRADED AGGREGATE BASE COURSE, TYPE 'B'.
- e. ALL COSTS TO UTILIZE MILLINGS IN RECYCLED HOT-MIX WILL BE INCIDENTAL TO THE UNIT PRICE BID FOR THE HOT-MIX ITEM USING THE RECYCLED MATERIAL.
- f. SPECIAL PROVISION 302514 MILLED HOT-MIX BASE COURSE IS PROVIDED TO SPECIFY THE MEANS OF LAY DOWN AND COMPACTION AS WELL AS THE MATERIAL REQUIREMENTS FOR MILLINGS USED AS BASE COURSE. ALL COSTS TO BRING THE MILLINGS INTO COMPLIANCE WITH THE REQUIREMENTS OF ITEM 302514 MILLED HOT-MIX BASE COURSE ARE INCIDENTAL TO ITEM 302007 GRADED AGGREGATE BASE COURSE, TYPE 'B'. NO PAYMENT WILL BE MADE FOR ITEM 302514 MILLED HOT-MIX BASE COURSE. THE QUANTITY OF MILLINGS USED FOR BASE COURSE WILL BE PAID FOR UNDER ITEM 302007 GRADED AGGREGATE BASE COURSE.

SECTION 600

5. THE DEPARTMENT AND THE CONTRACTOR SHALL INSPECT ALL EXISTING PIPES AND DRAINAGE STRUCTURES TO BE USED IN THE FINAL DRAINAGE SYSTEM AND AGREE ON THE CONDITION PRIOR TO THE START OF CONSTRUCTION, EXISTING PIPES AND DRAINAGE STRUCTURES DAMAGED DUE TO CONTRACTOR OPERATIONS SHALL BE REPAIRED OR REPLACED IN-KIND AT THE CONTRACTOR'S EXPENSE, THE DEPARTMENT WILL VIDEO INSPECT NEW PIPE RUNS TO CONFIRM CONDITION PRIOR TO ACCEPTANCE, PIPE CLEANING PRIOR TO VIDEO INSPECTION AND MAINTENANCE OF TRAFFIC DURING THE VIDEO INSPECTION ARE THE RESPONSIBILITY OF THE CONTRACTOR AND INCIDENTAL TO THE PIPE ITEM THAT IS BEING VIDEO INSPECTED.

SECTION 700

- 6. IN AREAS WHERE PROPOSED CURB MEETS EXISTING CURB AND THE TWO CURB TYPES ARE NOT SIMILAR, THE PROPOSED CURB SHALL BE TRANSITIONED IN 10 LINEAR FEET, UNLESS OTHERWISE DIRECTED BY THE ENGINEER. PAYMENT FOR THIS WORK, INCLUDING SAW CUTTING EXISTING CURB SHALL BE INCIDENTAL TO THE PROPOSED CURB ITEM.
- 7. PORTLAND CEMENT CONCRETE CH<mark>ANNE</mark>LIZING ISLANDS THAT ARE LESS THAN 75 SQ FT MAY BE POURED MONOLITHICALLY, OR AS DIRECTED BY THE ENGINEER.
- 8. STATION AND ELEVATION DATA G<mark>IVEN F</mark>OR DRAINAGE STRUCTURES ARE TO BE APPLIED TO THE CENTER OF THE GRATE FOR INLETS, AND TO THE CENTER OF THE STRUCTURE FOR JUNCTION BOXES AND MANHOLES.
- DRAINAGE INLET GRATES ADJACENT TO THE ROAD, WITHIN THE PROJECT LIMITS, WHICH ARE NOT TYPE 1 SHALL BE REPLACED.

 THE ACTUAL LOCATIONS, THE NEED FOR ANY GRATE MODIFICATIONS OR FOR NEW FRAMES SHALL BE DETERMINED BY THE

 ENGINEER. ALL REPLACED GRATES/FRAMES SHALL BE DELIVERED TO THE NEAREST DISTRICT MAINTENANCE YARD WITH THE

 COST OF DELIVERY INCIDENTAL TO ITEM 708060 REPLACING DRAINAGE INLET GRATE(S). FINAL PAYMENT FOR REPLACED

 GRATES/FRAMES SHALL NOT BE MADE UNTIL RECEIPT OF DELIVERED MATERIALS IS PRODUCED, SIGNED BY A DELDOT

 MAINTENANCE YARD SUPERVISOR.
- 10. ALL PAVED AREAS TO BE RECON<mark>STRU</mark>CTED OR WIDENED SHALL BE SAWCUT AT THE POINT WHERE THE NEW PAVEMENT IS TO TIE INTO THE EXISTING PAVEMENT.
- 11. ALL WORK REQUIRED FOR CALCULATING AND STAKING OF GRADES SHALL BE PAID FOR UNDER ITEM 763621 -


SECTION 900

- 12. IN AREAS WHERE EXISTING DITCHES ARE TO BE REGRADED DUE TO CURB PLACEMENT, ITEM 908020 EROSION CONTROL BLANKET MULCH SHALL BE USED. LOCATIONS INCLUDE IN THE CENTER MEDIAN AT STATIONS 106+40 TO 106+70 AND STATIONS 107+90 TO 108+30, TOTALLING APPROXIMATELY 62 SQUARE YARDS.
- 13. THIS PROJECT IS COVERED UNDER AN NPDES GENERAL PERMIT FOR CONSTRUCTION. UNDER THE GENERAL PERMIT, COMPLIANCE WITH DELDOT'S APPROVED SEDIMENT AND STORMWATER MANAGEMENT PLANS WILL CONSTITUTE COMPLIANCE WITH THE NPDES INDUSTRIAL PERMITTING REQUIREMENTS FOR THIS CONSTRUCTION PROJECT. A COPY OF THE NPDES GENERAL PERMIT AND NOI IS KEPT ON FILE IN EACH OF THE CONSTRUCTION OFFICES AND THE DEPARTMENT'S TEAM SUPPORT SECTION. A COPY OF THE GENERAL PERMIT OR THE NOI CAN BE OBTAINED UPON REQUEST FROM EITHER THE DEPARTMENT'S STORMWATER ENGINEER OR THE APPROPRIATE CONSTRUCTION ENGINEER.

MISCELLANEOUS


- 14. THE CONTRACTOR SHALL CONTACT MICHAEL ELLER, THE CHIEF OF SCHEDULING FOR DART FIRST STATE, 14 DAYS PRIOR TO THE START OF CONSTRUCTION AT 302-576-6061.
- 15. THERE ARE NO ENVIRONMENTAL PERMITS ASSOCIATED WITH THIS PROJECT. AS SUCH, AN ENVIRONMENTAL COMPLIANCE SHEET WAS NOT PREPARED.

CONTRACT	BRIDGE NO.	NA	
201600901	BIND OF THE	IVA	
COUNTY	DESIGNED BY:	ANM	
SUSSEX	CHECKED BY:	JLC	



	CURB SCHEDULE								
NO.	ITEM DESCRIPTION / TYPE	LENGTH							
1	PCC CURB, TYPE 2	191′							
2	PCC CURB, TYPE 2	** 131'							
3	PCC CURB, TYPE 2	358′							
4	PCC CURB, TYPE 2	** 118'							
5	PCC CURB, TYPE 2	192'							

^{**}THE COST FOR CONSTRUCTING THIS CURB IS INCIDENTAL TO ITEM 705530 - TRIANGULAR CHANNELIZING ISLANDS.



DELAWARE
DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

SCALE

30 60


FEET

TASK 1 – HEP SC, US 113 AT ENNIS ROAD/NORTH STREET

CONTRACT	BRIDGE NO.	NA				
T201600901						
COUNTY	DESIGNED BY:	ANM				
SUSSEX	CHECKED BY:	JLC				

CONSTRUCTION PLAN

		SHEET NO.
	DI ANI	5
ON	PLAN	TOTAL SHTS.
		12



	CO	ORDINATE	LIST	
POINT NO.	STATION	OFFSET	NORTHING	EASTING
71000	105+70.21	<i>33. 12</i>	<i>251853.6135</i>	661303. 3878
71001	105+80.45	<i>33. 13</i>	<i>251863. 6009</i>	661301.1416
71002	106+75. 31	6.80	<i>251950. 3373</i>	661254. 5830
71003	107+03 . 95	-9.74	<i>251974.6381</i>	661232.1436
71004	107+09.66	- <i>22. 13</i>	<i>251977. 4789</i>	661218. 8005
71005	107+02.97	-34.02	<i>251968. 3370</i>	661208. 6747
71006	106+75. 29	- <i>42. 37</i>	<i>251939.</i> 4982	661206.6226
71007	106+65. 29	- <i>42. 43</i>	<i>251929. 7303</i>	<i>661208. 7654</i>
71008	108+98. 39	-34.04	<i>252158. 9617</i>	<i>661165.636</i> 9
71009	108+88.40	- <i>34.05</i>	252149. 2097	<i>661167.8231</i>
71010	107+93. 22	- <i>7. 78</i>	<i>252062. 1512</i>	661214. 3981
71011	107+64.33	<i>8. 93</i>	<i>252037. 6451</i>	<i>661237. 0593</i>
71012	107+58.63	21. 26	<i>252034. 7990</i>	661250. 3385
71013	107+65. 22	<i>33. 13</i>	<i>252043. 8397</i>	661260.4727
71014	107+92.97	41.71	<i>252072. 7978</i>	661262. 7324
71015	108+02.97	41.83	<i>252082. 5794</i>	661260.6470
71016	304+80.16	<i>30. 24</i>	<i>251983. 7714</i>	661150. 3727
71017	<i>304+83. 27</i>	<i>27. 98</i>	<i>251985.6177</i>	<i>661153. 7454</i>
71018	304+73.93	<i>2. 34</i>	<i>252012. 2402</i>	661147. 7500
71019	304+72.07	1.02	<i>252013. 7827</i>	661146.0675
71020	304+34.99	<i>0. 76</i>	<i>252018. 7633</i>	661109. 3279
71021	304+34.28	4.64	<i>252015.0102</i>	661108. 1305
71022	<i>500+87. 35</i>	- <i>4.57</i>	<i>251998. 7813</i>	661322. 1736
71023	501+19.20	-4.69	251994. 4646	<i>661353. 7237</i>
71024	501+19.95	- <i>8.53</i>	<i>251998. 1696</i>	661355 . 0096
71025	500+79.46	- <i>32. 41</i>	<i>252027. 4507</i>	661318 . 2380
71026	500+76.34	-30.14	<i>252025. 6395</i>	661314.8337
71027	500+85.47	- <i>5.86</i>	<i>252000. 3265</i>	661320.4929
71028	107+60.70	- <i>40.83</i>	<i>252023.</i> 1460	661189. 3220
71029	106+61.21	<i>37. 74</i>	<i>251943. 4003</i>	661287.8668
71030	106+61.96	41.60	251944. 9745	661291.4678
71031	107+05.80	41. 48	<i>251987. 7113</i>	661281.6954
71032	107+07.44	40.62	<i>251989.1199</i>	661280.4947
71033	108+05.60	- <i>37. 85</i>	<i>252067. 6029</i>	661182. 3417
71034	108+04.85	-41.71	252066.0214	661178.7479
71035	107+62.33	-41.68	252024. 5560	661188. 1281

NOTES:

- 1. OFFSETS SHOWN IN THE COORDINATE LIST WITH A MINUS SIGN ARE TO THE LEFT OF THE CONSTRUCTION BASELINE.
- 2. UNLESS OTHERWISE NOTED, POINT GEOMETRY ADJACENT TO CURB AND CURB AND GUTTER IS GIVEN TO EDGE OF PAVEMENT.
- 3. RADII ARE GIVEN TO THE EDGE OF PAVEMENT.
- 4. UNLESS OTHERWISE NOTED, EDGE OF PAVEMENT ELEVATIONS AT INTERSECTIONS ARE GIVEN AT 10 FOOT INTERVALS.
- 5. ALL WORK REQUIRED FOR CALCULATING AND STAKING OUT OF GRADES SHALL BE PAID FOR UNDER ITEM 763621 CONSTRUCTION ENGINEERING.
- 6. PROPOSED CURBS OR PAVEMENT THAT TIE INTO EXISTING PAVEMENT OR EXISTING CURBS SHALL MATCH THE EXISITING PAVEMENT OR CURB ELEVATIONS.

DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

SCALE

O 30 60


FEET

TASK 1 - HEP SC, US 113 AT ENNIS ROAD/NORTH STREET

CONTRACT	BRIDGE NO.	NA	
201600901		1 12 1	
COUNTY	DESIGNED BY:	ANM	
SUSSEX	CHECKED BY:	JLC	

GRADES AND GEOMETRICS

6
TOTAL SHTS.



SEWER MANHOLE VERTICAL ADJUSTMENT

NOT TO SCALE

NOTE:

I. ALL WORK AND MATERIALS SHOWN IN DETAIL ABOVE SHALL BE INCLUDED UNDER ITEM 710506 - ADJUST AND REPAIR EXISTING SANITARY MANHOLE.

DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

NOT TO SCALE

TASK 1- HEP SC, US 113 AT ENNIS ROAD/NORTH STREET

CONTRACT
BRIDGE NO.

T201600901

COUNTY


DESIGNED BY: ANM


CHECKED BY: JLC

CONSTRUCTION DETAILS

7
TOTAL SHTS.


12





CHECKED BY: JLC


SUSSEX



ENNIS ROAD/NORTH STREET

ONTRACT	BRIDGE NO.	NA	
01600901	DECIONED DV	1 27 1	CC
COUNTY	DESIGNED BY:	ANM	<u></u>
SUSSEX	CHECKED BY:	JLC	CO

CONSTRUCTION PHASING, M.O.T., AND EROSION CONTROL PLAN – PHASE 2



	SIGN SCHEDULE																	
<u>"</u> ;	SHEET	PLAN	CODE	QTY	DESCRIPTION	ASSEMBLY	SIGN WIDTH	SIGN HEIGHT	SIGN AREA	ITEM 7496	87 SINGLE POST (EACH)		690 MULTI POST ST NEEDED)	POST INSTALLATION	Code X11 12' Post	ITEM 749688 4" HOLE, 0-6"	ITEM 749689 4" HOLE, >6"	REMARKS
"	NO.	INDICATOR	CODE		DESCRIPTION	NO.	(IN)	(IN)	(SF)	SIGN DISPOSTION	REMOVE INSTALL C	SIGN DISPOSTION	REMOVE INSTALL		(W/ Basepost)		(EACH)	TEMARKS
1678	12	1	D3-1a(12)		STREET NAME + ROUTE SHIELD (1 Line)		0	12"	0	REMOVE	1		00000 00000 00000 00000 00000		0	0	0	
4	12	2	R1-1(36)		STOP		36"	36"	0	REMOVE	2000 000 2000 000 200		00000 00000 00000 00000 00000 00000		0	0	0	
406	12	3	R6-3(30)		DIVIDED HIGHWAY CROSSING (4 - Legged Intersection) - 30x24	4	30"	24"	0	REMOVE	1000000		5000 5000 5000 5000 5000 5000 5000 500		0	0	0	
1677	12	5	D3-1a(9)		STREET NAME + ROUTE SHIELD (1 Line)		0	9"	0	REMOVE	1		6000 0000		0	0	0	
1677	12	6	D3-1a(9)		STREET NAME + ROUTE SHIELD (1 Line)		0	9"	0	REMOVE					0	0	0	
7	12	7	R1-2(30)		YIELD		30"	30"	0	REMOVE	1		9000 10000 1		0	0	0	
4	12	7A	R1-1(36)		STOP		36"	36"	9	NEW	1				1	0	0	
1678	12	8	D3-1a(12)		STREET NAME + ROU <mark>TE S</mark> HIELD (1 Line)		0	12"	0	REMOVE	1		2005 2005 2005 2005 2005 2005 2005 2005		0	0	0	
395	12	9	R6-1_L(54)		ON <mark>E W</mark> AY (ENCLOSED IN <mark>LEF</mark> T ARROW) - 54x18		54"	18"	0	REMOVE			50000000000000000000000000000000000000		0	0	0	
1677	12	10	D3-1a(9)		STREET NAME + ROU <mark>TE S</mark> HIELD (1 Line)		18"	9"	1.25	NEW	1		5000 5000 5000 5000 5000 5000 5000 500		1	0	0	Ennis Rd
1678	12	11	D3-1a(12)		STREET NAME + ROUTE SHIELD (1 Line)		30"	12"	2.5	NEW					0	0	0	DuPont Bl∨d
124	12	13	R3-5_R		MAN <mark>DAT</mark> ORY MOVEMENT LANE CONTROL (Right)		30"	36"	7.5	NEW	1				1	0	0	
1677	12	14	D3-1a(9)		STREET NAME + ROUTE SHIELD (1 Line)		18"	9"	1.25	NEW	1				-	0	0	Ennis Rd
1678	12	15	D3-1a(12)		STREET NAME + ROU <mark>TE S</mark> HIELD (1 Line)		30"	12"	2.5	NEW	2000 C C C C C C C C C C C C C C C C C C				0	0	0	DuPont Blvd
124	12	16	R3-5_R		MAN <mark>DAT</mark> ORY MOVEMENT LANE CONTROL (Right)		30"	3 <mark>6" </mark>	7.5	NEW					0	0	0	
1955	12	17	OM1-3		TYPE 1 OBJECTMARKER		18"	18"	2.25	NEW					0	0	0	
7	12	19	R1-2(30)		YIELD		30"	30"	0	REMOVE	-1				0	0	0	
4	12	20	R1-1(36)		STOP		36"	36"	9	NEW	1				1	0	0	
359	12	20A	R5-1(36)		DO NOT ENTER-36x36		36"	36"	9	NEW	1		2000 2000 2000 2000 2000 2000 2000 200		1	0	0	
4	12	21	R1-1(36)		STOP		36"	36"	0	REMOVE	-		0000 0000 0000 0000 0000 0000 0000		0	0	0	
1652	12	22	D1-2(B)		DESTINATION (2 Line)		0	12"	0	REMOVE	1		CONTO		0	0	0	
1652	12	23	D1-2(B)		DESTINATION (2 Line)		0	12"	0	REMOVE	\$500000 \$5000000 \$500000000000000000000		5555 5555 5555 5555 5555 5555 5555 5555 5555		0	0	0	
1652	12	24	D1-2(B)		DESTINATION (2 Line)		36"	12"	3	NEW	1		30000 300000 30000000 3000000 300000000		1	0	0	Howerd T Ennis School —>
1652	12	25	D1-2(B)		DESTINATION (2 Line)		18"	12"	1.5	NEW	20000000 20000000000000000000000000000		00005 00005 00005 00005 00005 00005		0	0	0	Swain Acres —>
1652	12	26	D1-2(B)		DESTINATION (2 Line)		36"	12"	3	NEW	1		00000 00000 00000 00000 00000		1	0	0	<howerd ennis="" school<="" t="" td=""></howerd>
1652	12	27	D1-2(B)		DESTINATION (2 Line)		18"	12"	1.5	NEW	\$ \$200.000		CODY		0	0	0	<swain acres<="" td=""></swain>
1652	12	28	D1-2(B)		DESTINATION (2 Line)		0	12"	0	REMOVE	1		55575 55		0	0	0	
1652	12	29	D1-2(B)		DESTINATION (2 Line)		0	12"	0	REMOVE	2.5.0.0070 2.5.0.0070		50000 500000 50000 50000 50000 50000 50000 50000 50000 50000 500000 50000 50000 50000 50000 50000 50000 50000 50000 500000 50000		0	0	0	
4	12	30	R1-1(36)		STOP		36"	36"	0	REMOVE	1				0	0	0	
359	12	30A	R5-1(36)		DO NOT ENTER-36x36		36"	36"	9	NEW	1		9999 100 100 100 100 100 100 100 100 100		1	0	0	
7	12	31	R1-2(30)		YIELD		30"	30"	0	REMOVE	1				0	0	0	
4	12	32	R1-1(36)		STOP		36"	36"	9	NEW	1				1	0	0	
43	12		R2-1-25(36)		SPEE <mark>D LIMIT (25 MPH - 36x48)</mark>		36"	48"	12	RENEW	1 1				0	0	0	
	12	34		***************************************	CHILDREN AT PLAY					REMOVE	1				0	0	0	
124	12	35	R3-5_R		MANDATORY MO <mark>VEM</mark> ENT LANE CONT <mark>RO</mark> L (Right)		30"	36"	7.5	NEW	1				1	0	0	
124	12	36	R3-5_R		MANDATORY MO <mark>VEM</mark> ENT <mark>LAN</mark> E CONT <mark>ROL</mark> (Right)		30"	<mark>3</mark> 6"	7.5	NEW	1		2005 2005 2005 2005 2005 2005 2005		1	0	0	
1955	12	37	OM1-3		TYPE 1 OBJECTMARKER		18"	18"	2.25	NEW					0	0	0	
4	12	38	R1-1(36)		STOP		36"	36"	0	REMOVE	1				0	0	0	
406	12	39	R6-3(30)		DIVIDED HIGHWAY CROS <mark>SING (4 - Legged Intersection) -</mark> 30x24	4	30"	24"	0	REMOVE					0	0	0	
7	12	40	R1-2(30)		YIELD		30"	30"	0	REMOVE	1				0	0	0	
4	12	40a	R1-1(36)		STOP		36"	36"	9	NEW	1				1	0	0	
252	12	42	R3-20-DE		TURN LANE		18"	18"	2.25	NEW	000000				0	0	0	
252	12	43	R3-20-DE		TURN LANE		18"	18"	0	REMOVE	2000 2000 2000 2000 2000 2000 2000 200		-		0	0	0	
395	12	48	R6-1_L(54)		ONE WAY (ENCLOSED IN LEFT ARROW) - 54x18		54"	18"	6.75	NEW								
395	12	49	R6-1_L(54)		ONE WAY (ENCLOSED IN LEFT ARROW) - 54x18		54"	18"	6.75	NEW			3.000 3.000		0	0	0	
					JOB TOTALS				132.75		14 14		0 0		13	0	0	



DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

NOT

NOT TO SCALE


TASK 1 – HEP SC, US 113 AT ENNIS ROAD/NORTH STREET


CONTRACT	BRIDGE NO.	NA	
201600901			
COUNTY	DESIGNED BY:	ANM	
SUSSEX	CHECKED BY:	JLC	

SIGNING, STRIPING AND CONDUIT PLAN

STRIPING
OUIT PLAN

12
TOTAL SHTS.
12





U.S. CUSTOMARY THE STATE OF DELAWARE DEPARTMENT OF TRANSPORTATION



FINAL PLANS

CONSTRUCTION PLANS FOR:


OPEN-END CONSTRUCTION SERVICES, SUSSEX COUNTY TASK 2 - HRRRP SC, US 13 AT SR 30/ DOROTHY ROAD/WHITESVILLE ROAD

CONTRACT NUMBER: T201600901 FEDERAL AID PROJECT NUMBER: ESTP-2015(31)

COUNTY: SUSSEX

M.R. #: 001 M.R. #: 064

> **END TASK STATION** 118 + 50.00



BEGIN TASK STATION 100 + 00.00

LOCATION MAP NOT TO SCALE

SEAL

RECOMMENDED

No. 12898

SEAL

STORMWATER ENGINEER

DATE ___07/15/2015

RECOMMENDED

DATE ____07/14/2015

SQUAD MANAGER, TRANSPORTATION SOLUTIONS (PROJECT DEVELOPMENT OR BRIDGE DESIGN)

No. 16847 S AWAS MIL SIONAL END

SEAL

RECOMMENDED BRIDGE DESIGN ENGINEER

May 1 GROUP ENGINEER, PROJECT DEVELOPMENT DATE ____07/20/2015

RECOMMENDED



ASSISTANT DIRECTOR,

TRANSPORTATION SOLUTIONS

RECOMMENDED

DATE ____07/20/2015

DESIGN DESIGNATION D.H.V. PROJECTED: 1,932 YEAR: 2040 FUNCTIONAL CLASS: PRINCIPAL ARTERIAL DESIGN SPEED: 60 M.P.H. TRUCKS: 12 % DIRECTION OF DISTRIBUTION: 60 % D.H.V. PROJECTED: 151 YEAR: 2040 FUNCTIONAL CLASS: MAJOR COLLECTOR DESIGN SPEED: 45 M.P.H. TRUCKS: 10 % DIRECTION OF DISTRIBUTION: 56 % A.A.D.T. PROJECTED: 2,700 YEAR: 2040

INDEX OF SHEETS

SHEET Nº	TABLE OF CONTENTS	
1	TITLE SHEET	
2	PLAN SHEET INDEX	
3	LEGEND	
4	NOTES	
5	HORIZONTAL AND VERTICAL CONTROL	
6 - 8	CONSTRUCTION PLANS	
9 - 12	GRADES AND GEOMETRICS	
13 - 14	CONSTRUCTION DETAILS	
15 - 24	CONSTRUCTION PHASING, M.O.T., AND ERSION CONTROL PLANS	
25 - 28	SIGNING, STRIPING, AND CONDUIT PLANS	

TOTAL SHEETS: 28

APPROVED DESIGN EXCEPTIONS

DESIGN PARAMETER	REQUIRED	PROVIDED	DATE

ADDENDA & REVISIONS


NAME & DATE **DESCRIPTION**

ASSOCIATED CONTRACTS CONTRACT NO. **CONTRACT NAME** US 13 MD LINE TO LAUREL 84-063-01 1149 DELMAR TO GEORGETOWN LAUREL RD

APPROVED

CHIEF ENGINEER CHEER OFLAWARE IN SIONAL ENVI

DATE ____07/21/2015






PLAN SHEET INDEX CROSS REFERENCE

CONSTRUCTION PLA	V	6	7	8
GRADES AND GEOMETRICS		9	10, 11	12
CONSTRUCTION PHAS M.O.T. AND E&S	NG,	15, 18, 21	16, 19, 22	17, 20, 23
SIGNING, STRIP <mark>ING</mark> AND CONDUIT P <mark>LAI</mark>	/	24	25	26

(DOROTHY ROAD)



DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

SCALE
90 90 180

FEET

TASK 2 – HRRRP SC, US 13 AT SR 30/ DOROTHY ROAD/WHITESVILLE ROAD

T201600901

COUNTY

SUSSEX

BRIDGE NO.

DESIGNED BY: NER

CHECKED BY: JLC

PLAN SHEET INDEX

TOTAL SHTS.

EXISTING SYMBOLS

	DRAINAGE
—— qq ————	DITCH OR STREAM CENTERLINE
	DIRECTIONAL STREAM FLOW ARROW
C.B. D.I.	DRAINAGE INLET
J.B.	DRAINAGE JUNCTION BOX
0	DRAINAGE MANHOLE
SIZE/TYPE_LABEL	DRAINAGE PIPE AND FLOW ARROW
	DRAINAGE PIPE HEADWALL
	RIPRAP - AREA FEATURE
Olio	RIPRAP - LINEAR FEATURE

MANM	ADE ROADSIDE FEATURES
0	BOLLARD - STEEL POLE
	BOLLARD - WOOD POST
(TYPE LABEL)	CURB
(TYPE LABEL)	CURB AND GUTTER
—х——	FENCE - CHAINLINK OR STRANDED
—-a——	FENCE - STOCKADE OR SPLIT RAIL
FP #	FLAG POLE
	GUARDRAIL - STEEL BEAM
_0	GUARDRAIL - WIRE ROPE
LAMP	LAMP AND POST - RESIDENTIAL
MB	MAILBOX
PM	PARKING METER AND POST
	PAVEMENT - FLEXIBLE
	PAVEMENT - RIGID
	PILE - BRIDGE
0	PILLAR OR MISCELLANEOUS POST
7	TRAFFIC SIGN AND POST
0000	WALL - BRICK OR BLOCK
00000	WALL - STONE

NATURAL ROADSIDE FEATURES		
	GRASS LAWN	
acacacaca	HEDGEROW OR THICKET	
	MARSH BOUNDARY LINE	
X	TREE - CONIFEROUS	
	TREE - DECIDUOUS	
ā	TREE STUMP	
©	SHRUBBERY	
WL	DELINEATED WETLAND BOUNDARY LINE	
	WOODS LINE BOUNDARY	

	RIGHT-OF-WAY SYMBOLS
C.M.	PROPERTY MARKER - CONCRETE MON.
I.P.	PROPERTY MARKER - IRON PIPE
100+00	HISTORIC RIGHT-OF-WAY BASELINE
	EXISTING RIGHT-OF-WAY
—— ग	EXISTING PROPERTY LINE
—— EASEMENT TYPE ——	EXISTING EASEMENT
——— DA ———	EXISTING DENIAL OF ACCESS
R/W-DA	EXISTING R/W & DENIAL OF ACCESS

SURVEY CO	ONTROL & MONUMENTATION
B.M.	SURVEY BENCHMARK LOCATION
T.P.	SURVEY TIE POINT LOCATION
Δ	SURVEY TRAVERSE POINT
0	POINT OF CURVATURE OR TANGENCY
0	POINT OF INTERSECTING TANGENTS

UTILITY

SOIL BORING LOCATION

•	UTILITY TEST HOLE LOCATION
TV	CABLE TV DISTRIBUTION BOX
(E)	ELECTRIC MANHOLE
EM	ELECTRIC METER
E	ELECTRIC TRANSFORMER
	POLE MOUNTED LUMINAIRE
©	GAS MANHOLE
G.M.	GAS METER
G.V.	GAS VALVE
G.P.	GAS PUMP - SERVICE STATION
	RAILROAD TRACKS
(\$)	SANITARY SEWER MANHOLE
S.V.	SANITARY SEWER VALVE
VENT	SANITARY SEWER VENT OR CLEANOUT
[S.D.F]	SEPTIC DRAIN FIELD
В	TELEPHONE BOOTH
\bigcirc	TELEPHONE MANHOLE
T	TELEPHONE TEST POINT
J.W.	TRAFFIC - CONDUIT JUNCTION WELL
©	TRAFFIC - LIGHT POLE AND BASE
	TRAFFIC - PEDESTRIAN POLE & BASE
9	TRAFFIC - SIGNAL CABINET & BASE
\otimes	TRAFFIC - SIGNAL POLE AND BASE
U	UTILITY BOX
⋄→	UTILITY POLE GUY WIRE ANCHOR
Ø	UTILITY POLE
F.H.	WATER - FIRE HYDRANT
W.M.	WATER METER
₩ . ∨.	WATER VALVE
WELL	WELL HEAD
?	MANHOLE - UNDETERMINED OWNER

UTILIT	Y COMPANY FAC <mark>ILITIE</mark> S
COM-C	COMCAST CABLE
— ESNG-G —	EASTERN SHORE N <mark>atur</mark> al Gas
	VERIZON
VER-AB	VERIZON, ABANDONE <mark>D</mark>

PROPOSED SYMBOLS

CONSTRUCTION			IDENTIFIERS
CONCRETE SAFETY BAR	RIER - PERMANENT	(A)	ADJUST BY CONTRACTOR
×BFS× BIOFILTRATION SWALE		A	ADJUST BY OTHERS
BRICK PATTERNED SURF	FACE	(B)	CONCRETE SAFETY BARRIER
BUTT JOINT		<u>©</u>	CURB OR CURB & GUTTER
100+00 CONSTRUCTION BASELINE	=	<u>CJB</u>	CONVERT TO JUNCTION BOX
	FENCE	(CMF)	CONVERT TO DRAINAGE MANHOLE
CURB, TYPE 1 & TYPE 3	3	CO	CURB OPENING
CURB, TYPE 2		€ R	CURB RAMP / TYPE
CURB & G <mark>UTTE</mark> R, TYPE	1	(CR-N)	CURB RAMP / TYPE - WITHOUT SIDEWALK SURFACE
CURB & GUTTER, TYPE	2	(SF)	CONSTRUCTION SAFETY FENCE
CURB & GUTTER, TYPE	3	(D)	DRAINAGE INLET
CURB & GUTTER, TYPE	4	(DND)	DO NOT DISTURB
CURB OPENING		£	ENERGY DISSIPATOR
——————————————————————————————————————		É	FENCE
■ DRAINAGE INLET		FES .	FLARED END SECTION
×———× DITCH		(FF)	FILL WITH FLOWABLE FILL
O—O—O FENCE - METAL		[S]	FILTRATION STRUCTURE
FENCE - WOOD		(CR)	GUARDRAIL
FLARED END SECTION		<i>JB</i>	JUNCTION BOX
GUARDRAIL, TYPE 1		MH	MANHOLE
<u>ं वं वं वं वं</u> GUARDRAIL, TYPE 2		M	MONUMENT - RIGHT-OF-WAY
GUARDRAIL, TYPE 3		P	PIPE
GUARDRAIL END ANCHOR	RAGE	(RL)	RELOCATE BY CONTRACTOR
GUARDRAIL END TREATM	IENT, TYPE 1	(RL O	RELOCATE BY OTHERS
GUARDRAIL END TREATM	IENT, TYPE 2	RMC	REMOVE BY CONTRACTOR
GUARDRAIL END TREATM	MENT, TYPE 3	RMO	REMOVE BY OTHERS
IMPACT ATTENUATOR			UNDERDRAIN / LENGTH
JUNCTION BOX - DRAINA	AGE	<u>u</u>	UN <mark>DERD</mark> RAIN OUTLET P <mark>IPE</mark>
LO LATERAL OFFSET		SES	SAFETY END STRUCTURE
LOC LIMIT OF CONSTRUCTION		S	SIGNING
MAIL BOX			LANDSCADING

LANDSCAPING		
<u>(IS</u>)	LANDSCAPE PLANTINGS	
€3	SHRUBBERY	
\otimes	CONIFEROUS TREE	
\odot	DECIDUOUS TREE	

TRAFFIC			
ITMS-CON ITMS CONDUIT			
——SIG-CON —— SIGNAL CONDUIT			
•	CONDUIT JUNCTION WELL		
	LUMINAIRE		
→	PAVEMENT MARKINGS		
	PAVEMENT STRIPING		
TRAFFIC SIGN			

PAVEMENT SECTION(S)				
	RECONSTRUCTED PAVEMENT			
	2" BITUMINOUS CONCRETE PAVEMENT, SUPERPAVE, TYPE C, 160 GYRATIONS, 70-22 (NON-CARBONATE STONE) - ITEM 401830			
	3" BITUMINOUS CONCRETE PAVEMENT, SUPERPAVE, TYPE B, 160 GYRATIONS, PG 64-22 - ITEM 401810			
	6" BITUMINOUS CONCRETE PAVEMENT, SUPERPAVE, BCBC, 160 GYRATIONS, PG 64-22 - ITEM 401819			

8" GABC, TYPE B - ITEM 302007

EROSIOI	N & SEDIMENT CONTROL
- DWBAG	DEWATERING BAG
- DWB	DEWATERING BASIN
ED	EARTH DIKE
	INLET SEDIMENT CONTROL
·=====================================	PERIMETER DIKE/SWALE
(S)	PORTABLE SEDIMENT TANK
SBD	SANDBAG DIKE
SB SB	SANDBAG DIVERSION
	STONE CHECK DAM
SCE	STABILIZED CONSTRUCTION ENTRANCE
<u>₹</u>	SILT FENCE / LENGTH
——SF——	SILT FENCE
RSF	SILT FENCE - REINFORCED
SP	SUMP PIT
<u> </u>	SEDIMENT TRAP / NUMBER
SI	SEDIMENT TRAP
\$7	SEDIMENT TRAP WITH INLET AS OUTLET
ST-	SEDIMENT TRAP PIPE OUTLET
SW SW	STILLING WELL
·====	TEMPORARY SWALE
<i>TSD</i>	TEMPORARY SLOPE DRAIN
TXXX	TURBIDITY CURTAIN / LENGTH
——————	TURBIDITY CURTAIN
—— <i>CFL</i> ——	COMPOST FILTER LOG

			(
_	_	_	_

DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

TASK 2 – HRRRP SC, US 13 AT SR 30/ DOROTHY ROAD/WHITESVILLE ROAD NOT TO SCALE

CONTRACT	BRIDGE NO.	X
T201600001		X
T201600901	DESIGNED BY:	NED
COUNTY	DESIGNED B1.	INER
SUSSEX	CHECKED BY:	JLC

TOTAL SHTS 28

MANHOLE

PAVEMENT REMOVAL - TOPSOIL, SEED AND MULCH

→ UNDERDRAIN

RIPRAP

100+00

PAVEMENT PATCH

P.C.C. SIDEWALK - 4"

UNDERDRAIN OUTLET

----PE---- PROPOSED PERMANENT EASEMENT

- R/W-DA - PROPOSED R/W & DENIAL OF ACCESS

--- TCE --- TEMPORARY CONSTRUCTION EASEMENT

- PIPE & DIRECTIONAL FLOW ARROW

RIGHT-OF-WAY SYMBOLS

PROPOSED DENIAL OF ACCESS

PROPOSED RIGHT-OF-WAY MONUMENT

PROPOSED RIGHT-OF<mark>-WA</mark>Y BASELINE

USE ITEM 705005 - P.C.C. SIDEWALK, 8" 8" GABC

GENERAL NOTES

1. THIS PROJECT IS TO BE CONSTRUCTED IN ACCORDANCE WITH THE DELAWARE DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS", DATED AUGUST 2001 AND THE DELAWARE DEPARTMENT OF TRANSPORTATION "STANDARD CONSTRUCTION DETAILS", DATED 2001, INCLUDING ALL REVISIONS UP TO THE DATE OF ADVERTISEMENT.

2.							
∠•	EROSION POTENTIAL FOR THIS PROJECT	CONTRACTOR ESC SUPERVISOR REQUIREMENT					
	() INSIGNIFICANT	NONE					
	(X) MINOR	CONTRACTOR TRAINING PROGRAM, AS DEFINED IN SECTION 6.2 OF THE DELAWARE SEDIMENT AND STORMWATER REGULATIONS.					
	() MEDIUM	CONTRACTOR TRAINING PROGRAM, AS DEFINED IN SECTION 6.2 OF THE DELAWARE SEDIMENT AND STORMWATER REGULATIONS.					
	() MAJOR	CERTIFIED CONSTRUCTION REVIEWER (CCR), AS DEFINED IN SECTION 6.3 OF THE DELAWARE SEDIMENT AND STORMWATER REGULATIONS.					

3. ELECTRONIC PROJECT FILES THAT WILL BE MADE AVAILABLE TO THE AWARDED CONTRACTOR, INCLU<mark>DE:</mark>

()	NONE
(X)	ASCII DATA FILES WITH COORDINATES AND ELEVATIONS FOR PROPOSED POINTS AS SELECTED BY THE ENGINEER.
(X)	ALL PLAN SHEETS, IN PDF FORMAT.
()	EXISTING DIGITAL TERRAIN MODEL, IN .DTM FILE FORMAT, COMPATIBLE WITH SOFTWARE CURRENTLY USED BY DELDOT.
()	PROPOSED DIGITAL TERRAIN MODEL, IN .DTM FILE FORMAT, COMPATIBLE WITH SOFTWA <mark>RE CU</mark> RRENTLY U <mark>SED</mark> BY DELDOT.
()	DESIGN FILE, IN .DGN FILE FORMAT, CONTAINING ONLY THE PROPOSED 3D TRIANGLES OF THE PROPOSED DIGITAL TERRAIN MODEL (DTM).

NOTE: THE DOCUMENT ENTITLED "RELEASE FOR DELIVERY OF DOCUMENTS IN ELECTRONIC FORM TO A CONTRACTOR" MUST BE SIGNED BY ALL PARTIES PRIOR TO THE DELIVERY OF ANY ELECTRONIC PROJECT FILES.

4. PROJECT FILES THAT WILL BE MADE AVAILABLE TO THE CONTRACTOR, INCLUDE:

()	CROSS SECTIONS (WILL BE MADE AVAILABLE TO THE AWARDED CONTRACTOR)
()	RIGHT-OF-WAY PLANS (WILL BE MADE AVAILABLE TO THE AWARDED CONTRACTOR)

5. AMERICAN TRAFFIC SAFETY SERVICES ASSOCIATION (ATSSA) CERTIFIED TRAFFIC CONTROL SUPERVISOR REQUIREMENT FOR THIS PROJECT.

()	THE CONTRACTOR SHALL NOT BE REQUIRED TO HAVE AN ATSSA SUP <mark>ERVISO</mark> R ASSIGNED TO THIS PROJECT.
()	THE CONTRACTOR SHALL HAVE AN ATSSA SUPERVISOR ASSIGNED TO THIS PROJECT. THE CONTRACTOR'S GENERAL SUPERINTENDENT FOR THIS PROJECT OR ANOTHER ATSSA CERTIFIED MEMBER OF THE CONTRACTOR'S PROJECT STAFF MAY BE THE ATSSA SUPERVISOR. PAYMENT FOR ATSSA SUPERVISOR IS INCIDENTAL TO ITEM 743000.
(X)	THE CONTRACTOR SHALL HAVE AN ATSSA SUPERVISOR ASSIGNED TO THIS PROJECT. THE ATSSA SUPERVISOR'S SOLE JOB SHALL BE SUPERVISION OF THE INSTALLATION, OPERATION AND MAINTENANCE OF TRAFFIC CONTROL DEVICES FOR THIS PROJECT. THE CONTRACTOR'S GENERAL SUPERINTENDENT FOR THIS PROJECT SHALL NOT BE THE ATSSA SUPERVISOR. PAYMENT FOR ATSSA SUPERVISOR SHALL BE PAID FOR UNDER ITEM 743031.

- 6. THE DISTURBED AREA FOR THIS PROJECT IS 3.1699 ACRES.
- THE SEDIMENT AND STORMWATER MANAGEMENT PLANS HAVE BEEN APPROVED BY DELDOT'S STORMWATER ENGINEER UNDER DELDOT'S DELEGATED AUTHORITY. THE SEDIMENT AND STORMWATER MANAGEMENT PLANS ARE VALID FOR A THREE YEAR PERIOD, BEGINNING ON THE DATE THE STORMWATER ENGINEER SIGNED THE CONSTRUCTION TITLE SHEET. IF THE FINAL ACCEPTANCE OF THE PROJECT IS ANTICIPATED TO EXTEND BEYOND THE THREE YEARS, THE CONTRACTOR WILL INFORM THE ENGINEER THREE MONTHS PRIOR TO THE EXPIRATION OF THE APPROVED SEDIMENT AND STORMWATER MANAGEMENT PLANS. THE STORMWATER ENGINEER WILL REVIEW THE CURRENT SEDIMENT AND STORMWATER MANAGEMENT PLAN AND ISSUE AN EXTENSION WITH ANY APPROPRIATE MODIFICATIONS.

PROJECT NOTES

SECTION 100

1. ANY DAMAGE TO ITEMS NOTED TO BE RELOCATED OR RESET BY THE CONTRACTOR, AT THE DISCRETION OF THE ENGINEER, SHALL BE REPAIRED AND/OR REPLACED IN KIND AT THE CONTRACTOR'S EXPENSE.

SECTION 200

2. THE ENGINEER MAY REQUIRE THE CONTRACTOR TO EXCAVATE TEST PITS ALONG PROPOSED DRAINAGE RUNS, AT POINTS OF POSSIBLE UTILITY CONFLICTS, TO DETERMINE IF A CONFLICT EXISTS. ANY CONFLICTS SHALL BE COORDINATED BY THE CONTRACTOR, WITH THE ENGINEER AND THE UTILITY COMPANY INVOLVED. THE ENGINEER SHALL ULTIMATELY DETERMINE THE SOLUTION TO THE UTILITY CONFLICT. TEST HOLES SHALL BE MEASURED AND PAID FOR IN ACCORDANCE WITH ITEM 202000 EXCAVATION AND EMBANKMENT, BUT ONLY TO THE ACTUAL DEPTH EXCAVATED.

SECTION 300

- 3. A. THE CONTRACTOR MAY ELECT TO USE ANY OF THE FOLLOWING MATERIALS TO MEET THE REQUIREMENTS OF ITEM 302007

 GRADED AGGREGATE BASE COURSE, TYPE 'B':
- a. CRUS<mark>HED S</mark>TONE (PER STANDARD SPECIFICATION 821)
- b. CRUSHED CONCRETE (PER STANDARD SPECIFICATION 821)
- c. HOT-MIX MILLINGS (PER SPECIAL PROVISION 302514 MILLED HOT-MIX BASE COURSE)

THE CONTRACTOR WILL NOT BE ALLOWED TO MIX DIFFERENT MATERIALS (OR SIMILAR MATERIALS FROM DIFFERENT SOURCES) TO MEET THE REQUIREMENTS OF ITEM 302007 - GRADED AGGREGATE BASE COURSE, TYPE 'B'.

ALL OF THE ABOVE LISTED MATERIALS ARE PERMITTED FOR USE ON THE JOB, PROVIDED THEY ARE SEPARATED INTO APPROVED AREAS. EACH AREA OF BASE COURSE MUST BE CONSTRUCTED USING MATERIALS FROM A SINGULAR SOURCE, FULL DEPTH, IN ORDER THAT PROPER TESTING MAY BE ACCOMPLISHED. THE CONTRACTOR AND DELDOT'S PROJECT ENGINEER SHALL AGREE ON THE LIMITS OF EACH SOURCE OF MATERIAL PRIOR TO PLACEMENT.

- B. THE QUANTITY USED FOR BASE OF EACH OF THE ABOVE LISTED MATERIALS WILL BE THE CONTRACTOR'S CHOICE, WITH THE TOTAL MEETING THE ADVERTISED QUANTITY OF ITEM 302007 GRADED AGGREGATE BASE COURSE, TYPE 'B'.
- C. THE CONTRACTOR MAY ALSO ELECT TO RECYCLE MILLINGS FOR USE IN HOT-MIX AS PERMITTED BY THE STANDARD SPECIFICATIONS. THE CHOICE OF THE QUANTITY OF MILLINGS USED FOR THIS PURPOSE, OR FOR BASE COURSE, LIES WITH THE CONTRACTOR. ALL MILLING MATERIAL SHALL BECOME PROPERTY OF THE CONTRACTOR.
- HOT-MIX MILLINGS MAY BE GENERATED FROM THE FOLLOWING SOURCES:
- a. MATERIAL MADE AVAILABLE WHEN MILLED ON THIS CONTRACT UNDER ITEM 760507.
- MATERIAL MILLED ON THIS CONTRACT AT THE CONTRACTOR'S CHOICE UNDER ITEM 202000.
- c. MILLED MATERIAL FURNISHED ON THE JOB FROM THE CONTRACTOR'S YARD OR OTHER OUTSIDE SOURCE.

 ALL MILLED MATERIALS SHALL MEET THE MATERIAL REQUIREMENTS OF ITEM 302514 MILLED HOT-MIX BASE COURSE.
- E. PAYMENT CLARIFICATION:
- a. SHOULD THE CONTRACTOR ELECT TO MILL PORTIONS OF HOT-MIX SHOWN ON THE PLANS TO BE REMOVED UNDER ITEM 202000 EXCAVATION AND EMBANKMENT THE COST OF MILLING THIS HOT-MIX WILL BE PAID AS ITEM 202000 EXCAVATION AND EMBANKMENT. THE MILLINGS GENERATED MAY BE RECYCLED INTO HOT-MIX, UTILIZED FOR BASE COURSE, OR DISPOSED OF TO AN APPROVED SITE. HAULING COSTS FOR DISPOSAL AND/OR RECYCLING ARE INCIDENTAL TO ITEM 202000 EXCAVATION AND EMBANKMENT.
- MILLINGS GENERATED UNDER ITEM 760502 PAVEMENT MILLINGS, TAPERCUT MAY BE RECYCLED INTO HOT-MIX,

 UTILIZED FOR BASE COURSE OR DISPOSED OF BY THE CONTRACTOR TO AN APPROVED SITE, NO SEPARATE PAYMENT

 WILL BE MADE FOR TRANSPORTING MILLINGS ON SITE OR TO AN APPROVED DISPOSAL SITE.
- SHOULD THE CONTRACTOR ELECT TO TEMPORARILY STOCKPILE MILLINGS ON THE JOB SITE FOR LATER USE, ALL COSTS FOR STOCKPILING AND SUBSEQUENT REHANDLING SHALL BE INCIDENTAL TO ITEM 202000 EXCAVATION AND EMBANKMENT.
- II. MILLINGS USED FOR BASE COURSE SHALL BE PLACED IN ACCORDANCE WITH THE REQUIREMENTS OF SPECIAL PROVISION 302514 MILLED HOT-MIX BASE COURSE, NO SEPARATE PAYMENT WILL BE MADE TO FURNISH MILLINGS FROM AN OUTSIDE SOURCE OR TRANSPORT MILLINGS WITHIN THE PROJECT LIMITS, MILLINGS USED FOR BASE COURSE WILL BE PAID IN PLACE AT THE UNIT BID PRICE FOR ITEM 302007 GRADED AGGREGATE BASE COURSE, TYPE 'B'.
- e. ALL COSTS TO UTILIZE MILLINGS IN RECYCLED HOT-MIX WILL BE INCIDENTAL TO THE UNIT PRICE BID FOR THE HOT-MIX
 ITEM USING THE RECYCLED MATERIAL.
- f. SPECIAL PROVISION 302514 MILLED HOT-MIX BASE COURSE IS PROVIDED TO SPECIFY THE MEANS OF LAY DOWN AND COMPACTION AS WELL AS THE MATERIAL REQUIREMENTS FOR MILLINGS USED AS BASE COURSE. ALL COSTS TO BRING THE MILLINGS INTO COMPLIANCE WITH THE REQUIREMENTS OF ITEM 302514 MILLED HOT-MIX BASE COURSE ARE INCIDENTAL TO ITEM 302007 GRADED AGGREGATE BASE COURSE, TYPE 'B'. NO PAYMENT WILL BE MADE FOR ITEM 302514 MILLED HOT-MIX BASE COURSE. THE QUANTITY OF MILLINGS USED FOR BASE COURSE WILL BE PAID FOR UNDER ITEM 302007 GRADED AGGREGATE BASE COURSE.

SECTION 600

ADDENDUMS / REVISIONS

4. THE DEPARTMENT AND THE CONTRACTOR SHALL INSPECT ALL EXISTING PIPES AND DRAINAGE STRUCTURES TO BE USED IN THE FINAL DRAINAGE SYSTEM AND AGREE ON THE CONDITION PRIOR TO THE START OF CONSTRUCTION. EXISTING PIPES AND DRAINAGE STRUCTURES DAMAGED DUE TO CONTRACTOR OPERATIONS SHALL BE REPAIRED OR REPLACED IN-KIND AT THE CONTRACTOR'S EXPENSE. THE DEPARTMENT WILL VIDEO INSPECT NEW PIPE RUNS TO CONFIRM CONDITION PRIOR TO ACCEPTANCE. PIPE CLEANING PRIOR TO VIDEO INSPECTION AND MAINTENANCE OF TRAFFIC DURING THE VIDEO INSPECTION ARE THE RESPONSIBILITY OF THE CONTRACTOR AND INCIDENTAL TO THE PIPE ITEM THAT IS BEING VIDEO INSPECTED.

SECTION 700

- 5. PORTLAND CEMENT CONCRETE CHANNELIZING ISLANDS THAT ARE LESS THAN 75 SQ FT MAY BE POURED MONOLITHICALLY, OR AS DIRECTED BY THE ENGINEER.
- 6. STATION AND ELEVATION DATA GIVEN FOR DRAINAGE STRUCTURES ARE TO BE APPLIED TO THE CENTER OF THE GRATE FOR INLETS, AND TO THE CENTER OF THE STRUCTURE FOR JUNCTION BOXES AND MANHOLES.
- 7. DRAINAGE INLET GRATES ADJACENT TO THE ROAD, WITHIN THE PROJECT LIMITS, WHICH ARE NOT TYPE 1 SHALL BE REPLACED. THE ACTUAL LOCATIONS, THE NEED FOR ANY GRATE MODIFICATIONS OR FOR NEW FRAMES SHALL BE DETERMINED BY THE ENGINEER. ALL REPLACED GRATES/FRAMES SHALL BE DELIVERED TO THE NEAREST DISTRICT MAINTENANCE YARD WITH THE COST OF DELIVERY INCIDENTAL TO ITEM 708060 REPLACING CATCH BASIN GRATES. FINAL PAYMENT FOR REPLACED GRATES/FRAMES SHALL NOT BE MADE UNTIL RECEIPT OF DELIVERED MATERIALS IS PRODUCED, SIGNED BY A DELDOT MAINTENANCE YARD SUPERVISOR.
- 8. ALL PAVED AREAS TO BE RECONSTRUCTED OR WIDENED SHALL BE SAWCUT FULL DEPTH AT THE POINT WHERE THE NEW PAVEMENT IS TO TIE INTO THE EXISTING PAVEMENT.
- 9. ALL WORK REQUIRED FOR CALCULA<mark>TING A</mark>ND STAKING OUT OF GRADES SHALL BE PAID FOR UNDER ITEM 763621 CONSTRUCTION ENGIN<mark>EERIN</mark>G.

SECTION 900

10. THIS PROJECT IS COVERED UNDER AN NPDES GENERAL PERMIT FOR CONSTRUCTION. UNDER THE GENERAL PERMIT,

COMPLIANCE WITH DELDOT'S APPROVED SEDIMENT AND STORMWATER MANAGEMENT PLANS WILL CONSTITUTE COMPLIANCE WITH

THE NPDES INDUSTRIAL PERMITTING REQUIREMENTS FOR THIS CONSTRUCTION PROJECT. A COPY OF THE NPDES GENERAL

PERMIT AND NOI IS KEPT ON FILE IN EACH OF THE CONSTRUCTION OFFICES AND THE DEPARTMENT'S TEAM SUPPORT SECTION.

A COPY OF THE GENERAL PERMIT OR THE NOI CAN BE OBTAINED UPON REQUEST FROM EITHER THE DEPARTMENT'S


STORMWATER ENGINEER OR THE APPROPRIATE CONSTRUCTION ENGINEER.

MISCELLANEOUS

- 11. THERE ARE NO ENVIRONMENTAL PERMITS ASSOCIATED WITH THIS PROJECT. AS SUCH, AN ENVIRONMENTAL COMPLIANCE SHEET WAS NOT PROVIDED.
- 12. THE CONTRACTOR SHALL CONTACT MICHAEL ELLER, THE CHIEF OF SCHEDULING FOR DART FIRST STATE, 14 DAYS PRIOR TO THE START OF CONSTRUCTION AT 302-576-6061.
- 13. REFER TO THE CONSTRUCTION PLAN SHEETS FOR THE LOCATION OF THE CLEAR ZONE AREA LIMITS.



CONTRACT	BRIDGE NO.	Y	
T00100001	51 NB 02 1101	A	
T201600901	DECIONED DV: I	NED	
COUNTY	DESIGNED BY: I	NEK	
SUSSEX	CHECKED BY:	JLC	



 CURB SCHEDULE

 NO.
 ITEM DESCRIPTION / TYPE
 LENGTH


 1
 P. C. C. CURB, TYPE 2
 72.00'

 2
 P. C. C. CURB, TYPE 2
 52.00'

		DRAINA	GE INLET S	CHEDU	JLE	
NO.	STATION	OFFSET	BOX SIZE	GRATE	T.G. EL.	INV. EL.
1	101+05.97	0.00′	34" x 24"	3	45 . 59′	40. 26′
2	102+69.41	0.00′	34" x 24"	3	46. 18′	41.70′
3	103+99.41	0.00′	34" x 24"	3	46.08′	42. 31'
4	105+55. 41	0.00′	34" x 24"	3	45 . 98′	<i>42.</i> 84′

	DRAINAGE PIPE SCHEDULE						
NO.	SIZE / TYPE	CLASS	LENGTH	SLOPE	INT. EL.	DIS. EL.	
1	15" RCP	IV	160.00′	0.0090	41. 70′	40. 26′	
2	15" RCP	IV	128.00′	0.0048	42. 31'	41. 70′	
3	15" RCP	IV	152 . 00′	0.0035	<i>42. 84′</i>	42. 31'	
4	15" RCP	1V	152.00′	0.0035	<i>43. 45′</i>	42. 84′	

* DRAINAGE INLET 1 IS A DOGHOUSE INLET



DELAWARE
DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

SCALE

30 30 60

FEET

TASK 2 – HRRRP SC, US 13 AT SR 30/ DOROTHY ROAD/WHITESVILLE ROAD

CONTRACT
BRIDGE NO.

T201600901

COUNTY

DESIGNED BY: NER

SUSSEX
CHECKED BY: JLC

CONSTRUCTION PLAN

AN


SHEET NO.

6


TOTAL SHTS.

28





DRAINAGE PIPE SCHEDULE						
NO.	SIZE / TYPE	CLASS	LENGTH	SLOPE	INT. EL.	DIS. EL.
5	15" RCP	1V	82 . 00′	<i>0.</i> 0035	<i>43. 36′</i>	<i>43.07′</i>
6	15" RCP	1V	80 . 00′	0.0066	<i>43.</i> 07′	<i>42.</i> 54′
7	15" RCP	1V	176 . 00′	0.0074	<i>42.</i> 54′	41. 23'
8	14" x 23" RCP	1V	160.00′	0.0036	41. 23'	40.65′
9	14" x 2 <mark>3" R</mark> CP	1 V	144.00′	0.0044	40 . 65′	39. 93′



HOT MIX

48070 98104

ADDENDUMS / REVISIONS

DELAWARE DEPARTMENT OF TRANSPORTATION

532-6.00-80.01 CHURCH OF GOD OF PROPHECY D 3260 127

SCALE
0 30 60 9

TASK 2 – HRRRP SC, US 13 AT SR 30/ DOROTHY ROAD/WHITESVILLE ROAD

CONTRACT	BRIDGE NO.	Y	
201600901		X	
COUNTY	DESIGNED BY:	NER	
SUSSEX	CHECKED BY:	JLC	

CONSTRUCTION PLAN


OTAL SHTS

28

	CURB SCHEDULE	
NO.	ITEM DESCRIPTION / TYPE	LENGTH
7	P.C.C. CURB, TYPE 2	53 . 00'
8	P.C.C. CURB, TYPE 2	72.00′

DRAINAGE INLET SCHEDULE						
NO.	STATION	OFFSET	BOX SIZE	GRATE	T.G. EL.	INV. EL.
11	115+78 . 70	0.00′	48" x 30"	3	43. 13'	<i>39. 93′</i>
12	117+10.70	0.00′	48" x 30"	3	<i>42.</i> 50′	<i>39. 20′</i>


DRAINAGE PIPE SCHEDULE						
NO.	SIZE / TYPE	CLASS	LENGTH	SLOPE	INT. EL.	DIS. EL.
10	14" x 23" RCP	1V	128 . 00′	0.0057	<i>39. 93′</i>	<i>39. 20′</i>
11	14" x 23" RCP	1V	68 . 00′	0.0033	<i>39. 20′</i>	<i>38.</i> 96′
12	24" RCP	1V	8 . 00'	0.0088	<i>39. 03′</i>	<i>38.</i> 96′
13	24" RCP	1 V	8 . 00'	0.0013	<i>38.</i> 96′	<i>38.</i> 95′




SAFETY END STRUCTURE							
NO.	STATION	OFFSET	TYPE/SIZE	GRATE	INV. EL.		
1	116+90.03	70. 44′	10: 1	YES	<i>39. 03′</i>		
2	117+22.02	70 . 35′	10: 1	YES	<i>38.</i> 95′		

	JUNCT	ION BOX	SCHEDULE	
NO.	STATION	OFFSET	BOX SIZE	INV. EL.
1	117+10.70	72. 41′	48" x 30"	<i>38.</i> 96′

332-7.00-19.00 LEVIN N DICKERSON TRUSTEE D 3594 080





332-7.00-19.03 IVA DICKERSON TRUSTEE D 3594 082

DELAWARE
DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

SCALE

30 30 60

FEET

TASK 2 – HRRRP SC, US 13 AT SR 30/ T20160 DOROTHY ROAD/WHITESVILLE ROAD

NTRACT	BRIDGE NO.	X		
1600001	5,400	X		
1600901	DESIGNED BY: NER			
YTNUC	DESIGNED DI-	NER		
JSSEX	CHECKED BY:	JLC		

CONSTRUCTION PLAN


SHEET NO.	
8	
TOTAL SHTS.	
28	

COORDINATE LIST					
POINT NO.	STATION	OFFSET	NORTHING	EASTING	
70000	101+84.56	50 . 00′	181991.9570	615948.5168	
70001	101+84.58	70.00′	181991.6042	<i>615968. 5137</i>	
70002	104+24.58	69 . 90′	182231.5657	615972.8117	
70003	104+24.56	49. 90′	182231.9185	<i>615952.8148</i>	
70004	104+50.01	<i>25. 00′</i>	<i>182257.8228</i>	615928. 4046	
70005	104+50.00	21.00′	1 <i>82257</i> . <i>8939</i>	615924. 4053	
70006	104+69.02	21.00′	182276.9023	615924.7431	
70007	105+71.75	9.81′	182379 . 8200	<i>615915. 4365</i>	
70008	106+00.54	-12. 38'	182409.0104	<i>615893.7751</i>	
70009	106+99.81	- <i>20.</i> 45′	182508. 4145	<i>615887</i> . <i>5276</i>	
70010	106+99. 81	-24. 45′	182508 . 4856	<i>615883. 5283</i>	

COORDINATE LIST					
POINT NO.	STATION	OFFSET	NORTHING	EAST ING	
70011	102+57.31	21. 13'	182065. 2217	<i>615920. 9806</i>	
70012	102+57.31	<i>25.</i> 1 <i>3′</i>	182065 . 1506	615924.9800	
70013	102+55. 31	21. 13'	182063 . 2220	<i>615920. 9451</i>	
70014	102+55. 29	-12.13'	182063 . 8131	615887.6955	
70015	102+02. 24	-16.77′	<i>182010.8615</i>	615882.0793	
70016	101+89.68	19.06′	181997.6422	615917.6754	
70017	101+87.68	21. 17'	181995 . 6078	615919. 7429	
70018	102+00.75	-20.10′	182009. 4267	<i>615878. 7235</i>	
70019	101+74.54	<i>25.</i> 18′	181982 . 3966	<i>615923</i> . <i>5091</i>	
70020	101+81.68	21. 18'	181989.6085	615919.6363	
70021	101+81.66	-20.08'	181990 . 3418	<i>615878. 3875</i>	
70022	101+74.52	-24.08'	181983. 2721	615874. 2618	
70023	101+74.54	21. 18'	181982. 4677	615919 . 5097	
70024	101+74.52	- 20 . 08′	181983 . 2010	<i>615878. 2612</i>	

- NOTES:

 1. OFFSETS SHOWN IN THE COORDINATE LIST WITH A MINUS SIGN ARE TO THE LEFT OF THE CONSTRUCTION BASELINE.
- 2. UNLESS OTHERWISE NOTED, POINT GEOMETRY ADJACENT TO CURB AND CURB AND GUTTER IS GIVEN TO EDGE OF PAVEMENT.
- 3. RADII ARE GIVEN TO THE EDGE OF PAVEMENT.
- 4. UNLESS OTHERWISE NOTED, EDGE OF PAVEMENT ELEVATIONS AT INTERSECTIONS ARE GIVEN AT 10 FOOT INTERVALS.
- 5. ALL WORK REQUIRED FOR CALCULATING AND STAKING OUT OF GRADES SHALL BE PAID FOR UNDER ITEM 763621 - CONSTRUCTION ENGINEERING.
- 6. PROPOSED CURBS OR PAVEMENT TH<mark>AT T</mark>IE INTO EXISTING PAVEMENT OR EXISTING CURBS SHALL MATCH THE EXISTING PAVEMENT OR CURB ELEVATIONS.



DELAWARE	
DEPARTMENT OF TRANSPORTATION	
DEPARTIMENT OF TRANSPORTATION	


DENDUMS	/ REVISIONS				
			SCALE		
		0	3	0	60
				FEET	
		1			


TASK 2 - HRRRP SC, US 13 AT SR 30	
DOROTHY ROAD/WHITESVILLE ROAD	


CONTRACT	BRIDGE NO.	Y	
T201000001	37.115 02 7.100	X	_
T201600901	DECICNED DV: NED		
COUNTY	DESIGNED BY: NER		┚
SUSSEX	CHECKED BY:	JLC	

GRADES AND GEOMETRICS

SHEET NO.	
9	
TOTAL SHTS.	
28	







	CO	ORDINATE	LIST	
POINT NO.	STATION	OFFSET	NORTHING	EASTING
70061	117+21.24	12 . 29′	<i>183529.</i> 0680	<i>615938. 9985</i>
70062	117+75.78	20. 26′	<i>183583.</i> 4574	615947.9665
70063	118+08.68	24. 25′	<i>183616. 2773</i>	<i>615952. 5505</i>
70064	118+08.68	19 . 75′	<i>183616. 3571</i>	615948.0644
70065	117+94.86	20. 26′	<i>183602. 5275</i>	<i>615948. 3052</i>
70066	117+94.83	-21. 23'	<i>183603. 2645</i>	615906.8456
70067	118+08.66	-21. 23'	183617.0854	<i>615907.</i> 0895
70068	11 <mark>8+0</mark> 8.65	- <i>25. 23′</i>	<i>183617. 1565</i>	615903.0901
70069	11 <mark>7+7</mark> 4. 29	16 . 93′	1 <i>83582.</i> 0227	615944.6109
70070	117+88.68	-21.21'	<i>183597. 1120</i>	615906.7371
70071	11 <mark>7+9</mark> 1.97	-50 . 48′	<i>183600. 9353</i>	615877 . 5396
70072	11 <mark>7+8</mark> 6.84	-19.10'	183595. 2316	615908.8154
70073	11 <mark>7+9</mark> 1.95	-70. 48'	18 <mark>3601.</mark> 2881	615 <mark>857. 542</mark> 7
70074	117+21.22	-21.16′	183 <mark>529.</mark> 6626	615905. 5464
70075	11 <mark>7+1</mark> 9. 22	-21.16′	18 <mark>3527.</mark> 6629	615905.5111
70076	11 <mark>7+1</mark> 9. 22	-25. 16'	183527. 7340	<mark>615</mark> 901.5118
70077	11 <mark>5+5</mark> 1.95	-70.31′	183 <mark>361.</mark> 3255	615853. 3090
70078	115+51.97	-50. 31'	18 3360. 9727	615873. 3059

NOTES:

1. OFFSETS SHOWN IN THE COORDINATE LIST WITH A MINUS SIGN ARE TO THE LEFT OF THE CONSTRUCTION BASELINE.

- 2. UNLESS OTHERWISE NOTED, POINT GEOMETRY ADJACENT TO CURB AND CURB AND GUTTER IS GIVEN TO EDGE OF PAVEMENT.
- 3. RADII ARE GIVEN TO THE EDGE OF PAVEMENT.
- 4. UNLESS OTHERWISE NOTED, EDGE OF PAVEMENT ELEVATIONS AT INTERSECTIONS ARE GIVEN AT 10 FOOT INTERVALS.
- 5. ALL WORK REQUIRED FOR CALCULATING AND STAKING OUT OF GRADES SHALL BE PAID FOR UNDER ITEM 763621 - CONSTRUCTION
- 6. PROPOSED CURBS OR PAVEMENT THAT TIE INTO EXISTING PAVEMENT OR EXISTING CURBS SHALL MATCH THE EXISTING PAVEMENT OR CURB ELEVATIONS.

DELAWARE DEPARTMENT OF TRANSPORTATION


ADDENDUMS / REVISIONS


TASK 2 – HRRRP SC, US 13 AT SR 30/DOROTHY ROAD/WHITESVILLE ROAD


CONTRACT	BRIDGE NO.	Y			
20100001	5,400	A			
201600901	DECICNED DV: NED				
COUNTY	DESIGNED BY: NER				
SUSSEX	CHECKED BY:	JLC			

GRADES AND GEOMETRICS

12 OTAL SHTS 28







DE DE

DELAWARE
DEPARTMENT OF TRANSPORTATION

NOT TO SCALE

ADDENDUMS / REVISIONS


TASK 2 – HRRRP SC, US 13 AT SR 30/DOROTHY ROAD/WHITESVILLE ROAD


CONTRACT	BRIDGE NO.	NA	
T201600901	25 02	14/4	
COUNTY	DESIGNED BY: NER		
SUSSEX	CHECKED BY:	JLC	


CONSTRUCTION DETAILS

•	13	
.S	TOTAL SHTS.	
	28	

SHEET NO.







DELAWARE
DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

NOT TO SCALE

TASK 2 – HRRRP SC, US 13 AT SR 30/ DOROTHY ROAD/WHITESVILLE ROAD

CONTRACT	BRIDGE NO.	NA		
T001C00001	5,4,5 62 7,6			
T201600901	DESIGNED DV: NED			
COUNTY	DESIGNED BY: NER			
SUSSEX	CHECKED BY:	JLC		


CONSTRUCTION DETAILS

•	14
5	TOTAL SHTS.
	28


SHEET NO.

GENERAL MOT NOTES

- 1. MAINTENANCE OF TRAFFIC DURING LANE CLOSURES SHALL CONFORM TO TYPICAL APPLICATION 3A, 10, 33 AND 34 OF THE DELAWARE MUTCD.
- 2. GRADING AND MAINTAINING HOT MIX TRM THAT IS BEING USED AS A TRAVELWAY, DRIVEWAY, ACCESS RAMP, ETC. SHALL BE INCIDENTAL TO ITEM 743000 -MAINTENANCE OF TRAFFIC. EXCESS BASE COURSE MATERIAL SHALL BE PUSHED AHEAD AND USED IN THE NEXT SEGMENT AND SHALL BE INCIDENTAL TO THE PARTICULAR BASE COURSE PAY ITEM. NO PAYMENT SHALL BE MADE FOR TEMPORARY ROADWAY MATERIAL (TRM) USED TO PROTECT EDGE DROP-OFFS, UNLESS THE MATERIAL IS EVENTUALLY UTILIZED AS PART OF A PERMANENT ROADWAY AT WHICH TIME THE MATERIAL WOULD BE PAID FOR UNDER THE RESPECTIVE CONTRACT MATERIAL ITEM. CONSTRUCTION OF A PLANNED RUNAROUND OR DETOUR WOULD BE ELIGIBLE FOR PAYMENT AS SPECIFIED IN THE CONTRACT.
- 3. THE CONTRACTOR SHALL SUPPLY PORTABLE CHANGEABLE MESSAGE BOARDS (PCMS) UNDER ITEM 743004. ONE PCMS WILL BE PLACED ALONG US13 NORTHBOUND AND SOUTHBOUND DIRECTIONS PRIOR TO THE WORK AREA AT SR30 EASTBOUND AND WESTBOUND DIRECTIONS. PLACEMENT SHALL BE COORDINATED WITH THE DISTRICT SAFETY OFFICER. THE PCMS'S SHOULD BE PLACED A MINIMUM OF TEN (10) DAYS PRIOR TO THE BEGINING OF CONSTRUCTION TO REMIND ROAD USERS OF PENDING LANE CLOSURES. DISPLAY MESSAGE C FOR 10 DAYS PRIOR TO WORK THEN MESSAGE D FOR 5 DAYS AFTER. THE PCM SHOULD HAVE THE FOLLOWING MESSAGE:



- 4. THE CONTRACTOR IS RESPONSIBLE FOR MAINTENANCE OF EXISTING PAVEMENT WITHIN THE PROJE<mark>CT LIM</mark>ITS FOR THE DURATION OF THE CONTRACT AS DIRECTED BY THE ENGINEER. ALL REPAIRS ARE AT THE CONTRACTORS EXPENSE AS DIRECTED BY THE ENGINEER.
- 5. THE ROADWAY AND SHOULDER WORK SHALL BE PERFORMED IN A MANNER SUCH THAT POSITIVE DRAINAGE OF THE ROADWAY SURFACE IS MAINTAINED THROUGHOUT CONSTRUCTION, ALL WORK AND MATERIALS TO PROVIDE AND MAINTAIN THIS DRAINAGE SHALL BE INCIDENTAL TO ITEM 743000 - MAINTAINCE OF TRAFFIC.
- 6. THIS PROJECT IS CONSIDERED A SIGNIFICANT PROJECT AS DEFINED BY DELDOT'S WORK ZONE MOBILITY PROCEDU<mark>RES AND GUIDELINES, A TY</mark>PE B TRANSPORTATION MANAGEMENT PLAN (TMP) HAS BEEN PREPARED AN<mark>D IS A</mark>VAILABLE FOR VIEW<mark>ING BY</mark> CONTACTIN<mark>G TH</mark>E DEPARTMENT'S SAFETY PROGRAMS MANAGER AT (302)659-4060, ALL MONITORING REQUIREMENTS OF THE TMP SHALL BE CONDUCTED BY DELDOT FORCES UNLESS OTHERWISE DIRECTED BY THE ENGINEER, MODIFICATIONS TO THE TMP SHALL BE COMPLETED BY THE CONTRACTOR IF CHANGES TO THE TIME RESTRICTIONS OR THE TRAFFIC CONTROL PLAN ARE DESIRED. THE MODIFIED TMP SHALL BE PREPARED BY A PROFESSIONAL ENGINEER, REGISTERED IN THE STATE OF DELAWARE.
- 7. BASED ON TRAFFIC VOLUMES ALONG US13 IN THIS AREA, LANE CLOSURES CAN OCCUR ANYTIME DURING THE DAY.
- 8. THE CONTRACTOR SHOULD MOUNT A "NEW TRAFFIC PATTERN" PLAQUE (W-23-2P-DE) ABOVE THE NEW INTERSECTION WARNING SIGN IN THE NORTHBOUND AND SOUTHBOUND DIRECTIONS ON US13 AND IN THE WETSBOUND AND EASTBOUND DIRECTION OF SR 30. THE SIGN SHOULD BE MOUNTED FOR NINETY (90) DAYS AFTER THE NEW TRAFFIC PATTERN IS IN PLACE. THE CONTRACTOR SHALL COORDINATE WITH DELDOT'S SIGN SHOP FOR FABRICATION OF THE SIGN. IN ADDITION, THE CONTRACTOR SHOULD ADVISE DELDOT'S SIGN SHOP WHEN THE NINETY (90) DAY EXPIRATION IS ANTEDATED FOR DELDOT TO SCHEDULE THE REMOVE OF THE SIGN.
- 9. PIPE CROSSING AT STA. 117+00: AT THE COMPLETION OF EACH WORK DAY, THE PIPE TRENCH SHALL BE STEEL PLATED OR BACK FILLED IN ACCORDANCE TO ITEM 743000 AND THE DELAWARE MUTCD.



DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS


NOT TO SCALE

TASK 2 - HRRRP SC, US 13 AT SR 30/ DOROTHY ROAD/WHITESVILLE ROAD

CONTRACT X BRIDGE NO. T201600901 DESIGNED BY: NER CHECKED BY: JLC SUSSEX


CONSTRUCTION PHASING, M.O.T., AND EROSION CONTROL PLAN

STAL SHTS 28



DELAWARE
DEPARTMENT OF TRANSPORTATION


| ADDENDUMS / REVISIONS | SCALE | SHOE NO. | SHOE



SEQUENCE OF CONSTRUCTION - PHASE 1

- 1. PLACE ALL ADVANCE WARNING SIGNS AND TEMPORARY TRAFFIC CONTROL DEVICES.
- 2. INSTALL ALL EROSION AND SEDIMENT CONTROL.
- 3. TRAFFIC ON US 13 USING TA 33 AND TA 34.
- 4. EXCAVATE AND CONSTRUCT PROPOSED PAVEMENT WIDENING.
- 5. EXCAVATE AND CONSTRUCT PROPOSED DRAINAGE PIPE AT STA. 117+10.
- 6. STABILIZE WORK AREAS IN ACCORDANCE WITH DIVISION 900 OF THE DELAWARE STANDARD SPECIFICATIONS.





CONSTRU	JCTION PHASING & M.O.T
Ħ	BARRICADE, TYPE 3
	CONCRETE SAFETY BARRIER - PORTABLE
(CSF) WXX	CONSTRUCTION SAFETY FENCE / LENGTH
—CSF—	CONSTRUCTION SAFETY FENCE
 	CONSTRUCTION WARNING SIGN LOCATION
END ROAD WORK	CONSTRUCTION WARNING SIGN
********	CRASH CUSHION ARRAY
•	DRUM - TRAFFIC CONTROL
. ◆	FLAGGER LOCATION
PRICE	PHASING TRAFFIC FLOW ARROW
	TEMPORARY CONSTRUCTION
→	TEMPORARY PAVEMENT MARKING ARROW
	TRUCK WITH MOUNTED ATTENUATOR
	WORK AREA - ACTIVE PHASE

	DELAWARE	
	DEPARTMENT OF TRANSPORTATION	
-		


ADDENDUMS / REVISIONS				
	SCALE			
	0	30	60	
		FE	ET	


ASK 2 - F	IRRRP	SC, US	13	AT	SR	30/	
OROTHY	ROAD	WHITES	SVIL	LE	ROA	D [_

CONTRACT	BRIDGE NO.	X I	
T201600901	DECIONED DV	AIFD	
COUNTY	DESIGNED BY: NER		
SUSSEX	CHECKED BY:	JLC	

3,
1

Ī	SHEET NO.
	18
	TOTAL SHTS.
I	28






SEQUENCE OF CONSTRUCTION - PHASE 2

- 1. PLACE ALL ADVANCE WARNING SIGNS AND TEMPORARY TRAFFIC CONTROL DEVICES.
- 2. INSTALL ALL EROSION AND SEDIMENT CONTROL.
- 3. CLOSE MEDIAN CROSS OVER ON US 13.
- 4. TRAFFIC ON US 13 USING TA 34.
- 5. EXCAVATE AND CONSTRUCT PROPOSED DRAINAGE PIPE AT STA. 117+10.
- 6. STABILIZE WORK AREAS IN ACCORDANCE WITH DIVISION 900 OF THE DELAWARE STANDARD SPECIFICATIONS.





CONSTRU	JCTION PHASING & M.O.T
	BARRICADE, TYPE 3
	CONCRETE SAFETY BARRIER - PORTABLE
(CSF) XXXX	CONSTRUCTION SAFETY FENCE / LENGTH
—— <i>CSF</i> ——	CONSTRUCTION SAFETY FENCE
→	CONSTRUCTION WARNING SIGN LOCATION
END ROAD WORK	CONSTRUCTION WARNING SIGN
•••••	CRASH CUSHION ARRAY
•	DRUM - TRAFFIC CONTROL
. ◆	FLAGGER LOCATION
PAGE_>	PHASING TRAFFIC FLOW ARROW
	TEMPORARY CONSTRUCTION
_	TEMPORARY PAVEMENT MARKING ARROW
	TRUCK WITH MOUNTED ATTENUATOR
	WORK AREA - ACTIVE PHASE


		I
	DELAWARE	ŀ
	DELAWARE DEPARTMENT OF TRANSPORTATION	ŀ
·		ı

ADDENDUMS	/ REVISIONS			
			SCA	1LE
		0	30	60
			FE	ET

CONTRACT	BRIDGE NO.	X				
T201600901	2500052 27 1152					
COUNTY	DESIGNED BY:	NER				
SUSSEX	CHECKED BY:	JLC	(

CONSTRUCTION PHASING, M.O.T., AND EROSION CONTROL PLAN - PHASE 2

	SHEET NO.
	21
,	TOTAL SHTS.
4	28



DELAWARE DEPARTMENT OF TRANSPORTATION

SCALE
0 30 60
FEET

TASK 2 – HRRRP SC, US 13 AT SR 30/ DOROTHY ROAD/WHITESVILLE ROAD

T201600901

COUNTY

SUSSEX


BRIDGE NO.

DESIGNED BY: NER

CHECKED BY: JLC

CONSTRUCTION PHASING, M.O.T., AND EROSION CONTROL PLAN - PHASE 3


TAL SHTS



SEQUENCE OF CONSTRUCTION - PHASE 3

- 1. PLACE ALL ADVANCE WARNING SIGNS AND TEMPORARY TRAFFIC CONTROL DEVICES.
- 2. INSTALL ALL EROSION AND SEDIMENT CONTROL.
- 3. TRAFFIC ON US 13 USING TA 33.
- 4. EXCAVATE AND CONSTRUCT PROPOSED DRAINAGE SYSTEM.
- 5. EXCAVATE AND CONSTRUCT PROPOSED ROAD BOX.
- 6. INSTALL PERMANENT SIGNING AND STRIPING. OPEN TO TRAFFIC.
 - STABILIZE WORK AREAS IN ACCORDANCE WITH DIVISION 900 OF THE DELAWARE STANDARD SPECIFICATIONS.





CONSTRUCTION PHASING & M.O.T BARRICADE, TYPE 3 CONCRETE SAFETY BARRIER - PORTABLE CONSTRUCTION SAFETY FENCE / LENGTH ——*CSF*—— CONSTRUCTION SAFETY FENCE CONSTRUCTION WARNING SIGN LOCATION CONSTRUCTION WARNING SIGN ********* CRASH CUSHION ARRAY DRUM - TRAFFIC CONTROL FLAGGER LOCATION PHASING TRAFFIC FLOW ARROW TEMPORARY CONSTRUCTION TEMPORARY PAVEMENT MARKING ARROW TRUCK WITH MOUNTED ATTENUATOR WORK AREA - ACTIVE PHASE

DFI	LAWARE OF TRANSPORTATION
DEDARTMENT C	YE TRANICPORTATION !
DEI AITTIVIEITI O	
	L-

ADDENDUMS	/ REVISIONS				
		l		SCALE	
		0	30)	60
				FFFT	
		ł			

CONTRACT	BRIDGE NO.	×				
T201600901						
COUNTY	DESIGNED BY: NER					
COUNTY						
SUSSEX	CHECKED BY: JLC					


WORK AREA - PREVIOUS PHASES


SHEET NO.


24

TOTAL SHTS.

28








474 LF

63 SF

16 SF



332-7.00-19.03 IVA DICKERSON TRUSTEE D 3594 082

STEEL POST

EXISTING R/W

!---<u>LOC -----</u>----

DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

SCALE
O 30 60
FEET

TASK 2 – HRRRP SC, US 13 AT SR 30/ DOROTHY ROAD/WHITESVILLE ROAD

CONTRACT	BRIDGE NO.	X					
T201600901							
COUNTY	- DESIGNED BY:	DESIGNED BY: NER					
SUSSEX	CHECKED BY:	JLC					

SIGNING, STRIPING AND CONDUIT PLAN

SHEET NO.

27

TOTAL SHTS.

28

	SIGN SCHEDULE																
" SHEET	PLAN				SIGN	I .	I	SIGN	ITEM 749	687 SINGLE (EACH)	POST		90 MULTI POST POST T NEEDED) INSTALLATION	Code X11		ITEM 749689	
	INDICATOR	CODE	QTY.	DESCRIPTION	ASSEMBLY NO. WIDT			AREA (SF)	SIGN		INISTALL			12' Post (W/ Basepost	4" HOLE, 0-6" t) (EACH)	4" HOLE, >6" (EACH)	REMARKS
FOE OF	-	140 1700V		U INICTIONI 20.01	(114)		N)	(31)	DISPOSTION	1 HEMOVE	INSTALL	SIGN DISPOSTION	MEMOVE INSTALL TIFL	Ι (γγγ μασεμυσί) (LACI)	(LACI)	
505 25 490 25	I 	M2-1(30) M1-5(36)		JUNCTION - 30x21 STATE ROUTE (2 - Digit Sign) - 36x36	30" 36"		1" 6"		REMOVE REMOVE	<u> </u>					+		30
505 25	<u> </u>	M2-1(30)		JUNCTION - 30x21	30"		1"	4.4	NEW		1			1	0	0	
490 25	1	M1-5(36)		STATE ROUTE (2 - Digit Sign) - 36x36	36"	31	6"	9	NEW					0	0	0	30
512 25 490 25	2	M3-2(36)		CARDINAL DIRECTION - EAST - 36x18					REMOVE	1				500 500 500 500 500 500 500 500 500 500			
490 25 606 25	2	M1-5(36) M6-1_R(30)		STATE ROUTE (2 - Digit Sign) - 36x36 DIRECTIONAL ARROW (Right) - 30x21					REMOVE REMOVE					20 20 20 30 30 30 30 30 30 30 30 30 30 30 30 30			
512 25	2	M3-2(36)		CARDINAL DIRECTION - EAST - 36x18	36"	1:	8"	4.5	NEW		1			1	0	0	
490 25	2	M1-5(36)		STATE ROUTE (2 - Digit Sign) - 36x36	36"		6"	9	NEW	0.00000 0.00000 0.00000 0.00000 0.00000				0	0	0	30
606 25 252 25	2	M6-1_R(30) R3-20-DE		D <mark>IREC</mark> TIONAL ARROW (Ri <mark>ght) -</mark> 30x21 TURN LANE	30" 18"		1" 8"	4.4	NEW NEW		1			0	0	0	
252 25 518 25	3 4	M3-4(36)		CARDINAL DIRECTION - WEST - 36x18	36"		o" 8"	2.25 4.5	NEW		1				0	n	
490 25	4	M1-5(36)		STATE ROUTE (2 - Digit Sign) - 36x36	36"	31	6"	9	NEW	\$ 2000 \$				0	0	0	30
307 25	4	M6-1_L(30)	_	DIRECTIONAL ARROW (Left) - 30x21	30"		1"	4.4	NEW	9 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)				0	0	0	
52 25 4 25	4	R3-20-DE R1-1(36)		TURN LANE STOP	18" 36"		8" 6"	2.25	NEW NEW		1			0	0	0	
62 26	<u> </u>	R5-1a(36)		WRONG WAY - 36x24	36"		0 4"	6	RENEW	1	1				0		
59 26	7	R5-1(36)		DO NOT ENTER - 36x36	36"		6"	-	REMOVE	1				-	_	_	
59 26	7	R5-1(36)		DO NOT ENTER - 36x36	36"		6"	9	NEW		1			1	0	0	
59 26 95	7	R5-1(36) R6-1_L(54)		DO NOT ENTER - 36x36 ONE WAY (ENCLOSED IN LEFT ARROW) - 54x18	36" 54"		6" 8"	9	NEW REMOVE	1	1			1	1 0	0	
4		R1-1(36)		STOP	36"		6"	7	REMOVE							 	
95 26	8	R6-1_L(54)		ONE WAY (ENCLOSED IN LEFT ARROW) - 54x18	54"		8"	6.75	NEW	1950a	1			1	0	0	
4 26	8	R1-1(36)		STOP	36"		6"	9	NEW					0	0	0	
512 26 490 26	9 0	M3-2(36) M1-5(36)		CARDINAL DIRECTION - EAST - 36x18	36" 36"		8" 6"	4.5	RENEW RENEW	1	1			0	0	0	30
26	9A	1011-5(36)		STATE ROUTE (2 - Digit Sign) - 36x36 ADOPT A HIGHWAY	30	- 31	0	J J	REMOVE	1					0		JU
26	9A			I AM MY BROTHERS KEEPER M/M					REMOVE	•				0	0	0	
372 26	9A	D14-3-DE		ADOPT A HIGHWAY	24"		8	3	NEW		1			1	0	0	
24 26	10	R3-5_R		MANDATORY MOVEMENT LANE CONTROL (Right)	30"		6" 2"	7.5	NEW	-	1			1	0	0	
74 26 75 26	11	D3-1(12) D3-1(16)		STREET NAME (1 Line) STREET NAME (1 Line)	U 0		6"	<u> </u>	REMOVE REMOVE	I				Π	0 0	n	SUSSEX HWY WHITESVILLE RD
74 26	11	D3-1(12)		STREET NAME (1 Line)	30	1:	2"	2.5	NEW		1			1	0	Ö	Sussex Hwy
75 26	11	D3-1(16)		STRE <mark>ET N</mark> AME (Î Line)	42		6"	5	NEW					0	0	0	Whitesville Ŕd
33 26	11	R6-1_R(54)		ONE WAY (ENCLOSED IN RIGHT ARROW) - 54x18	54"	 	8"		REMOVE					0	0	0	
35 26 4 26	<u> </u>	R6-1_L(54) R1-1(36)		ONE WAY (ENCLOSED IN LEFT ARROW) - 54x18 STOP	54" 36"		8" 6"	9	REMOVE RENEW					U N	U O	<u> </u>	
07 26	11	R6-3(36)		DIVIDED HIGHWAY CROSS <mark>ING (4 - Legged Int</mark> ersect <mark>ion) -</mark> 36x30	36"		0"	-	REMOVE					0	Ö	Ö	
7 26	12	R2-1-55(36)		SPEED LIMI <mark>T (55</mark> MPH - 3 <mark>6x48</mark>)	36"		8"	12	RENEW	1	1			0	0	0	
324 26	12A	EM-1-DE		EVACUATION ROUTE	24"		4"	4	RENEW		1			0	0	0	
520 26 57 26	12A 13	M6-3(30) R2-1-55(36)		DIRECTIONAL ARROW (Up) - 30x21 SPEED LIMIT (55 MPH - 36x48)	30" 36"		1" 8"	4.4	RENEW REMOVE	-				U	- U		
7 26	13	R2-1-55(36)		SPEED LIMIT (55 MPH - 36×48)	36"		8"	12	NEW		1			1	0	0	
52 26	14	R3-20-DE		TURN LANE	18"		8"	2.25	NEW		1			1	0	0	
12 26	15	M3-2(36)		CARDINAL DIRECTION - EAST - 36x18	36"		8"	4.5	RENEW	1	1			0	0	0	
90 26 07 26	15 15	M1-5(36) M6-1_L(30)		STATE ROUTE (2 - Digit Sign) - 36x36 DIRECTIONAL ARROW (Left) - 30x21	36" 30"		6" 1"	44	RENEW RENEW	CCCCC				U N	0	0	30
52 26	15	R3-20-DE		TURN LANE	18"		' 8"	2.25	RENEW	2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -				0	0	0	
18 26	16	M3-4(36)		CARDINAL DIRECTION - WEST - 36x18	36"		8"	4.5	RENEW	-	1			0	0	0	
30 26	16	M1-5(36)		STATE ROUTE (2 - Digit Sign) - 36x36	36"		6"	9	RENEW					0	0	0	30
06 26 62 26	16 17	M6-1_R(30) R5-1a(36)		DIRECTIONAL ARROW (Right) - 30x21 WRONG WAY - 36x24	30" 36"		1" 4"	4.4 6	RENEW RENEW	1	1			<u>U</u>	U n	U	
52 26 59 26	18	R5-18(36)		DO NOT ENTER - 36x36	36"		4" 6"	9	NEW	1	1			1	0	0	
9 26	18	R5-1(36)		DO NOT ENTER - 36x36	36"	31	6"	<u>-</u>	REMOVE	1				-		_	
9 26	18	R5-1(36)		DO NOT ENTER - 36x36	36"		6"	9	NEW	20 1 5 1 5 1 5 1 5 1 5 1 5 1 5 1 5 1 5 1	1			1	0	0	
18 26 30 26	19 19	M3-4(36) M1-5(36)		CARDINAL DIRECTION - WEST - 36x18 STATE ROUTE (2 - Digit Sign) - 36x36	36" 36"		8" 6"	4.5 a	RENEW RENEW	1	1			0 n	0	U	30
5 26	20	R2-1-40(36)		SPEED LIMIT (40 MPH - 36x48)	36"		8"	12	RENEW	1	1			0	0	0	Ju
4 26	21	R3-5_R		MANDATORY MOVEMENT LANE CONTROL (Right)	30"	31	6"	7.5	NEW		1			1	0	0	
4 26	22	D3-1(12)		STREET NAME (1 Line)	0		2"	0	REMOVE	1				0	0	0	SUSSEX HWY
5 26 4 26	22 22	D3-1(16) D3-1(12)		STREET NAME (1 Line) STREET NAME (1 Line)	0	- ''	6" 2"	0 2.5	REMOVE NEW		1			1	0	U 0	WHITESVILLE RD Sussex Hwy
41 26 5 26	<u>22</u> 22	D3-1(12)		STREET NAME (T Line) STREET NAME (1 Line)	U	- '	<u>2"</u> 6"	5.5	NEW					Π	n	0	Sussex Hwy Whitesville Rd
3 26	22	R6-1_R(54)		ONE WAY (ENCLOSED IN RIGHT ARROW) - 54x18	54"		8"		REMOVE					0	Ö	<u> </u>	
5 26	22	R6-1_L(54)		ONE WAY (ENCLOSED IN LEFT ARROW) - 54x18	54"		8"		REMOVE	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2				0	0	0	
26 7 26	22	R1-1(36) R6-3(36)		STOP DIVIDED HIGHWAY CROSSING (4 - Legged Intersection) - 36x30	36" 36"		6" 0"	9	RENEW					0 n	0 0	0	
26	23	R2-1-55(36)		SPEED LIMIT (55 MPH - 36x48)	36"		8"		REMOVE REMOVE	1				U	+ "		
8 26	24	W2-1(36)		CROSS ROAD - 36x36	36"	31	6"		REMOVE	2				50 50 50 50 50 50 50 50 50 50 50 50 50 5			
32 26	24	D3-2(30)		ADVANCE STREET NAME (2 Line)	0	31	0"	0	REMOVE		-1			-			
7 26 8 27	23 24	R2-1-55(36) W2-1(36)		SPEED LIMIT (55 MPH - 36x48) CROSS ROAD - 36x36	36" 36"	4 4	8" 6"	12 9	NEW NEW	00 (1 2			<u> </u>	U 0	U	
7 26 82 26 7 26 8 27 82 27	24	D3-2(30)		ADVANCE STREET NAME (2 Line)	48	31	0"	10	NEW		-			0	0	0	Dorothy Rd —>, <—Whitesv
27	25	R1-1(36)		STOP	36"	31	6"	9	NEW	00 CD	1			1	0	0	, , , , , , , , , , , , , , , , , , , ,
				JOB TOTALS				#REF!		19	30		0 0	21	0	0	
				ADDENDUMS / F	REVISIONS									CONTRACT	BRIDGE NO.	Х	
		DELAW	ARE								TΔ	SK 2 _ HRI	RRP SC. US 13 AT SR 30	T201600901			SIGNING STRIP

DELAWARE DEPARTMENT OF TRANSPORTATION

TASK 2 – HRRRP SC, US 13 AT SR 30/ T201600901
DOROTHY ROAD/WHITESVILLE ROAD COUNTY

CONTRACT
BRIDGE NO.

T201600901

COUNTY

SUSSEX


CHECKED BY: JLC

SIGNING, STRIPING AND CONDUIT PLAN SHEET NO.

28

TOTAL SHTS.

28



EXISTING SYMBOLS DRAINAGE DITCH OR STREAM CENTERLINE —— a a ——— DIRECTIONAL STREAM FLOW ARROW **──** DRAINAGE INLET DRAINAGE JUNCTION BOX DRAINAGE MANHOLE SIZE/TYPE LABEL DRAINAGE PIPE AND FLOW ARROW DRAINAGE PIPE HEADWALL RIPRAP - AREA FEATURE RIPRAP - LINEAR FEATURE 0% MANMADE ROADSIDE FEATURES BOLLARD - STEEL POLE \bigcirc \boxtimes BOLLARD - WOOD POST CURB (TYPE LABEL) CURB AND GUTTER (TYPE LABEL) FENCE - CHAINLINK OR STRANDED ——Х——— FENCE - STOCKADE OR SPLIT RAIL FLAG POLE GUARDRAIL - STEEL BEAM ____ GUARDRAIL - WIRE ROPE _0___ LAMP AND POST - RESIDENTIAL MAILBOX PARKING METER AND POST PAVEMENT - FLEXIBLE _____ PAVEMENT - RIGID PILE - BRIDGE PILLAR OR MISCELLANEOUS POST \bigcirc TRAFFIC SIGN AND POST WALL - BRICK OR BLOCK 00000 WALL - STONE

NATURAL ROADSIDE FEATURES								
	GRASS LAWN							
ancancanca	HEDGEROW OR THICKET							
MARSH BOUNDARY LINE								
*	TREE - CONIFEROUS							
	TREE - DECIDUOUS							
£	TREE STUMP							
©	SHRUBBERY							
WL	DELINEATED WETLAND BOUNDARY LINE							
	WOODS LINE BOUNDARY							

RIGHT-OF-WAY SYMBOLS
PROPERTY MARKER - CONCRETE MON.
PROPERTY MARKER - IRON PIPE
HISTORIC RIGHT-OF-WAY BASELINE
EXISTING RIGHT-OF-WAY
EXISTING PROPERTY LINE
EXISTING EASEMENT
EXISTING DENIAL OF ACCESS
EXISTING R/W & DENIAL OF ACCESS

SURVEY C	ONTROL & MONUMENTATION
В.М.	SURVEY BENCHMARK LOCATION
T.P.	SURVEY TIE POINT LOCATION
Δ	SURVEY TRAVERSE POINT
0	POINT OF CURVATURE OR TANGENCY
<u> </u>	POINT OF INTERSECTING TANGENTS

\triangle	SURVEY TRAVERSE POINT	
0	POINT OF CURVATURE OR TANGENCY	
0	POINT OF INTERSECTING TANGENTS	
2	UTILITY	
•	SOIL BORING LOCATION	
•	UTILITY TEST HOLE LOCATION	
M	CABLE TV DISTRIBUTION BOX	
©	ELECTRIC MANHOLE	
EM	ELECTRIC METER	
E	ELECTRIC TRANSFORMER	
	POLE MOUNTED LUMINAIRE	
©	GAS MANHOLE	
G _. M.	GAS METER	
G.V.	GAS VALVE	
G.P.	GAS PUMP - SERVICE STATION	
	RAILROAD TRACKS	
\$	SANITARY SEWER MANHOLE	
S.V.	SANITARY SEWER VALVE	
VENT	SANITARY SEWER VENT OR CLEANOUT	
S.D.F.	SEPTIC DRAIN FIELD	
В	TELEPHONE BOOTH	
T	TELEPHONE MANHOLE	
I	TELEPHONE TEST POINT	
J.W.	TRAFFIC - CONDUIT JUNCTION WELL	
©	TRAFFIC - LIGHT POLE AND BASE	
•	TRAFFIC - PEDESTRIAN POLE & BASE	
9	TRAFFIC - SIGNAL CABINET & BASE	
⊗	TRAFFIC - SIGNAL POLE AND BASE	
U	UTILITY BOX	
0-≯	UTILITY POLE GUY WIRE ANCHOR	
Ø	UTILITY POLE	
F.H.	WATER - FIRE HYDRANT	
W.M.	WATER METER	
w.v.	WATER VALVE	
WELL	WELL HEAD	
?	MANHOLE - UNDETERMINED OWNER	
1171117	Y COMPANY FACILITIES	

UTILITY COMPANY FACILITIES			
CU-G	CHESAPEAKE UTILITIES		
ESNG-G-	EASTERN SHORE N <mark>atur</mark> al Gas		
——DP-E——	DELMARVA POWER - ELECTRIC		
VER-C	VERIZON		
VER-AB	VERIZON - ABANDON <mark>ED</mark>		
——EX-SIG——	DELDOT SIGNAL CONDUIT		

PROPOSED SYMBOLS

	CONSTRUCTION		IDENTIFIERS
	CONCRETE SAFETY BARRIER - PERMANENT	(A)	ADJUST BY CONTRACTOR
×	BIOFILTRATION SWALE	(A)	ADJUST BY OTHERS
	BRICK PATTERNED SURFACE	B	CONCRETE SAFETY BARRIER
	BUTT JOINT	©	CURB OR CURB & GUTTER
100+00	CONSTRUCTION BASELINE	<u>CIB</u>	CONVERT TO JUNCTION BOX
CSF	CONSTRUCTION SAFETY FENCE	<u>CMP</u>	CONVERT TO DRAINAGE MANHOLE
	CURB, TYPE 1 & TYPE 3	(c)	CURB OPENING
	CURB, TYPE 2	<u>CR</u>	CURB RAMP / TYPE
	CURB & GU <mark>TTER</mark> , TYPE 1	(CR-N)	CURB RAMP / TYPE - WITHOUT SIDEWALK SURFACE DETECTABLE WARNING SYSTEM
	CURB & GUTTER, TYPE 2	(SP)	CONSTRUCTION SAFETY FENCE
	CURB & GUTTER, TYPE 3	(D)	DRAINAGE INLET
	CURB & GUTTER, TYPE 4	(OND)	DO NOT DISTURB
	CURB OPENING	(P)	ENERGY DISSIPATOR
—— cz ——	CLEAR ZONE	(£)	FENCE
•	DRAINAGE INLET	(ES)	FLARED END SECTION
xx	DITCH	FFC	FILL WITH FLOWABLE FILL
o—o—	FENCE - METAL	FS	FILTRATION STRUCTURE
•	FENCE - WOOD	<u>GR</u>	GUARDRAIL
	FLARED END SECTION	JB	JUNCTION BOX
Å Å å	GUARDRAIL, TYPE 1	MH	MANHOLE
<u> </u>	GUARDRAIL, TYPE 2	M	MONUMENT - RIGHT-OF-WAY
<u> </u>	GUARDRAIL, TYPE 3	P	PIPE
Cn h h	GUARDRAIL END ANCHORAGE	RLC	RELOCATE BY CONTRACTOR
	GUARDRAIL END TREATMENT, TYPE 1	(RL O	RELOCATE BY OTHERS
« سيد	GUARDRAIL END TREATMENT, TYPE 2	(RM)	REMOVE BY CONTRACTOR
	GUARDRAIL END TREATMENT, TYPE 3	RM	REMOVE BY OTHERS
	IMPACT ATTENUATOR	(ID)	UNDERDRAIN / LENGTH
	JUNCTION BOX - DRAINAGE	<u>w</u>	UNDE <mark>RDRA</mark> IN OUTLET PIPE
LO	LATERAL OFFSET		LANDCOADINO

	LA <mark>NDS</mark> CAPING
<u>(IS</u>)	LANDSCAPE PLANTINGS
	SHRUBBERY
\otimes	CONIFEROUS TREE
\odot	DECIDUOUS TREE

TRAFFIC		
ITMS-CON	ITMS CONDUIT	
SIG-CON	SIGNAL CONDUIT	
	CONDUIT JUNCTION WELL	
	LUMINAIRE	
→	PAVEMENT MARKINGS	
	PAVEMENT STRIPING	
	TRAFFIC SIGN	

PAVEMENT SECTION(S)
RECONSTRUCTED PAVEMENT 2" BITUMINOUS CONCRETE PAVEMENT, TYPE C, 160 GYRATION
PG 70-22, (NON-CARBONATE STONE) - ITEM 401830 3" BITUMINOUS CONCRETE PAVEMENT, TYPE B, 160 GYRATIONS, PG 70-22 - ITEM 401813

6" BITUMINOUS CONCRETE BASE COURSE,

160 GYRATIONS, PG 64-22 - ITEM 401819 8" GABC, TYPE B - ITEM 302007

DELAWARE
DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

NOT TO SCALE

-----LOC----- LIMIT OF CONSTRUCTION

MAILBOX

MANHOLE

PAVEMENT REMOVAL - TOPSOIL, SEED AND MULCH

RIPRAP

UNDERDRAIN

---- PE--- PROPOSED PERMANENT EASEMENT

--- TCE --- TEMPORARY CONSTRUCTION EASEMENT

100+00

PAVEMENT PATCH

P.C.C. SIDEWALK - 4"

UNDERDRAIN OUTLET

PIPE & DIRECTIONAL FLOW ARROW

P.C.C. SIDEWALK 8" - ITEM 705005 OVER 8" GABC

RIGHT-OF-WAY SYMBOLS

PROPOSED DENIAL OF ACCESS

PROPOSED RIGHT-OF-WAY MONUMENT

PROPOSED RIGHT-OF-WAY BASELINE

TASK 3 - HEP SC, US113 AT MILLSBORO TOWNE SQUARE/ **1ST STREET**

CONTRACT	BRIDGE NO.	NA	
T201600901	DECIONED DV	1 12 1	
COUNTY	DESIGNED BY:	ANM	
SUSSEX	CHECKED BY:	JLC	

TOTAL SHTS

GENERAL NOTES

1. THIS PROJECT IS TO BE CONSTRUCTED IN ACCORDANCE WITH THE DELAWARE DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS", DATED AUGUST 2001 AND THE DELAWARE DEPARTMENT OF TRANSPORTATION "STANDARD CONSTRUCTION DETAILS", DATED 2001, INCLUDING ALL REVISIONS UP TO THE DATE OF ADVERTISEMENT.

2.		
∠.	EROSION POTENTIAL FOR THIS PROJECT	CONTRACTOR ESC SUPERVISOR REQUIREMENT
	() INSIGNIFICANT	NONE
	(X) MINOR	CONTRACTOR TRAINING PROGRAM, AS DEFINED IN SECTION 6.2 OF THE DELAWARE SEDIMENT AND STORMWATER REGULATIONS.
	() MEDIUM	CONTRACTOR TRAINING PROGRAM, AS DEFINED IN SECTION 6.2 OF THE DELAWARE SEDIMENT AND STORMWATER REGULATIONS.
	() MAJOR	CERTIFIED CONSTRUCTION REVIEWER (CCR), AS DEFINED IN SECTION 6.3 OF THE DELAWARE SEDIMENT AND STORMWATER REGULATIONS.

3. ELECTRONIC PROJECT FILES THAT WILL BE MADE AVAILABLE TO THE AWARDED CONTRACTOR, INCLUDE:

()	NONE
(X)	ASCII DATA FILES WITH COORDINATES AND ELEVATIONS FOR PROPOSED POINTS AS SELECTED BY THE ENGINEER.
(X)	ALL PLAN SHEETS, IN PDF FORMAT.
()	EXISTING DIGITAL TERRAIN MODEL, IN .DTM FILE FORMAT, COMPATIBLE WITH SOFTWARE CURRENTLY USED BY DELDOT.
()	PROPOSED DIGITAL TERRAIN MODEL, IN .DTM FILE FORMAT <mark>, COMP</mark> ATIBLE WITH SOFTWA <mark>RE CU</mark> RRENTLY U <mark>SED</mark> BY DELDOT.
()	DESIGN FILE, IN .DGN FILE FORMAT, CONTAINING ONLY THE P <mark>ROPOSED 3D TRIANGLES</mark> OF THE PROPOS <mark>ED DI</mark> GITAL TERRAIN MODEL (DTM).

NOTE: THE DOCUMENT ENTITLED "RELEASE FOR DELIVERY OF DOCUMENTS IN ELECTRONIC FORM TO A CONTRACTOR" MUST BE SIGNED BY ALL PARTIES PRIOR TO THE DELIVERY OF ANY ELECTRONIC PROJECT FILES.

4. PROJECT FILES THAT WILL BE MADE AVAILABLE TO THE CONTRACTOR, INCLUDE:

()	CROSS SECTIONS
()	RIGHT-OF-WAY PLANS (WILL BE MADE AVAILABLE TO THE AWARDED CONTRACTOR)

5. AMERICAN TRAFFIC SAFETY SERVICES ASSOCIATION (ATSSA) CERTIFIED TRAFFIC CONTROL SUPERVISOR REQUIREMENT FOR THIS PROJECT.

()	THE CONTRACTOR SHALL NOT BE REQUIRED TO HAVE AN ATSSA SUPERVISOR ASSIGNED TO THIS PROJECT.
(X)	THE CONTRACTOR SHALL HAVE AN ATSSA SUPERVISOR ASSIGNED TO TH <mark>IS PR</mark> OJECT. THE CONTRACTOR'S GENERAL SUPERINTENDENT FOR THIS PROJECT OR ANOTHER ATSSA CERTIFIED MEMBER OF THE CONTRACTOR'S PROJECT STAFF MAY BE THE ATSSA SUPERVISOR. PAYMENT FOR ATSSA SUPERVISOR IS INCIDENTAL TO ITEM 743000.
()	THE CONTRACTOR SHALL HAVE AN ATSSA SUPERVISOR ASSIGNED TO THIS PROJECT. THE ATSSA SUPERVISOR'S SOLE JOB SHALL BE SUPERVISION OF THE INSTALLATION, OPERATION AND MAINTENANCE OF TRAFFIC CONTROL DEVICES FOR THIS PROJECT. THE CONTRACTOR'S GENERAL SUPERINTENDENT FOR THIS PROJECT SHALL NOT BE THE ATSSA SUPERVISOR. PAYMENT FOR ATSSA SUPERVISOR SHALL BE PAID FOR UNDER ITEM 743031.

- 6. THE DISTURBED AREA FOR THIS PROJECT IS 3.78 ACRES.
- 7. THE SEDIMENT AND STORMWATER MANAGEMENT PLANS HAVE BEEN APPROVED BY DELDOT'S STORMWATER ENGINEER UNDER DELDOT'S DELEGATED AUTHORITY. THE SEDIMENT AND STORMWATER MANAGEMENT PLANS ARE VALID FOR A THREE YEAR PERIOD, BEGINNING ON THE DATE THE STORMWATER ENGINEER SIGNED THE CONSTRUCTION TITLE SHEET. IF THE FINAL ACCEPTANCE OF THE PROJECT IS ANTICIPATED TO EXTEND BEYOND THE THREE YEARS, THE CONTRACTOR WILL INFORM THE ENGINEER THREE MONTHS PRIOR TO THE EXPIRATION OF THE APPROVED SEDIMENT AND STORMWATER MANAGEMENT PLANS. THE STORMWATER ENGINEER WILL REVIEW THE CURRENT SEDIMENT AND STORMWATER MANAGEMENT PLAN AND ISSUE AN EXTENSION WITH ANY APPROPRIATE MODIFICATIONS.

PROJECT NOTES

SECTION 100

1. ANY DAMAGE TO ITEMS NOTED TO BE RELOCATED OR RESET BY THE CONTRACTOR, AT THE DISCRETION OF THE ENGINEER, SHALL BE REPAIRED AND/OR REPLACED IN KIND AT THE CONTRACTOR'S EXPENSE.

SECTION 200

- 2. THE CONTRACTOR SHALL REMOVE AND RESET ALL MAILBOXES TO MAINTAIN MAIL SERVICE AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL RELOCATE MAILBOXES AS REQUIRED BY THE PROPOSED GEOMETRICS AND AS DIRECTED BY THE ENGINEER. WHEN RELOCATING MAILBOXES IN CURBED SECTIONS, THE FACE OF THE MAILBOX SHALL BE FLUSH WITH THE BACK EDGE OF CURB. WHEN RELOCATING MAILBOXES IN OPEN SECTIONS, THE FACE OF THE MAILBOX SHALL SET BACK 8 INCHES FROM THE EDGE OF THE PAVED SHOULDER. THE BOTTOM OF THE MAILBOX SHALL BE SET 46 INCHES ABOVE THE ROADWAY SURFACE. MAILBOXES LOCATED AT DRIVEWAY ENTRANCES SHALL BE PLACED ON THE FAR SIDE OF THE DRIVEWAY IN THE DIRECTION OF TRAVEL. POSTS BEING RESET IN CONCRETE SIDEWALK SHALL BE PLACED IN AN APPROPRIATE SIZE PVC SLEEVE. COST FOR ALL WORK AND MATERIALS SHALL BE PAID UNDER ITEM 202000 EXCAVATION AND EMBANKMENT.
- 3. THE ENGINEER MAY REQUIRE THE CONTRACTOR TO EXCAVATE TEST PITS ALONG PROPOSED DRAINAGE RUNS, AT POINTS OF POSSIBLE UTILITY CONFLICTS, TO DETERMINE IF A CONFLICT EXISTS. ANY CONFLICTS SHALL BE COORDINATED BY THE CONTRACTOR, WITH THE ENGINEER AND THE UTILITY COMPANY INVOLVED. THE ENGINEER SHALL ULTIMATELY DETERMINE THE SOLUTION TO THE UTILITY CONFLICT. TEST HOLES SHALL BE MEASURED AND PAID FOR IN ACCORDANCE WITH ITEM 202000 EXCAVATION AND EMBANKMENT, BUT ONLY TO THE ACTUAL DEPTH EXCAVATED.

SECTION 300

- 4. A. THE CONTRACTOR MAY ELECT TO USE ANY OF THE FOLLOWING MATERIALS TO MEET THE REQUIREMENTS OF ITEM 302007

 GRADED AGGREGATE BASE COURSE, TYPE 'B':
 - a. CRUSHED STONE (PER STANDARD SPECIFICATION 821)
 - b. CRUSHED CONCRETE (PER STANDARD SPECIFICATION 821)
 - c. HOT-MIX MILLINGS (PER SPECIAL PROVISION 302514 MILLED HOT-MIX BASE COURSE)

THE CONTRACTOR WILL NOT BE ALLOWED TO MIX DIFFERENT MATERIALS (OR SIMILAR MATERIALS FROM DIFFERENT SOURCES) TO MEET THE REQUIREMENTS OF ITEM 302007 - GRADED AGGREGATE BASE COURSE, TYPE 'B'.

ALL OF THE ABOVE LISTED MATERIALS ARE PERMITTED FOR USE ON THE JOB, PROVIDED THEY ARE SEPARATED INTO APPROVED AREAS, EACH AREA OF BASE COURSE MUST BE CONSTRUCTED USING MATERIALS FROM A SINGULAR SOURCE, FULL DEPTH, IN ORDER THAT PROPER TESTING MAY BE ACCOMPLISHED. THE CONTRACTOR AND ENGINEER SHALL AGREE ON THE LIMITS OF EACH SOURCE OF MATERIAL PRIOR TO PLACEMENT.

- B. THE QUANTITY USED FOR BASE OF EACH OF THE ABOVE LISTED MATERIALS WILL BE THE CONTRACTOR'S CHOICE, WITH
 THE TOTAL BEING EQUAL TO THE ACTUAL QUANTITY USED UNDER ITEM 302007 GRADED AGGREGATE BASE COURSE, TYPE 'B'.
- C. THE CONTRACTOR MAY ALSO ELECT TO RECYCLE MILLINGS FOR USE IN HOT-MIX AS PERMITTED BY THE STANDARD SPECIFICATIONS. THE CHOICE OF THE QUANTITY OF MILLINGS USED FOR THIS PURPOSE, OR FOR BASE COURSE, LIES WITH THE CONTRACTOR. ALL EXCESS MILLING MATERIAL SHALL BECOME PROPERTY OF THE CONTRACTOR.
- D. HOT-MIX MILLINGS MAY BE GENERATED FROM THE FOLLOWING SOURCES:
 - a. MATERIAL MADE AVAILABLE WHEN MILLED ON THIS CONTRACT UNDER ITEM 760507.
 - b. MATERIAL MILLED ON THIS CONTRACT AT THE CONTRACTOR'S CHOICE UNDER ITEM 202000.
- C. MILLED MATERIAL FURNISHED ON THE JOB FROM THE CONTRACTOR'S YARD OR OTHER OUTSIDE SOURCE.

 ALL MILLED MATERIALS SHALL MEET THE MATERIAL REQUIREMENTS OF ITEM 302514 MILLED HOT-MIX BASE COURSE.

E. PAYMENT CLARIFICATION:

- a. SHOULD THE CONTRACTOR ELECT TO MILL PORTIONS OF HOT-MIX SHOWN ON THE PLANS TO BE REMOVED UNDER ITEM 202000 EXCAVATION AND EMBANKMENT THE COST OF MILLING THIS HOT-MIX WILL BE PAID AS ITEM 202000 EXCAVATION AND EMBANKMENT. THE MILLINGS GENERATED MAY BE RECYCLED INTO HOT-MIX, UTILIZED FOR BASE COURSE, OR DISPOSED OF TO AN APPROVED SITE. HAULING COSTS FOR DISPOSAL AND/OR RECYCLING ARE INCIDENTAL TO ITEM 202000 EXCAVATION AND EMBANKMENT.
- b. MILLINGS GENERATED UNDER ITEM 760502 PAVEMENT MILLINGS, TAPERCUT MAY BE RECYCLED INTO HOT-MIX,
 UTILIZED FOR BASE COURSE OR DISPOSED OF BY THE CONTRACTOR TO AN APPROVED SITE. NO SEPARATE PAYMENT
 WILL BE MADE FOR TRANSPORTING MILLINGS ON SITE OR TO AN APPROVED DISPOSAL SITE.
- c. SHOULD THE CONTRACTOR ELECT TO TEMPORARILY STOCKPILE MILLINGS ON THE JOB SITE FOR LATER USE, ALL COSTS FOR STOCKPILING AND SUBSEQUENT REHANDLING SHALL BE INCIDENTAL TO ITEM 202000 EXCAVATION AND EMBANKMENT.
- d. MILLINGS USED FOR BASE COURSE SHALL BE PLACED IN ACCORDANCE WITH THE REQUIREMENTS OF SPECIAL PROVISION 302514 MILLED HOT-MIX BASE COURSE. NO SEPARATE PAYMENT WILL BE MADE TO FURNISH MILLINGS FROM AN OUTSIDE SOURCE OR TRANSPORT MILLINGS WITHIN THE PROJECT LIMITS. MILLINGS USED FOR BASE COURSE WILL BE PAID FOR AT THE UNIT BID PRICE FOR ITEM 302007 GRADED AGGREGATE BASE COURSE, TYPE 'B'.
- e. ALL COSTS TO UTILIZE MILLINGS IN RECYCLED HOT-MIX WILL BE INCIDENTAL TO THE UNIT PRICE BID FOR THE HOT-MIX ITEM USING THE RECYCLED MATERIAL.
- 1. SPECIAL PROVISION 302514 MILLED HOT-MIX BASE COURSE IS PROVIDED TO SPECIFY THE MEANS OF LAY DOWN AND COMPACTION AS WELL AS THE MATERIAL REQUIREMENTS FOR MILLINGS USED AS BASE COURSE. ALL COSTS TO BRING THE MILLINGS INTO COMPLIANCE WITH THE REQUIREMENTS OF ITEM 302514 MILLED HOT-MIX BASE COURSE ARE INCIDENTAL TO ITEM 302007 GRADED AGGREGATE BASE COURSE, TYPE 'B'. NO PAYMENT WILL BE MADE FOR ITEM 302514 MILLED HOT-MIX BASE COURSE. THE QUANTITY OF MILLINGS USED FOR BASE COURSE WILL BE PAID FOR UNDER ITEM 302007 GRADED AGGREGATE BASE COURSE.

SECTION 600

5. THE DEPARTMENT AND THE CONTRACTOR SHALL INSPECT ALL EXISTING PIPES AND DRAINAGE STRUCTURES TO BE USED IN THE FINAL DRAINAGE SYSTEM AND AGREE ON THE CONDITION PRIOR TO THE START OF CONSTRUCTION. EXISTING PIPES AND DRAINAGE STRUCTURES DAMAGED DUE TO CONTRACTOR OPERATIONS SHALL BE REPAIRED OR REPLACED IN-KIND AT THE CONTRACTOR'S EXPENSE. THE DEPARTMENT WILL VIDEO INSPECT NEW PIPE RUNS TO CONFIRM CONDITION PRIOR TO ACCEPTANCE. PIPE CLEANING PRIOR TO VIDEO INSPECTION AND MAINTENANCE OF TRAFFIC DURING THE VIDEO INSPECTION ARE THE RESPONSIBILITY OF THE CONTRACTOR AND INCIDENTAL TO THE PIPE ITEM THAT IS BEING VIDEO INSPECTED.

SECTION 700

- 6. IN AREAS WHERE PROPOSED CURB MEETS EXISTING CURB AND THE TWO CURB TYPES ARE NOT SIMILAR, THE PROPOSED CURB SHALL BE TRANSITIONED IN 10 LINEAR FEET, UNLESS OTHERWISE DIRECTED BY THE ENGINEER. PAYMENT FOR THIS WORK, INCLUDING SAW CUTTING EXISTING CURB SHALL BE INCIDENTAL TO THE PROPOSED CURB ITEM.
- 7. PORTLAND CEMENT CONCRETE CHANNELIZING ISLANDS THAT ARE LESS THAN 75 SQ FT MAY BE POURED MONOLITHICALLY, OR AS DIRECTED BY THE ENGINEER.
- 8. STATION AND ELEVATION DATA GIVEN FOR DRAINAGE STRUCTURES ARE TO BE APPLIED TO THE CENTER OF THE GRATE FOR INLETS, AND TO THE CENTER OF THE STRUCTURE FOR JUNCTION BOXES AND MANHOLES.
- PRAINAGE INLET GRATES ADJACENT TO THE ROAD, WITHIN THE PROJECT LIMITS, WHICH ARE NOT TYPE 1 SHALL BE REPLACED.

 THE ACTUAL LOCATIONS, THE NEED FOR ANY GRATE MODIFICATIONS OR FOR NEW FRAMES SHALL BE DETERMINED BY THE ENGINEER. ALL REPLACED GRATES/FRAMES SHALL BE DELIVERED TO THE NEAREST DISTRICT MAINTENANCE YARD WITH THE COST OF DELIVERY INCIDENTAL TO ITEM 708060 REPLACING DRAINAGE INLET GRATE(S). FINAL PAYMENT FOR REPLACED GRATES/FRAMES SHALL NOT BE MADE UNTIL RECEIPT OF DELIVERED MATERIALS IS PRODUCED, SIGNED BY A DELDOT MAINTENANCE YARD SUPERVISOR.
- 10. ALL PAVED AREAS TO BE RECON<mark>STRU</mark>CTED OR WIDENED SHALL BE SAWCUT FULL DEPTH AT THE POINT WHERE THE NEW PAVEMENT IS TO TIE INTO THE EXISTING PAVEMENT.
- 11. ALL WORK REQUIRED FOR CALCULATING AND STAKING OUT OF GRADES SHALL BE PAID FOR UNDER ITEM 763621 -


SECTION 900

12. THIS PROJECT IS COVERED UNDER AN NPDES GENERAL PERMIT FOR CONSTRUCTION. UNDER THE GENERAL PERMIT, COMPLIANCE WITH DELDOT'S APPROVED SEDIMENT AND STORMWATER MANAGEMENT PLANS WILL CONSTITUTE COMPLIANCE WITH THE NPDES INDUSTRIAL PERMITTING REQUIREMENTS FOR THIS CONSTRUCTION PROJECT, A COPY OF THE NPDES GENERAL PERMIT AND NOIS KEPT ON FILE IN EACH OF THE CONSTRUCTION OFFICES AND THE DEPARTMENT'S TEAM SUPPORT SECTION. A COPY OF THE GENERAL PERMIT OR THE NOICAN BE OBTAINED UPON REQUEST FROM EITHER THE DEPARTMENT'S STORMWATER ENGINEER OR THE APPROPRIATE CONSTRUCTION ENGINEER.


MISCELLANEOUS

- 13. THE CONTRACTOR SHALL CONTACT MICHAEL ELLER, THE CHIEF OF SCHEDULING FOR DART FIRST STATE, 14 DAYS PRIOR TO THE START OF CONSTRUCTION AT 302-576-6061.
- 14. THERE ARE NO ENVIRONMENTAL PERMITS ASSOCIATED WITH THIS PROJECT. AS SUCH, AN ENVIRONMENTAL COMPLIANCE SHEET WAS NOT PREPARED.

CONTRACT	BRIDGE NO.	NA						
T001000001								
T201600901	DECICNED DV. ANIM							
COUNTY	DESIGNED BY:	DESIGNED BY: ANM						
SUSSEX	CHECKED BY:	JLC						



ADDENDUMS / REVISIONS



NOTE: NEGATIVE DENOTES LEFT OF BASELINE

CONSTRUCTION ALIGNMENT CONTROL									
PO INT	STATION	OFFSET	NORTHING	EASTING					
60002	126+50.00	0.00′	211881.5769	<i>691842. 1548</i>					
60003	133+50.00	0.00′	212460. 4721	691448. 6064					
	125+00.00	0.00′	<i>211757. 5279</i>	691926. 4866					
	130+00.00	0.00′	212171.0245	<i>691645. 3806</i>					
	135+00.00	0.00′	212584. 5211	691364.2746					

DATUM REFERENCE:

HORIZONTAL - THIS PROJECT IS REFERENCED TO THE DELAWARE STATE PLANE COORDINATE SYSTEM (NAD 83/91).

VERTICAL - THIS PROJECT IS REFERENCED TO NAVD 88.

TASK 3 - HEP SC, US113 AT MILLSBORO TOWNE SQUARE/1ST STREET

CONTRACT	BRIDGE NO.	NA
T201600901	DECIONED BY	1 47 1
COUNTY	- DESIGNED BY:	ANM
SUSSEX	CHECKED BY:	JLC

HORIZONTAL AND VERTICAL CONTROL

SHEET NO.

4


TOTAL SHTS.


11


:\SUSSEX\113\ROAD\T201300302\PLANS\H\

DELAWARE

DEPARTMENT OF TRANSPORTATION







HOLE.

DELAWARE
DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

NOT TO SCALE

TASK 3 - HEP SC, US113 AT MILLSBORO TOWNE SQUARE/1ST STREET

CONTRACT
BRIDGE NO.

T201600901

COUNTY

DESIGNED BY: ANM

CHECKED BY: JLC


CONSTRUCTION DETAILS


SHEET NO.


7

TOTAL SHTS.

11







								SIGN SCH	EDULE									
			SIGN SIGN SIGN			ITEM 749687 SINGLE POST		ITEM 749690 MULTI POST		OST	POST	Code X11	ITEM 749688	ITEM 749689				
# SHEET	PLAN	CODE	QTY. DESCRIPTION	ASSEMBLY NO.	1	HEIGHT	AREA		(EACH)			FNEEDED))	INSTALLATION	12' Post	4" HOLE, 0-6"	4" HOLE, >6"	REMARKS
" NO.	INDICATOR	0022	B20014111014	7 JOSEMBET 143.	(IN)	(IN)	(SF)	SIGN	 REMOVE	INSTALL	SIGN	REMOVE	INSTALL		(W/Basepost)	(EACH)	(EACH)	I CENTER OVE
252 10	2	R3-20-DE	TURN LANE		18"	18"	2.25	DISPOSTION REPOSITION	1	1	DISPOSTION		55 55 57 57		Π	Π	n	
328 10	5	W2-2_L(36)	SIDE ROAD (Perpendicular - Left) - 36x36		36"	36"	2.20 Q	RENEW	<u> </u>	1 1					Ο Π	0	0	
4 10	<u></u>	R1-1(36)	STOP		36"	36"	<u> </u>	REMAIN	<u> </u>	<u> </u>					<u> </u>	0 N	n	
4 10		R1-1(36)	1 STOP		36"	36"	q	REPOSITION	<u> </u>	1					Π	<u> </u>	n	
1 41 10	<u> </u>	R7-107-DE(18			18"	24"		REMAIN	<u> </u>	'					Π	<u> </u>	n	
395 10	7	R6-1_L(54)	1 NE WAY (ENCLOSED IN LEFT ARROW) - 54x		54"	18"	6.75	REPOSITION	1	1					Π	n o	ň	
4 10	8	R1-1(36)	1 STOP		36"	36"	9	REPOSITION		' 						n	ñ	
52 10	9	R3-20-DE	1 TURN LANE		18"	18"	2.25	RENEW	1	1					Λ	n	n	
52 10	<u>-</u> 10	R3-20-DE	TURN LANE		18"	18"	2.25	REPOSITION	1	i			20 00 00 00 00 00 00 00 00 00 00 00 00 0		Ū	 0	0	
63 10	11	R5-1a(42)	WRONG WAY - 42x30		42"	30"		REMAIN	-						0		Ō	
9 10	12	R5-1(36)	DO NOT ENTER - 36x36		36"	36"	9	REPOSITION	-	1			9		0	0	0	
35 10	13	R6-1_L(54)	1 NE WA <mark>Y (EN</mark> CLOSED IN LEFT ARROW) - <mark>54x</mark>	18	54"	18"	6.75	REPOSITION	1	1					0	0	0	
4 10	14	R1-1(36)	1 STOP Í		36"	36"	9	REPOSITION							0	0	0	
59 10	15	R5-1(36)	1 DO NOT ENTER - 36x36		36"	36"		REMAIN							0	0	0	
3 10	16	R6-1_R(54)	1 NE WAY (ENCLOSED IN RIGHT ARROW) - 54:	×18	54"	18"		REMAIN							0	0	0	
2 10	17	R3-20-DE	1 TURN LANE		18"	18"	2.25	REPOSITION	1	1					0	0	0	
24 10	18	R7-4-DE(18)	1 D STOP <mark>PING,</mark> STANDING, O <mark>R PA</mark> RKING - <mark>18x</mark>	ć24	18"	24"		REMAIN					30 00 00 00 00 00 00 00 00 00 00 00 00 0		0	0	0	
46 10	19	R7-201P_B	1 TOW AWAY ZONE (plaque - black)		12"	6"		REMAIN					900		O	0	0	
59 10	20	R5-1(36)	1 DO NOT ENTER - 36x36		36"	36"		REMAIN							0	0	0	
78 10	21	W3-3(48)	1 SIGNAL AHEAD (Symbol) - 48x48		48"	48"		REMAIN							0	0	0	
24 10	22	EM-1-DE	1 EVACUATION ROUTE		24"	24"		REMAIN					90 90 90 90 90 90 90 90 90 90 90 90 90 9		0	0	0	
19 10	23	M6-3(21)	1 DIRECTIONAL ARROW (Up) - 21x15		21"	15"		REMAIN							0	0	0	
78 10	24	W3-3(48)	1 SIGNAL AHEAD (Symbol) - 48x48		48"	48"		REMAIN							0	0	0	
56 10	25	R4-18(36)	1 DO NOT PASS ON SHOULDER - 36x48		36"	48"	12	NEW		1					1	0	0	
24 10		R7-4-DE(18)	1 D STOPPING, STANDING, OR PARKING - 18x	(24	18"	24"	3	RENEW	1	1					Ō	0	0	
46 10	27	R7-201P_B	1 TOW AWAY ZONE (plaque - black)		12"	6"	0.5	RENEW							0	0	0	
24 10	28	R3-5_R	1 NDATORY MOVEMENT LANE CONTROL (Ri	ight)	30"	36"	7.5	NEW		1					1	0	0	
59 10	30	R5-1(36)	1 DO NOT ENTER - 36x36		36"	36"	9	NEW		1					1	0	0	
59 10	37	R5-1(36)	1 DO N <mark>OT E</mark> NTER - 36x36		36"	36"	9	NEW		1					1	0	0	
59 10	38	R5-1(36)	1 DO NO <mark>T EN</mark> TER - 36x36		36"	36"	9	NEW		1					- 1	0	0	
33 10	39	R6-1_R(54)	1 NE WAY (ENCLOS <mark>ED IN</mark> RIGHT A <mark>RROW) - 5</mark> 4:	x18	54"	18"	6.7 <mark>5</mark>	NEW		1					1	0	0	
																0	0	
															<u>[</u>	0	0	
															0	Ü	U	
															U	U	U	
															U	U	U	
															U	U	U	
															U	U	U	
$\overline{}$															U	U	U	
													50 S		U	U	U	
			PAGE TOTALS				124.25	i	10	16		0	0		6	0	0	



DELAWARE DEPARTMENT OF TRANSPORTATION

ADDENDUMS / REVISIONS

TASK 3 - HEP SC, US113 AT MILLSBORO TOWNE SQUARE/1ST STREET

CONTRACT	BRIDGE NO.	NA					
T001600001	5, W9 0 2 1, 10 4	14/4					
T201600901	DECIONED DV- ANIM						
COUNTY	DESIGNED BY:	AINIVI					
SUSSEX	CHECKED BY:	JLC					

SIGNING, STRIPING AND CONDUIT PLAN

TOTAL SHTS.