

STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION



BID PROPOSAL

CONTRACT T202201102

US 13 SOUTHBOUND BBRT LANE

FTA Funding No. 5307-2022(08)
FTA is providing 100 % of funding for this project
CFDA: 20.507

Advertisement Date: November 7, 2025

INCLUDED IN THIS DOCUMENT:

BID PROPOSAL:

GENERAL DESCRIPTION
PROSPECTIVE BIDDERS NOTES
GENERAL NOTICES
PREVAILING WAGES
SPECIAL PROVISIONS
STATEMENTS
QUANTITY SHEET SUMMARY

ADDITIONAL BID PROPOSAL ITEMS:

ATTACHED OR POSTED DOCUMENTS:

PROJECT PLANS
QUESTIONS & ANSWERS (if posted)
BIDDERS LIST

**PAPER BIDDERS CONTACT DELDOT
FOR BID SUBMITTAL DOCUMENTS:**

DRUG TESTING AFFIDAVIT
CERTIFICATION FORM
BID BOND FORM
CD FOR BID PRICE ENTRY & PRINTING
BIDDERS LIST

This Bid Proposal and related documents can be viewed on bids.delaware.gov and, for subscribers bidx.com/de/

Internet Bids for Bidders with Bid Express® accounts can be submitted at [BIDX.com/de](https://bidx.com/de/); **OR**;
Paper Bids with CD will be received in the Bidder's Room at the DelDOT Administration Building, Dover, DE;
ALL BIDS DUE PRIOR TO 2:00 P.M. Local Time, DECEMBER 9, 2025

GENERAL DESCRIPTION

A. BIDS DUE: DECEMBER 9, 2025 PRIOR TO 2:00 P.M. Local Time – unless changed via Addendum.

BIDS MUST BE SUBMITTED VIA:

(a) **Internet** - Bidders with DelDOT Bid Express® accounts can submit bids at www.bidx.com/de/.

OR:

(b) **Paper Bid Delivered To:** Delaware Department of Transportation, Administration Building
North Entrance, Bidders Room, 800 Bay Road, Dover, DE 19901

For paper bids, contact DelDOT at dot-ask@delaware.gov or (302) 760-2031 to request a CD for bidding, required forms, and instructions. Bidders enter their Bid Item prices onto the supplied CD then print the form and deliver in a sealed envelope; the Bid Form, completed CD, and required documents prior to the Bid due date and time.
(CD's cannot be used to submit bids to bidx.com)

Do not submit both Internet and Paper Bids. If so, the Internet bid and documents will be rejected.

BID OPENING: Bids will be publicly opened and read aloud at the Date and Time of the Bid Opening. The Bid Opening will be held at the 'Paper Bid Delivered To' address shown above. Bidder bears the risk of late delivery, bids received after the stated time will be returned unopened.

REVISED ←

Attendance is not required. DelDOT offers a call-in number to hear the Bid Opening telephonically. The telephone number to call is (302) 504-8986.

When prompted, enter Meeting number (access code): 651 529 280#

It is anticipated the telephone access information will remain the same for all Bid Openings.

B. PRE-BID MEETING: No

C. DBE GOAL: 0% Disadvantaged Business Enterprise Percent.

Pursuant to the Interim Final Rule ("IFR") issued by the United States Department of Transportation ("U.S. DOT") on September 30, 2025, this letting does not have a DBE participation goal as all DelDOT DBEs were decertified by the IFR. DelDOT is undertaking the recertification process for DBEs pursuant to the IFR requirements. As DelDOT currently has no certified DBEs, it is not feasible to impose or enforce a DBE participation goal for this letting. Upon completion of DelDOT's DBE recertification process, or upon any modification of the IFR, whether through amendment, clarification, or judicial action, DelDOT reserves the right to revise or reestablish a DBE participation goal for this letting as may be directed by the U.S. DOT and in accordance with applicable federal regulations.

D. OJT TRAINEES: n/a

E. LOCATION: New Castle County

These improvements are more specifically shown on the Location Map(s) of the attached Plans.

F. DESCRIPTION: The improvements consist of furnishing all labor and materials to implement a Bus-Bike-Right-Turn (BBRT) lane on southbound US 13 from I-495 to Bacon/Boulden Boulevard. Follow other incidental construction in accordance with the location, notes and details shown on the plans, and as directed by the Engineer.

G. BUY AMERICA REQUIREMENTS APPLY – Build America, Buy America Act, refer to 'FEDERAL TRANSIT ADMINISTRATION PROVISIONS.

H. COMPLETION TIME: All work on this contract must be complete within 124 Calendar Days.

Extensions of contract time due to weather are specified in the Standard Specifications Section 108.7F, weather days. It is estimated a Notice to Proceed is issued such that work starts on or about February 23, 2026.

I. SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, DELAWARE DEPARTMENT OF TRANSPORTATION, JANUARY 2024 apply to this Bid Proposal and Project. The Contractor shall make himself aware of any revisions and corrections and apply them to the applicable item(s) of this contract. The Standard Specifications can be viewed [here](#). Units of Measure can be found at 101.4.

J. ATTACHMENTS: Included as part of this Bid Proposal are; *Project Plans; Questions & Answers* (if posted); *Addenda* (if issued), *Referenced Documents, Documents Posted with this Bid Proposal*; and *Bid documents mailed to contractors*.

K. ADDENDA: All Addenda are posted on the internet at bids.delaware.gov, and www.bidx.com/de/ and are included as part of the Bid Proposal. The Bidder is responsible to check the Website as needed to ensure that the Bidder is aware of Addenda that are included in the Bid Proposal. If Addenda are issued, the final Addendum will be posted no later than the end of the day two business days prior to the bid date. Each Addendum number and issue date must be entered on the submitted Certification Form. This original Bid Proposal will not be updated, you must refer to each Addendum.

L. QUESTIONS: E-MAIL TO: dot-ask@delaware.gov
 Questions regarding this project are to be e-mailed to the above address no less than **six business days** prior to the bid opening date to receive a posted response. Please include the Contract number in the subject line. Questions and responses are posted at bids.delaware.gov, and bidx.com/de/. The date of the final posted Questions and Answers document must be entered on the submitted Certification Form.

M. ROAD USER COSTS:

The Maintenance of Traffic Plans for Contract T202201102 has Road User Costs associated with lane closures along US 13. As detailed in the plans, all work requiring lane closures along US 13 must be completed during allowable lane closure hours as identified in the Allowable Lane Closure Hour Matrices in the Maintenance of Traffic Plans.

Interim Road User Costs (RUC) for delays in opening lanes on US 13 NB and SB will be enforced per 15- minutes per lane closed. The Interim Road User Costs (RUC) established will be **\$3,500.00 per 15 minutes per lane closed** beyond the allowable lane closure hours, Monday through Sunday.

For every hour, or portion thereof, after the allowable lane closure hour, the following RUC will be assessed:

Lane(s) Closed beyond X:59 am/pm*	Additional Contractor Damages for Failure to Reopen Lanes beyond X:59 am/pm
(X+1):00 AM/PM	+\$3,500.00 per 15 Minutes per Lane

*See Allowable Lane Closures Matrices in the Maintenance of Traffic Plans for Contract T201901104.

Assessment of Road User Costs will be made through Item 736525: Road User Cost. There is no limit on the number of days that RUCs can be assessed. The Engineer will be the sole approving authority as to when lane closures are complete after traffic is returned to the unrestricted travel.

All vertical differences as determined by the DE MUTCD along the shoulder shall be addressed prior to opening the roadway to traffic. The Contractor will be assessed the Road User Costs for failure to open the roadway on time per the Contract.

Example Calculations for Assessment of Road User Cost

1) After 6:59 AM on Tuesday US 13 NB at Station 500+00:

One Lane closure on US 13 NB at Station 500+00 until 8:08 AM on a Tuesday, Verizon time: A RUC of

\$3,500.00 per 15-minute per lane will be assessed.

Lane Closure RUC from 7:00 am to 8:08 am on US 13 NB at Station 500+00

7:00 AM to 7:14 AM	\$3,500.00
7:15 AM to 7:29 AM	\$3,500.00
7:30 AM to 7:44 AM	\$3,500.00
7:45 AM to 7:59 AM	\$3,500.00
8:00 AM to 8:14 AM	\$3,500.00
Total	\$17,500.00

2) After 4:59 AM on Tuesday US 13 NB at Station 500+00:

Three Lane closure on US 13 NB at Station 500+00 until 6:08 AM on a Tuesday, Verizon time: A RUC of \$3,500.00 per 15-minute per lane will be assessed.


Lane Closure RUC from 5:00 am to 6:08 am on US 13 NB at Station 500+00

5:00 AM to 5:14 AM	\$3,500.00
5:15 AM to 5:29 AM	\$3,500.00
5:30 AM to 5:44 AM	\$3,500.00
5:45 AM to 5:59 AM	\$3,500.00
6:00 AM to 6:14 AM	\$7,000.00
Total	\$21,000.00

N. FLAGGERS:

- A. Included in the Bid Proposal are the prevailing wages for highway construction as determined by the Department of Labor of the State of Delaware in accordance with [Title 29 Del. C. §6960](#), relating to wages and the regulations implementing that Section.
- B. Flaggers must be bid at a minimum equal to the Laborer wage rate and may be bid up to, but not to exceed, 3 times the Laborer wage rate in accordance with the County where the Work is being performed.
- C. The Department will adjust the bid to the minimum for prices bid below the minimum acceptable bid and to the maximum for prices bid above the maximum allowable bid prior to award of the Contract.
 - 1. Flagger overtime must be bid at minimum of 1.45 times and may be bid up to a maximum of 4.35 times, the Laborer wage rate in accordance with the County where the Work is being performed.
 - 2. When a Contract for a Project contains both Federal Davis-Bacon and State of Delaware prevailing wage standards, the employer’s minimum wage obligations are determined by whichever standards are higher.
- D. Overtime:
 - 1. Payment for overtime will be considered on a weekly basis for time worked in excess of 40 hours for a continuous 7-day period beginning Monday and ending Sunday inclusive.
 - 2. Time worked on other Projects or Work activities other than flagging will not be counted in the normal 40 hours or the overtime.
- E. The cost of the flagging operation when performed by others who are not the Contractor’s employees will not be included in the 50% subcontracting limit as outlined in Section 108.1.

O. PROSPECTIVE BIDDERS NOTES:

- 1. **BIDDERS MUST BE REGISTERED** with DelDOT in order to submit a bid. Registrations are now completed online through SimpliGov. To complete registration or for more information, click [here](#). **REVISED** 
- 2. **SURETY BOND** - Each proposal must be accompanied by a deposit of either surety bond or security for a sum equal to at least 10% of the amount bid.
- 3. **DELAWARE’S CONTRACTOR REGISTRATION ACT** - 19 Del.C. §§ 3601 *et seq*, requires all contractors and subcontractors to register with the Delaware Department of Labor before performing construction services or maintenance. Refer to the GENERAL NOTICES section for further information.

4. **DRUG TESTING** - Regulation 4104; The state Office of Management and Budget has developed regulations that require Contractors and Subcontractors to implement a program of mandatory drug testing for Employees who work on Large Public Works Contracts funded all or in part with public funds pursuant to 29 Del.C. §6908(a)(6). **Refer to the full requirements at the following link:**

<http://regulations.delaware.gov/register/december2017/final/21%20DE%20Reg%20503%2012-01-17.htm>

Note a few of the requirements;

- * At bid submission - Each bidder must submit with the bid a single signed affidavit certifying that the bidder and its subcontractors has in place or will implement during the entire term of the contract a Mandatory Drug Testing Program that complies with the regulation (*a blank affidavit form is attached*);
 - * At least two business days prior to contract execution - The awarded Contractor shall provide to DelDOT copies of the Employee Drug Testing Program for the Contractor, each participating DBE firm, and all other listed Subcontractors;
 - * Subcontractors - Contractors that employ Subcontractors on the job site may do so only after submitting a copy of the Subcontractor's Employee Drug Testing Program along with the standard required subcontractor information. A Subcontractor shall not commence work until **DelDOT** has approved the program in writing.
5. **PERFORMANCE-BASED RATING SYSTEM** - 29 Del.C. §6962 (c)(12)(a) requires DelDOT to include a performance-based rating system for contractors. The Performance Rating for each Contractor shall be used as a prequalification to bid at the time of bid. Refer to 'General Notices' for details.
6. **NO RETAINAGE** will be withheld on this contract unless through the Performance-Based Rating System.
7. **EXTERNAL COMPLAINT PROCEDURE** can be viewed on DelDOT's Website, [Contractor Compliance/EEO - Delaware Department of Transportation](#) or request a copy by calling (302) 760-2555.

REVISED



8. **DBE PROGRAM REQUIREMENTS** As a result of the Issuance of the IFR on September 30, 2025, all of DelDOT DBEs were decertified. DelDOT is undertaking the recertification process for DBEs pursuant to the IFR requirements. As DelDOT currently has no certified DBEs, it is not feasible to require the submission of a DelDOT DBE Project Participation Affidavit for this letting. Companies bidding on this letting are NOT required to submit a DBE Project Participation Affidavit with their bid. Once DelDOT has recertified DBEs using the IFR requirements, this requirement will be reinstated.

REVISED



9. **DELDOT CERTIFIED DBE UTILIZATION COMMITMENT STATEMENT** As a result of the Issuance of the IFR on September 30, 2025, all DelDOT DBEs were decertified. DelDOT is undertaking the recertification process for DBEs pursuant to the IFR requirements. As DelDOT currently has no certified DBEs, it is not feasible to require the submission of a DelDOT Certified DBE Utilization Commitment Statement for this letting. Companies bidding on this letting are NOT required to submit a DelDOT Certified DBE Utilization Commitment Statement with their bid. Once DelDOT has recertified DBEs using the IFR requirements, this requirement will be reinstated.

10. **FLATWORK CONCRETE TECHNICIAN CERTIFICATION TRAINING:**

Section 501.3, 503.3, 505.3, 610.3, 701.3 and 702.3 of the 2024 Standard Specifications require contractors to provide an American Concrete Institute (ACI) or National Ready-Mix Concrete Association (NRMCA) certified concrete flatwork technician to supervise all finishing of flatwork concrete.

11. **SIGNAGE LANGUAGE:**

In order to maintain effective communication with the traveling public, only place signs, banners, flags, or other displays within the projects limits that meet the requirements of the latest version of the Delaware Manual on Uniform Traffic Control Devices. Any signs or other materials which deviate from the MUTCD, must be preapproved by the Engineer. The only signage and materials which may be displayed upon vehicles and equipment within the Project area are signs

denoting the name of the Contractor and any subcontractors and other signs and/or materials required and approved pursuant to the MUTCD and the Engineer. Contractor shall immediately remove any signs or materials within the Project that does not meet these requirements immediately upon notification by the Engineer. Failure to remove signs or other materials following notification from the Engineer will result in Liquidated Damages being assessed in the manner and amount specified in the Standard Specifications section 108.9.A.

REVISED ←

12. Bidders List Requirement:

Under [49 CFR 26.11](#) DelDOT must collect bidders list information from **ALL** contractors and subcontractors who seek to work on federally assisted contracts. The submitted information must be complete and must include the required information for the prime and all (DBE and non-DBE) subcontractors, service providers, manufacturers, distributors, and suppliers.

ALL bidders must complete the [Bidders List Form](#) (attached as an exhibit) and submit it at the time of bid. Late submission of this information will not be accepted. Submitted information must include the following for those being proposed to work on the contract if awarded:

- Firm name;
- Firm address including ZIP code;
- Firm's status as a DBE or non-DBE (SEE NOTE BELOW effective 10-1-2025);
- NAICS code applicable to each scope of work the firm sought to perform in its bid;
- Age of the firm; and
- The annual gross receipts of the firm shown as an approximate range (i.e., \$1-3 million)

This information will be maintained as confidential to the extent allowable by federal and state law.

NOTE: Based upon the IFR issued September 30, 2025, all DelDOT certified DBEs have been decertified. As such, for this letting, bidders should NOT identify in the bidders list whether a proposed contractor or subcontractor is a DBE as no companies have currently been certified as a DBE under the new IFR requirements. That block should be left blank. Bidders will be advised once DBE's have been re-certified pursuant to the requirements of the IFR at which time bidders will be required to provide this information.

Additionally, pursuant to the IFR, and the guidance letter issued by U.S. DOT on September 30, 2025, DelDOT has been directed not to use of race or sex as presumptions for consideration of a company as a DBE. As such, bidders should NOT identify in the bidders list a proposed contractor or subcontractor's sex or race. Those blocks should be left blank. DelDOT anticipates providing a revised Bidders List Form in the near future, which contains only those sections required by the IFR.

Failure to submit the required bidders list documentation at the time bid will result in the bidder being deemed non-responsive and therefore ineligible for award of the contract.

13. FTA Requirements are posted and must be signed and submitted with your bid.

- end -

remainder of page is blank

GENERAL NOTICES

CONTRACTOR REGISTRATION ACT

On July 1, 2021, the Contractor Registration Act, as codified in 19 Del.C. §§ 3601 *et seq*, took effect. This law requires all contractors to register with the Delaware Department of Labor before performing construction services or maintenance. The Contractor Registration Act applies to all contractors that engage in construction and maintenance within the State of Delaware. Additionally, it requires contractors to have Delaware workers' compensation insurance where required, compliance with labor laws, and proof of a state business license. The Delaware Department of Labor's Office of Contractor Registration is responsible for enforcement of the requirements of the Contractor Registration Act. If you have any questions about the contractor registration process, please call 302-430-7739 or email Contract.Registry@delaware.gov. Registration at <https://onestop.delaware.gov/>.

SPECIFICATIONS :

The Delaware specifications entitled "*Standard Specifications for Road and Bridge Construction January 2024*", hereinafter referred to as the *Standard Specifications*; the *Supplemental Specifications* to the Standard Specifications effective as of the advertisement date of this Bid Proposal and hereby included by reference; the *Special Provisions*; *Notes on the Plans*; this *Bid Proposal* including referenced documents; any *Addenda* thereto; and any posted *Questions and Answers*; shall govern the work to be performed under this contract. The Contractor shall make itself aware of these specifications, revisions and corrections, and apply them to the applicable item(s) of this contract.

CLARIFICATIONS :

Under any Section or Item included in the Contract, the Contractor shall be aware that when requirements, responsibilities, and furnishing of materials are outlined in the details and notes on the Plans and in the paragraphs preceding the "Basis of Payment" paragraph in the Standard Specifications or Special Provisions, no interpretation shall be made that such stipulations are excluded because reiteration is not made in the "Basis of Payment" paragraph.

The Department requires the use of various electronic applications for various documentation processes. These processes will be identified, and the Contractor's required use will be detailed during the Preconstruction Meeting. No additional payments will be made to the contractor to use or interface with the applications.

ATTESTING TO NON-COLLUSION :

The Department requires as a condition precedent to acceptance of bids a sworn statement executed by, or on behalf of, the person, firm, association, or corporation to whom such contract is to be awarded, certifying that such person, firm, association, or corporation has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free competitive bidding in connection with such contract. The form for this sworn statement is included in the proposal and must be properly executed in order to have the bid considered.

QUANTITIES :

The quantities shown are for comparison of bids only. The Department may increase or decrease any quantity or quantities without penalty or change in the bid price.

PERFORMANCE-BASED RATING SYSTEM

29 Del.C. §6962 (c)(12)(a) requires a Department of Transportation project, excluding a Community Transportation Fund or municipal street aid contract, to include a performance-based rating system. At the time of bid, the Performance Rating for each Contractor shall be used as a prequalification to bid.

Bidders with Performance Rating scores equal to or greater than 85% shall be permitted to bid. Bidders with scores of less than 85% who comply with the retainage requirements of 29 Del.C. §6962 shall be permitted to bid provided the *Agreement to Accept Retainage* (located on the Certification Page) is executed and submitted with the bid. Lack of an executed *Agreement to Accept Retainage* will result in the rejection of the bid by the Department. Successful bidders awarded

Department contracts who have no performance history within the last five (5) years will be assigned a provisional Performance Rating of 85% at the date of advertisement.

Notification of Performance Rating. The Department shall post publicly the Performance Rating for all Contractors on the Department's [website](#). DelDOT will complete performance-based evaluations on the construction company contracted by the Department to build the project (the "Contractor"). Provisions to appeal Performance Ratings are described in the regulations. The regulations are set forth in Section 2408 of Title 2, Delaware Administrative Code, found [here](#).

EQUALITY OF EMPLOYMENT OPPORTUNITY ON PUBLIC WORKS :

Delaware Code, Title 29, Chapter 69, Section 6962, Paragraph (d), Subsection (7) states;

- a. As a condition of the awarding of any contract for public works financed in whole or in part by State appropriation, such contracts shall include the following provisions:

During the performance of this contract, the contractor agrees as follows:

1. The contractor will not discriminate against any employee or applicant for employment because of race, creed, color, sex, sexual orientation, gender identity or national origin. The contractor will take positive steps to ensure that applicants are employed and that employees are treated during employment without regard to their race, creed, color, sex, sexual orientation, gender identity or national origin. Such action shall include, but not be limited to, the following: employment, upgrading, demotion or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship. The contractor agrees to post in conspicuous places available to employees and applicants for employment notices to be provided by the contracting agency setting forth this nondiscrimination clause.
2. The contractor will, in all solicitations or advertisements for employees placed by or on behalf of the contractor, state that all qualified applicants will receive consideration for employment without regard to race, creed, color, sex, sexual orientation, gender identity or national origin.
3. The contractor will ensure employees receive equal pay for equal work, without regard to sex. Employee pay differential is acceptable if pursuant to a seniority system, a merit system, a system which measures earnings by quantity or quality of production, or if the differential is based on any other factor other than sex.

TAX CLEARANCE :

As payments to each vendor or contractor aggregate \$2,000, the Division of Accounting will report such vendor or contractor to the Division of Revenue, who will then check the vendor or contractor's compliance with tax requirements and take such further action as may be necessary to ensure compliance.

LICENSE :

A person desiring to engage in business in this State as a contractor on a project designated to include federal funds, shall obtain a Delaware business license upon making application to the Division of Revenue. Proof of said license compliance to be made prior to, or in conjunction with, the execution of a contract to which he has been named.

SUBCONTRACTOR LICENSE: 29 DEL. C. §6967:

- (c) Any contractor that enters a public works contract must provide to the agency to which it is contracting, within 30 days of entering such public works contract, copies of all occupational and business licenses of subcontractors and/or independent contractors that will perform work for such public works contract. However, if a subcontractor or independent contractor is hired or contracted more than 20 days after the contractor entered the public works contract the occupational or business license of such subcontractor or independent contractor shall be provided to the agency within 10 days of being contracted or hired.

DIFFERING SITE CONDITIONS:

SUSPENSIONS OF WORK and SIGNIFICANT CHANGES IN THE CHARACTER OF WORK:

Differing site conditions: During the progress of the work, if subsurface or latent physical conditions are encountered at the site differing materially from those indicated in the contract or if unknown physical conditions of an unusual nature, differing materially from those ordinarily encountered and generally recognized as inherent in the work provided for in the contract are encountered at the site, the party discovering such conditions shall promptly notify the other party in writing of the specific differing conditions before they are disturbed and before the affected work is performed.

Upon written notification, the engineer will investigate the conditions, and if he/she determines that the conditions materially differ and cause an increase or decrease in the cost or time required for the performance of any work under the contract, an adjustment, excluding loss of anticipated profits, will be made and the contract modified in writing accordingly. The engineer will notify the contractor of his/her determination whether or not an adjustment of the contract is warranted.

No contract adjustment which results in a benefit to the contractor will be allowed unless the contractor has provided the required written notice. No contract adjustment will be allowed under their clause for any effects caused on unchanged work.

Suspensions of work ordered by the engineer: If the performance of all or any portion of the work is suspended or delayed by the engineer in writing for an unreasonable period of time (not originally anticipated, customary or inherent to the construction industry) and the contractor believes that additional compensation and/or contract time is due as a result of such suspension or delay, the contractor shall submit to the engineer in writing a request for adjustment within 7 calendar days of receipt of the notice to resume work. The request shall set forth the reasons and support for such adjustment.

Upon receipt, the engineer will evaluate the contractor's request. If the engineer agrees that the cost and/or time required for the performance of the contract has increased as a result of such suspension and the suspension was caused by conditions beyond the control of and not the fault of the contractor, its suppliers, or subcontractors at any approved tier, and not caused by weather, the engineer will make an adjustment (excluding profit) and modify the contract in writing accordingly. The engineer will notify the contractor of his/her determination whether or not an adjustment of the contract is warranted.

No contract adjustment will be allowed unless the contractor has submitted the request for adjustment within the time prescribed. No contract adjustment will be allowed under this clause to the extent that performance would have been suspended or delayed by any other cause, or for which an adjustment is provided for or excluded under any other term or condition of this contract.

Significant changes in the character of work: The engineer reserves the right to make, in writing, at any time during the work, such changes in quantities and such alterations in the work as are necessary to satisfactorily complete the project. Such changes in quantities and alterations shall not invalidate the contract nor release the surety, and the contractor agrees to perform the work as altered.

If the alterations or changes in quantities significantly change the character of the work under the contract, whether or not changed by any such different quantities or alterations, an adjustment, excluding loss of anticipated profits, will be made to the contract. The basis for the adjustment shall be agreed upon prior to the performance of the work. If a basis cannot be agreed upon, then an adjustment will be made either for or against the contractor in such amount as the engineer may determine to be fair and equitable.

The term "significant change" shall be construed to apply only to the following circumstances:

- (A) When the character of the work as altered differs materially in kind or nature from that involved or included in the original proposed construction, or
- (B) When a major item of work, as defined elsewhere in the contract, is increased in excess of 125 percent or decreased below 75 percent of the original contract quantity. Any allowance for an increase in quantity shall apply only to that portion in excess of 125 percent of original contract item quantity, or in case of a decrease below 75 percent, to the actual amount of work performed.

CONFLICT WITH FEDERAL STATUTES OR REGULATIONS:

Delaware Code, Title 29, Chapter 69, Section 6904, Paragraph (a):

"If any provision of this subchapter conflicts or is inconsistent with any statute, rule or regulation of the federal government applicable to a project or activity, the cost of which is to be paid or reimbursed in whole or in part by the federal government, and due to such conflict or inconsistency the availability of federal funds may be jeopardized, such provision shall not apply to such project or activity."

FEDERAL LABOR AND EMPLOYMENT REQUIREMENTS

Federal Regulation 23 CFR § 635.117(b) Labor and employment, states:

"No procedures or requirement shall be imposed by any State which will operate to discriminate against the employment of labor from any other State, possession or territory of the United States, in the construction of a Federal-aid project."

CONVICT PRODUCED MATERIALS:

(a) Materials produced after July 1, 1991, by convict labor may only be incorporated in a Federal-aid highway construction project if such materials have been:

- (1) Produced by convicts who are on parole, supervised release, or probation from a prison or
- (2) Produced in a qualified prison facility and the cumulative annual production amount of such materials for use in Federal-aid highway construction does not exceed the amount of such materials produced in such facility for use in Federal-aid highway construction during the 12-month period ending July 1, 1987.

(b) Qualified prison facility means any prison facility in which convicts, during the 12-month period ending July 1, 1987, produced materials for use in Federal-aid highway construction projects.

RIGHT TO AUDIT

The Department shall have the right to audit the books and records of the contractor or any subcontractor under this contract or subcontract to the extent that the books and records relate to the performance of the contract or subcontract. The books and records shall be maintained by the contractor for a period of 3 years from the date of final payment under the prime contract and by the subcontractor for a period of 3 years from the date of final payment under the subcontract (29 Del.C. §6930)

TO REPORT BID RIGGING ACTIVITIES:

The U. S. Department of Transportation (DOT) operates the below toll-free "hotline" Monday through Friday, 8:00 a.m. to 5:00 p.m. eastern time. Anyone with knowledge of possible bid rigging, bidder collusion, or other fraudulent activities should use the "hotline" to report such activities.

The "hotline" is part of the DOT's continuing effort to identify and investigate highway construction contract fraud and abuse and is operated under the direction of the DOT Inspector General. All information will be treated confidentially and caller anonymity will be respected.

TO REPORT BID RIGGING ACTIVITIES
CALL 1-800-424-9071

NOTICE OF REQUIREMENT FOR AFFIRMATIVE ACTION
TO ENSURE EQUAL EMPLOYMENT OPPORTUNITY
(EXECUTIVE ORDER 11246)

1. The Offeror's or Bidder's attention is called to the "Equal Opportunity Clause" and the "Standard Federal Equal Employment Specifications" set forth herein.
2. The goals and timetables for minority and female participation, expressed in percentage terms for the Contractor's aggregate work force in each trade on all construction work in the covered area, are as follows:

Goals for Minority Participation In
Each Trade

12.3% (New Castle County)
14.5% (Kent & Sussex Counties)

Goals for Female Participation In
Each Trade

6.9% (Entire State)

These goals are applicable to all the Contractor's construction work (whether or not it is Federal or federally assisted) performed in the covered area. If the contractor performs construction work in a geographical area located outside of the covered area, it shall apply the goals established for such geographical area where the work is actually performed. With regard to this second area, the contractor also is subject to the goals for both its federally involved and non-federally involved construction.

The Contractor's compliance with the Executive Order and the Executive Order and the regulations in CFR Part 60-4 shall be based on its implementation of the Equal Opportunity Clause, specific affirmative action obligations required by the specifications set forth in 41 CFR 60-4.3(a), and its efforts to meet the goals. The hours of minority and female employment and training must be substantially uniform throughout the length of the contract, and in each trade, and the contractor shall make a good faith effort to employ minorities and women evenly on each of its projects. The transfer of minority or female employees or trainees from Contractor to Contractor or from project to project for the sole purpose of meeting the Contractor's goals shall be a violation of the contract, the Executive Order, and the regulations in 41 CFR Part 60-4. Compliance with the goals will be measured against the total work hours performed.

3. The Contractor shall provide written notification to the Director of the Office of Federal Contract Compliance Programs within 10 working days of award of any construction subcontract in excess of \$10,000 at any tier for construction work under the contract resulting from this solicitation. The notification shall list the name, address, and telephone number of the subcontractor; employer identification number of the subcontractor; estimated dollar amount of the subcontract; estimated starting and completion dates of the subcontract; and the geographical area in which the subcontract is to be performed.
4. As used in this Notice, and in the contract resulting from this solicitation, the "covered area" is the County specified in the General Description section.

REV. 11-3-80

STANDARD FEDERAL EQUAL EMPLOYMENT OPPORTUNITY
CONSTRUCTION CONTRACT SPECIFICATIONS (EXECUTIVE ORDER 11246)

1. As used in these specifications:
 - a. "Covered area" means the geographical area described in the solicitation from which this contract resulted;
 - b. "Director" means Director, Office of Federal Contract Compliance Programs, United States Department of Labor, or any person to whom the Director delegates authority;
 - c. "Employer identification number" means the Federal Social Security number used on the Employer's Quarterly Federal Tax Return, U.S. Treasury Department Form 941.
 - d. "Minority" includes:
 - i. Black (all persons having origins in any of the Black African racial groups not of Hispanic origin);
 - ii. Hispanic (all persons of Mexican, Puerto Rican, Cuban, Central or South American or other Spanish Culture or origin, regardless of race);
 - iii. Asian and Pacific Islander (all persons having origins in any of the original peoples of the Far East, Southeast Asia, the Indian Subcontinent, or the Pacific Islands); and
 - iv. American Indian or Alaskan Native (all persons having origins in any of the original peoples of North America and maintaining identifiable tribal affiliations through membership and participation or community identification).
2. Whenever the Contractor, or any Subcontractor at any tier, subcontracts a portion of the work involving any construction trade, it shall physically include in each subcontract in excess of \$10,000 the provisions of these specifications and the Notice which contains the applicable goals for DBE participation, and which is set forth in the solicitations from which this contract resulted.
3. If the Contractor is participating (pursuant to 41 CFR 60-4.5) in a Hometown Plan approved by the U.S. Department of Labor in the covered area either individually or through an association, its affirmative action obligations on all work in the Plan area (including goals and timetables) shall be in accordance with that Plan for those trades which have unions participating in the Plan. Contractors must be able to demonstrate their participation in and compliance with the provisions of any such Hometown Plan. Each Contractor or Subcontractor participating in an approved Plan is individually required to comply with its obligations under the EEO clause, and to make a good faith effort to achieve each goal under the Plan in each trade in which it has employees. The overall good faith performance by other Contractors or Subcontractors toward a goal in an approved plan does not excuse any covered Contractor's or Subcontractor's failure to take good faith efforts to achieve the Plan goals and timetables.
4. The Contractor shall implement the specific affirmative action standards provided in paragraphs 7a through 7p of these specifications. The goals set forth in the solicitation from which this contract resulted are expressed as percentages of the total hours of employment and training of minority and female utilization the Contractor should reasonably be able to achieve in each construction trade in which it has employees in the covered area. Covered Construction contractors performing construction work in geographical areas where they do not have a Federal or federally assisted construction contract shall apply the minority and female goals established for the geographical area where the work is being performed. Goals are published periodically in the Federal Register in notice form, and such notices may be obtained from any Office of Federal Contract Compliance Program Office or from the Federal procurement contracting offices. The Contractor is expected to make substantially uniform progress in meeting its goals in each craft during the period specified.
5. Neither the provisions of any collective bargaining agreement, nor the failure by a union with whom the Contractor has a collective bargaining agreement, to refer either minorities or women shall excuse the Contractor's obligations under these specifications, Executive Order 11246, or the regulations promulgated pursuant thereto.
6. In order for the nonworking training hours of apprentices and trainees to be counted in meeting the goals, such apprentices and trainees must be employed by the Contractor during the training period, and the Contractor must have made a commitment to employ the apprentices and trainees at the completion of their training, subject to the availability of employment opportunities. Trainees must be trained pursuant to training programs approved by the U.S. Department of Labor.

7. The Contractor shall take specific affirmative actions to ensure equal employment opportunity. The evaluation of the Contractor's compliance with these specifications shall be based upon its effort to achieve maximum results from its actions. The Contractor shall document these efforts fully, and shall implement affirmative action steps at least as extensive as the following:
- a. Ensure and maintain a working environment free of harassment, intimidation, and coercion at all sites, and in all facilities at which the Contractor's employees are assigned to work. The Contractor, where possible, will assign two or more women to each construction project. The Contractor shall specifically ensure that all foremen, superintendents, and other on-site supervisory personnel are aware of and carry out the Contractor's obligation to maintain such a working environment, with specific attention to minority or female individuals working at such sites or in such facilities.
 - b. Establish and maintain a current list of minority and female recruitment sources, provide written notification to minority and female recruitment sources and to community organizations when the Contractor or its unions have employment opportunities available, and maintain a record of the organizations' responses.
 - c. Maintain a current file of the names, addresses and telephone numbers of each minority and female off-the-street applicant and minority or female referral from a union, a recruitment source or community organization and of what action was taken with respect to each such individual. If such individual was sent to the union hiring hall for referral and was not referred back to the Contractor by the union or, if referred, not employed by the Contractor, this shall be documented in the file with the reason therefor, along with whatever additional actions the Contractor may have taken.
 - d. Provide immediate written notification to the Director when the union or unions with which the Contractor has a collective bargaining agreement has not referred to the Contractor a minority person or woman sent by the Contractor, or when the Contractor has other information that the union referral process has impeded the Contractor's efforts to meet its obligations.
 - e. Develop on-the-job training opportunities and/or participate in training programs for the area which expressly include minorities and women, including upgrading programs and apprenticeship and trainee programs relevant to the Contractor's employment needs, especially those programs funded or approved by the Department of Labor. The Contractor shall provide notice of these programs to the sources compiled under 7b above.
 - f. Disseminate the Contractor's EEO policy by providing notice of the policy to unions and training programs and requesting their cooperation in assisting the Contractor in meeting its EEO obligations; by including it in any policy manual and collective bargaining agreement; by publicizing it in the company newspaper, annual report, etc.; by specific review of the policy with all management personnel and with all minority and female employees at least once a year; and by posting the company EEO policy on bulletin boards accessible to all employees at each location where construction work is performed.
 - g. Review, at least annually, the company's EEO policy and affirmative action obligations under these specifications with all employees having any responsibility for hiring, assignment, layoff, termination or other employment decisions including specific review of these items with on-site supervisory personnel such as Superintendents, General Foreman, etc., prior to the initiation of construction work at any job site. A written record shall be made and maintained identifying the time and place of these meetings, persons attending, subject matter discussed, and disposition of the subject matter.
 - h. Disseminate the Contractor's EEO policy externally by including it in any advertising in the news media, specifically including minority and female news media, and providing written notification to and discussing the Contractor's EEO policy with other Contractors and Subcontractors with whom the Contractor does or anticipates doing business.
 - i. Direct its recruitment efforts, both oral and written, to minority, female and community organizations, to schools with minority and female students and to minority and female recruitment and training organizations serving the Contractor's recruitment area and employment needs. Not later than one month prior to the date for the acceptance of applications for apprenticeship or other training by any recruitment source, the Contractor shall send written notification to organizations such as the above, describing the openings, screening procedures, and tests to be used in the selection process.
 - j. Encourage present minority and female employees to recruit other minority persons and women and, where reasonable, provide after school, summer and vacation employment to minority and female youth both on the site and in other areas of a Contractor's work force.
 - k. Validate all tests and other selection requirements where there is an obligation to do so under 41 CFR Part 60-3.

- l. Conduct, at least annually, an inventory and evaluation at least of all minority and female personnel for promotional opportunities and encourage these employees to seek or to prepare for, through appropriate training, etc., such opportunities.
 - m. Ensure that seniority practices, job classifications, work assignments and other personnel practices, do not have a discriminatory effect by continually monitoring all personnel and employment related activities to ensure that the EEO policy and the Contractor's obligations under these specifications are being carried out.
 - n. Ensure that all facilities and company activities are nonsegregated except that separate or single-user toilet and necessary changing facilities shall be provided to assure privacy between the sexes.
 - o. Document and maintain a record of all solicitations of offers for subcontractors from minority and female construction contractors and suppliers, including circulation of solicitations to minority and female contractor associations and other business associations.
 - p. Conduct a review, at least annually, of all supervisors' adherence to and performance under the Contractor's EEO policies and affirmative action obligations.
8. Contractors are encouraged to participate in voluntary associations which assist in fulfilling one or more of their affirmative action obligations (7a through p). The efforts of a contractor association, joint contractor-union, contractor-community, or other similar group of which the Contractor is a member and participant, may be asserted as fulfilling any one or more of its obligations under 7a through p of these Specifications provided that the Contractor actively participates in the group, makes every effort to assure that the group has a positive impact on the employment of minorities and women in the industry, ensures that the concrete benefits of the program are reflected in the Contractor's minority and female work force participating, makes a good faith effort to meet its individual goals and timetables, and can provide access to documentation which demonstrates the effectiveness of actions taken on behalf of the Contractor. The obligation to comply, however, is the Contractor's and failure of such a group to fulfill an obligation shall not be a defense for the Contractor's noncompliance.
9. A single goal for minorities and a separate single goal for women have been established. The Contractor, however, is required to provide equal employment opportunity and to take affirmative action for all minority groups, both male and female, and all women, both minority and non-minority. Consequently, the Contractor may be in violation of the Executive Order if a particular group is employed in a substantially disparate manner (for example, even though the Contractor has achieved its goals for women generally, the Contractor may be in violation of the Executive Order if a specific minority group of women is underutilized).
10. The Contractor shall not use the goals and timetables or affirmative action standards to discriminate against any person because of race, color, religion, sex, or national origin.
11. The Contractor shall not enter into any Subcontract with any person or firm debarred from Government contracts pursuant to Executive Order 11246.
12. The Contractor shall carry out such sanctions and penalties for violation of these specifications and of the Equal Opportunity Clause, including suspension, termination and cancellation of existing subcontracts as may be imposed or ordered pursuant to Executive Order 11246, as amended, and its implementing regulations, by the Order of Federal Contract Compliance Programs. Any Contractor who fails to carry out such sanctions and penalties shall be in violation of these specifications and Executive Order 11246, as amended.
13. The Contractor, in fulfilling its obligations under these specifications, shall implement specific affirmative action steps, at least as extensive as those standards prescribed in paragraph 7 of these specifications, so as to achieve maximum results from its efforts to ensure equal employment opportunity. If the Contractor fails to comply with the requirements of the Executive Order, the implementing regulations, or these specifications, the Director shall proceed in accordance with 41 CFR 60-4.8.
14. The Contractor shall designate a responsible official to monitor all employment-related activity to ensure that the company EEO policy is being carried out, to submit reports relating to the provisions hereof as may be required by the Government, and to keep records. Records shall at least include for each employee the name, address, telephone numbers, construction trade, union affiliation if any, employee identification number when assigned, social security number, race, sex, status (e.g., mechanic, apprentice, trainee, helper, or laborer), dates of changes in status, hours

worked per week in the indicated trade, rate of pay, and locations at which the work was performed. Records shall be maintained in an easily understandable and retrievable form; however, to the degree that existing records satisfy this requirement, contractors shall not be required to maintain separate records.

15. Nothing herein provided shall be construed as a limitation upon the application of other laws which establish different standards of compliance or upon the application of requirements for the hiring of local or other area residents (e.g., those under the Public Works Employment Act of 1977 and the Community Development Block Grant Program).

* * * * *

TRAINING SPECIAL PROVISIONS

This Training Special Provision supersedes subparagraph 7b of the Special Provision entitled "Specific Equal Employment Opportunity Responsibilities", (Attachment 1), and is in implementation of 23 U.S.C. 140(a).

As part of the contractor's equal employment opportunity affirmative action program, training shall be provided as follows:

The contractor shall provide on-the-job training aimed at developing full journeyman in the type of trade or job classification involved.

The number of trainees to be trained under the special provision will be as set forth in the General Description section of this document. In the event the contractor subcontracts a portion of the contract work, he shall determine how many, if any, of the trainees are to be trained by the subcontractor, provided however, that the contractor shall retain the primary responsibility for meeting the training requirements imposed by this special provision. The contractor shall also insure that this Training Special Provision is made applicable to such subcontract. Where feasible, 25 percent of apprentices or trainees in each occupation shall be in their first year apprenticeship or training.

The number of trainees shall be distributed among the work classification on the basis of the contractor's needs and the availability of journeymen in the various classifications within a reasonable area of recruitment. Prior to commencing construction, the contractor shall submit to the Department of Highways and Transportation for approval the number of trainees to be trained in each selected classification and training program to be used. Furthermore, the contractor shall specify the starting time for training in each of the classifications. The contractor will be credited for each trainee employed by him on the contract work who is currently enrolled or becomes enrolled in an approved program and will be reimbursed for such trainees as provided hereinafter.

Training and upgrading of minorities and women toward journeyman status is a primary objective of this Training Special Provision. Accordingly, the contractor shall make every effort to enroll minority trainees and women (e.g., by conducting systematic and direct recruitment through public and private sources likely to yield minority and women trainees) to the extent that such persons are available within a reasonable area of recruitment. The contractor will be responsible for demonstrating the steps that he has taken in pursuance thereof, prior to a determination as to whether the contractor is in compliance with this Training Special Provision. This training commitment is not intended, and not be used, to discriminate against any applicant for training, whether a member of a minority group or not.

No employee shall be employed as a trainee in any classification in which he has successfully completed a training course leading to journeyman status or in which he has been employed as a journeyman. The contractor should satisfy this requirement by including appropriate questions in the employee application or by other suitable means. Regardless of the method used the contractor's records should document the findings in each case.

The minimum length and type of training for each classification will be as established in the training program selected by the contractor and approved by the Department of Highways and Transportation and the Federal Highway Administration. The Department of Highways and Transportation and the Federal Highway Administration shall approve a program if it is reasonably calculated to meet the equal employment opportunity obligations of the contractor and to qualify the average trainee for journeyman status in the classification concerned by the end of the training period. Furthermore, apprenticeship programs registered with the U.S. Department of Labor, Bureau of Apprenticeship and Training, or with a State apprenticeship agency recognized by the Bureau and training programs approved but not necessarily sponsored by the U.S. Department of Labor, Manpower Administration, Bureau of Apprenticeship and Training shall also be considered acceptable provided it is being administered in a manner consistent with the equal employment obligations of Federal-aid highway construction contracts. Approval or acceptance of a training program shall be obtained from the State prior to commencing work the classification covered by the program. It is the intention of these provisions that the training is to be

provided in the construction crafts rather than clerk-typists or secretarial-type positions. Training is permissible in lower level management positions such as office engineers, estimators, timekeepers, etc., where the training is oriented toward construction applications. Training in the laborer classification may be permitted provided that significant and meaningful training is provided and approved by the division office. Some off-site training is permissible as long as the training is an integral part of an approved training program and does not comprise a significant part of the overall training.

Except as otherwise noted below, the contractor will be reimbursed 80 cents per hour of training given an employee on this contract in accordance with an approved training program. As approved by the engineer, reimbursement will be made for training persons in excess of the number specified herein. This reimbursement will be made even though the contractor receives additional training program funds from other sources, provided such other sources does not specifically prohibit the contractor from receiving other reimbursement. Reimbursement for off-site training indicated above may only be made to the contractor where he does one or more of the following and the trainees are concurrently employed on a Federal-aid project; contributes to the cost of the training; provides the instruction of the trainee; or pays the trainee's wages during the off-site training period.

No payment shall be made to the contractor if either the failure to provide the required training, or the failure to hire the trainees as a journeyman, is caused by the contractor and evidences a lack of good faith on the part of the contractor in meeting the requirements of this Training Special Provision. It is normally expected that a trainee will begin his training on the project as soon as feasible after start of work utilizing the skill involved and remain on the project as long as training opportunities exist in his work classification or until he has completed his training program. It is not required that all trainees be on board for the entire length of the contract. A contractor will have fulfilled his responsibilities under this Training Special Provision if he has provided acceptable training to the number of trainees specified. The number trained shall be determined on the basis of the total number enrolled on the contract for a significant period.

Trainees will be paid a least 60 percent of the appropriate minimum journeymen's rate specified in the contract for the first half of the of the training period, 75 percent for the third quarter of the training period, and 90 percent for the last quarter of the training period, unless apprentices or trainees is an approved existing program are enrolled as trainees on this project. In fact case, the appropriate rates approved by the Department of Labor or Transportation in connection with the existing program shall apply to all trainees being trained for the same classification who are covered by this Training Special Provisions.

The contractor shall furnish the trainee a copy of the program he will follow in providing the training.

The contractor shall provide each trainee with a certification showing the type and length of training satisfactorily completed.

The contractor will provide for the maintenance of records and furnish periodic reports documenting his performance under this Training Special Provision.

* * * * *

INTERMODAL SURFACE TRANSPORTATION EFFICIENCY ACT
& TRANSPORTATION EQUITY ACT

Recipients of Federal transit funds authorized by Titles I, III, V and VI of ISTEA, Pub. L. 102-240 or by Federal transit laws in Title 49, U.S. Code, or Titles I, III, and V of the TEA-21, Pub. L. 105-178 of the Transportation Equity Act for the 21st Century (TEA-21) are required to comply with the regulations of 49 Code of Federal Regulations (CFR) Part 26 - Participation by Disadvantaged Business Enterprises in Department of Transportation Financial Assistance Programs.

* * * * *

- continued next page -

REVISED

DISADVANTAGED BUSINESS ENTERPRISE (DBE) PROGRAM SPECIFICATION

DeIDOT has established a Disadvantaged Business Enterprise (DBE) program in accordance with the regulations of the United States Department of Transportation (USDOT), 49 CFR Part 26. The Department has received Federal financial assistance from the USDOT, and as a condition of receiving this assistance, the Department has signed an assurance that it will comply with 49 CFR Part 26.

It is the policy of DeIDOT to ensure that DBEs, as defined in 49 CFR Part 26, have an equal opportunity to receive and participate in USDOT-assisted contracts. It is also the policy of the DeIDOT:

1. To ensure nondiscrimination in the award and administration of USDOT-assisted contracts;
2. To create a level playing field on which DBEs can compete fairly for USDOT-assisted contracts;
3. To ensure that the DBE program is narrowly tailored in accordance with applicable law;
4. To ensure that only firms that fully meet 49 CFR Part 26 eligibility standards are counted as DBEs;
5. To help remove barriers to the participation of DBEs in USDOT-assisted contracts;
6. To assist in the development of firms that can compete successfully in the marketplace outside the DBE program and;
7. To promote the use of DBEs in all types of federally assisted contracts and procurement activities.

The following definitions apply to this subpart:

Commercially Useful Function (CUF) means a Commercially Useful Function as defined fully in 49 CFR §26.55, which definition is incorporated herein by reference. CUF is discussed further in the next section.

Committed DBE means a DBE that was identified by the contractor, typically on a DBE Project Participation Affidavit, to assist in making a good faith effort to meet an assigned DBE goal. This also includes any substitute DBE that has subsequently been committed work to meet the assigned contract goal.

Days mean calendar days. In computing any period of time described in this part, the day from which the period begins to run is not counted, and when the last day of the period is a Saturday, Sunday, or Federal holiday, the period extends to the next day that is not a Saturday, Sunday, or Federal holiday. Similarly, in circumstances where the DeIDOT's offices are closed for all or part of the last day, the period extends to the next day on which the agency is open.

DBE-Conscious means actions or a program that are focused specifically on assisting DBEs in increasing their participation in projects, targeted actions that specifically factor in a firm's certified DBE status to meet a contract goal.

DBE-Neutral means actions, or a program undertaken by DelDOT, that is used to assist all small business concerns.

Disadvantaged Business Enterprise or DBE means a for-profit small business concern (1) that is at least 51 percent owned by one or more individuals who are both socially and economically disadvantaged or, in the case of a corporation, in which 51 percent of the stock is owned by one or more such individuals; and, (2) whose management and daily business operations are controlled by one or more of the socially and economically disadvantaged individuals who own it.

DOT-assisted contract means any contract between a recipient and a contractor (at any tier) funded in whole or in part with DOT financial assistance, including letters of credit or loan guarantees, except a contract solely for the purchase of land.

Good Faith Efforts means efforts to achieve a DBE goal or other requirement of this part which, by their scope, intensity, and appropriateness to the objective, can reasonably be expected to fulfill the program requirement.

Joint Venture means an association of a DBE firm and one or more other firms to carry out a single, for-profit business enterprise, for which the parties combine their property, capital, efforts, skills and knowledge, and in which the DBE is responsible for a distinct, clearly defined portion of the work of the contract and whose share in the capital contribution, control, management, risks, and profits of the joint venture are commensurate with its ownership interest.

NAICS Code means the North American Industry Classification System (NAICS) is the standard used by Federal statistical agencies in classifying business establishments for the purpose of collecting, analyzing, and publishing statistical data related to the US business economy.

Non-DBE means any firm that is not a DBE or any entity which has not been certified by DelDOT as a DBE prior to bid closing.

Small Business concern means, with respect to firms seeking to participate as DBEs in DOT-assisted contracts, a small business concern as defined pursuant to section 3 of the Small Business Act and Small Business Administration regulations implementing it (13 CFR part 121) that also does not exceed the cap on average annual gross receipts specified in 49 CFR §26.65(b).

Socially and Economically Disadvantaged Owner (SEDO) means any individual who is a citizen (or lawfully admitted permanent resident) of the United States and who a certifier finds to be socially and economically disadvantaged on a case-by-case basis. A determination that an individual is socially and economically disadvantaged must not be made in whole or in part on race or sex. For that reason, applicants may qualify as socially and economically disadvantaged only if they can meet the relevant criteria as described in 49 CFR §26.67:

- i. Non-presumptive disadvantage. All applicants must demonstrate social and economic disadvantage (SED) affirmatively based on their own experiences and circumstances within American society, and without regard to race or sex
- ii. To satisfy the SED requirement and ensure all determinations of disadvantage are not based in whole or in part on race or sex, an owner must provide the certifier a Personal Narrative (PN) that establishes the existence of disadvantage by a preponderance of the evidence based on individualized proof regarding specific instances of economic hardship, systemic barriers, and denied opportunities that impeded the owner's progress or success in education,

employment, or business, including obtaining financing terms available to similarly situated, non-disadvantaged persons.

iii. *The PN* must state how and to what extent the impediments caused the owner economic harm, including a full description of type and magnitude, and must establish the owner is economically disadvantaged in fact relative to similarly situated non-disadvantaged individuals.

iv. *The owner must attach to the PN* a current Personal Net Worth (PNW) statement and any other financial information the owner considers relevant.

DBE Participation Goals

DelDOT has established an overall annual goal for DBE participation on Federal-aid contracts. DelDOT intends that the goal be met with a combination of DBE-conscious and DBE-neutral efforts. DBE-conscious participation occurs when the contractor uses a percentage of DBEs, as defined herein, to meet the contract-specified goal. DBE-neutral efforts are those that are, or can be, used to assist all small businesses or increase opportunities for all small businesses.

The regulation, 49 CFR, Part 26, also describes DBE-neutral participation as when a DBE wins a prime contract through customary competitive procurement procedures or is awarded a subcontract on a prime contract that does not carry a DBE contract goal.

DelDOT will establish specific goals for each particular DOT-assisted project which will be expressed as a percentage of the total dollar amount of contract bid. The specific contract goal for this contract is listed in the General Description section of this document.

The contractor shall make Good Faith Efforts to meet the goal specified herein with DBEs or establish that it was unable to meet the goal despite making good faith efforts to do so. Prime contractors are encouraged to obtain DBE participation above and beyond any goals that may be set for this project.

DBE Project Participation Affidavit

REVISED



As a result of the Issuance of the IFR on September 30, 2025, all DelDOT DBEs were decertified. DelDOT is undertaking the recertification process for DBEs pursuant to the IFR requirements. As DelDOT currently has no certified DBEs, it is not feasible to require the submission of a DelDOT DBE Project Participation Affidavit for this letting. Companies bidding on this letting are NOT required to submit a DBE Project Participation Affidavit with their bid. As soon as DelDOT is able to begin recertifying DBEs pursuant to the standards set forth in the IFR, this requirement will be reinstated in all lettings.

DBE Subcontract Provisions

REVISED



DelDOT continues to reserve the right to approve ALL DBE subcontractors and all substitutions of DBE subcontractors prior to award, and during the of completion of the contract. **ALL DBEs subcontracted (whether submitted for participation credit or not) must be submitted to DelDOT’s DBE Program Office for approval.** No contract work shall be performed by a DBE subcontractor until the executed DBE subcontract is approved in writing by DelDOT and DelDOT has issued the required Notice to Proceed. Any DBE subcontract relating to work to be performed pursuant to this contract, which is submitted to DelDOT for approval, must contain all DBE subcontractor information, the requirements contained in this contract, and must be fully executed by the contractor and DBE subcontractor.

Each contract between the prime contractor and each DBE subcontractor shall, at a minimum, include the following:

1. All pertinent provisions and requirements of the prime contract.
2. Assurance that the contractor and subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract.
3. Description of the work to be performed by the DBE subcontractor.
4. The dollar value of each item of work to be completed by the DBE subcontractor and the bid price of each item of work to be completed by the DBE subcontractor.
5. An attached copy of the most current FHWA 1273- Required Contract Provisions Federal-Aid Construction Contracts.
6. Language indicating that retainage will not be withheld unless the prime contract with DeIDOT allows for the withholding of retainage.
7. Language requiring the payment of all funds received from DeIDOT for work satisfactorily performed within the time frame contemplated by 49 CFR §26.29.

DeIDOT reserves the right to conduct periodic reviews of DBE and non-DBE subcontract documentation to ensure compliance with federal requirements.

* * * * *

REVISED



**CRITICAL DBE
REQUIREMENTS**

As a result of the Issuance of the IFR on September 30, 2025, all DeIDOT DBE's were decertified. DeIDOT is undertaking the recertification process for DBEs pursuant to the IFR requirements. The decertification of all DBEs impacts some of the critical contract requirements, but others remain in effect as identified below:

1. In the execution of this contract, the successful bidder agrees to comply with the following contract clauses:

Prompt Payment: The prime contractor/consultant receiving payments shall, within 30 days of receipt of any payment, file a statement with DeIDOT on a form to be determined by DeIDOT that all subcontractors furnishing labor or material have been paid the full sum due them at the stage of the contract, except any funds withheld under the terms of the contract as required by Chapter 8, Title 17 of the Delaware Code, annotated and as amended. Any delay or postponement of payment from the above referenced time frame may occur only for good cause following written approval of DeIDOT. This clause applies to both DBE and non-DBE subcontractors.

Retainage: The prime contractor agrees to return retainage to each subcontractor within 15 calendar days after the subcontractor's work is satisfactorily completed. Any delay or postponement of payment from the above referenced time frame may occur only for good cause following written approval of DeIDOT. This clause covers both DBE and non-DBE subcontractors. As guidance, once a subcontractor has satisfactorily completed the physical work, and has given to the prime contractor a certified statement that all laborers, lower tier contractors, and materialmen who have furnished labor and materials to the subcontractor have been paid all monies due them, the prime contractor shall return retainage to the subcontractor within 15 calendar days.

2. In the execution of this contract, the successful bidder agrees to comply with the following contract assurance and will include this same language in each subcontractor contract:

"The contractor or subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract. The contractor shall carry out applicable requirements of 49 CFR Part 26 in the award and administration of DOT-assisted contracts. Failure by the contractor to carry out these requirements is a material breach of this contract, which may result in the termination of this contract or such remedy as the recipient deems appropriate." 49 CFR Section 26.13

In addition to this specification, bidders must comply with all provisions of the rules and regulations adopted by the United States Department of Transportation for DBE participation in USDOT and DelDOT Programs (49 CFR Part 26) and the DelDOT Disadvantaged Business Enterprise Program Plan; each of which is hereby incorporated and made part of this specification. Bidders are also reminded that they must be responsive and responsible bidders in all other aspects aside from the DBE Program in order to be awarded the contract.

* * * * *

REVISED



GUIDANCE FOR GOOD FAITH
EFFORT

As a result of the Issuance of the IFR on September 30, 2025, all DelDOT DBE's were decertified. DelDOT is undertaking the recertification process for DBEs pursuant to the IFR requirements. As DelDOT currently has no certified DBEs, DelDOT has not included a DBE participation goal in this letting. As such, bidders are not required to provide documentation of Good Faith Efforts with their bids on this letting. As soon as DelDOT is able to begin recertifying DBEs pursuant to the standards set forth in the IFR, this requirement will be reinstated in all lettings.

* * * * *

- end -

remainder of page is blank

FEDERAL TRANSIT ADMINISTRATION PROVISIONS

Federal Transit Administration (FTA) requirements apply to project participants to the lowest tier necessary to ensure compliance with these requirements. The contractor will need to include applicable Federal requirements in each sub-agreement, lease, third party contract, or other document as necessary.

The requirements listed herein must be adhered to by any firms selected to perform work required under this agreement.

1. AUDIT AND INSPECTION OF RECORDS

The Contractor agrees to provide the Delaware Department of Transportation (Department), the FTA Administrator, the Comptroller General of the United States or any of their authorized representatives' access to any books, documents, papers and records of the Contractor which are directly pertinent to this contract for the purposes of making audits, examinations, excerpts and transcriptions. Contractor also agrees, pursuant to 49 C. F. R. 633.17 to provide the FTA Administrator or his authorized representatives including any PMO Contractor access to Contractor's records and construction sites pertaining to a major capital project, defined at 49 U.S.C. 5302(a)1, which is receiving federal financial assistance through the programs described at 49 U.S.C. 5307, 5309 or 5311. By definition, a major capital project excludes contracts of less than the simplified acquisition threshold. The Contractor agrees to permit any of the foregoing parties to reproduce by any means whatsoever or to copy excerpts and transcriptions as reasonably needed.

2. ACCESS REQUIREMENTS FOR INDIVIDUALS WITH DISABILITIES

The Contractor agrees to comply with all applicable requirements of the Americans with Disabilities Act of 1990 (ADA), 42 U.S.C. Section 12101 et seq. And 49 U.S.C. Section 322; Section 504 of the Rehabilitation Act of 1973, as amended, 29 U.S.C. Section 794; Section 16 of the Federal Transit Act, as amended, 49 U.S.C. App. Section 1612; and implementing regulations, as may be amended

3. CERTIFICATION REGARDING DEBARMENT, SUSPENSION, AND OTHER RESPONSIBILITY MATTERS – Lower Tier Covered Transactions (Third Party Contracts over \$100,000)

- a) By signing and submitting this bid or proposal, the prospective lower tier participant is providing the signed certification set out below.
- b) The certification in this clause is a material representation of fact upon which reliance was placed when this transaction was entered into. If it is later determined that the prospective lower tier participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the Department may pursue available remedies, including suspension and/or debarment.
- c) The prospective lower tier participant shall provide immediate written notice to the Department if at any time the prospective lower tier participant learns that its certification was erroneous when submitted or has become erroneous by reason of changed circumstances.
- d) The terms “covered transaction,” “debarred,” “suspended,” “ineligible,” “lower tier covered transaction,” “participant,” “persons,” “principal,” “proposal,” and “voluntarily excluded,” as used in this clause, have the meanings set out in the Definitions and Coverage sections of rules implementing Executive Order 12549 [49 CFR Part 29]. You may contact the Department for assistance in obtaining a copy of those regulations.
- e) The prospective lower tier participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized in writing by the Department.
- f) The prospective lower tier participant further agrees by submitting this proposal that it will include the clause “Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion - Lower Tier Covered Transaction”, without modification, in all lower tier covered transactions.
- g) A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that it is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A participant may decide the method and frequency by which it determines the eligibility of its principals. Each participant may, but is not required to, check the No procurement List issued by the U. S. General Service Administration.

- h) Nothing contained in the foregoing shall be construed to require establishment of system of records in order to render in good faith the certification required by this clause. The knowledge and information of a participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.
- i) Except for transactions authorized under Paragraph E of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible or voluntarily excluded from participation in this transaction, in addition to all remedies available to the Federal Government, the Department may pursue available remedies including suspension and/or debarment.
- j) The prospective lower tier participant certifies, by submission of this bid or proposal, that neither it nor its "principals" [as defined at 49 CFR §29.105(p)] is presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participation in this transaction by any Federal department or agency.
- k) When the prospective lower tier participant is unable to certify to the statements in this certification, such prospective participant shall attach an explanation to this proposal.

4. CLEAN WATER REQUIREMENTS

The Contractor agrees to comply with all applicable standards, orders or regulations issued pursuant to the Federal Water Pollution Control Act, as amended, 33 U.S.C. 1251 *et seq.* The Contractor agrees to report each violation to the Department and understands and agrees that the Department will, in turn, report each violation as required to assure notification to FTA and the appropriate EPA Regional Office. (2)The Contractor also agrees to include these requirements in each subcontract exceeding \$100,000 financed in whole or in part with Federal assistance provided by FTA.

5. FEDERAL CHANGES

Contractor shall at all times comply with all applicable FTA regulations, policies, procedures and directives, including without limitation those listed directly or by reference in the Master Agreement between the Department and FTA, as they may be amended or promulgated from time to time during the term of this contract. Contractor's failure to so comply shall constitute a material breach of this contract.

6. CLEAN AIR

(1) The Contractor agrees to comply with all applicable standards, orders or regulations issued pursuant to the Clean Air Act, as amended, 42 U.S.C. §§ 7401 *et seq.* . The Contractor agrees to report each violation to the Department and understands and agrees that the Department will, in turn, report each violation as required to assure notification to FTA and the appropriate EPA Regional Office. (2) The Contractor also agrees to include these requirements in each subcontract exceeding \$100,000 financed in whole or in part with Federal assistance provided by FTA.

7. ENERGY CONSERVATION

The Contractor shall recognize mandatory standards and policies relating to energy efficiency which are contained in the State Energy Conservation Plan issued in compliance with the Energy Policy and Conservation Act (42 US Section 321 *et seq.*).

8. CONTRACT TERMINATION

a) Termination for Convenience

The Department may terminate this contract, in whole or in part, at any time by written notice to the Contractor. The Contractor shall be paid its costs, including contract close-out costs, and profit on product delivered up to the time of termination. The Contractor shall promptly submit its termination claim for payment. If the Contractor has any property in its possession belonging to the Department, the Contractor will account for the same and dispose of it in the manner the Department directs.

b) Termination for Default

If the Contractor does not deliver supplies in accordance with the contract delivery schedule, or, if the contract is for services, the Contractor fails to perform in the manner called for in the contract, or if the Contractor fails to comply with any other provisions of the contract, the Department may terminate this contract for default. Termination shall be affected by serving a notice of termination on the Contractor setting forth the manner in which the Contractor is in default. The Contractor will only be paid the contract price for supplies delivered and accepted,

or services performed in accordance with the manner of performance set forth in the contract.

If it is later determined that the Contractor had an excusable reason for not performing, such as a strike, flood, events which are not the fault of or are beyond the control of the Contractor, the Department, after setting up a new delivery or performance schedule, may allow the Contractor to continue work, or treat the termination as a termination of convenience.

In the event the Department exercises its right of termination for default, and if an amount for liquidated damages is set forth, the Contractor shall be liable to the Department for excess costs and, in addition, for liquidated damages in the amount set forth, as fixed, agreed, and liquidated damages for each calendar day of delay, until such time as the Department may reasonably obtain delivery or performance of similar supplies or services.

If the contract is so terminated, the Contractor shall continue performance and be liable to the Department for such liquidated damages for each calendar day of delay until the supplies are delivered or services performed.

The Contractor shall not be liable for liquidated damages resulting from delays such as acts of God, strikes, fire or flood, and events which are not the fault of, or are beyond the control of the Contractor.

9. CIVIL RIGHTS

- (1) Nondiscrimination - In accordance with Title VI of the Civil Rights Act, as amended, 42 U.S.C. § 2000d, section 303 of the Age Discrimination Act of 1975, as amended, 42 U.S.C. § 6102, section 202 of the Americans with Disabilities Act of 1990, 42 U.S.C. § 12132, and Federal transit law at 49 U.S.C. § 5332, the Contractor agrees that it will not discriminate against any employee or applicant for employment because of race, color, creed, national origin, sex, age, or disability. In addition, the Contractor agrees to comply with applicable Federal implementing regulations and other implementing requirements FTA may issue.
- (2) Equal Employment Opportunity - The following equal employment opportunity requirements apply to the underlying contract:
 - (a) Race, Color, Creed, National Origin, Sex - In accordance with Title VII of the Civil Rights Act, as amended, 42 U.S.C. § 2000e, and Federal transit laws at 49 U.S.C. § 5332, the Contractor agrees to comply with all applicable equal employment opportunity requirements of U.S. Department of Labor (U.S. DOL) regulations, "Office of Federal Contract Compliance Programs, Equal Employment Opportunity, Department of Labor," 41 C.F.R. Parts 60 et seq., (which implement Executive Order No. 11246, "Equal Employment Opportunity," as amended by Executive Order No. 11375, "Amending Executive Order 11246 Relating to Equal Employment Opportunity," 42 U.S.C. § 2000e note), and with any applicable Federal statutes, executive orders, regulations, and Federal policies that may in the future affect construction activities undertaken in the course of the Project. The Contractor agrees to take affirmative action to ensure that applicants are employed, and that employees are treated during employment, without regard to their race, color, creed, national origin, sex, or age. Such action shall include, but not be limited to, the following: employment, upgrading, demotion or transfer, recruitment or recruitment advertising, layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship. In addition, the Contractor agrees to comply with any implementing requirements FTA may issue.
 - (b) Age - In accordance with section 4 of the Age Discrimination in Employment Act of 1967, as amended, 29 U.S.C. § 623 and Federal transit law at 49 U.S.C. § 5332, the Contractor agrees to refrain from discrimination against present and prospective employees for reason of age. In addition, the Contractor agrees to comply with any implementing requirements FTA may issue.
 - (c) Disabilities - In accordance with section 102 of the Americans with Disabilities Act, as amended, 42 U.S.C. § 12112, the Contractor agrees that it will comply with the requirements of U.S. Equal Employment Opportunity Commission, "Regulations to Implement the Equal Employment Provisions of the Americans with Disabilities Act," 29 C.F.R. Part 1630, pertaining to employment of persons with disabilities. In addition, the Contractor agrees to comply with any implementing requirements FTA may issue.
- (3) The contractor agrees to comply with all applicable requirements of the Americans with Disabilities Act of 1990 (ADA), 42 U.S.C. Section 12101 et seq. And 49 U.S.C. Section 322; Section 504 of the Rehabilitation Act of

1973, as amended, 29 U.S.C., Section 794; Section 16 of the Federal Transit Act, as amended, 49 U.S.C. App. Section 1612; and implementing regulations, as may be amended.

- (4) The Contractor also agrees to include these requirements in each subcontract financed in whole or in part with Federal assistance provided by FTA, modified only if necessary to identify the affected parties.

10. DISADVANTAGED BUSINESS ENTERPRISES

It is the policy of the Department of Transportation that Disadvantaged Business Enterprises as defined in 49 CFR Part 26 shall have the opportunity to participate in the performance of contracts financed in whole or part with Federal funds under this contract. Consequently the DBE Requirements of 49 CFR Part 26 apply to this contract. The recipient or its contractor agrees to ensure that Disadvantaged Business Enterprises as defined in 49 CFR Part 26 have the opportunity to participate in the performance of contracts and subcontracts financed in whole or in part with Federal funds provided under this contract. In this regard all recipients or contractors shall take all necessary and reasonable steps in accordance with 49 CFR Part 26 to ensure that Disadvantaged Business Enterprises have the opportunity to compete for and perform contracts. The contractor or subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract. The contractor shall carry out applicable requirements of 49 CFR part 26 in the award and administration of FTA assisted subcontracts. Failure by the contractor to carry out these requirements is a material breach of this contract, which may result in the termination of this contract or such other remedy, as the Department deems appropriate.

The successful bidder agrees to comply with the following clauses:

Prompt Payment: The prime contractor agrees to pay each subcontractor under this prime contract for satisfactory performance of its contract no later than 30 days from the receipt of each payment the prime contractor receives from the Department. This clause applies to both DBE and Non-DBE subcontractors.

Retainage: The prime contractor agrees to return retainage payments to each subcontractor within 30 days after the subcontractor's work is satisfactorily completed. Any delay or postponement of payment from the above referenced time frame may occur only for good cause following written approval of the Department. This clause applies to both DBE and non-DBE subcontractors. The specific DBE goal for this contract is shown elsewhere in this contract.

11. ENVIRONMENTAL VIOLATIONS

The Contractor agrees to comply with all applicable standards, orders, or requirements issued under Section 306 of the Clean Air Act (42 USC 1857 (h)), Section 508 of the Clean Water Act (33 USC 1368), Executive Order 11378, and Environmental Protection Agency regulations: (40 CFR, Part 15) which prohibit the use under nonexempt Federal contracts, grants or loans, of facilities included on the EPA List for Violating Facilities. The Contractor shall report violations to the FTA.

12. EQUAL EMPLOYMENT OPPORTUNITY

In connection with the execution of this contract, the Contractor shall not discriminate against any employee or applicant for employment because of race, creed, religion, color, national origin, age, sex or disability. The Contractor shall take affirmative action to insure that applicants are employed, and that employees are tested during their employment without regard to their race, creed, religion, color, national origin, age, sex or disability. Such actions shall include, but not be limited to the following, employment, upgrading, demotion, or transfer, recruitment or recruitment advertising, layoff or termination; rates of pay, or other forms of compensation. The Contractor further agrees to insert a similar provision in all subcontracts, except subcontracts for standard commercial supplies or raw materials.

13. FTA FUNDING REQUIREMENTS

This project may be financed in part by funds from the Federal Transit Administration. Contractor shall at all times comply with all applicable FTA regulations, policies, procedures and directives, including without limitation those listed directly or by reference in the Master Agreement between the Department and FTA, as they may be amended or promulgated from time to time during the term of this contract. Contractor's failure to so comply shall constitute a material breach of this contract.

14. INCORPORATION OF FEDERAL TRANSIT ADMINISTRATION (FTA) TERMS

The preceding provisions include, in part, certain Standard Terms and Conditions required by DOT, whether or not expressly set forth in the preceding contract provisions. All contractual provisions required by FTA, as set forth in FTA Circular 4220.1F are hereby incorporated by reference. Anything to the contrary herein notwithstanding, all FTA mandated terms shall be deemed to control in the event of a conflict with other provisions contained in this Agreement. The Contractor shall not perform any act, fail to perform any act, or refuse to comply with any Department requests which would cause the Department to be in violation of the FTA terms and conditions.

15. LOBBYING:

The Contractor is required to certify using the Certification of Restrictions on Lobbying Form included that, to the best of his or her knowledge and belief:

- (1) No Federal appropriated funds have been paid or will be paid, by or on behalf of the undersigned, to any person for influencing or attempting to influence an officer or employee of an agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement.
- (2) If any funds other than Federal appropriated funds have been paid or will be paid to any person for making lobbying contacts to an officer or employee of any agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with this Federal contract, grant, loan, or cooperative agreement, the undersigned shall complete and submit Standard Form--LLL, "Disclosure Form to Report Lobbying," in accordance with its instructions [as amended by "Government wide Guidance for New Restrictions on Lobbying," 61 Fed. Reg. 1413 (1/19/96). Note: Language in paragraph (2) herein has been modified in accordance with Section 10 of the Lobbying Disclosure Act of 1995 (P.L. 104-65, to be codified at 2 U.S.C. 1601, *et seq.*)]
- (3) The undersigned shall require that the language of this certification be included in the award documents for all subawards at all tiers (including subcontracts, subgrants, and contracts under grants, loans, and cooperative agreements) and that all subrecipients shall certify and disclose accordingly. The certification is a material representation of fact upon which reliance was placed when this transaction was made or entered into. Submission of the certification is a prerequisite for making or entering into this transaction imposed by 31, U.S.C. § 1352 (as amended by the Lobbying Disclosure Act of 1995). Any person who fails to file the required certification shall be subject to a civil penalty of not less than \$10,000 and not more than \$100,000 for each such failure. Pursuant to 31 U.S.C. § 1352(c)(1)-(2)(A), any person who makes a prohibited expenditure or fails to file or amend a required certification or disclosure form shall be subject to a civil penalty of not less than \$10,000 and not more than \$100,000 for each such expenditure or failure.

16. NO GOVERNMENT OBLIGATION TO THIRD PARTIES

- (1) The Department and Contractor acknowledge and agree that, notwithstanding any concurrence by the Federal Government in or approval of the solicitation or award of the underlying contract, absent the express written consent by the Federal Government, the Federal Government is not a party to this contract and shall not be subject to any obligations or liabilities to the Department, Contractor, or any other party (whether or not a party to that contract) pertaining to any matter resulting from the underlying contract.
- (2) The Contractor agrees to include the above clause in each subcontract financed in whole or in part with Federal assistance provided by FTA. It is further agreed that the clause shall not be modified, except to identify the subcontractor who will be subject to its provisions.

17. PROGRAM FRAUD AND FALSE OR FRAUDULENT STATEMENTS AND RELATED ACTS

- (1) The Contractor acknowledges that the provisions of the Program Fraud Civil Remedies Act of 1986, as amended, 31 U.S.C. § 3801 *et seq.* and U.S. DOT regulations, "Program Fraud Civil Remedies," 49 C.F.R. Part 31, apply to its actions pertaining to this Project. Upon execution of the underlying contract, the Contractor certifies or affirms the truthfulness and accuracy of any statement it has made, it makes, it may make, or causes to be made, pertaining to the underlying contract or the FTA assisted project for which this contract work is being performed. In addition

to other penalties that may be applicable, the Contractor further acknowledges that if it makes, or causes to be made, a false, fictitious, or fraudulent claim, statement, submission, or certification, the Federal Government reserves the right to impose the penalties of the Program Fraud Civil Remedies Act of 1986 on the Contractor to the extent the Federal Government deems appropriate.

- (2) The Contractor also acknowledges that if it makes, or causes to be made, a false, fictitious, or fraudulent claim, statement, submission, or certification to the Federal Government under a contract connected with a project that is financed in whole or in part with Federal assistance originally awarded by FTA under the authority of 49 U.S.C. § 5307, the Government reserves the right to impose the penalties of 18 U.S.C. § 1001 and 49 U.S.C. § 5307(n)(1) on the Contractor, to the extent the Federal Government deems appropriate.
- (3) The Contractor agrees to include the above two clauses in each subcontract financed in whole or in part with Federal assistance provided by FTA. It is further agreed that the clauses shall not be modified, except to identify the subcontractor who will be subject to the provisions.

18. PROTEST PROCEDURES

Protests based upon the award of the contract shall be made in writing to the Contract Services Administrator no later than ten (10) calendar days following the award of the contract. The protest must clearly specify in writing the grounds and evidence on which the protest is based. The protest will be reviewed and decided pursuant to; the proposal documents issued by the Department, the Delaware Code, and the Federal Transit Authority's regulations.

19. RECORD RETENTION

The Contractor agrees to maintain all books, records, accounts and reports required under this contract for a period of not less than three years after the date of termination or expiration of this contract, except in the event of litigation or settlement of claims arising from the performance of this contract, in which case Contractor agrees to maintain same until the Department, the FTA Administrator, the Comptroller General, or any of their duly authorized representatives, have disposed of all such litigation, appeals, claims or exceptions related thereto. Reference 49 CFR 18.39(i)(11).

20. SEISMIC SAFETY

The contractor agrees that any new building or addition to an existing building will be designed and constructed in accordance with the standards for Seismic Safety required in Department of Transportation Seismic Safety Regulations 49 CFR Part 41 and will certify to compliance to the extent required by the regulation. The contractor also agrees to ensure that all work performed under this contract including work performed by a subcontractor is in compliance with the standards required by the Seismic Safety Regulations and the certification of compliance issued on the project.

21. TITLE VI COMPLIANCE

During the performance of any Contract entered into pursuant to these specifications, the Contractor, for itself, its assignees and successor in interest, agrees that it shall comply with Title VI of the Civil Rights Act of 1964 (42 U.S.C. section 2000d) and the Regulations relative to nondiscrimination in federally assisted programs of the Department of Transportation, Title 49, Code of Federal Regulations Part 21, as they may be amended from time to time which are incorporated by reference and made a part of this contract.

22. INTELLIGENT TRANSPORTATION SYSTEMS

Intelligent transportation system (ITS) property and services must comply with the National ITS Architecture and Standards to the extent required by Section 5307(c) of SAFETEA-LU, FTA Notice, "FTA National ITS Architecture Policy on Transit Projects," 66 FR 1455 et seq., January 8, 2001, and later published policies or implementing directives FTA may issue. Consequently, third party contracts involving ITS are likely to require provisions to ensure compliance with Federal requirements.

23. SHIPMENTS OF PROPERTY—U.S. FLAG REQUIREMENTS.

- (a) Shipments by Ocean Vessel. The Common Grant Rules require third party contract provisions to ensure compliance with 46 U.S.C. Section 55303 and Maritime Administration regulations, "Cargo Preference-U.S. Flag Vessels," 46 CFR Part 381, implementing the codified Cargo Preference Act. With few exceptions, the regulations require that U.S. Flag vessels be used to transport at least 50 percent of any federally assisted property.

(b) Shipments by Air Carrier. Third party contracts involving shipments of federally assisted property by air carrier will require provisions to ensure compliance with Section 5 of the International Air Transportation Fair Competitive Practices Act of 1974, as amended (“Fly America” Act), 49 U.S.C. Section 40118, and GSA regulations, “Use of United States Flag Air Carriers,” 41 CFR Sections 301-10.131 through 301-10.143. The regulations require shipment by U.S. flag air carriers unless such carriers are not reasonably available within the standards of GSA’s implementing regulations.

24. DISPUTES, BREACHES, DEFAULTS, AND LITIGATION

Notification to FTA; Flow Down Requirement. If a current or prospective legal matter that may affect the Federal Government emerges, the Recipient must promptly notify the FTA Chief Counsel and FTA Regional Counsel for the Region in which the Recipient is located. The Recipient must include a similar notification requirement in its Third-Party Agreements and must require each Third-Party Participant to include an equivalent provision in its subagreements at every tier, for any agreement that is a “covered transaction” according to 2 C.F.R. §§ 180.220 and 1200.220.

25. BUY AMERICA REQUIREMENTS

REVISED ←

The Build America, Buy America Act (BABA), enacted as part of the Bipartisan Infrastructure Law (BIL) requires iron, steel, manufactured products, and construction materials used in infrastructure projects funded by Federal financial assistance to be produced in the United States (U.S.).

In accordance with 23 U.S.C. 313 and 23 CFR 635.410, all iron and steel materials permanently incorporated into this project will be produced in the U.S. and all manufacturing processes involving these materials will occur in the U.S., except that a minimal amount of foreign steel or iron materials may be used, provided the cost of the foreign materials does not exceed 0.1 percent of the total Contract cost or \$2,500.00, whichever is greater. If such minimal amount of foreign steel is used, the Contractor shall maintain a record of the costs to ensure that the allowable limit is not exceeded.

In accordance with 23 CFR 635.410, the final manufacturing process of all manufactured products that will be permanently incorporated into this project will be performed in the U.S. Iron or steel components of precast concrete products and cabinets or enclosures of any intelligent transportation systems and other electronic hardware systems classified as a manufactured product which is permanently incorporated into this project will be produced in the U.S. and all manufacturing processes involving the iron and steel will occur in the U.S., except that a minimal amount of foreign steel or iron materials may be used, provided the cost of the foreign materials does not exceed 0.1 percent of the total Contract cost or \$2,500.00, whichever is greater. If such minimal amount of foreign steel is used, the Contractor shall maintain a record of the costs to ensure that the allowable limit is not exceeded.

In accordance with 2 CFR 184, all non-ferrous metals, plastic and polymer-based products, glass, fiber optic cable, optical fiber, lumber, drywall, and engineered wood construction material permanently incorporated into this project will be produced in the U.S.

DelDOT maintains a list of all pay items, the applicable BABA category designation, and additional guidance at the following address: <https://deldot.gov/Business/prodlists/index.shtml?dc=buyAmerica>.

By signing and submitting this proposal, the bidder certifies that:

“All materials that will be permanently incorporated into this project will meet the Buy America material requirements. At the Department's request, I/we will provide manufacturer's/supplier's documentation verifying domestic origin as defined in the Contract. All Materials accepted on the basis of such Certificate of Compliance may be sampled by the Department and tested at any time. Use of Material on the basis of Certificate of Compliance shall not relieve the Contractor of responsibility for incorporating Material in the Project conforming to the requirements of the Contract. Any Material not conforming to such requirements will be subject to rejection whether in place or not. The Department reserves the right to refuse to permit the use of Material on the basis of Certificate of Compliance.”

26. RECYCLED MATERIALS

The Contractor agrees to provide a preference for those products and services that conserve natural resources, protect the environment, and are energy efficient by complying with and facilitating compliance with Section 6002 of the Resource Conservation and Recovery Act, as amended, 42 U.S.C. §6962, and U.S. Environmental Protection Agency (U.S. EPA), “Comprehensive Procurement Guideline for Products Containing Recovered Materials,” 40 C.F.R. part 247.

27. PREVAILING WAGE AND ANTI-KICKBACK

For all prime construction, alteration, or repair contracts in excess of \$2,000 awarded by FTA, the Contractor shall comply with the Davis-Bacon Act and the Copeland "Anti-Kickback" Act. Under 49 U.S.C. § 5333(a), prevailing wage protections apply to laborers and mechanics employed on FTA assisted construction, alteration, or repair projects. The Contractor will comply with the Davis-Bacon Act, 40 U.S.C. §§ 3141-3144, and 3146-3148 as supplemented by DOL regulations at 29 C.F.R. part 5, "Labor Standards Provisions Applicable to Contracts Governing Federally Financed and Assisted Construction."

In accordance with the statute, the Contractor shall pay wages to laborers and mechanics at a rate not less than the prevailing wages specified in a wage determination made by the Secretary of Labor. In addition, the Contractor agrees to pay wages not less than once a week. The Contractor shall also comply with the Copeland "Anti-Kickback" Act (40 U.S.C. § 3145), as supplemented by DOL regulations at 29 C.F.R. part 3, "Contractors and Subcontractors on Public Building or Public Work Financed in Whole or in part by Loans or Grants from the United States." The Contractor is prohibited from inducing, by any means, any person employed in the construction, completion, or repair of public work, to give up any part of the compensation to which he or she is otherwise entitled.

28. CONTRACT WORK HOURS AND SAFETY STANDARDS

For all contracts in excess of \$100,000 that involve the employment of mechanics or laborers, the Contractor shall comply with the Contract Work Hours and Safety Standards Act (40 U.S.C. §§ 3701-3708), as supplemented by the DOL regulations at 29 C.F.R. part 5. Under 40 U.S.C. § 3702 of the Act, the Contractor shall compute the wages of every mechanic and laborer, including watchmen and guards, on the basis of a standard work week of 40 hours. Work in excess of the standard work week is permissible provided that the worker is compensated at a rate of not less than one and a half times the basic rate of pay for all hours worked in excess of 40 hours in the work week. The requirements of 40 U.S.C. § 3704 are applicable to construction work and provide that no laborer or mechanic be required to work in surroundings or under working conditions which are unsanitary, hazardous, or dangerous.

In the event of any violation of the clause set forth herein, the Contractor and any subcontractor responsible therefor shall be liable for the unpaid wages. The Contractor or subcontractor shall insert in any subcontracts the clauses set forth in this section and also a clause requiring the subcontractors to include these clauses in any lower tier subcontracts. The prime Contractor shall be responsible for compliance by any subcontractor or lower tier subcontractor with the clauses set forth in this agreement.

APPENDICES TO THE TITLE VI ASSURANCE**APPENDIX A**

During the performance of this contract, the contractor, for itself, its assignees, and successors in interest (hereinafter referred to as the "contractor") agrees as follows:

1. **Compliance with Regulations:** The contractor (hereinafter includes consultants) will comply with the Acts and the Regulations relative to Non-discrimination in Federally-assisted programs of the U.S. Department of Transportation, (Federal Highway Administration (FHWA), or Federal Transit Authority (FTA)), as they may be amended from time to time, which are herein incorporated by reference and made a part of this contract.
2. **Non-discrimination:** The contractor, with regard to the work performed by it during the contract, will not discriminate on the grounds of race, color, or national origin in the selection and retention of subcontractors, including procurements of materials and leases of equipment. The contractor will not participate directly or indirectly in the discrimination prohibited by the Acts and the Regulations, including employment practices when the contract covers any activity, project, or program set forth in Appendix B of 49 CFR Part 21.
3. **Solicitations for Subcontracts, Including Procurements of Materials and Equipment:** In all solicitations, either by competitive bidding, or negotiation made by the contractor for work to be performed under a subcontract, including procurements of materials, or leases of equipment, each potential subcontractor or supplier will be notified by the

contractor of the contractor's obligations under this contract and the Acts and the Regulations relative to Non-discrimination on the grounds of race, color, or national origin.

4. Information and Reports: The contractor will provide all information and reports required by the Acts and the Regulations, and will permit access to its books, records, accounts, other sources of information, and its facilities as may be determined by the Recipient or the Federal Highway Administration (FHWA), or Federal Transit Authority (FTA) to be pertinent to ascertain compliance with such Acts, Regulations, and instructions. Where any information required of a contractor is in the exclusive possession of another who fails or refuses to furnish the information, the contractor will so certify to the Recipient or the Federal Highway Administration (FHWA), or Federal Transit Authority (FTA), as appropriate, and will set forth what efforts it has made to obtain the information.

5. Sanctions for Noncompliance: In the event of a contractor's noncompliance with the Non-discrimination provisions of this contract, the Recipient will impose such contract sanctions as it or the Federal Highway Administration (FHWA), or Federal Transit Authority (FTA) may determine to be appropriate, including, but not limited to:

withholding payments to the contractor under the contract until the contractor complies;
and/or cancelling, terminating, or suspending a contract, in whole or in part.

6. Incorporation of Provisions: The contractor will include the provisions of paragraphs one through five in every subcontract, including procurements of materials and leases of equipment, unless exempt by the Acts and the Regulations. The contractor will take action with respect to any subcontract or procurement as the Recipient or the Federal Highway Administration (FHWA), or Federal Transit Authority (FTA) may direct as a means of enforcing such provisions including sanctions for noncompliance. Provided, that if the contractor becomes involved in, or is threatened with litigation by a subcontractor, or supplier because of such direction, the contractor may request the Recipient to enter into any litigation to protect the interests of the Recipient. In addition, the contractor may request the United States to enter into the litigation to protect the interests of the United States.

APPENDIX E

During the performance of this contract, the contractor or consultant, for itself, its assignees, and successors in interest (hereinafter referred to as the "contractor") agrees to comply with the following nondiscrimination statutes and authorities; including but not limited to:

Pertinent Non-Discrimination Authorities:

Title VI of the Civil Rights Act of 1964 (42 U.S.C. § 2000d et seq., 78 stat. 252), (prohibits discrimination on the basis of race, color, national origin); and 49 CFR Part 21.

The Uniform Relocation Assistance and Real Property Acquisition Policies Act of 1970,(42 U.S.C. § 460 I), (prohibits unfair treatment of persons displaced or whose property has been acquired because of Federal or Federal-aid programs and projects);

Federal-Aid Highway Act of 1973, (23 U.S.C. § 324 et seq.), (prohibits discrimination on the basis of sex);

Section 504 of the Rehabilitation Act of 1973, (29 U.S.C. § 794 et seq.), as amended, (prohibits discrimination on the basis of disability); and 49 CFR Part27;

The Age Discrimination Act of 1975, as amended, (42 U.S.C. § 6101 et seq.), (prohibits discrimination on the basis of age);

Airport and Airway Improvement Act of 1982,(49 USC §471, Section 47123), as amended, (prohibits discrimination based on race, creed, color, national origin, or sex);

The Civil Rights Restoration Act of 1987,(PL 100-209), (Broadened the scope, coverage and applicability of Title VI of the Civil Rights Act of 1964,The Age Discrimination Act of 1975and Section 504 of the Rehabilitation Act of 1973,by expanding the definition of the terms "programs or activities" to include all of the programs or activities of the Federal-aid recipients, sub-recipients and contractors, whether such programs or activities are Federally funded or not);

Titles II and III of the Americans with Disabilities Act, which prohibit discrimination on the basis of disability in the operation of public entities, public and private transportation systems, places of public accommodation, and certain testing entities (42 U.S.C. §§ 12131 - 12189) as implemented by Department of Transportation regulations at 49 C.F.R. parts 37 and 38;

The Federal Aviation Administration's Non-discrimination statute (49 U.S.C. S 41123) (prohibits discrimination on the basis of race, color, national origin, and sex);

Executive Order 12898, Federal Actions to Address Environmental Justice in Minority Populations and Low-Income Populations, which ensures nondiscrimination against minority populations by discouraging programs; policies, and activities with disproportionately high and adverse human health or environmental effects on minority and low-income populations;

Executive Order 13166, Improving Access to Services for Persons with Limited English Proficiency, and resulting agency guidance, national origin discrimination includes discrimination because of limited English proficiency (LEP). To ensure compliance with Title VI, you must take reasonable steps to ensure that LEP persons have meaningful access to your programs (70 Fed. Reg. at 74087 to 74100);

Title IX of the Education Amendments of 1972, as amended, which prohibits you from discriminating because of sex in education programs or activities (20 U.S.C. 1681 et seq).

* * * * *

PREVAILING WAGES

Included in this proposal are the minimum wages to be paid various classes of laborers and mechanics as determined by the Department of Labor of the State of Delaware in accordance with Title 29 Del.C. §6960, relating to wages and the regulations implementing that Section.

REQUIREMENT BY DEPARTMENT OF LABOR FOR SWORN PAYROLL INFORMATION

Title 29 Del.C. §6960 stipulates;

- (b) Every contract based upon these specifications shall contain a stipulation that the employer shall pay all mechanics and laborers employed directly upon the site of the work, unconditionally and not less often than once a week and without subsequent deduction or rebate on any account, the full amounts accrued at time of payment, computed at wage rates not less than those stated in the specifications, regardless of any contractual relationship which may be alleged to exist between the employer and such laborers and mechanics. The specifications shall further stipulate that the scale of wages to be paid shall be posted by the employer in a prominent and easily accessible place at the site of the work, and that there may be withheld from the employer so much of accrued payments as may be considered necessary by the Department of Labor to pay to laborers and mechanics employed by the employer the difference between the rates of wages required by the contract to be paid laborers and mechanics on the work and rates of wages received by such laborers and mechanics to be remitted to the Department of Labor for distribution upon resolution of any claims.
- (c) **Every contract based upon these specifications shall contain a stipulation that sworn payroll information, as required by the Department of Labor, be furnished weekly. The Department of Labor shall keep and maintain the sworn payroll information for a period of 6 months from the last day of the work week covered by the payroll.**

Bidders are specifically directed to note the Department of Labor's prevailing wage regulations implementing §6960 relating to the effective date of the wage rates, at Part VI., Section C., which in relevant part states:

"Public agencies (covered by the provisions of 29 Del.C. §6960) are required to use the rates which are in effect on the date of the publication of specifications for a given project. In the event that a contract is not executed within one hundred twenty (120) days from the date the specifications were published, the rates in effect at the time of the execution of the contract shall be the applicable rates for the project."

PREVAILING WAGE REQUIREMENTS

It is DelDOT's understanding that the Davis-Bacon Act is not a preemptive statute in the broad sense, and does not preempt or displace State of Delaware prevailing wage requirements.

When a contract for a project contains both Federal Davis-Bacon and State of Delaware prevailing wage standards because of concurrent Federal and State coverage, the employer's minimum wage obligations are determined by whichever standards are higher.

Contractors with questions may contact:

Department of Labor, Division of Industrial Affairs, 4425 N. Market Street, Wilmington, DE 19802
Telephone (302) 761-8200 <https://dia.delawareworks.com/labor-law/>

STATE OF DELAWARE
DEPARTMENT OF LABOR
DIVISION OF INDUSTRIAL AFFAIRS
OFFICE OF LABOR LAW ENFORCEMENT
PHONE: (302) 318-2769

Mailing Address:
252 Chapman Road
Suite 210
Newark, DE 19702

Located at:
252 Chapman Road
Suite 210
Newark, DE 19702

PREVAILING WAGES FOR HIGHWAY CONSTRUCTION EFFECTIVE MARCH 14, 2025

CLASSIFICATION	NEW CASTLE	KENT	SUSSEX
BRICKLAYERS	66.79	66.79	71.09
CARPENTERS	67.79	62.56	50.80
CEMENT FINISHERS	72.72	44.60	45.46
ELECTRICAL LINE WORKERS	36.72	59.33	29.04
ELECTRICIANS	83.92	83.92	83.92
IRON WORKERS	89.37	32.59	34.62
LABORERS	56.58	52.08	51.11
MILLWRIGHTS	22.01	21.36	18.46
PAINTERS	83.14	83.14	83.14
PILEDRIVERS	98.33	32.46	91.23
POWER EQUIPMENT OPERATORS	84.74	54.11	49.57
SHEET METAL WORKERS	31.09	27.76	25.12
TRUCK DRIVERS	53.26	38.59	46.99

CERTIFIED: 7/28/2025


BY: *Delina Choudhary*
ADMINISTRATOR, OFFICE OF LABOR LAW ENFORCEMENT

NOTE: THESE RATES ARE PROMULGATED AND ENFORCED PURSUANT TO THE PREVAILING WAGE REGULATIONS ADOPTED BY THE DEPARTMENT OF LABOR ON APRIL 3, 1992.

CLASSIFICATIONS OF WORKERS ARE DETERMINED BY THE DEPARTMENT OF LABOR. FOR ASSISTANCE IN CLASSIFYING WORKERS, OR FOR A COPY OF THE REGULATIONS OR CLASSIFICATIONS, PHONE (302) 318-2769.

NON-REGISTERED APPRENTICES MUST BE PAID THE MECHANIC'S RATE.

PROJECT: T202201102 Federal Aid Project No. 5307- 2022 (08) US 13 Southbound BBR1 Lane, New Castle County



General Decision Number: DE20250005 05/02/2025

Superseded General Decision Number: DE20240005

State: Delaware

Construction Type: Highway

County: **New Castle County in Delaware.**

HIGHWAY CONSTRUCTION PROJECTS

Note: Contracts subject to the Davis-Bacon Act are generally required to pay at least the applicable minimum wage rate required under Executive Order 14026 or Executive Order 13658. Please note that these Executive Orders apply to covered contracts entered into by the federal government that are subject to the Davis-Bacon Act itself, but do not apply to contracts subject only to the Davis-Bacon Related Acts, including those set forth at 29 CFR 5.1(a)(2)-(60). If the contract is entered into on or after January 30, 2022, or the contract is renewed or extended (e.g., an option is exercised) on or after January 30, 2022, Executive Order 14026 generally applies to the contract. The contractor must pay all covered workers at least \$17.75 per hour (or the applicable wage rate listed on this wage determination, if it is higher) for all hours spent performing on the contract in 2025. If the contract was awarded on or between January 1, 2015 and January 29, 2022, and the contract is not renewed or extended on or after January 30, 2022, Executive Order 13658 generally applies to the contract. The contractor must pay all covered workers at least \$13.30 per hour (or the applicable wage rate listed on this wage determination, if it is higher) for all hours spent performing on that contract in 2025. The applicable Executive Order minimum wage rate will be adjusted annually. If this contract is covered by one of the Executive Orders and a classification considered necessary for performance of work on the contract does not appear on this wage determination, the contractor must still submit a conformance request. Additional information on contractor requirements and worker protections under the Executive Orders is available at <https://www.dol.gov/agencies/whd/government-contracts>.

Modification Number	Publication Date
0	01/03/2025
1	05/02/2025

	Rates	Fringes
POWER EQUIPMENT OPERATOR		
Backhoe/Excavator/Trackhoe..\$	45.81	30.38
Bobcat/Skid Steer/Skid		
Loader.....\$	43.76	29.77
Crane.....\$	45.81	30.38
Drill.....\$	43.76	29.77
Paver (Asphalt, Aggregate		
and Concrete).....\$	45.81	30.38
Pounder.....\$	43.76	29.77
Roller.....\$	43.40	29.66

LABO0199-001 05/01/2022		
	Rates	Fringes

LABORER (Asphalt, Includes
 Raker, Shoveler, Spreader and
 Distributor).....\$ 31.15 16.50

 SUDE2022-002 09/08/2022

	Rates	Fringes
CARPENTER.....	\$ 50.06	4.32
CEMENT MASON/CONCRETE FINISHER...	\$ 33.03	5.25
ELECTRICIAN.....	\$ 65.99	0.00
FORM WORKER.....	\$ 49.77	3.37
IRONWORKER, REINFORCING.....	\$ 55.67	0.00
LABORER: Common or General.....	\$ 36.33	3.50
LABORER: Mason Tender - Cement/Concrete.....	\$ 43.30	1.66
OPERATOR: Bulldozer.....	\$ 37.55	16.19
OPERATOR: Loader.....	\$ 38.36	4.31
OPERATOR: Mechanic.....	\$ 28.11	11.18
OPERATOR: Milling Machine.....	\$ 38.29	11.15
TRAFFIC CONTROL: Flagger.....	\$ 37.49	0.00
TRUCK DRIVER: Dump Truck.....	\$ 29.31	9.84

 WELDERS - Receive rate prescribed for craft performing
 operation to which welding is incidental.

=====
 Note: Executive Order (EO) 13706, Establishing Paid Sick Leave for Federal Contractors applies to all contracts subject to the Davis-Bacon Act for which the contract is awarded (and any solicitation was issued) on or after January 1, 2017. If this contract is covered by the EO, the contractor must provide employees with 1 hour of paid sick leave for every 30 hours they work, up to 56 hours of paid sick leave each year. Employees must be permitted to use paid sick leave for their own illness, injury or other health-related needs, including preventive care; to assist a family member (or person who is like family to the employee) who is ill, injured, or has other health-related needs, including preventive care; or for reasons resulting from, or to assist a family member (or person who is like family to the employee) who is a victim of, domestic violence, sexual assault, or stalking. Additional information on contractor requirements and worker protections under the EO is available at <https://www.dol.gov/agencies/whd/government-contracts>.

Unlisted classifications needed for work not included within the scope of the classifications listed may be added after award only as provided in the labor standards contract clauses (29CFR 5.5 (a) (1) (ii)).

 The body of each wage determination lists the classification and wage rates that have been found to be prevailing for the cited type(s) of construction in the area covered by the wage determination. The classifications are listed in alphabetical order under rate identifiers indicating whether the particular rate is a union rate (current union negotiated rate), a survey rate, a weighted union average rate, a state adopted rate, or a supplemental classification rate.

Union Rate Identifiers

A four-letter identifier beginning with characters other than ""SU"", ""UAVG"", ?SA?, or ?SC? denotes that a union rate was prevailing for that classification in the survey. Example: PLUM0198-005 07/01/2024. PLUM is an identifier of the union whose collectively bargained rate prevailed in the survey for this classification, which in this example would be Plumbers. 0198 indicates the local union number or district council number where applicable, i.e., Plumbers Local 0198. The next number, 005 in the example, is an internal number used in processing the wage determination. The date, 07/01/2024 in the example, is the effective date of the most current negotiated rate.

Union prevailing wage rates are updated to reflect all changes over time that are reported to WHD in the rates in the collective bargaining agreement (CBA) governing the classification.

Union Average Rate Identifiers

The UAVG identifier indicates that no single rate prevailed for those classifications, but that 100% of the data reported for the classifications reflected union rates. EXAMPLE: UAVG-OH-0010 01/01/2024. UAVG indicates that the rate is a weighted union average rate. OH indicates the State of Ohio.

The next number, 0010 in the example, is an internal number used in producing the wage determination. The date, 01/01/2024 in the example, indicates the date the wage determination was updated to reflect the most current union average rate.

A UAVG rate will be updated once a year, usually in January, to reflect a weighted average of the current rates in the collective bargaining agreements on which the rate is based.

Survey Rate Identifiers

The ""SU"" identifier indicates that either a single non-union rate prevailed (as defined in 29 CFR 1.2) for this classification in the survey or that the rate was derived by computing a weighted average rate based on all the rates reported in the survey for that classification. As a weighted average rate includes all rates reported in the survey, it may include both union and non-union rates. Example: SUFL2022-007 6/27/2024. SU indicates the rate is a single non-union prevailing rate or a weighted average of survey data for that classification. FL indicates the State of Florida. 2022 is the year of the survey on which these classifications and rates are based. The next number, 007 in the example, is an internal number used in producing the wage determination. The date, 6/27/2024 in the example, indicates the survey completion date for the classifications and rates under that identifier.

?SU? wage rates typically remain in effect until a new survey is conducted. However, the Wage and Hour Division (WHD) has the discretion to update such rates under 29 CFR 1.6(c)(1).

State Adopted Rate Identifiers

The ""SA"" identifier indicates that the classifications and prevailing wage rates set by a state (or local) government were adopted under 29 C.F.R 1.3(g)-(h). Example: SAME2023-007 01/03/2024. SA reflects that the rates are state adopted. ME refers to the State of Maine. 2023 is the year during which the

state completed the survey on which the listed classifications and rates are based. The next number, 007 in the example, is an internal number used in producing the wage determination.

The date, 01/03/2024 in the example, reflects the date on which the classifications and rates under the ?SA? identifier took effect under state law in the state from which the rates were adopted.

WAGE DETERMINATION APPEALS PROCESS

1.) Has there been an initial decision in the matter? This can be:

- a) a survey underlying a wage determination
- b) an existing published wage determination
- c) an initial WHD letter setting forth a position on a wage determination matter
- d) an initial conformance (additional classification and rate) determination

On survey related matters, initial contact, including requests for summaries of surveys, should be directed to the WHD Branch of Wage Surveys. Requests can be submitted via email to davisbaconinfo@dol.gov or by mail to:

Branch of Wage Surveys
Wage and Hour Division
U.S. Department of Labor
200 Constitution Avenue, N.W.
Washington, DC 20210

Regarding any other wage determination matter such as conformance decisions, requests for initial decisions should be directed to the WHD Branch of Construction Wage Determinations. Requests can be submitted via email to BCWD-Office@dol.gov or by mail to:

Branch of Construction Wage Determinations
Wage and Hour Division
U.S. Department of Labor
200 Constitution Avenue, N.W.
Washington, DC 20210

2.) If an initial decision has been issued, then any interested party (those affected by the action) that disagrees with the decision can request review and reconsideration from the Wage and Hour Administrator (See 29 CFR Part 1.8 and 29 CFR Part 7). Requests for review and reconsideration can be submitted via email to dba.reconsideration@dol.gov or by mail to:

Wage and Hour Administrator
U.S. Department of Labor
200 Constitution Avenue, N.W.
Washington, DC 20210

The request should be accompanied by a full statement of the interested party's position and by any information (wage payment data, project description, area practice material, etc.) that the requestor considers relevant to the issue.

3.) If the decision of the Administrator is not favorable, an interested party may appeal directly to the Administrative Review Board (formerly the Wage Appeals Board).

Write to:

Administrative Review Board
U.S. Department of Labor
200 Constitution Avenue, N.W.
Washington, DC 20210

=====

END OF GENERAL DECISION

Contract T202201102
US 13 SOUTHBOUND BBRT LANE

SPECIAL PROVISIONS

S.P. Code	SPECIAL PROVISION DESCRIPTION
401502-20	ASPHALT CEMENT COST ADJUSTMENT
401510-20	TACK COAT
401580-20	RIDE QUALITY OF BITUMINOUS PAVEMENT
401699-20	QUALITY CONTROL/QUALITY ASSURANCE OF BITUMINOUS CONCRETE
701511-20	PCC CURB, SPECIAL
705528-20	TEMPORARY PEDESTRIAN CONNECTION
763501-20	CONSTRUCTION ENGINEERING
763520-20	ELECTRONIC TICKETING
763525-20	ROAD USER COST
806500-20	TRAFFIC OFFICERS
831501-20	PROVIDE AND INSTALL 4" SCHEDULE 80 PVC CONDUIT (OPEN CUT)
831514-20	PROVIDE AND INSTALL 2-1/2" SCHEDULE 80 PVC CONDUIT (TRENCH)
831545-20	PROVIDE AND INSTALL 4" HDPE SDR-13.5 CONDUIT (BORE)
831564-20	PROVIDE AND INSTALL 1-1/2" GALVANIZED STEEL CONDUIT (TRENCH)

401502 - ASPHALT CEMENT COST ADJUSTMENT

For Sections 304, 401, 402, 403, 404, and 405, payments to the Contractor shall be adjusted to reflect increases or decreases in the Delaware Posted Asphalt Cement Price when compared to the Project Asphalt Cement Base Price, as defined in these Special Provisions.

The Delaware Posted Asphalt Cement Price will be issued monthly by the Department and will be the industry posted price for Asphalt Cement, F.O.B. Philadelphia, Pennsylvania. The link for the posting is https://deldot.gov/Business/bids/index.shtml?dc=asphalt_cement_english.

The Project Asphalt Cement Base Price will be the Delaware Posted Asphalt Cement Price in effect on the date of advertisement.

All deviations of the Delaware Posted Asphalt Cement Price from the Project Asphalt Cement Base Price are eligible for cost adjustment. No minimum increases or decreases or corresponding percentages are required to qualify for cost adjustment.

Actual quantity of asphalt cement qualifying for any Asphalt Cement Cost Adjustment will be computed using the weight of eligible asphalt that is shown on the QA/QC pay sheets as a percentage for the delivered material.

If the mix was not inspected and no QA/QC pay sheet was generated, then the asphalt percentage will be obtained from the job mix formula for that mix ID. The asphalt percentage eligible for cost adjustment shall only be the virgin asphalt cement added to the mix.

There shall be no separate payment per ton cost of asphalt cement. That cost shall be included in the various unit prices bid per ton for those bid items that contain asphalt cement (mentioned above).

The Asphalt cement cost adjustment will be calculated on grade PG 64-22 asphalt regardless of the actual grade of asphalt used.

If the Contractor exceeds the authorized allotted completion time, the price of asphalt cement on the last authorized allotted workday, shall be the prices used for cost adjustment during the time liquidated damages are assessed. However, if the industry posted price for asphalt cement goes down, the asphalt-cement cost shall be adjusted downward accordingly.

Contract No. T202201102

NOTE:

Application of Asphalt Cement Cost Adjustment requirements as indicated above shall apply only to those contracts involving items related to bituminous base and pavements, and with bitumen, having a total of 1,000 tons or more of hot-mix bid quantity in case of Sections 401, 402 and 403; and 15,000 gallons or more in case of Sections 304, 404 and 405.

12/14/2020

401510 – TACK COAT

Description:

The Department will not measure and will make no payment for this item. This language replaces Section 1011 of the Standard Specifications.

SECTION 1011 -TACK COAT

1011.1 Description.

Provide material in accordance with 1011.2 for thin lift maintenance applications, or as directed by the engineer. Provide material in accordance with Section 1011.3 and selected from the approved product list and in accordance with manufacturer recommendations for all other applications.

1011.2 Asphalt Cement (PG Graded).

Provide PG-64-22 (PG 64S-22) as tack coat in lieu of emulsified asphalts.

1011.3 Emulsified Asphalts.

1. Anionic emulsified asphalt in accordance with M140 except the sieve test requirement for field samples collected at the point of use shall be a maximum of 0.4 percent.
2. Cationic emulsified asphalt in accordance with M208 except the sieve test requirement for field samples collected at the point of use shall be a maximum of 0.4 percent.
3. Polymer-modified cationic emulsified asphalts in accordance with M316 except the sieve test requirement for field samples collected at the point of use shall be a maximum of 0.4 percent.
4. Non-Tracking emulsified asphalt in conformance with Table 1011.3-1.

Table 1011.3-1 Non-Tracking Emulsified Asphalt Requirements.		
Property	Test Method	Requirement
Saybolt Viscosity at 77 F, (SFS)	AASHTO T59	15-100
Storage Stability Test, 24 hours, (%)	AASHTO T59	1 maximum
Residue by Distillation or Residue by Evaporation, (%)	AASHTO T59	50 minimum
Sieve Test, No. 20, (%)	AASHTO T59	0.4 maximum for field samples
Penetration at 77 F, 100 g, 5 s, (dmm)	AASHTO T49	10-40
Solubility in Trichloroethylene, (%)	AASHTO T44	97.5 minimum

6/11/2024

401580 - RIDE QUALITY OF BITUMINOUS PAVEMENT

Description:

This specification outlines requirements for an acceptable ride surface in addition to requirements established in DelDOT Standard Specifications. The Contractor is responsible for providing smoothness characteristics that meet these requirements. The Contractor is responsible for providing equipment, maintenance of traffic (MOT) as required by the Delaware MUTCD, and performing testing in accordance to this specification. All costs for testing and MOT are incidental to this item. Both the International Roughness Index (IRI) and deviations located within a 10' straightedge are used to characterize smoothness in this Special Provision.

Definitions:

Class 1 Project - a project that consists of full depth construction. Full depth construction is considered to be when contract documents or modifications provide opportunity for preparation of the subgrade prior to paving.

Class 2 Project - a project that consists of a minimum of two smoothness opportunities.

Class 3 Project - a project that consists of one smoothness opportunity.

Deviation - a hump or depression that exceeds defined tolerances.

Smoothness Opportunity - a smoothness opportunity is considered to be any of the following; roadway milling, placement of a leveling course, in-place recycling, or placement of a lift of bituminous concrete. The final wearing surface is considered one smoothness opportunity.

Equipment:

The Contractor must have a 10' straightedge available during all paving operations.

The Contractor must also have a high speed or lightweight inertial profiling system that meets requirements of AASHTO M328 capable of collecting data in both wheelpaths simultaneously.

Contract No. T202201102

Prior to the start of corrective actions, the Contractor must provide to the Engineer:

1. Manufacturer, Make, and Model of the test system
2. Equipment Owner,
3. Relevant Certifications,
4. Manufacturer Calibration Procedures, and
5. Relevant Operator Training information.

Testing:

The Contractor is responsible for testing the pavement surface using an approved inertial profiler in accordance to manufacturer and AASHTO R57 from the start of paving limits to the end of pavement limits. Testing must be performed 3 times in each lane paved in the direction of traffic flow. Testing must be performed within seven (7) days of completion of project paving operations in each location.

The Contractor is responsible for providing information relative to locations that are to be excluded from calculation of the International Roughness Index. These areas must still meet 10' straightedge requirements.

Areas that are to be tested but will be removed prior to IRI analysis are:

1. 50 feet prior to the first bridge deck expansion joint and 50 feet after the last expansion joint if a bridge deck is excluded from smoothness operations.
2. 50' longitudinally from the center of an existing obstruction within the test area such as a manhole, water main, or catch basin that impedes paving operations.
3. 50' longitudinally from transverse joints that separate it from existing pavement not included on this contract.

Areas that are not to be profiled but are still subject to 10' straightedge requirements are:

1. Shoulder areas
2. Parking lots
3. Ramps, Streets, or Acceleration / Deceleration lanes less than 1000' in length.

Submission Requirements:

Test results must be submitted to the Engineer within five working days of completion of testing. Results not received within the allotted time frame will be assessed a charge of \$1,000.00 per day at the discretion of the Engineer.

The Contractor is required to submit summary table IRI reports from their test equipment for 1 run for each lane and direction of paving. This report must also include:

1. Profiling Company Name
2. Date of Test
3. Contract Number
4. Location Description
5. Testing Personnel

The Contractor is required to submit ERD files for each of the 3 tests run in each lane and direction of paving to the Engineer for analysis. The Contractor must provide to the Engineer written documentation indicating the start and end of bridges and the center of obstructions relative to the stationing used on the testing that are not subject to IRI analysis.

Acceptance and Payment:

Acceptance of the final pavement will be based on Engineer calculated IRI values using ProVAL software upon removal of allowable areas of exemption and the number of deviations found in the pavement surface. The IRI measurements will be calculated in 0.1 mile (528 foot) sections for payment purposes. The average value of the three test runs will be used and the average value will be rounded to the nearest tenth. Payments for each section will be based on estimated tonnage calculated from plan thickness and widths using the average maximum specific gravity ("Rice") for all surface mix used at that location.

Deviations equal to or in excess of 0.25" in 10' are to be corrected at the Contractor's expense or will have a discount charge of \$200.00 per deviation.

$$\text{Estimated Tonnage} = [L * W * T] * \text{Rice} * 62.4 \text{ (lb/ft}^3\text{)} * (0.0005 \text{ tons / 12 in.)}$$

Contract No. T202201102

Where: L = Length Segment (ft.)

W = Lane Width (ft.)

T = Plan Thickness (in.)

$$IRI \text{ Incentive / Disincentive} = \text{Estimated Tonnage} * UP * (PA-100)/100$$

Where: UP = Contract Unit Price (Dollars)

PA = Pay Adjustment (Table A)

The total pay adjustment for paving work performed on each location is:

$$(\sum IRI \text{ adj for each section}) - \text{Total Deviations} * 200$$

It is possible to receive incentive for IRI measurements and a discount charge for excessive deviations on the same project. If a 528' section has an IRI value resulting in a deduction of at least 84% of the section pay, the deviation discount charge for that section is disregarded and the IRI discount charge is the only action taken for that section.

Table A: Payment Adjustments for IRI	
Class 1	
IRI per 0.1 mile Segment (in./mi.)	Pay Adjustment
≤ 50	103%
> 50 and < 145	100+ 0.2(65- IRI)
≥ 145	84%
Class 2	
IRI per 0.1 mile Segment (in./mi.)	Pay Adjustment
≤ 60	106%
> 60 and < 170	100+ 0.2(90- IRI)

Contract No. T202201102

≥ 170	84%
------------	-----

Correction to the paving surface, such as diamond grinding with approved equipment, patching, or other measures may be taken at the Contractor's expense and at the Engineers discretion to correct pavement surfaces assessed a discount charge. The Engineer may require corrective actions including remove & replace if the deviation discount charge exceeds 50% of the cost of materials or the IRI pay adjustment is 84%. Deviations must be corrected if it is determined that they are at a height or depth that may create a safety concern.

4/10/2019

401699 - QUALITY CONTROL/QUALITY ASSURANCE OF BITUMINOUS CONCRETE

.01 Description

This item shall govern the Quality Assurance Testing for supplying bituminous asphalt plant materials and constructing bituminous asphalt pavements and the calculation for incentives and disincentives for materials and construction. The Engineer will evaluate all materials and construction for acceptance. The procedures for acceptance are described in this Section. Include the costs for all materials, labor, equipment, tools, and incidentals necessary to meet the requirements of this specification in the bid price per ton for the bituminous asphalt. Payment to the Contractor for the bituminous asphalt item(s) will be based on the Contract price per ton and the pay adjustments described in this specification.

.02 Bituminous Concrete Production – Quality Acceptance

(a) Material Production - Tests and Evaluations.

All acceptance tests shall be performed by qualified technicians at qualified laboratories following AASHTO or DelDOT procedures and shall be evaluated using Quality Level Analysis. The Engineer will conduct acceptance tests. The Engineer will directly base acceptance on the acceptance test results, the asphalt cement quality, the Contractor's QC Plan work, and the comparisons of the acceptance test results to the QC test results. The Engineer may elect to utilize test results of the Contractor in some situations toward judging acceptance.

Supply and capture samples, as directed by the Engineer under the purview of the Engineer from delivery trucks before the trucks leave the production plant. Hand samples to the Engineer to be marked accordingly. The sample shall represent the material produced by the Contractor and shall be of sufficient size to allow the Engineer to complete all required acceptance tests. The Engineer will direct the Contractor when to capture these samples, on a statistically random, unbiased basis, established before production begins each day based upon the anticipated production tonnage. The captured sample shall be from the Engineer specified delivery truck. The Contractor may visually inspect the specified delivery load during sampling and elect to reject the load. If the contractor elects to reject the specified delivery truck, each subsequent load will be inspected until a visually acceptable load is produced for acceptance testing. All visually rejected loads shall not be sent to a Department project.

The first sample of the production day will be randomly generated by the Engineer between loads 0 and 12 (0-250 tons). Subsequent samples will be randomly generated by the Engineer on 500-ton sub-lots for the production day. Samples not retrieved in accordance with the Contractor's QC plan will be deemed unacceptable and may be a

Contract No. T202201102

basis for rejection of material produced. Parallel tests or dispute resolution tests will only be performed on material captured at the same time and location as the acceptance test sample. Parallel test samples or Dispute Resolution samples will be created by splitting a large sample or obtaining multiple samples that equally represent the material. The Engineer will perform all splitting and handling of material after it is obtained by the Contractor.

The Contractor may retain dispute resolution samples or perform parallel tests with the Engineer on any acceptance sample.

The Engineer will evaluate and accept the material on a lot basis. All the material within a lot shall have the same JMF (mixture ID). The lot size shall be targeted for 2000 tons or a maximum period of three days, whichever is reached first. If the 2000th ton target lot size is achieved during a production day, the lot size shall extend to the end of that production day. The Contractor may interrupt the production of one JMF in order to produce different material; this type of interruption will not alter the determination of the size or limits of material represented by a lot. The Engineer will evaluate each lot on a subplot basis. The size for each subplot shall be 100 to 500 tons and testing for the sub lots will be completed on a daily basis. For each subplot, the Engineer will evaluate one sample.

The target size of sub-lots within each lot, except for the first sample of the production day, is equal-sized 500 ton sub lots and will be based upon anticipated production, however, more or fewer sublots, with differing sizes, may result due to the production schedule and conditions. If the actual production is less than anticipated, and it's determined a sample will not be obtained (based upon the anticipated tonnage), a new sample location will be determined on a statistically random, unbiased basis based upon the new actual production. If the actual production is going to be 50 tons or greater over the anticipated sub lot production, a new sample location will be determined on a statistically random, unbiased basis based upon the new actual production. The Engineer will combine the evaluation and test results for all of the applicable sublots in order to evaluate each individual lot.

If the Engineer is present, and the quantity exceeds 25 tons, a statistically random sample will be used for analysis. When the anticipated production is less than 100 tons and greater than 25 tons, and the Engineer is not present, the contractor shall randomly select a sample using the Engineer's random location program. The captured sample shall be placed in a suitable box, marked to the attention of the Engineer, and submitted to the Engineer for testing. A box sample shall also be obtained by the contractor at the same time and will be used as the Dispute Resolution sample if requested by the Engineer. The Contractor shall also obtain one liquid asphalt sample (1 pint) per grade of asphalt used per day and properly label it with all pertinent information.

The Engineer will conduct the following tests in order to characterize the material for the pavement compaction quality and to judge acceptance and the pay adjustment for the material:

- AASHTO T312 - Preparing and Determining the Density of Hot Mix Asphalt (HMA) Specimens by Means of the Superpave Gyrotory Compactor

Contract No. T202201102

- AASHTO T166, Method C (Rapid Method) - Bulk Specific Gravity of Compacted Hot Mix Asphalt (HMA) Using Saturated Surface Dry Specimens
- AASHTO T308 - Determining the Asphalt Binder Content of Hot Mix Asphalt (HMA) by the Ignition Method
- AASHTO T30 - Mechanical Analysis of Extracted Aggregate
- AASHTO T209 - Theoretical Maximum Specific Gravity and Density of Hot Mix Asphalt (HMA)
- ASTM D7227 - Standard Practice for Rapid Drying of Compacted Asphalt Specimens using Vacuum Drying Apparatus

(b) Pavement Construction - Tests and Evaluations.

The Engineer will directly base acceptance on the compaction acceptance test results, and on the inspection of the construction, the Contractor's QC Plan work, ride smoothness as referenced in the contract documents, lift thickness as referenced in the contract documents, joint quality as referenced in the contract documents, surface texture as referenced in the contract documents, and possibly the comparisons of the acceptance test results to the independent test results. For the compaction acceptance testing, the Engineer will sample the work on a statistically random basis and will test and evaluate the work based on daily production.

Notify the Engineer of any locations within that road segment that may not be suitable to achieve minimum (93%) compaction due to existing conditions prior to paving the road segment. Schedule and hold a meeting in the field with the Engineer in order to discuss all areas that may potentially be applicable to Table 5a before paving starts. Areas that will be considered for Table 5a will be investigated in accordance with the method described in Appendix B. If this meeting is not held prior to paving, no areas will be considered for Table 5a. Areas of allowable exemptions that will not be cored include the following: partial-depth patch areas, driveway entrances, paving locations of less than 100 tons, areas around manholes and driveway entrances, and areas of paving that are under 400 feet in continuous total length and/or 5 feet in width.

The exempt areas around manholes will be a maximum of 4 feet transversely on either side from the center of the manhole, and 20 feet longitudinally on either side from the center of the manhole. The exempt areas around driveway entrances shall be the entire width of the driveway, and 3 feet from the edge of the longitudinal joint next to the driveway. Areas of exemption that will be cored for informational purposes only include: areas where the mat thickness is less than three times the nominal maximum aggregate size as directed by the Engineer, violations of Section 401.08 in the Standard Specifications as directed by the Engineer, and areas shown to contain questionable subgrade properties as proven by substantial yielding under a fully legally loaded truck. Failure to obtain core samples in these areas will result in zero payment for compaction regardless of the exempt status.

The Engineer will evaluate and accept the compaction work on a daily basis. Payment for the compaction will be calculated by using the material production lots as referenced in **.02 Acceptance Plan (a) Material Production - B Tests and Evaluation** and analyzing the compaction results over the individual days covered in the

Contract No. T202201102

material production lot. The compaction results will be combined with the material results to obtain a payment for this item.

The minimum size of a compaction lot shall be 100 tons. If the compaction lot is between 101 and 1000 tons, the Engineer shall randomly determine four compaction acceptance test locations. If the compaction lot is between 1001 and 1500 tons, the Engineer shall randomly determine six compaction acceptance test locations. If the compaction lot is between 1501 and 2000 tons, the Engineer shall randomly determine eight compaction acceptance test locations. If the compaction lot is greater than 2000 tons, the Engineer shall randomly determine two compaction acceptance test locations per 500 tons.

If a randomly selected area falls within an Engineer approved exemption area, the Engineer will select one more randomly generated location to be tested per the requirements of this Specification. If that cannot be accomplished, or if an entire location has been declared exempt, the compaction testing shall be performed as per these Specifications, but a note will be added to the results that the location was an Engineer approved exempt location.

Testing locations will be a minimum of 1.0 feet from the newly placed longitudinal joint and 50 feet from a new transverse joint. Cut one six (6) inch diameter core through the full lift depth at the exact location marked by the Engineer. Cores submitted that are not from the location designated by the Engineer will not be tested and will be paid at zero pay. Notify the Engineer prior to starting paving operations with approximate tonnage to be placed. The Contractor is then responsible for notifying the appropriate Engineer test personnel within 12 hours of material placement. The Engineer will mark core locations within 24 hours of notification. After determination of locations, the Contractor shall complete testing within two operational days of the locations being marked. If the cores are not cut within two operational days, the area in question will be paid at zero pay for compaction testing.

Provide any traffic control required for the structural number investigation, sampling, and testing work at no additional cost to the Department. Commence coring of the pavement after the pavement has cooled to a temperature of 140°F or less. Cut each core with care in order to prevent damaging the core. Damaged cores will not be tested. Label each core with contract number, date of construction, and number XX of XX upon removal from the roadway. Place cores in a 6-inch diameter plastic concrete cylinder mold or approved substitute for protection. Separate cores in the same cylinder mold with paper. Attach a completed QC test record for the represented area with the corresponding cores. The Engineer will also complete a test record for areas tested for the QA report and provide to Materials & Research. Deliver the cores to the Engineer for testing, processing, and report distribution at the end of each production day. Repair core holes per Appendix A, Repairing Core Holes in Bituminous Asphalt Pavements. Core holes shall be filled immediately. Failure to repair core holes at the time of coring will result in zero pay for compaction testing for the area in question.

The Engineer will conduct the following tests on the applicable portion of the cores in order to evaluate their quality:

Contract No. T202201102

- AASHTO T166, Method C (Rapid Method) B Bulk Specific Gravity of Compacted Hot Mix Asphalt (HMA) Using Saturated Surface Dry Specimens
- AASHTO T209 - Theoretical Maximum Specific Gravity and Density of Hot Mix Asphalt
- ASTM D7227 - Standard Practice for Rapid Drying of Compacted Asphalt Specimens using Vacuum Drying Apparatus

The Engineer will use the average of the last five test values of the same JMF (mixture ID) material at the production plant in order to calculate the average theoretical maximum specific gravity of the cores. The average will be based on the production days test results and as many test results needed from previous days production to have an average of five samples. If there are less than five values available, the Engineer will use the JMF design value in addition to the available values to calculate the average theoretical maximum specific gravity.

.03 Payment and Pay Adjustment Factors

The Engineer will determine pay adjustments for the bituminous asphalt item(s) in accordance with this specification. The Engineer will determine a pay adjustment factor for the material produced and a pay adjustment factor for the pavement construction. Pay adjustments for material and construction will be calculated independently. When the pay adjustment calculation for either material or construction falls to zero payment per tables 4, 5, or 5a, the maximum pay adjustment for the other factor will not exceed 100.

Pay Adjustment factors will only be calculated on in place material. Removed material will not be used in payment adjustment calculations.

Material Production Pay Adjustments will be calculated based upon 70% of the contract unit price and calculated according to section .03(a) of this specification. Pavement construction Pay Adjustments will be calculated based upon 30% of the contract unit price and calculated according to section .03(b) of this specification.

(a) Material Production - Pay Adjustment.

Calculate the material pay adjustment by evaluating the production material based on the following parameters:

Table 2 - Material Parameter Weight Factors		
Material Parameter	Single Test Tolerance (+/-)	Weight Factor
Asphalt Content	0.4	0.30
#8 Sieve (>=19.0 mm)	7.0	0.30
#8 Sieve (<=12.5 mm)	5.0	0.30
#200 Sieve (0.075mm Sieve)	2.0	0.30
Air Voids (4.0% Target)	2.0	0.10

Using the JMF target value, the single test tolerance (from Table 2), and the test values, the Engineer will use the following steps to determine the material pay adjustment factor for each lot of material:

1. For each parameter, calculate the mean value and the standard deviation of the test values for the lot to the nearest 0.1 unit.
2. For each parameter, calculate the Upper Quality Index (QU):

$$QU = ((JMF \text{ target}) + (\text{single test tolerance}) - (\text{mean value})) / (\text{standard deviation}).$$
3. For each parameter, calculate the Lower Quality Index (QL):

$$QL = ((\text{mean value}) - (JMF \text{ target}) + (\text{single test tolerance})) / (\text{standard deviation}).$$
4. For each parameter, locate the values for the Upper Payment Limit (PU) and the Lower Payment Limit (PL) from Table 3 - Quality Level Analysis by the Standard Deviation Method. (Use the column for “n” representing the number of sublots in the lot. Use the closest value on the table when the exact value is not listed).
5. Calculate the PWL for each parameter from the values located in the previous step:

$$PWL = PU + PL - 100.$$
6. Calculate each parameter’s contribution to the payment adjustment by multiplying its PWL by the weight factor shown in Table 2 for that parameter.
7. Add the calculated adjustments of all the parameters together to determine the Composite PWL for the lot.

Contract No. T202201102

8. From Table 4, locate the value of the Pay Adjustment Factor corresponding to the calculated PWL. When all properties of a single test are within the single test tolerance of Table 2, Pay Adjustment factors shall be determined by Column B. When any property of a single test is outside of the Single Test Tolerance parameters defined in Table 2, the Material Pay Adjustment factor shall be determined by Column C.
9. For each lot, determine the final material price adjustment:

Final Material Pay Adjustment =

(Lot Quantity) x (Item Bid Price) x (Pay Adjustment Factor) x 70%. This final pay calculation will be paid to the cent.

In lieu of being assessed a pay adjustment penalty, the Contractor may choose to remove and replace the material at no additional cost to the Department. When the PWL of any material parameter in Table 2 is below 60, the Engineer may require the removal and replacement of the material at no additional cost to the Department. Test results on removed material shall not be used in calculation of future PWL calculations for Mixture ID.

The test results from the Engineer on production that is less than 100 tons will be combined with the two most recently completed Engineer tests with the same Mixture ID to calculate payment for the lot encompassing the single test. If that cannot be accomplished, the approved JMF will be used to calculate payment for the lot encompassing the single test. Payment for previously closed lots will not be affected by the analysis.

When a sample is outside of the allowable single test tolerance for any Materials criteria in Table 2, that sample will be isolated. For payment purposes, the test result of the out of acceptable tolerance sample will be combined with the two previous acceptable samples of the same JMF and analyzed per this specification. The material that is considered out of the acceptable tolerance will only include the material within the represented sub-lot (i.e., a maximum of 500 tons). If the previous acceptable test result is from the previous production day, only the material produced on the second production day will be considered out of tolerance. All future sub lots will not include the isolated test. The pay factors for the out of tolerance sample lot will be calculated using column C of table 4.

If, during production, a QA sample test result does not meet the acceptable tolerances and the Contractors QC sample duplicates the QA sample test result, the Contractor can make an appropriate change to the mixture (within the JMF boundaries), and request to have that sample further isolated. After the Contractor has made appropriate changes, the Contractor will visually inspect each produced load. The first visually acceptable load will be sampled and tested. If that sample test result shows compliance with the specifications, the material that is considered out of the acceptable tolerance will include the material from the previous acceptable test result to the third load after the initially sampled and tested sample. If the sample does not meet the specification requirements, the Engineer will no longer accept material. Production may resume when changes have been made and an acceptable sample and test result is obtained.

Table 3 B Quality Level Analysis by the Standard Deviation Method							
PU or PL	QU and QL for An@ Samples						
	n = 3	n = 4	n = 5	n = 6	n = 7	n = 8	n = 9
100	1.16	1.50	1.79	2.03	2.23	2.39	2.53
99	-	1.47	1.67	1.80	1.89	1.95	2.00
98	1.15	1.44	1.60	1.70	1.76	1.81	1.84
97	-	1.41	1.54	1.62	1.67	1.70	1.72
96	1.14	1.38	1.49	1.55	1.59	1.61	1.63
95	-	1.35	1.44	1.49	1.52	1.54	1.55
94	1.13	1.32	1.39	1.43	1.46	1.47	1.48
93	-	1.29	1.35	1.38	1.40	1.41	1.42
92	1.12	1.26	1.31	1.33	1.35	1.36	1.36
91	1.11	1.23	1.27	1.29	1.30	1.30	1.31
90	1.10	1.20	1.23	1.24	1.25	1.25	1.26
89	1.09	1.17	1.19	1.20	1.20	1.21	1.21
88	1.07	1.14	1.15	1.16	1.16	1.16	1.17
87	1.06	1.11	1.12	1.12	1.12	1.12	1.12
86	1.04	1.08	1.08	1.08	1.08	1.08	1.08
85	1.03	1.05	1.05	1.04	1.04	1.04	1.04

Contract No. T202201102

84	1.01	1.02	1.01	1.01	1.00	1.00	1.00
83	1.00	0.99	0.98	0.97	0.97	0.96	0.96
82	0.97	0.96	0.95	0.94	0.93	0.93	0.93
81	0.96	0.93	0.91	0.90	0.90	0.89	0.89
80	0.93	0.90	0.88	0.87	0.86	0.86	0.86
79	0.91	0.87	0.85	0.84	0.83	0.82	0.82
78	0.89	0.84	0.82	0.80	0.80	0.79	0.79
77	0.87	0.81	0.78	0.77	0.76	0.76	0.76
76	0.84	0.78	0.75	0.74	0.73	0.73	0.72
75	0.82	0.75	0.72	0.71	0.70	0.70	0.69
74	0.79	0.72	0.69	0.68	0.67	0.66	0.66
73	0.75	0.69	0.66	0.65	0.64	0.63	0.63
72	0.74	0.66	0.63	0.62	0.61	0.60	0.60
71	0.71	0.63	0.60	0.59	0.58	0.57	0.57
70	0.68	0.60	0.57	0.56	0.55	0.55	0.54
69	0.65	0.57	0.54	0.53	0.52	0.52	0.51
68	0.62	0.54	0.51	0.50	0.49	0.49	0.48
67	0.59	0.51	0.47	0.47	0.46	0.46	0.46

Contract No. T202201102

66	0.56	0.48	0.45	0.44	0.44	0.43	0.43
65	0.52	0.45	0.43	0.41	0.41	0.40	0.40
64	0.49	0.42	0.40	0.39	0.38	0.38	0.37
63	0.46	0.39	0.37	0.36	0.35	0.35	0.35
62	0.43	0.36	0.34	0.33	0.32	0.32	0.32

Table 3 B Quality Level Analysis by the Standard Deviation Method

QU and QL for An@ Samples							
PU or PL	n = 3	n = 4	n = 5	n = 6	n = 7	n = 8	n = 9
61	0.30	0.32	0.31	0.30	0.30	0.30	0.30
60	0.36	0.30	0.28	0.27	0.27	0.27	0.26
59	0.32	0.27	0.25	0.25	0.24	0.24	0.24

Table 4 - PWL Pay Adjustment Factors

PWL	Pay Adjustment Factor (%) Column B	Pay Adjustment Factor (%) Column C
100	+5	0
99	+4	-1
98	+3	-2
97	+2	-3
96	+1	-4

Contract No. T202201102

95	0	-5
94	-1	-6
93	-2	-7
92	-3	-8
91	-4	-9
PWL<91	PWL - 100	PWL - 100

(b) Pavement Construction - Pay Adjustments.

The Engineer will determine the pavement construction pay adjustment by evaluating the construction of the pavement, based on the following parameter:

- Degree of compaction of the in-place material

Using the test values for the cores, the Engineer will use the following steps to determine the pavement construction pay adjustment for each lot of work.

1. Calculate the core bulk specific gravity values from the subplot tests values, to the nearest 0.001 unit. Obtain the Theoretical maximum Specific Gravity values from the corresponding laboratory subplot tests.
2. Calculate the Degree of Compaction:
Degree of Compaction =
$$\left(\frac{\text{Core Bulk Specific Gravity}}{\text{Theoretical Maximum Specific Gravity}} \right) \times 100\%$$
 recorded to the nearest 0.1%.
3. The average compaction for the sublots shall be averaged together for the compaction level of the lot. The lots compaction test level shall be averaged and recorded to the nearest whole percent.
4. Locate the value of the Payment Adjustment Factor corresponding to the calculated degree of compaction from Table 5 or Table 5a.
5. Determine the pavement construction price adjustment by using the following formula:

Contract No. T202201102

Construction Pay adjustment = (Lot Quantity) x (Bid Price) x (Pay Adjustment Factor) x 30%.

Table 5: Compaction Price Adjustment Highway Locations		
Degree of Compaction (%)	Range	Pay Adjustment Factor (%)
>= 97.0	>= 96.75	-100*
96.5	96.26 – 96.74	-5
96.0	95.75 – 96.25	-3
95.5	95.26 – 95.74	-2
95.0	94.75 – 95.25	0
94.5	94.26 – 94.74	0
94.0	93.75 – 94.25	1
93.5	93.26 – 93.74	3
93.0	92.75 – 93.25	5
92.5	92.26 – 92.74	3
92.0	91.75 – 92.25	0
91.5	91.26 – 91.74	0
91.0	90.75 – 91.25	-5
90.5	90.26 – 90.74	-15
90.0	89.75 – 90.25	-20
89.5	89.26 – 89.74	-25
89.0	88.75 – 89.25	-30
88.5	88.26 – 88.74	-50
=<88.0	=<88.25	-100*

* or remove and replace it at Engineer's discretion

Table 5A: Compaction Price Adjustment Other¹ Locations

Degree of Compaction	Range	Pay Adjustment Factor (%)
≥ 97.0	≥ 96.75	-100*
96.5	96.26 – 96.74	-5
96.0	95.75 – 96.25	-3
95.5	95.26 – 95.74	-2
95.0	94.75 – 95.25	0
94.5	94.26 – 94.74	0
94.0	93.75 – 94.25	0
93.5	93.26 – 93.74	1
93.0	92.75 – 93.25	3
92.5	92.26 – 92.74	1
92.0	91.75 – 92.25	0
91.5	91.26 – 91.74	0
91.0	90.75 – 91.25	0
90.5	90.26 – 90.74	0
90.0	89.75 – 90.25	0
89.5	89.26 – 89.74	0
89.0	88.75 – 89.25	-1
88.5	88.26 – 88.74	-3
88.0	87.75 – 88.25	-5
87.5	87.26 – 87.74	-10
87.0	86.75 – 87.25	-15
86.5	86.26 – 86.74	-20
86.0	85.75 – 86.25	-25
85.5	85.26 – 85.74	-30
85.0	84.75 – 85.25	-40
84.5	84.26 – 84.74	-50
≤ 84.0	≤ 84.25	-100*

* or remove and replace at Engineer's discretion

¹ This chart is to be used for areas where the structural value of the area to be paved is less than 1.75 as determined by the Engineer. See Appendix B - Method for Obtaining Cores for Determination of Roadway Structure. This chart is applicable to rehabilitation work only; full depth construction will not be considered for Table 5a.

.04 Dispute Resolution

Disputes or questions about any test result shall be brought to the attention of the Contractor and the Engineer within two operational days of reported test results. The following dispute resolution procedures will be used. The Engineer and the Contractor will review the sample quality, the test method, the laboratory equipment, and the laboratory technician. If these factors are not the cause of the dispute, a third-party dispute resolution will be used.

Third party resolution testing can be performed at either another Contractor's laboratory, the Engineer's laboratory, or an independent accredited laboratory. Unless otherwise mutually agreed upon by DAPA and the Engineer, the Engineer's qualified laboratory in Dover and qualified personnel shall conduct the necessary testing for third party Dispute Resolution after the Engineer has provided reasonable notice to allow the Contractor to witness this testing. When disputes over production testing occur, the samples used for Dispute Resolution testing will be those samples the properly captured, labeled, and stored, as described in the second paragraph of the section of these specifications titled **.02 Acceptance Plan, (a) Material Production - Tests and Evaluations**. If no samples are available, the original testing results will be used for payment calculations.

Dispute Resolution samples for air void content will be heated by a microwave oven.

If there is a discrepancy between the Engineer's acceptance test result and the Contractor's test result, the Contractor may ask for the Dispute Resolution sample to be tested. The Contractor may request up to two dispute resolution samples be tested per calendar year without charge. Any additional Dispute Resolution samples run at the Contractors request where the results substantiate the acceptance test result will be assessed a fee of \$125. Any additional Dispute Resolution samples that substantiate the Contractors test result will not be assessed the fee.

When disputes over compaction core test results occur, the Engineer's acceptance core will be used for the dispute resolution sample. The Contractor will be advised on when the testing will occur as referenced above to witness the testing. The results of the dispute resolution testing shall replace all of the applicable disputed test results for payment purposes.

Appendix A - Repairing Core Holes in Bituminous Asphalt Pavement

Description.

This appendix describes the procedure required to repair core holes in a bituminous concrete pavement.

Materials and Equipment.

The following material shall be available to complete this work:

- Patch Material - DelDOT approved High Performance Cold Patch material shall be used.

The following equipment shall be available to complete this work:

- Sponge or other absorbent material - Used to extract water from the hole.
- Compaction Hammer - mechanical (electrical, pneumatic, or gasoline driven) tamping device with a flat, circular tamping face smaller than 6 inches in diameter.

Construction Method.

After core removal from the hole, remove all excess water from within the hole, and prevent water from re-entering the hole.

Place the patch material in lifts no greater than 3 inches and compact with mechanical tamping device. If the hole is deeper than 3 inches, use two lifts of approximately equal depths so that optimum compaction is achieved. Make sure that the patch surface matches the grade of the existing roadway. Make every effort to achieve the greatest possible compaction

Performance Requirements.

The Engineer will judge the patch on the following basis:

Contract No. T202201102

- The patch shall be well compacted
- The patch surface shall match the grade of the surrounding roadway surface.

Basis of Payment.

No measurement or payment will be made for the patching work. The Contractor must gain the Engineer's acceptance of the patching work before the Engineer will accept the material represented by the core.

Appendix B - Method for Obtaining Cores for Determination of Roadway Structure

The Contractor is responsible for obtaining cores in areas that they propose are eligible for compaction price adjustments according to Table 5a in this specification. Table 5a is not applicable for new full-depth pavement box construction. Cores submitted for this process shall be obtained according to the following process.

1. Contact Materials & Research (M&R) personnel to determine if information about the area is already available. If M&R has already obtained cores in the location that is being investigated, the contractor may opt to use the laboratory information for the investigation and not core the area on their own.
2. If M&R does not have information concerning the section of the roadway, the contractor needs to contact M&R to arrange for verification of coring operations. Arrangements shall be made to allow for an individual from M&R to be on the site when the cores are obtained. Cores will be turned over to M&R for evaluation.
3. The Contractor is responsible for providing all traffic control and repairing core holes in accordance to 401699 Appendix A - Repairing Core Holes in Bituminous Asphalt Pavements.
4. Cores are to be taken throughout the entire project for the area in question. Cores will be spaced, from the start of the project in increments determined based on field and project specifics. Cores will be evenly distributed throughout the project location. The cores will be taken in the center of the lane in question.
5. Additional cores may be taken at other locations, if surface conditions indicate that there may be a substantial difference in the underlying section. The location of these cores should be documented and submitted to M&R.
6. Cores shall be full depth and include underlying materials. If there is a stone base included in the pavement section, at a minimum 1 core must have information concerning the thickness of the base. This is determined by augering to the subgrade surface.

Contract No. T202201102

7. The calculations used to determine the structural capacity of the roadway is as follows. If the contractor finds, upon starting the coring process, that the areas are of greater thickness than applicable to Table 5a, they may terminate the coring process on their own and retract the request.

Structural Number Calculations

Each pavement box material is assigned a structural coefficient based upon AASHTO design guides. The structural coefficient is used to determine the total strength of the pavement section.

Materials used in older pavement sections are assigned lower structural coefficients to compensate for aging of the materials. The coefficients used to determine the structural number of an existing pavement are:

Existing Material	Structural Coefficient
HMA	0.32
Asphalt Treated Base	0.26
Soil Cement	0.16
Surface Treatment (Tar & Chip)	0.10
GABC	0.14
Concrete	0 - 0.7*

* The Structural Coefficient of Concrete is dependent upon the condition of the concrete. Compressive strengths & ASR analysis are used to determine condition - contact the Engineer if this situation arises.

Contract No. T202201102

For the Type C lift the calculation would be:

Newly Placed B	$2.25 * 0.4$	=	0.90
Existing HMA	$2 * 0.32$	=	0.64
GABC	$7 * 0.14$	=	0.98
			<u>2.52</u>

11/3/20

Contract No. T202201102
701511 - PCC Curb, Special

Description:

This work consists of constructing Portland Cement Concrete Curb, Special.

Materials:

In accordance with Section 701.2.

Construction Methods:

Construct PCC Curb, Special in accordance with Section 701.3.

Method of Measurement:

The Department will measure PCC curb, special as the numb of linear feet measured along the face of acceptably placed and completed curb.

Basis of Payment:

The Department will pay the quantity of PCC curb, special in accordance with Section 701.5

3/19/24

705528 - TEMPORARY PEDESTRIAN CONNECTION

DESCRIPTION:

This work consists of constructing and maintaining temporary pedestrian connections at required locations.

MATERIALS:

A. Graded Aggregate	Section 1005
B. Asphalt Cement	Section 1012
C. Asphalt Materials Production	Section 1014
D. Cold Patch	Section 1015
E. PCC, Class B	Section 1022
F. Curing Compound	Section 1022
G. Wood	Section 1041
H. 1/2-Inch Preformed Expansion Joint Material	Section 1042
I. Joint or Crack Sealant Material	Section 1042
J. Truncated dome detectable warning surface	Section 705

Prefabricated pedestrian connection systems that meet the accessibility requirements may be used with approval of the engineer.

SUBMITTALS:

- A. Submit proposed temporary pedestrian connection locations and materials to be used during each stage of construction to the engineer for approval. Perform no fabrication or installation until approved by the engineer.
- B. Provide a concrete flatwork technician with an ACI or NRMCA certification, or a certification from another Department approved certification program, to supervise all required concrete finishing. Provide the certification to the engineer before placing concrete.

ACCESSIBILITY REQUIREMENTS:

- A. Temporary pedestrian connections are required wherever an accessible pedestrian route crosses a curb or experiences a change of grade requiring a temporary pedestrian connection.
- B. Constructed temporary pedestrian connections must meet the accessibility standards contained in the current edition of the DeIDOT PAS Manual at the date of advertisement. If there is a conflict between the accessibility requirements identified in the current edition of the DeIDOT PAS Manual and the accessibility requirements listed below, the requirements of the DeIDOT PAS Manual will take precedence.
 - 1. Continuous clear width.
 - a. Provide a minimum continuous clear width of temporary pedestrian connections through medians and pedestrian refuge islands of 5-feet.
 - b. Provide a minimum continuous clear width of temporary pedestrian connections not through medians and pedestrian refuge islands of 4-feet.

Contract No. T202201102

2. Turning spaces.
 - a. Provide turning spaces at locations where the pedestrian must change their primary direction of travel. Turning spaces on pedestrian connections occur at the following locations.
 - i. Perpendicular curb ramps – at the top of the curb ramp.
 - ii. Parallel curb ramps – at the bottom of the curb ramp.
 - iii. Diagonal curb ramps – at the top of the curb ramp.
 - iv. Combination curb ramps – between the parallel curb ramp used to lower the elevation of the approach pedestrian access route and the perpendicular ramp which connects to the pedestrian street crossing.
 - v. Depressed corners – location will vary by application.
 - b. Provide a turning space running slope which is limited to 2.0 percent maximum.
 - c. Turning space cross slope will vary based on pedestrian connection type and subsequent location of the turning space.
 - i. Provide a turning space cross slope of 2.0 percent maximum at locations where the turning space does not adjoin the pedestrian street crossing.
 - ii. At locations where the turning space adjoins the pedestrian street crossing, the cross slope is limited as follows.
 - (1.) Limit cross slope to 2.0 percent maximum when the pedestrian street crossing has a cross slope less than 2.0 percent.
 - (2.) The cross slope of the turning space may match the cross slope of the pedestrian street crossing when the cross slope of the pedestrian street crossing exceeds 2.0 percent.
 - d. Size.
 - i. Provide a 4-foot x 4-foot minimum turning space at unconstrained turning space locations. Unconstrained turning spaces are turning spaces where no feature adjacent to the turning space projects more than 2-inches above the pedestrian access route.
 - ii. Provide a 5-foot x 4-foot minimum turning space at constrained turning space locations. Constrained turning spaces are turning spaces where a feature adjacent to the turning space projects more than 2-inches above the pedestrian access route. The orientation of the 5-foot dimension varies by location.
 - (1.) Perpendicular curb ramp – the long dimension in the direction of the ramp run.
 - (2.) Parallel curb ramp – the long dimension in the direction of the pedestrian street crossing.
 - (3.) Diagonal curb ramp – the long dimension in the direction of the ramp run.
3. Ramp runs.
 - a. Ramp running slope.
 - i. Provide a ramp running slope as flat as practical and which does not exceed 8.3 percent if the ramp length is under 15-feet in length.
 - ii. Ramps that are 15-feet in length may have a running slope that exceeds 8.3 percent.
 - b. Ramp cross slope will vary based on pedestrian connection type and location of the ramp run.
 - i. Provide a ramp cross slope less than 2.0 percent when the ramp run does not adjoin the pedestrian street crossing.
 - ii. At locations where the ramp run adjoins the pedestrian street crossing, the cross slope is limited as follows.
 - (1.) Limit cross slope to 2.0 percent maximum when the pedestrian street crossing has a cross slope less than 2.0 percent.
 - (2.) The cross slope of the ramp run may match the cross slope of the pedestrian street crossing when the cross slope of the pedestrian street crossing exceeds 2.0 percent.

Contract No. T202201102

4. Provide a temporary pedestrian connection surface that is firm, stable, and slip resistant.
5. Grade breaks:
 - a. Provide grade breaks at the top and bottom of curb ramp runs perpendicular to the direction of the ramp run.
 - b. Surfaces that meet at grade breaks must be flush.
6. Where vertical deviations are permitted, they are limited based on the change in level between the two adjacent surfaces:
 - a. Changes in level between 0-inches to 1/4-inches are permitted to be vertical.
 - b. Bevel at a slope no steeper than 2:1 (H:V) for changes in level between 1/4-inches to 1/2-inches.
 - c. Ramp at a slope no steeper than 8.3 percent for changes in level greater than 1/2-inches.
7. Provide flared sides on perpendicular curb ramps and blended transitions where the ramp or blended transition edge abuts a walkable surface. Flared sides are to have a maximum slope of 10.0 percent measured at the back of the depressed curb.
8. Provide a counter slope at the gutter pan or street at the foot of the curb ramp run, blended transition, and turning space at no more than 5.0 percent maximum.
9. Truncated dome detectable warnings:
 - a. Provide dome pattern, dome spacing, dome size, and contrast that meets the DeDOT PAS Manual requirements.
 - b. Provide a detectable warning surface that extends 2-foot minimum in the direction of travel and extends the full width of the curb ramp, blended transition, or turning space.
 - c. Location of the detectable warning will vary by facility.
 - i. Perpendicular curb ramp – place detectable warning surface as follows:
 - (1.) Place detectable warning surface at the back of curb at locations where the ends of the bottom grade break are in front of the back of curb.
 - (2.) Place detectable warning surface within one dome spacing of the bottom grade break at locations where the distance from either end of the bottom grade brake to the back of curb is 5-feet or less.
 - (3.) Place detectable warning surface at the back of curb at locations where the bottom grade brake to the back of curb is more than 5-feet.
 - ii. Parallel curb ramp – detectable warning surface at the back of curb on the turning space at the flush transition between the street and sidewalk.
 - iii. Blended Transitions – detectable warning surface at the back of curb at the flush transition between the street and sidewalk.
10. Align the pedestrian connection and the crosswalk so that a 4-foot x 4-foot clear space area located below the bottom grade break of curb ramp and blended transition is contained wholly within the crosswalk. Only diagonal curb ramps require that the clear space be located outside of the parallel vehicle travel lane and that a segment of curb 2-foot long minimum be located on each side of the diagonal curb ramp's flared sides and be within the marked crossing.
11. Provide positive drainage to prevent water and debris accumulation.

CONSTRUCTION:

- A. Construction methods will vary based upon construction material utilized.
 1. Place PCC in accordance with Section 501.

Contract No. T202201102

2. Place bituminous pavement in accordance with Section 401 or Section 403, as determined by the engineer.
- B. Maintain temporary pedestrian connections in a manner that preserves the accessibility of the feature and of the pedestrian access route it serves. Maintenance may require temporary pedestrian connection relocation or repositioning due to space limitations during the contract duration.
- C. Remove and replace any damaged pedestrian connections that no longer meet Accessibility Requirements.
- D. Replace any stolen pedestrian connection.
- E. Remove temporary pedestrian connections at the completion of the project or at the direction of the engineer. Restore the area to its previous condition unless directed otherwise by the engineer. All material used to construct the temporary pedestrian connection will be the property of the contractor.

METHOD OF MEASUREMENT:

- A. The Department will measure the quantity of temporary pedestrian connections as the number of each installed, accepted, and removed.

BASIS OF PAYMENT:

- A. The Department will pay the quantity of temporary pedestrian connections at the contract unit price per each. Price and payment will constitute full compensation for:
 1. Providing and placing of all materials,
 2. all submittals;
 3. maintenance of the pedestrian connection, and
 4. removal of temporary pedestrian connections.
- B. The Department will not pay for pedestrian connections required to be replaced due to damage or theft.

11/22/2024

763501 - CONSTRUCTION ENGINEERING

763597 – UTILITY CONSTRUCTION ENGINEERING

DESCRIPTION:

- A. This work consists of construction lay out. Subsection 105.10 Construction Stakes, Lines and Grades will be replaced by this spec.
- B. The Department will only establish the following:
 - 1. Original and final cross-sections for borrow pits.
 - 2. Final cross-sections:
 - a. Top and bottom pay limit elevations for all excavation bid items that are not field measured by construction inspection personnel.
 - b. The contractor shall notify the engineer when these pay limit elevations are ready and allow for a minimum of two calendar days for the engineer to obtain the information.
 - 3. Line and grade for extra work added on to the Plans.
- C. When applicable, this work will also consist of providing construction and right-of-way/easement information to utility companies performing work (as defined in the Utility Statement) within the LOC.

MATERIALS:

Not applicable.

CONSTRUCTION METHODS:

- A. Equipment
 - 1. Use and provide written certification that the equipment/instrument has been calibrated and is within manufacturer's tolerance. The certification shall be dated a maximum of 9-months before the start of construction. Renew the certification a minimum of every 9-months. The equipment/instrument shall have a minimum measuring accuracy of [3mm+2ppmxD] and an angle accuracy of up to 2.0-arc-seconds or 0.6-milligons.
 - 2. If the use of GPS technology in construction stakeout is chosen, provide the engineer with a GPS rover and automatic level for the duration of the contract. The GPS rover must be in good working condition and of similar make and model. Provide formal training on the GPS system being used to a maximum of 4, of the engineer's appointees. The formal training must be up to 8-hours or to the satisfaction of the engineer. At the end of the contract, the engineer will return the GPS rover. If any of the equipment/instruments are found to be out of adjustment or inadequate to perform its function, they shall be immediately replaced to the satisfaction of the engineer.

Contract No. T202201102

3. Choosing to use GPS technology does not give the authority to use machine control. Construction Engineering (GPS) Machine Control Grading shall only be used if noted in the contract outlining the available files that will be provided and "the Release for delivery of documents in electronic form to a contractor" are signed by all parties prior to delivery of any electronic files. Only files designated in the contract shall be provided. If machine control grading is allowed on the project, see the machine control section of this specification. GPS technology and machine control technology shall not be used in the construction of bridges.

B. Engineering/Survey Staff

1. Provide and have available an adequate engineering staff that is competent and experienced to set lines, grades, and compatibility with the scope of the project. Additionally, employ an engineer or surveyor, licensed in the State of Delaware, to be responsible for the quality and accuracy of the work done by the engineering staff. When individuals or firms other than the contractor perform any professional services under this item, that work shall not be subject to the subcontracting requirements of Section 108.1. Assume full responsibility for any errors and/or omissions in the work of the engineering staff.

C. Performance Requirements

1. Construction Engineering shall include establishing:
 - a. the survey points and survey centerlines;
 - b. finding, referencing, offsetting the project control points;
 - c. running a horizontal and vertical circuit to verify the precision of given control points.
2. Establishing plan coordinates and elevation marks for:
 - a. culverts,
 - b. slopes,
 - c. subbase,
 - d. subsurface drains,
 - e. paving,
 - f. subgrade,
 - g. retaining walls,
 - h. any other stakes required for control lines and grades.
3. Setting vertical control elevations for:
 - a. footings,
 - b. caps,
 - c. bridge seats and deck screed.
4. Preserve the Department's project control points and benchmarks. Establish and preserve any temporary control points (traverse points or benchmarks) needed for construction. Any project control points (traverse points) or benchmarks conflicting with construction of the project shall be relocated. Replace any or all stakes that are destroyed at any time during the life of the contract as directed by the engineer. Re-establish

Contract No. T202201102

centerline points and stationing prior to final cross-sections by the engineer. The vertical control error of closure shall not exceed 0.035-feet. The horizontal control precision ratio shall have a minimum precision of 1:20,000 feet of distance traversed prior to adjustment.

5. Perform construction centerline layout of all roadways, ramps, connections, and driveways from project control points set by the engineer. Use the profiles and typical sections provided in the plans shall calculate proposed grades at the edge of pavement or verify information shown on the Plans.
6. Advise the engineer of any horizontal or vertical alignment revisions needed to establish smooth transitions to existing facilities. Immediately bring to the attention of the engineer any potential drainage problem within the project limits. The engineer must approve any proposed variation in profile, width, or cross slope.
7. Establish the working points at centerlines of bearings on bridge abutments and on piers, mark the location of anchor bolts to be installed, check the elevation of bearing surfaces before and after they are ground, and set anchor bolts at their exact elevation and alignment in accordance with the contract. Before completion of the fabrication of beams for bridge superstructures, verify the locations, both vertically and horizontally, of all bearings and assume full responsibility for fabricated beams fitting and bearing as constructed. After beam erection and concurrently with the Department project surveyors or their designated representative, survey top of beam elevations at a maximum of 10-foot stations and compute screed grades. Submit the beam elevations to the engineer for review and approval before the stay-in-place forms are set. Construction stakes and other reference control marks shall be set at intervals as established by the engineer to assure that all components of the structure are constructed in accordance with the lines and grades shown on the plans. Take full responsibility for all structure alignment control, grade control and all necessary calculations to establish and set these controls.
8. Investigate proposed construction for possible conflicts with existing and proposed utilities. Report any conflicts to the engineer for resolution.
9. Stake all sidewalk and curb ramp grades in accordance with the contract. Review the stakeout with the engineer prior to construction. The engineer must approve any deviation from the Contract in writing.
10. Stake all drainage inlets in accordance with the Contract. The offsets and top of grate elevations need to be calculated for each type of drainage inlet specified in the contract in order to line up the drainage inlet's flow line with the specified curb or ditch flow line as shown in the contract. The engineer must approve any deviations from the Contract in writing.
11. If wetland areas are involved and specifically defined on the plans the following shall apply:
 - a. Do not enter, damage, or destroy wetland areas, which exist beyond the LOC. These provisions will be strictly enforced, and all personnel shall understand the importance of these provisions.
 - b. Delineate wetlands at the LOC throughout the entire project, before any clearing operations commence as shown on the plans to the satisfaction of the engineer.

Contract No. T202201102

- c. Use orange vinyl flagging material with "Wetland Boundary" printed on the flagging. In wooded areas, tie the flagging on the trees, at approximate 20-foot intervals through wetland areas. In open field and yard areas that have been identified as wetlands, drive 6-foot posts into the ground at approximate 50-foot intervals and tie with the flagging. The flagging shall extend approximately 12-inches in length beyond the post. Use oak posts with cross sectional dimensions of 1 1/2-inches to 2-inches by 1 1/2-inches to 2-inches or 1/4-inch rebar.
 - d. If the flagging has been destroyed and the engineer determines that its use is still required, reflag the area. Flagging shall be replaced within 48-hours of notification that replacement is needed. After 48-hours the engineer may proceed to have the area reflagged.
 - e. Remove all posts and flagging at Project acceptance.
 - f. Assume any responsibility for any damages to wetlands located beyond the LOC, which occurs from his/her operations during the life of the contract. Restore all temporarily disturbed wetland areas to their preconstruction conditions.
12. Whenever the engineer will be recording data for establishment of pay limits, the Contractor will be invited to obtain the data jointly with the engineer's survey crew(s) in order to agree with the information. If the Contractor's representative is not able to obtain the same data, then the information obtained by the engineer shall be considered the information to be used in computing the quantities in question.

D. Submittals

1. All computations, survey notes, electronic files, and other records necessary to accomplish the work shall be preserved and made available to the Department in a neat and organized manner at any time as directed by the engineer. The engineer may check all or any portion of the stakeout survey work or notes and any necessary correction to the work shall be made as soon as possible. Provide the engineer with such assistance as may be required for checking all lines, grades, and measurements necessary for the execution of the work. Checking by the engineer shall not relieve responsibility for the accuracy or completeness of the work. Copies of all notes must be provided to the engineer at the completion of the Project.
2. Submit any of the following at the engineer's request:
 - a. Proposed method of recording information in field books to ensure clarity and adequacy.
 - b. A printout of horizontal control verification, as well as coordinates, differences, and error of closure for all reestablished or temporary control points.
 - c. A printout of vertical control verification, with benchmark location elevation and differences from plan elevation.
 - d. Sketch of location of newly referenced horizontal control, with text printout of coordinates, method of reference and field notes associated with referencing control - traverse closure report.
 - e. Description of newly established benchmarks with location, elevation, and closed loop survey field notes - bench closure report
 - f. All updated electronic and manuscript survey records.

Contract No. T202201102

- g. Stakeout plan for each structure and culvert.
- h. Computations for buildups over beams, screed grades, and overhang form elevations.
- i. A report showing differences between supplied baseline coordinates and field obtained coordinates, including a list of preliminary input data.
- j. Any proposed plan alteration to rectify a construction stakeout error, including design calculations, narrative and sealed drawings.
- k. Baseline for each borrows pit location.
- l. Detailed sketch of proposed overhead ground mounted signs or signals showing obstructions that may interfere with their installation.
- m. Copies of cut sheets.

E. Machine Control Grading

- 1. Machine control grading to be used on the project if authorized by the engineer.
- 2. Use of this procedure and equipment is intended for grading the subgrade surface; it is not intended for the use in constructing final surface grades.
- 3. Materials:
 - a. Provide all equipment required to perform GPS machine control grading, including equipment needed by to verify the work to the engineer.
 - b. Use manufacturer's GPS machine control equipment and system to achieve the grading requirements in accordance with the Contract.
- 4. Construction
 - a. Convert the electronic data provided by the Department into the format required for the equipment.
 - b. The Department will provide no additional electronic data.
 - c. Perform at least one 500-foot test section with the selected GPS system to demonstrate the capabilities, knowledge, equipment, and experience to properly operate the system and meet acceptable tolerances. The engineer will evaluate and make the determination as to whether additional 500-foot test sections are required. Failure to demonstrate this ability to the satisfaction of the engineer, construct the project using conventional surveying and staking methods.
 - d. DelDOT Responsibilities:
 - i. The Department will set initial vertical and horizontal control points in the field for the project as indicated in the contract.
 - ii. The Department will provide the project specific localized coordinate system.
 - iii. The Department may provide data in an electronic format as indicated in the general notes.
 - (1.) The information provided shall not be considered a representation of actual conditions to be encountered during construction. Providing this information does not relieve the responsibility of making an investigation of conditions to be encountered. This includes site visits and basing the bid on information obtained from these investigations, and the professional interpretations

Contract No. T202201102

and judgments of the Contractor.

- (2.) The Department will develop and provide electronic data for use as part of the Contract in the format as indicated in the Plans.
- iv. The Department will provide the following electronic files:
 - (1.) ASCII data files with coordinates and elevations for proposed points as selected by the engineer.
 - (2.) Existing digital terrain model in .dtm file format compatible with software currently used by the Department.
 - (3.) Proposed digital terrain model in .dtm file format compatible with software currently used by the Department.
 - (4.) Design file in .dgn file format, that contains 3D features lines for the proposed design, 3D feature lines are for the proposed top surface elevation only.
- v. The engineer will perform spot checks of the machine control grading results, surveying calculations, records, field procedures, and actual staking. If the work is not being performed in a manner that will assure accurate results, the engineer may order the work to be redone to the requirements of the contract. The engineer may also require the use of conventional surveying and staking.
- e. Contractor's responsibilities:
 - i. No less than 2-weeks before the scheduled preconstruction meeting, submit to the engineer for review a written machine control grading work plan which shall include the equipment type, control software manufacturer and version, and proposed location of the local GPS base station used for broadcasting differential correction data to rover units.
 - ii. If the need to establish new control points, traverse from existing control points and verify to be accurate by conventional surveying techniques.
 - iii. Assume all risks and liabilities of any assumptions or manipulations marked from the electronic information provided or if chosen to develop a separate digital terrain model.
 - iv. Ensure that the electronic data provided will function in their machine control grading system.
 - v. Provide the engineer with a GPS rover and Automatic Level, for use during the duration of the contract. At the end of the contract, the GPS rover and Automatic Level will be returned. Provide a total of 8-hours of formal training on the GPS machine control system to the engineer and up to 3 additional Department appointees per rover.
 - vi. Review and apply the data provided by the Department to perform GPS machine control grading.
 - vii. Convert the electronic data provided by the Department into a format compatible with their system.
 - viii. At the beginning of each work day check and if necessary, recalibrate the GPS machine control system in accordance with the manufacturer's recommendations, or more frequently as needed to meet the requirements of the project.

Contract No. T202201102

- ix. Meet the accuracy requirements as detailed per the Department's standards.
- x. Establish secondary control points at appropriate intervals and at locations along the length of the project. These points shall be outside the project limits and/or where work is performed. These points shall not to exceed 1000-foot intervals. The horizontal position of these points shall be determined by conventional survey traverse and adjustments from the original baseline control points. The conventional traverse shall meet or exceed the Department's Standards. The elevation of these control points shall be established using differential leveling from the project benchmarks, forming a closed loop. A copy of all new control point information including closure report shall be provided and approved by the engineer prior to construction activities. Assume responsibility for all errors resulting from these efforts and correct deficiencies to the satisfaction of the engineer.
- xi. Provide stakes at all alignment control points, at every 500-foot stationing, and where required for coordination activities involving environmental agencies and utility companies.
- xii. Set hubs, at a minimum of 500-foot intervals, at the top of finished grade at all hinge points on the cross section on the main line and at least 4 cross sections on side roads and ramps as directed by the engineer or as shown on the plans. Placement of a minimum of 4 control points outside the limits of disturbance for the excavation of borrow pits, Stormwater Management Ponds, and wetland mitigation sites. These control points shall be established using conventional survey methods for use by the engineer to check the accuracy of the construction.
- xiii. Preserve all reference points and monuments that are identified and established by the engineer for the Project.
- xiv. Provide control points and conventional grades stakes at critical points such as, PC's, PT's, superelevation points, and other critical points required for the construction of drainage and roadway structures.
- xv. Follow the guidelines set forth in the "Geometric Geodetic Accuracy Standards and Specifications for Using GPS Relative Positioning Techniques" and follow a minimum of Second Order Class 1, (2-I) classification standards.
- xvi. Automated equipment operations have a high reliance on accurate control networks from which to take measurements, establish positions, and verify locations and features. Therefore, a strong contract control network in the field which is the same or is strongly integrated with the project control used during the design of the contract is essential to the successful use of this technology with the proposed Digital Terrain Model (DTM). Consistent and well designed site calibration for all machine control operations are required to ensure the quality of the contract deliverables. The Contract Control Plan is intended to document which horizontal and vertical control will be held for these operations. Continued incorporation of the Base Station(s) as identified in the Contract Control Plan is essential to maintaining the integrity of positional locations and elevations of features. The Contract Control Plan shall be submitted to the Department for review and approval

Contract No. T202201102

by the Departments Survey Section 3 weeks prior to the start of any machine control work. Operate and maintain all elements of the Machine Grade Control continuously once the operations begin until otherwise approved by the engineer.

5. Contract Control Plan:

- a. Develop and submit a Contract Control Plan for use of Machine Control Grading. Contract control includes all primary and secondary horizontal and vertical control which will be used for the construction contract. Upon the completion of the initial survey reconnaissance and control verification, but prior to beginning primary field operations, submit a Contract Control Plan document. The Contract Control plan shall be signed and sealed by a Delaware licensed Land Surveyor or Delaware Professional Engineer who oversees its preparation for acceptance by the engineer. The plan shall include the following:
 - i. A control network diagram of all existing horizontal and vertical control recovered in the field as contract control.
 - ii. Include a summary of the calculated closures of the existing control network, and which control has been determined to have been disturbed or out of tolerance from its original positioning.
 - iii. An explanation of which horizontal and vertical control points will be held for construction purposes. If necessary, include all adjustments which may have been made to achieve required closures.
 - iv. An explanation of what horizontal and vertical control (including base stations) was set to accomplish the required stakeout or automated machine operation. Include how the position of these new control points was determined.
 - v. Describe the proposed method and technique (technology and quality control) for utilizing the control to establish the existing and/or proposed feature location and to verify the completed feature location and/or measured quantity.
 - vi. A listing of the horizontal and vertical datums to be used and the combined factor to be used to account for ellipsoidal reduction factor and grid scale factor.
 - vii. If chosen to use machine control as a method of measuring and controlling excavation, fill, material placement or grading operations as a method of measuring and controlling excavation, fill, material placement or grading operations, the Control Plan shall include the method by which the automated machine guidance system will initially be site calibrated to both the horizontal and vertical contract control, and shall describe the method and frequency of the calibration to ensure consistent positional results.

F. Utility construction methods:

1. The engineer must approve all requests for Utility Construction Engineering before the work begins.
2. Instruct utility companies to submit their requests to the engineer. The engineer will decide if the requested work meets the criteria for Utility Construction Engineering or is normal Construction Engineering and

Contract No. T202201102

pass the requests along with the decision.

3. The survey crew size shall be adequate to efficiently perform the work required and must be approved by the engineer.
4. Work covered under Utility Construction Engineering will fall into two categories:
 - a. Engineering/surveying work that is not necessary for construction of the Project, staking the clear zone line, providing cut/fill grades at proposed utility pole locations, staking back of drainage structures, and staking right-of-way lines where construction of the Project (exclusive of utilities) is within the right-of-way.
 - b. Engineering/surveying work that is necessary for construction but must be provided for utility companies well in advance of the need and will likely need to be redone later, as determined by the engineer. This can be any of the Construction Engineering work that when done early cannot be expected to remain undisturbed until needed for construction of the Project (non-utility).

METHOD OF MEASUREMENT:

- A. The Department will not measure construction engineering.
- B. The Department will measure the quantity of utility construction engineering as the number of hours the survey crew is in the field actively engaged in utility construction engineering work.

BASIS OF PAYMENT:

- A. The Department will pay the lump sum unit bid price for this work. Price and payment constitute full compensation for:
 1. the work associated with construction engineering;
 2. providing all equipment and instruments;
 3. providing and placing stakes;
 4. flagging and any reflagging;
 5. reconstruction of work;
 6. all costs related to the development of separate digital terrain model;
 7. reestablishing reference points; and
 8. wetland restoration.
- B. The Department will pay for utility construction engineering at the contract unit price per hour actively engaged in performing the work. Price and payment will constitute full compensation for:
 1. Office work;
 2. providing all labor;
 3. equipment;
 4. instruments;
 5. stakes; and
 6. other materials necessary to complete the Work.

Contract No. T202201102

- C. The Department will make monthly payment in proportion to the amount of work done as determined by the engineer.
- D. The Department will not make any adjustment in payment for any issues with equipment to operate the GPS machine control system for any construction items or be justification for granting contract time extension.
- E. The Department will not make any consideration for any extension of Contract Time or additional compensation due to delays, corrective work, or additional work that may result from faulty and erroneous construction stakeout, surveying, and engineering required.
- F. The Department will not make any adjustments for all liability, costs, or delays if the Contractor chooses to develop a separate digital terrain model.

2/9/23

763520 - ELECTRONIC TICKETING

Description:

This work consists of providing electronic data for material weight tickets delivered to the project. This work also consists of placing an identifying vehicle number on the driver side and the passenger or rear sides of the delivery vehicle. This does not preclude or dismiss any requirement for paper tickets required by the Standard Specifications or other rules and regulations.

General Requirements:

- A. Send electronic tickets (eTicket) to the Department’s Electronic Ticketing Portal <https://tickets.delldot.gov> as they are generated. The Department will reject any load that does not have a corresponding eTicket unless the cause is beyond the contractor’s control. In such circumstances paper tickets may be permitted at the discretion of the engineer.
- B. Payment for material weight delivered to the project will be based upon the eTickets marked “*Delivered*”, less waste, excess material weight as noted in 105.12 of the Standard Specifications, and any audit corrections.
- C. Do not reissue or reprint tickets that have been marked “*Delivered*” or “*Rejected*” without first notifying the engineer. The engineer may reject a reissued or reprinted ticket at their discretion. When a reissued or reprinted ticket is rejected, payment will be based upon the original ticket.

Data Integration:

Request a list of the Department’s naming nomenclature. Include in the request an identification of what system the supplier utilizes for its load read-out weighing system. If necessary, create an Application Programming Interface (API) to integrate with the Department’s eTicketing Portal. Utilize the API to provide electronic data from the load read-out weighing system at the material source that is readable by the Department’s eTicketing Portal. Update the load read-out weighing system and API as necessary to maintain connection the Department’s eTicketing Portal.

The data shall be provided as follows:

Reference Field No.	Description	Examples	Data Type	Required
1	Ticket Number	5126349, 101R, 539-19	String	Yes
2	Contract Number	T202011001	String	Yes

Contract No. T202201102

3	Contract Name (Job)	Walnut Street Streetscape Improvements	String	Yes
4	Contractor Name (Customer)	Mumford & Miller, Inc.; A Del Construction	String	Yes
5	Supplier Name	River Asphalt; Allan Myers Materials	String	Yes
6	Supplier Plant	Plant #1 Dagsboro; Dover Asphalt	String	Yes
7	Job Number (Location)	Task 1; Location 5	String	Yes
8	Weigh Master Name	Johnny Scales	String	Yes
9	Weigh Master ID	1234567	String	Yes
10	Left Intentionally Blank			No
11	Mix Design ID (Product)	1628p; AM-WILM-29 76-22	String	Yes
12	Material Type (Product Description)	9.5mm top; 19MM 76-22 NON CARB	String	Yes
13	Item No. (Product Code)	401005; 401016	String	Yes
14	Load Number	75	Number	Yes
15	Identifying Vehicle Number	T-1	String	Yes
16	Hauler	John Doe Trucking	String	Yes
17	Legal Gross Vehicle Weight	73,280	Number	Yes
18	Loading Date & Time	2020-06-15T13:45:30	String	Yes
19	Gross Weight	72,980	Number	Yes
20	Net Weight	27,900	Number	Yes
21	Truck Tare Weight	45,080	Number	Yes
22	Void	280	Number	No
23	Daily Running Total	44.43	Number	Yes

All provided weights shall be accurate to 0.01 tons.

Loads which do not have the required data shall be rejected.

Setup and Calibration:

Conduct a test of each supplier's integration with the Department's eTicketing Portal prior to shipping material. Complete test at least 14 days prior to shipping material unless otherwise approved by the engineer. The test must involve at least four calibration eTickets from each supplier approved for use on the project. The calibration eTickets must accurately reflect the categories 1-7 shown above; all other categories shall be marked "TEST". After the engineer confirms the calibration eTickets have been entered into the Department's eTicket Portal, void the eTickets with the reason "Calibration Testing".

Uptime:

Uptime reliability of the material supplier's ticketing system must be 99.5% over any 30-day rolling period. Uptime is defined as the ability for the Department to receive electronic tickets within a maximum of 10 minutes from when the ticket was created.

Load Identification:

Ensure the identifying vehicle numbers on the delivery vehicle correspond to the ticket. Place the numbers on the delivery vehicles such that at least one can be safely read from within the work area. Delivery vehicles without identifying vehicle numbers shall be rejected.

Method of Measurement:

The Department will not measure electronic ticketing.

Basis of Payment:

- A. The cost associated with creating and maintaining an API, providing electronic ticketing data, and placing identifying vehicle numbers on the delivery vehicles is incidental to the item being placed.
- B. The Department will make no payment for material that is rejected.

01/18/2022

Contract No. T202201102

763525 – ROAD USER COST

Description:

Road User Cost shall be assessed to compensate failure to open the project to unrestricted highway traffic on time in accordance with the contract's General Description.

Method of Measurement:

The Department will not measure Road User Cost.

Basis of Payment:

The assessment will be determined by the Road User Cost documentation in the General Description of the Contract.

8/3/23

806500 – TRAFFIC OFFICERS

Description:

In accordance with Section 806.1.

Materials:

Not applicable.

Construction:

In accordance with Section 806.3.

Method of Measurement:

In accordance with Section 806.4.

Basis of Payment:

- A. The Department will pay for traffic officers at the contract unit price per hour. Price and payment constitute full compensation for providing traffic officers, vehicles, and equipment.
- B. For bidding purposes, the Department has fixed the unit price at \$180.00 per hour. The Department will pay for traffic officers based on a submitted invoice from the police department plus 10 percent.

Contract No. T202201102

- 831500 - PROVIDE AND INSTALL UP TO 6" SCHEDULE 80 PVC CONDUIT (OPEN CUT)**
 - 831501 - PROVIDE AND INSTALL 4" SCHEDULE 80 PVC CONDUIT (OPEN CUT)**
 - 831502 - PROVIDE AND INSTALL 3" SCHEDULE 80 PVC CONDUIT (OPEN CUT)**
 - 831503 - PROVIDE AND INSTALL 2-1/2" SCHEDULE 80 PVC CONDUIT (OPEN CUT)**
 - 831504 - PROVIDE AND INSTALL 2" SCHEDULE 80 PVC CONDUIT (OPEN CUT)**
 - 831505 - PROVIDE AND INSTALL 1" SCHEDULE 80 PVC CONDUIT (OPEN CUT)**
- 831506 - PROVIDE AND INSTALL 1" FLEXIBLE METALLIC-LIQUIDTIGHT CONDUIT**
- 831507 - PROVIDE AND INSTALL 2" FLEXIBLE METALLIC-LIQUIDTIGHT CONDUIT**
- 831508 - PROVIDE AND INSTALL 3" FLEXIBLE METALLIC-LIQUIDTIGHT CONDUIT**
- 831509 - PROVIDE AND INSTALL 4" FLEXIBLE METALLIC-LIQUIDTIGHT CONDUIT**
 - 831512 - PROVIDE AND INSTALL 1" SCHEDULE 80 PVC CONDUIT (TRENCH)**
 - 831513 - PROVIDE AND INSTALL 2" SCHEDULE 80 PVC CONDUIT (TRENCH)**
 - 831514 - PROVIDE AND INSTALL 2-1/2" SCHEDULE 80 PVC CONDUIT (TRENCH)**
 - 831515 - PROVIDE AND INSTALL 3" SCHEDULE 80 PVC CONDUIT (TRENCH)**
 - 831516 - PROVIDE AND INSTALL 4" SCHEDULE 80 PVC CONDUIT (TRENCH)**
- 831517 - PROVIDE AND INSTALL 1" SCHEDULE 80 PVC CONDUIT (ON STRUCTURE)**
- 831518 - PROVIDE AND INSTALL 2" SCHEDULE 80 PVC CONDUIT (ON STRUCTURE)**
- 831519 - PROVIDE AND INSTALL 2-1/2" SCHEDULE 80 PVC CONDUIT (ON STRUCTURE)**
- 831520 - PROVIDE AND INSTALL 3" SCHEDULE 80 PVC CONDUIT (ON STRUCTURE)**
- 831521 - PROVIDE AND INSTALL 4" SCHEDULE 80 PVC CONDUIT (ON STRUCTURE)**
 - 831522 - PROVIDE AND INSTALL 1" GALVANIZED STEEL CONDUIT (TRENCH)**
 - 831523 - PROVIDE AND INSTALL 2" GALVANIZED STEEL CONDUIT (TRENCH)**
 - 831524 - PROVIDE AND INSTALL 2-1/2" GALVANIZED STEEL CONDUIT (TRENCH)**
 - 831525 - PROVIDE AND INSTALL 3" GALVANIZED STEEL CONDUIT (TRENCH)**
 - 831526 - PROVIDE AND INSTALL 4" GALVANIZED STEEL CONDUIT (TRENCH)**
 - 831527 - PROVIDE AND INSTALL 1" GALVANIZED STEEL CONDUIT (BORE)**
 - 831528 - PROVIDE AND INSTALL 2" GALVANIZED STEEL CONDUIT (BORE)**
 - 831529 - PROVIDE AND INSTALL 2-1/2" GALVANIZED STEEL CONDUIT (BORE)**
 - 831530 - PROVIDE AND INSTALL 3" GALVANIZED STEEL CONDUIT (BORE)**
 - 831531 - PROVIDE AND INSTALL 4" GALVANIZED STEEL CONDUIT (BORE)**
 - 831532 - PROVIDE AND INSTALL 1" GALVANIZED STEEL CONDUIT (OPEN CUT)**
 - 831533 - PROVIDE AND INSTALL 2" GALVANIZED STEEL CONDUIT (OPEN CUT)**
 - 831534 - PROVIDE AND INSTALL 2-1/2" GALVANIZED STEEL CONDUIT (OPEN CUT)**

- 831535 - PROVIDE AND INSTALL 3" GALVANIZED STEEL CONDUIT (OPEN CUT)
- 831536 - PROVIDE AND INSTALL 4" GALVANIZED STEEL CONDUIT (OPEN CUT)
- 831537 - PROVIDE AND INSTALL 1" GALVANIZED STEEL CONDUIT (ON STRUCTURE)
- 831538 - PROVIDE AND INSTALL 2" GALVANIZED STEEL CONDUIT (ON STRUCTURE)
- 831539 - PROVIDE AND INSTALL 2-1/2" GALVANIZED STEEL CONDUIT (ON STRUCTURE)
- 831540 - PROVIDE AND INSTALL 3" GALVANIZED STEEL CONDUIT (ON STRUCTURE)
- 831541 - PROVIDE AND INSTALL 4" GALVANIZED STEEL CONDUIT (ON STRUCTURE)
- 831542 - PROVIDE AND INSTALL 2" HDPE SDR-13.5 CONDUIT (BORE)
- 831543 - PROVIDE AND INSTALL 2-1/2" HDPE SDR-13.5 CONDUIT (BORE)
- 831544 - PROVIDE AND INSTALL 3" HDPE SDR-13.5 CONDUIT (BORE)
- 831545 - PROVIDE AND INSTALL 4" HDPE SDR-13.5 CONDUIT (BORE)
- 831560 - PROVIDE AND INSTALL UP TO 4" SCHEDULE 80 PVC CONDUIT (OPEN CUT)
- 831561 - PROVIDE AND INSTALL 1-1/2" SCHEDULE 80 PVC CONDUIT (TRENCH)
- 831562 - PROVIDE AND INSTALL 1-1/2" SCHEDULE 80 PVC CONDUIT (ON STRUCTURE)
- 831563 - PROVIDE AND INSTALL 1-1/2" GALVANIZED STEEL CONDUIT (OPEN CUT)
- 831564 - PROVIDE AND INSTALL 1-1/2" GALVANIZED STEEL CONDUIT (TRENCH)
- 831565 - PROVIDE AND INSTALL 1-1/2" GALVANIZED STEEL CONDUIT (BORE)
- 831566 - PROVIDE AND INSTALL 1-1/2" GALVANIZED STEEL CONDUIT (ON STRUCTURE)
- 831569 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 1" SCHEDULE 80 PVC CONDUITS IN TRENCH OR OPEN CUT
- 831570 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 1-1/2" SCHEDULE 80 PVC CONDUITS IN TRENCH OR OPEN CUT
- 831571 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 2" SCHEDULE 80 PVC CONDUITS IN TRENCH OR OPEN CUT
- 831572 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 2-1/2" SCHEDULE 80 PVC CONDUITS IN TRENCH OR OPEN CUT
- 831573 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 3" SCHEDULE 80 PVC CONDUITS IN TRENCH OR OPEN CUT
- 831574 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 4" SCHEDULE 80 PVC CONDUITS IN TRENCH OR OPEN CUT
- 831575 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 2" HDPE 13.5 SDR CONDUIT IN DIRECTIONAL BORE
- 831576 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 2-1/2" HDPE 13.5 SDR CONDUIT IN DIRECTIONAL BORE
- 831577 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 3" HDPE 13.5 SDR CONDUIT IN DIRECTIONAL BORE

Contract No. T202201102

831578 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 4" HDPE 13.5 SDR CONDUIT IN DIRECTIONAL BORE

831579 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 1" GALVANIZED STEEL CONDUIT IN TRENCH OR OPEN CUT

831580 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 1-1/2" GALVANIZED STEEL CONDUIT IN TRENCH OR OPEN CUT

831581 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 2" GALVANIZED STEEL CONDUIT IN TRENCH OR OPEN CUT

831582 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 2-1/2" GALVANIZED STEEL CONDUIT IN TRENCH OR OPEN CUT

831583 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 3" GALVANIZED STEEL CONDUIT IN TRENCH OR OPEN CUT

831584 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 4" GALVANIZED STEEL CONDUIT IN TRENCH OR OPEN CUT

831585 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 1" STEEL CONDUIT IN DIRECTIONAL BORE

831586 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 1-1/2" STEEL CONDUIT IN DIRECTIONAL BORE

831587 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 2" STEEL CONDUIT IN DIRECTIONAL BORE

831588 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 2-1/2" STEEL CONDUIT IN DIRECTIONAL BORE

831589 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 3" STEEL CONDUIT IN DIRECTIONAL BORE

831590 - PROVIDE & INSTALL SECOND AND SUBSEQUENT ADDITIONAL 4" STEEL CONDUIT IN DIRECTIONAL BORE

DESCRIPTION:

This work consists of providing and installing a conduit or shield, of the type and size required.

MATERIALS:

A. Conduit Section 831

CONSTRUCTION METHODS:

A. General Installation Requirements –

1. The Department has the right to reject any installation method proposed for a given work site. PVC shall not be installed under existing pavement unless it is on a continuous roll or with the engineer's written approval.

Contract No. T202201102

2. Conduit installed underground shall be installed in a straight line between terminal points. In straight runs, junction well spacing shall be no more than 600 feet for fiber optic conduit or no more than 300 feet for copper in conduit, or as directed by the engineer. If bends are required during installation, they must be manufactured sweeping bends. The engineer will be consulted before any bends are installed to ensure that the proper arc is provided.
3. Underground conduit shall have a minimum cover as measured from the finished grade of 24 inches and a maximum cover of 48 inches. The opening shall be filled halfway with the cover material and tamped down firmly before filling in the remainder of the opening. Additional lifts shall be used as required to install the metallic warning tape at the specified depth. All cover material shall be free of rocks, debris, vegetation or other deleterious material that may damage the conduit. An underground utility warning tape shall be installed as specified in this section and the remainder of the fill shall be added, tamping down the top layer.
4. Conduit not terminated to a base or in a junction well shall be terminated 2 feet beyond the edge of the pavement unless otherwise directed by the engineer, and properly capped. Tape is not an approved method. Conduit shall not extend more than 3 inches inside a junction well. See Standard Construction Details or applicable Plan Details for typical methods of termination.
5. All underground conduits shall be marked in the ground with a metallic warning tape. The marking tape shall be buried directly above the conduit run that it identifies, at a depth of approximately 12 inches below final grade. The tape identifying all conduits shall be at least 6 inches wide and have a minimum thickness of 3 mils and 500 percent elongation.
6. The color of the metallic warning tape identifying fiber optic cable should be bright orange (preferably AULCC orange) and shall read "WARNING - OPTICAL CABLE" or other wording approved by the engineer that conveys the same message. The color of the tape identifying all other cables shall be bright red and shall read "WARNING -BURIED ELECTRIC BELOW" or other wording approved by the engineer that conveys the same message.
7. Using conduit tools, rigid metallic conduit shall be cut, reamed, and threaded. The thread length shall be as necessary to ensure that the sections of conduits when screwed into a coupling and tightened correctly will butt together and the joint will be watertight. A three-piece threaded union, as approved by the engineer, shall be used to join two threaded lengths of conduit in the case where a standard coupling will not work. A threaded union shall not be used in a conduit run that is to be driven. At no time is a threadless coupling or a split-bolt coupling to be used for direct buried conduit.
8. All lengths of HDPE conduit shall be connected with irreversible fusion couplings. Mechanical and removable couplings will not be accepted.
9. All lengths of PVC conduit shall be connected by one conduit end fitting inside the flared end of the other conduit section. If this is not possible, then a coupling may be used. Regardless of how connection is made, all joints shall be sealed with the appropriate epoxy to ensure that the two conduit pieces bond to one another to form a solid waterproof link. Using conduit tools, the conduit shall be cut and prepared. If approved by the engineer, a coupler module may be used where conduit segments do not align properly to allow the flared end of one conduit segment to mate with the normal end of the other segment.
10. Sealed end caps (with knockouts if empty) shall be placed on the ends of all conduits, after compressed air has been used to clear all foreign matter.
11. If not already pre-installed by the manufacturer, a polyester or polypropylene pulling rope or tape (fish wire) with a minimum rated strength of 1,250 pounds shall be installed in each conduit for future use. In instances where the Contractor installs the cable, the fish wire may be eliminated.
12. All PVC and HDPE conduits shall have a continuous metallic trace wire installed for the entire length of the conduit run for all fiber installations.
13. Stabilize slopes in accordance with section 908 as directed by the engineer.

B. Installation of Conduit Under Existing Pavement, Directional Bore -

1. Directional bore shall be used for installation of conduits under existing pavement with a conduit diameter not less than 1-1/2-inch. The size of a bore shall not exceed the outside diameter of the conduit by more

Contract No. T202201102

than 1 inch. If it does, cement grout shall be pumped into the void. Only HDPE and/or Galvanized Steel conduit may be installed by Directional Bore methods.

C. Installation of Conduit Under Existing Pavement, Open Cut -

1. Installation by saw cutting the full pavement depth and removing the existing pavement with an excavator or by hand methods, shall be used only for conduits not less than 1-1/2-inch diameter. The engineer must first approve all open cutting of roadways. The width and length of open cut and patch restoration materials shall be as shown on the plan details. The Contractor shall be responsible for the removal of all cut pavement and surplus excavation, and for the replacement and correction of any damaged pavement outside the sawcut limits after the conduit(s) are installed.

D. Installation of Conduit Under Existing Pavement, Unpaved Trench -

1. Trenching or other approved method shall be used for installation of conduit in unpaved trench or under new pavement. Backfill in conduit trenches shall be compacted thoroughly as it is being placed. At the discretion of the engineer, remove sod to place conduit with an approved sod cutter and replace, or place 6 inches of topsoil and seed in accordance with section 908. In areas where new pavement is to be placed or in areas where total reconstruction is taking place, sodding or seeding may not be required by the engineer.

E. Installation of Conduit on Structure -

1. Conduit installed on structure shall consist of drilling anchors into concrete, brick, stone, steel or wood and mounting the conduit with the proper clamps or hangers. The conduit shall be attached to the structure by use of one-hole conduit hangers and approved anchors not more than 36 inches apart. Any 90-degree turns in the conduit run shall be accomplished by placing the proper size and type manufactured sweeping bends for the application needed.

F. Installation of Additional Conduit in Trench or Open Cut Pavement -

1. In the case of slotted or trenched installations, install additional conduits at the same time as the initial installation. The engineer shall indicate the quantity of conduits to be installed during a build. Additional conduits may be stacked one on top of the other, side by side or in a matrix. Conduits shall not twist around one another or be allowed to deviate from straight line paths except in the case of bend installations. Conduits installed at the same time in the same trench or slot shall remain oriented the same in relation to one another throughout the conduit run.

G. Installation of Additional Conduits in Directional Bore -

1. In the case of a directional bore that more than one conduit shall be installed at the same time as the initial installation, install 1 or more additional conduits. The engineer shall indicate the quantity of conduits to be installed during a build. The additional conduits may be stacked one on top of the other, side by side or in a matrix. Conduits shall not twist around one another or be allowed to deviate from straight line paths except in the case of a gentle bend. Conduits installed at the same time, in the same bore shall remain oriented in the same relation to one another throughout the conduit run.

METHOD OF MEASUREMENT:

- A. The Department will measure the quantity of conduit in linear feet of conduit provided and installed and accepted.
- B. The Department will measure the quantity of conduit in linear feet of conduit installed under existing pavement by a directional bore or by open cutting the pavement along the path of the bore or open cut, from the point that cannot be trenched to the point that trenching can resume.
- C. The Department will measure the quantity of conduit in linear feet of conduit reduced or divided (with a junction well or conduit body) as part of the larger conduit.

BASIS OF PAYMENT:

- A. The Department will pay for providing and installing conduit at the contract unit price per linear foot. Price and payment will constitute full compensation for:
 - 1. Providing all materials;
 - 2. labor;
 - 3. topsoil; and
 - 4. seed.
- B. The Department will pay for installing conduit by directional bore at the contract unit price per linear foot. Price and payment will constitute full compensation for:
 - 1. Excavation and backfilling;
 - 2. placing the conduit;
 - 3. caps, if required; and
 - 4. all other requirements.
- C. The Department will pay for installing conduit by open cutting existing pavement at the contract unit price per linear foot. Price and payment will constitute full compensation for:
 - 1. Excavation and backfilling;
 - 2. placing the conduit;
 - 3. disposal of excess materials; and
 - 4. all other requirements.
- D. The Department will pay for installing conduit by unpaved trench at the contract unit price per linear foot. Price and payment will constitute full compensation for:
 - 1. Excavation and backfilling;
 - 2. removal of sod, if required;
 - 3. placing the conduit;
 - 4. disposal of excess materials;
 - 5. replacing excavated on site sod, if required;
 - 6. seeding, if required; and
 - 7. all other requirements.
- E. The Department will pay for:
 - 1. Borrow in accordance with section 209;
 - 2. Base courses in accordance with sections 301 and 302;
 - 3. Bituminous pavement materials in accordance with section 402;
 - 4. PCC patching in accordance with section 505;
 - 5. Saw cutting in accordance with section 762; and
 - 6. Sodding and/or topsoil from an outside source in accordance with section 908.

8/10/21

STATEMENTS

Included on the following pages:

UTILITY STATEMENTS

RIGHT-OF-WAY STATEMENTS

ENVIRONMENTAL STATEMENTS

RAILROAD STATEMENTS



STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION
800 BAY ROAD
P.O. BOX 778
DOVER, DELAWARE 19903

NICOLE MAJESKI
SECRETARY

UTILITY STATEMENT
November 27, 2024
STATE CONTRACT NO.: T202201102
PROJECT I.D. NO.: 22-22222
FAP NO.: 5307-2022(08)
US 13 SOUTHBOUND BBRT LANE
NEW CASTLE COUNTY

The following utility companies may own and/or maintain facilities within the project limits:

Artesian Water Company
AT&T
Comcast Cable Communications, Inc.
Crown Castle (Fibertech)
Delaware Pipeline Company
Delmarva Power
Delmarva Power
Lumen (CenturyLink/Level3)
New Castle County – Special Services (Sanitary Sewer)
Verizon of Delaware Inc.

The following is a breakdown of the utilities involved, adjustments and/or relocations as required (all locations, offsets, lengths, working days and calendar days are approximate):

Artesian Water Company – Water:

Artesian Water Company maintains underground facilities throughout the project limits with various water mains and services crossing US 13 as shown in the plans.

There are no apparent conflicts and no anticipated Artesian involvement during this project. **All proposed sign structures and subsequent improvements shown in the contract documents shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities.**

Artesian's review is based upon information contained in DelDOT's **Final** Plans for contract **T202201102**, received on 8/31/2023 and all data available as of this date.

Should the utility apertures be in conflict with the scope of work, the contractor shall coordinate directly with the utility company. Cost of any coordination with the utility companies shall be incidental to the contract.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

Under no circumstances shall any valve box or manhole be paved over, filled, or knocked out of vertical alignment during construction.

Caution: When saw cutting in close proximity to water facilities, the contractor is recommended to verify the depth of the water main before saw cutting and/or excavation to ensure shallow pipe is not encountered. The contractor shall exercise caution when excavating along the curb lines at these locations.

Note: The Contractor is not permitted to draw water from any hydrant for any use, without the written permission of the Artesian Water Company and proper metering and backflow prevention equipment in place.

No working/existing Artesian Water Company facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

24 hour emergency phone number - 1-800-332-5114.

AT&T:

- AT&T maintains underground and aerial facilities within the project limits as shown on the plans.
- AT&T owns underground facilities within the Verizon conduits on the west side of US 13.
- AT&T owns and maintains underground fiber on the west side of US 13 throughout the project limits behind the curb line as shown on the plans.

There are no apparent conflicts and no anticipated AT&T involvement during this project. **All proposed sign structures and subsequent improvements shown in the contract documents shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities.**

AT&T's review is based upon information contained in DelDOT's **Final** Plans for contract **T202201102**, received on 8/31/2023 and all data available as of this date.

Should the utility apertures be in conflict with the scope of work, the contractor shall coordinate directly with the utility company. Cost of any coordination with the utility companies shall be incidental to the contract.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

The contractor must use care when working in these underground areas as well as in the vicinity of overhead cable. The time to complete any relocations/adjustments found to be necessary, as

directed by the engineer, during the construction of the highway contract will depend on the nature of the work.

No working/existing AT&T facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

Comcast Cable Communications, Inc.:

Comcast maintains underground and aerial facilities within the project limits. Aerial facilities are located on the Delmarva utility poles on the east and west side of US 13, with various underground as shown in the plans.

There are no apparent conflicts and no anticipated Comcast involvement during this project. **All proposed sign structures and subsequent improvements shown in the contract documents shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities.**

Comcast's review is based upon information contained in DelDOT's **Final** Plans for contract **T202201102**, received on 8/31/2023 and all data available as of this date.

Should the utility apertures be in conflict with the scope of work, the contractor shall coordinate directly with the utility company. Cost of any coordination with the utility companies shall be incidental to the contract.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

The contractor must use care when working in these underground areas as well as in the vicinity of overhead cable. The time to complete any relocations/adjustments found to be necessary, as directed by the engineer, during the construction of the highway contract will depend on the nature of the work.

No working/existing Comcast facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

Crown Castle Communications:

Crown Castle Communications maintains underground and aerial facilities throughout the project limits as shown in the plans.

Crown Castle maintains aerial facilities as follows:

- Crown Castle owns and maintains aerial facilities attached to the existing pole line along east and west side of US13 and outside of the project limits.

Crown Castle maintains underground facilities within the project limits.

- Crown Castle owns underground facilities within the Lumen (CenturyLink) conduits.
- Crown Castle owns and maintains (2) 1.5" conduits within US13 median.

There are no apparent conflicts and no anticipated Crown Castle involvement during this project. **All proposed sign structures and subsequent improvements shown in the contract documents**

shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities.

Crown Castle's review is based upon information contained in DelDOT's **Final Plans** for contract **T202201102**, received on 8/31/2023 and all data available as of this date.

Should the utility apertures be in conflict with the scope of work, the contractor shall coordinate directly with the utility company. Cost of any coordination with the utility companies shall be incidental to the contract.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

The contractor must use care when working in these underground areas as well as in the vicinity of overhead cable. The time to complete any relocations/adjustments found to be necessary, as directed by the engineer, during the construction of the highway contract will depend on the nature of the work.

No working/existing Crown Castle facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

Delaware Pipeline Company:

The Delaware Pipeline Company (DPC) maintains a 16" high pressure liquid petroleum pipeline throughout the median within the project limits as shown on the plans.

There are no apparent conflicts and no anticipated Delaware Pipeline involvement during this project. **All proposed sign structures and subsequent improvements shown in the contract documents shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities.**

The Delaware Pipeline Company requests that no digging or excavating be done until a site meeting with the contractor occurs, and there must be a DPC representative on site while working near the Delaware Pipeline Company's line.

Delaware Pipeline's review is based upon information contained in DelDOT's **Final Plans** for contract **T202201102**, received on 8/31/2023 and all data available as of this date.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

ALL prospective bidders are advised to contact the Delaware Pipeline Company before bidding to receive all documents pertaining to working around the Delaware Pipeline Company's facilities before submitting a bid. All plans and written correspondence shall be sent to:

Delaware Pipeline Company, Attention: Maintenance Department,
1811 River Road, Delaware City, DE 19706.

The Delaware City, DE Maintenance Department's contact number is 1-302-836-6500.

No working/existing DPC facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

The Delaware Pipeline Company's 24-hour toll-free emergency contact number is 1-855-887-9768.

Delmarva Power - Electric:

Delmarva Power Electric Distribution (Delmarva) maintains aerial and underground facilities within the project limits as shown in the plans.

Delmarva Power has a 3 phase overhead electrical distribution system along US13 on both sides of the highway with several overhead road crossings.

There are no apparent conflicts and no anticipated Delmarva involvement during this project. **All proposed sign structures and subsequent improvements shown in the contract documents shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities. It is important to note, all contractors must maintain a minimum distance of 10'-0" from all energized electric lines during construction and any permanent facilities must be installed a minimum distance of 10'-0" from all aerial electric lines. Additional clearance may be required from high voltage transmission lines.**

Delmarva's review is based upon information contained in DelDOT's **Final Plans** for contract **T202201102**, received on 8/31/2023 and all data available as of this date.

Should the utility apertures be in conflict with the scope of work, the contractor shall coordinate directly with the utility company. Cost of any coordination with the utility companies shall be incidental to the contract.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

DelDOT has not planned for or coordinated with Delmarva Power -Electric Distribution for any temporary power outages, relocations, physical pole support for excavation nor arranged for the installation of insulation of any power line during this contract other than as outlined in the above description. Due to varying construction possibilities; if a contractors means-and-methods should require support from Delmarva Power to fulfill the requirement of 16 Del. C. § 7405B, OSHA Regulations Table A of § 1926.1408, other applicable federal, state or local law or regulation or the Contractor's company policy; it shall be at the Contractor's sole expense and the contractor shall directly coordinate this request with Delmarva Power. All costs associated with any temporary power outages, relocations, physical pole support for excavation or the installation of insulation of any power line during this contract shall be incidental, including the cost of the coordination, to the work being performed. The Department makes no guarantees that the request for any temporary power outages, relocation or the installation of insulation of any power line

during this contract will be granted by Delmarva Power in part or in total; or during the time periods requested by the Contractor for construction purposes. Any proposed coordination with Delmarva Power shall be included in the contractor's CPM schedule. In addition, Delmarva Power will determine if these outages can be accommodated.

No working/existing Delmarva facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

To report a downed wire, call 1-800-898-8042.

Delmarva Power has a written requirement regarding working near overhead power lines.

Customer/Contractor Acknowledgement Performing Work within Dangerous Proximity of High Voltage Lines

"You are hereby notified by Delmarva Power that NO work can be performed at this location within dangerous proximity to Delmarva's overhead lines and that you are required by law to comply with applicable OSHA regulations and the applicable state High Voltage Safety Act. Performance of any activity or causing any person, equipment or things to come within dangerous proximity of Delmarva's overhead lines creates an extreme risk of severe injury or death. You are further notified that no activities may be conducted within dangerous proximity of Delmarva's overhead lines until mutually agreeable measures to prevent contact with overhead lines have been reached with Delmarva and Delmarva has provided you with written authorization to perform the activities. Additionally any work involving the use of a crane with intentions to remain outside of dangerous proximity, but within 20 feet of the Company's overhead lines, requires an Encroachment Prevention Plan in order to satisfy OSHA"

Delmarva Power - Gas:

Delmarva (Gas) maintains underground facilities within the project limits on the northbound shoulder and median of US 13, with various services throughout the project limits as shown in the plans.

There are no apparent conflicts and no anticipated Delmarva involvement during this project. **All proposed sign structures and subsequent improvements shown in the contract documents shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities.**

Delmarva's review is based upon information contained in DelDOT's **Final Plans** for contract **T202201102**, received on 8/31/2023 and all data available as of this date.

Should the utility apertures be in conflict with the scope of work, the contractor shall coordinate directly with the utility company. Cost of any coordination with the utility companies shall be incidental to the contract.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

Caution: When saw cutting or digging in close proximity to gas facilities, the contractor is required to verify the depth of the gas main or service to ensure shallow pipe is not encountered. The contractor shall exercise caution when excavating along the curb lines at these locations.

Under no circumstances shall any valve box or manhole be paved over, filled, or knocked out of vertical alignment during construction.

If gas equipment such as pipe, tracer wire, valve boxes, etc. are damaged or you smell gas, call **DPL's emergency number at 302-454-0317 (24 hours a day)** from a safe location. Do not call the project engineer or other contacts from DPL Gas.

No working/existing DPL Gas facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

Lumen (CenturyLink/Level3) – Fiber Optic:

Lumen maintains underground facilities in the median of US 13 throughout the project limits as shown in the plans.

- Lumen owns and maintains existing (12) 1.25" HDPE Duct Banks within the median.

There are no apparent conflicts and no anticipated Lumen involvement during this project. **All proposed sign structures and subsequent improvements shown in the contract documents shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities.**

Lumen's review is based upon information contained in DelDOT's **Final Plans** for contract **T202201102**, received on 8/31/2023 and all data available as of this date.

Should the utility apertures be in conflict with the scope of work, the contractor shall coordinate directly with the utility company. Cost of any coordination with the utility companies shall be incidental to the contract.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

No working/existing Lumen facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

New Castle County – Sanitary Sewer:

New Castle County Sanitary Sewer (NCC) maintains underground facilities within the project limits along the northbound US 13 shoulder and behind the northbound curb line as shown in the plans.

There are no apparent conflicts and no anticipated NCC involvement during this project. **All proposed sign structures and subsequent improvements shown in the contract documents shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities.**

NCC's review is based upon information contained in DelDOT's **Final Plans** for contract T201901102, received on 8/31/2023 and all data available as of this date.

Should the utility apertures be in conflict with the scope of work, the contractor shall coordinate directly with the utility company. Cost of any coordination with the utility companies shall be incidental to the contract.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

Under no circumstances shall any valve box or manhole be paved over, filled, or knocked out of vertical alignment during construction.

No working/existing New Castle County Sanitary Sewer facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

Verizon of Delaware Inc. – Communications:

Verizon of Delaware Inc. maintains the following aerial facilities within the project limits:

1. Verizon maintains aerial facilities along the Northwest side of US 13 Dupont Hwy from Pole#47644\41352 at station 589+40 L144 extending Northeast then crossing US 13 Dupont Hwy to Pole# Unknown at station 599+64 R45 then continuing Southeast and beyond the project limits. (CP-01, CP-02)
2. Verizon maintains aerial facilities along the Northwest side of US 13 Dupont Hwy from Pole#47644\41352 at station 589+40 L144 extending Southwest and beyond the project limits. (CP-01)
3. Verizon maintains aerial facilities along the Southwest side of Bacon Av from Pole#47649\41373 at station 591+58 R200 extending Northwest and beyond the project limits. (CP-01)
4. Verizon maintains aerial facilities along the Northwest side of US 13 Dupont Hwy from MH 1616 at station 608 +10 L143 extending Southwest to a Verizon aerial splice case at approximate station 607+70 L150. (CP-03)
5. Verizon maintains aerial facilities along the Northwest side of US 13 Dupont Hwy from Pole# Unknown at station 824+18 L45 extending Northeast to Pole# 48126\42038 at station 1031+80 L145. (CP-06, CP-07, CP-08, CP-09, CP-10, CP-11)
6. Verizon maintains aerial facilities along the Northeast side of W Hazeldell Av from Pole# 48149+42072 at station 1036+45 L165 extending North and beyond the project limits. (CP-11)
7. Verizon maintains aerial facilities along the Southeast side of US 13 Dupont Hwy from Pole#47659\41335 at station 589+00 R48 extending Northeast and beyond the project limits. (CP-01, CP-02, CP-03, CP-04)
8. Verizon maintains aerial facilities along the Southeast side of US 13 Dupont Hwy from Pole#47659\41335 at station 589+00 R48 extending Southwest and beyond the project limits. (CP-01)
9. Verizon maintains aerial facilities along the Southeast side of US 13 Dupont Hwy from Pole#48003\41840 at station 1008+48 R48 extending Northeast to Pole# 48092\41965 at station 1023+80 R50. (CP-08, CP-09, CP-10)

10. Verizon maintains aerial facilities along the Southeast side of US 13 Dupont Hwy from Pole#48103\41977 at station 1025+27 R50 extending Northeast to Pole# 48263+42205. (CP-10, CP-11, CP-12, CP-13)
11. Verizon maintains aerial facilities along the Southeast side of US 13 Dupont Hwy from Pole#48103\41977 at station 1025+27 R50 extending Southwest along Wildel Av and beyond the project limits. (CP-10)
12. Verizon maintains aerial facilities along the Southeast side of US 13 Dupont Hwy from Pole#48123\42006 at station 1029+10 R50 extending Southwest along Minquadale Blvd and beyond the project limits. (CP-10)
13. Verizon maintains aerial facilities along the Southeast side of US 13 Dupont Hwy from Pole#48148\XX09X at station 1033+20 R49 extending Southeast along E Hazeldell Av and beyond the project limits. (CP-11)
14. Verizon maintains aerial facilities along the Southeast side of US 13 Dupont Hwy from Pole#48178\42081 at station 1038+22 R48 extending Northeast along Memorial Dr and beyond the project limits. (CP-11)

Verizon of Delaware Inc. maintains the following buried/underground facilities within the project limits:

1. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 1620 at station 591+50 L130 extending Northeast and Southwest and beyond the project limits. (CP-01, CP-02, CP-03, CP-04, CP-05, CP-06, CP-07, CP-08, CP-09, CP-10, CP-11, CP-12, CP-13)
2. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 1620 at station 591+50 L130 extending Southwest along Bacon Av to Pole# 47649\41373 at station 591+55 L200. (CP-01)
3. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 1620 at station 591+50 L130 extending Northeast along Bacon Av to Pole# Unknown at station 591+50 L188. (CP-01)
4. Verizon maintains UG\buried facilities crossing US 13 Dupont Hwy from MH 1618 at station 597+55 L108 extending southeast to Pole# 47708\41410 at station 598+04 R38. (CP-02)
5. Verizon maintains UG\buried facilities crossing US 13 Dupont Hwy from MH 1616 at station 608+10 L140 extending southeast to Pole# Unknown at station 607+40 R68. (CP-03)
6. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 2110 at station 823+75 L30 extending Northwest along Private Road and beyond the project limits. (CP-06)
7. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 2107 at station 829+78 L28 extending Northwest along Central Av and beyond the project limits. (CP-06)
8. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from a split duct location at approximate station 833+98 L49 extending Northwest along Lovelace Av and beyond the project limits. (CP-07)
9. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 2104 at station 1013+35 L130 extending Northwest along Fairview Av and beyond the project limits. (CP-08)
10. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 2119 at station 1026+12 L130 extending Northwest to a Verizon CEV at approximate station 1026+10 L160. (CP-10)

11. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 293 at station 1036+40 L128 extending Northwest along W Hazeldell Ave to Pole# 48149\42072 at station 1036+40 L165. (CP-11)

12. Verizon maintains UG\buried facilities crossing US 13 Dupont Hwy from MH 293 at station 1036+40 L128 extending Southeast to MH 294 at station 1034+92 R20. (CP-11)

13. Verizon maintains UG\buried facilities along the Southeast side of US 13 Dupont Hwy from MH 294 at station 1034+92 R20 extending Southwest to MH 295 at station 1033+25 R25 turning Southeast to Pole# 48148\XX09X at station 1033+20 R47 continuing and Dead Ending along E Hazeldell Av. (CP-11)

14. Verizon maintains UG\buried facilities along the Southeast side of US 13 Dupont Hwy from MH 294 at station 1034+92 R20 extending Northeast then turning Southeast along Memorial Dr to MH 296 at station 1037+20 R80 continuing along Memorial Dr and beyond the project limits. (CP-11)

15. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 290 at station 1045+00 L130 extending Northwest along Hessler Blvd and beyond the project limits. (CP-12)

16. Verizon maintains UG\buried facilities along the Northwest side of US 13 Dupont Hwy from MH 289 at station 1048+90 L127 extending Northeast to Pole#802\28 at station 1049+70 142. (CP-13)

The following adjustments are required for the existing Verizon facilities. All adjustments shall be performed so that there are no unnecessary disruptions of services:

Anticipated Aerial Relocations:

None Anticipated

Anticipated Buried/Underground relocations:

Verizon to allow the State Contractor to adjust manhole covers at the following locations as needed:

- Station 591+55, 132' L
- Station 596+85, 136' L
- Station 597+75, 134' L
- Station 603+95, 137' L
- Station 1039+15, 133' L
- Station 1045+10, 133' L
- Station 1048+85, 133' L

Verizon's review is based upon information contained in DelDOT's **Final** Plans for contract **T202201102**, received on 8/31/2023 and all data available as of this date.

There are no anticipated impacts to these facilities other than what is outlined above. The States's contractor shall adjust each manhole to match the surface elevation and slope. The State's contractor shall contact the *Verizon Delaware Inc.* representative prior to any adjustment to existing manholes.

All proposed sign structures and subsequent improvements shown in the contract documents shall be adjusted in the field to avoid any and all existing underground or aerial utility facilities, this includes any private utility facilities.

Should the utility apertures be in conflict with the scope of work, the contractor shall coordinate directly with the utility company. Cost of any coordination with the utility companies shall be incidental to the contract.

Should any conflicts be encountered as a result of the contractor's means and methods during construction, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as described by the District Engineer. See General Utility Notes below.

The contractor must use care when working in these underground areas as well as in the vicinity of overhead cable. The time to complete any relocations/adjustments found to be necessary, as directed by the engineer, during the construction of the highway contract will depend on the nature of the work.

Under no circumstances shall any valve box or manhole be paved over, filled, or knocked out of vertical alignment during construction.

No working/existing Verizon facilities can be taken out of service. These facilities will remain in place and active during the duration of this contract.

GENERAL UTILITY NOTES

Outside of the companies and facilities discussed above, no additional utility involvement is anticipated. Should any conflicts be encountered as a result of the contractor's means and methods during construction requiring adjustment and/or relocation, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as directed by the District Engineer. The State Contractor shall coordinate any potential conflicts with utility companies and provide adequate notice prior to performing work. Any utility conflicts that are not readily discernable shall be coordinated by the State Contractor once the conflict is recognized. The time to complete any relocations/adjustments found to be necessary during construction of the highway project will depend on the nature of the work.

Any utility conflicts that are not readily discernable shall be coordinated by the State Contractor once the conflict is recognized. The time to complete any relocations/adjustments found to be necessary during construction of the highway project will depend on the nature of the work. Once the State's contractor has given the Utility the advance notice required above, it is the responsibility of the State's contractor to have the work area prepared and accessible for the Utility to perform the tasks listed above. If the site conditions are not ready and the state contractor has given notice to the utility on when the work is to be accomplished, the State's Contractor shall be responsible for any extra cost incurred by the utility company and the State Contractor shall also be responsible for any time delays. Between when the required notice is given to the Utility and when the work is performed and completed, the coordination and scheduling of the Utility is the sole responsibility of the State's Contractor. All costs related to the coordination and scheduling of the utilities is incidental to the contract.

Any adjustments and/or relocations of municipally owned sewer or water facilities shall be performed by the State's Contractor in accordance with the respective agency's standard specifications as directed by the District Engineer. The State contractor shall coordinate any potential conflicts of municipally owned sewer or water facilities with facility owners and provide adequate notice to the municipally and to the District Engineer prior to performing work.

GENERAL NOTES

- 1. The Contractor's attention is directed to Section 105.09 Utilities, Delaware Standard Specifications, August 2020. The Contractor shall contact Miss Utility (1-800-282-8555) two working days prior to any excavation. The Contractor is responsible for the support and protection of all utilities when excavating. The Contractor is responsible for ensuring proper clearances, including safety clearances, from overhead utilities for construction equipment. The Contractor is advised to check the site for access and operating purposes for his equipment and, if necessary, make arrangements directly with the utility companies for field adjustments for adequate clearances.**
- 2. The information shown in the Contract Documents, including the Utility Statement and the Utility Schedule contained herein, concerning the location, type and size of existing and proposed utilities, their locations, and construction timing has been compiled by the preparer based on information furnished by each of the involved Utility Companies. It shall be the responsibility of the State's Contractor to verify all information and coordinate with the Utility Companies prior to and during construction, as specified in Section 105.09 of the Standard Specifications.**
- 3. It is understood and agreed that the Contractor has considered in his bid all permanent and temporary utility appurtenances in their present and relocated positions as shown on the plans or described in the Utility Statement or are readily discernible and that no additional compensation will be allowed for any delays, inconvenience, or damage due to any interference from the utility facilities and appurtenances or the operation of moving them, except that the Contractor may be granted an equitable extension of time unless the delay is caused by the Contractor's delay in having the site conditions ready for the utility relocation work after the Contractor has provided the advance notice that the site conditions would be ready for the utility relocation work. The contractor's means and method of construction are not taken into account when known utility conflicts are identified. If the Contractor's means and method of construction create a utility conflict the Utility Statement will prevail in discussions with the utility and the Contractor. The State's Contractor shall be responsible for any costs associated with any temporary outages; holding, bracing, and shielding of utility facilities; temporary relocations; or permanent relocations that are not specifically identified in this utility statement or shown in the contract plan set.**
- 4. Coordination and cooperation among the Utility Companies and the State's Contractor are of prime importance. Therefore, the Contractor is directed to contact the following Utility Company representatives with any questions regarding this work prior to submitting bids and work schedules. Proposed work schedules should reflect the Utility Companies' proposed relocations. The Utility Companies do not work on weekends, nights, or legal holidays.**

Company	Name	Email	Phone
AT&T (TREC Group)	Jay Everly	jay@trecgroup.com	(610) 238-6465
Artesian Water	Wayne Tyler	WTyler@artesianwater.com	(302) 453-6987
Comcast Cable Communications, Inc.	Darren Marstellar	dmarstellar@americomm-llc.com	(717) 509-7873x1004
Crown Castle	Bill Muehlberger	Bill.Muehlberger@crowncastle.com	(215) 384-7817
Delaware Pipeline Company	Darrell Eller	Darrell.Eller@pbfenergy.com	(302) 379-4452
Delmarva Power - Gas	Fikayo Falade	fikayo.falade@exeloncorp.com	(667) 313-0873
Delmarva Power – Electric	Tom Smith	thomas.smith1@delmarva.com	(302) 283-5757
Lumen (CenturyLink/Level3)	Patrick Provost	Patrick.provost@centurylink.com	(720) 888-4686
New Castle County – Special Services	Dan Netta	dan.netta@newcastlede.gov	(302) 395-5817
Verizon of Delaware	George Zang Darren Coppersmith	george.w.zang@verizon.com Darren.Coppersmith@kci.com	(410) 316-7974

5. As outlined in Chapter 3 of the DelDOT Utilities Manual, individual utility companies are responsible for obtaining all required permits from municipal, State, and federal government agencies and railroads. This includes but is not limited to water quality permits/DNREC Water Quality Certification, DNREC Subaqueous Lands/Wetlands permits, DNREC Coastal Zone Consistency Certification, County Floodplain permits (New Castle County only), U.S. Coast Guard permits, US Army Corps 404 permits, sediment and erosion permits, and railroad crossing permits.
6. Individual utility companies are required to restore any areas disturbed in conjunction with their relocation work. If an area is disturbed by a utility company and is not properly restored, the Department may have the State's Contractor perform the necessary restoration. Any additional costs incurred as a result will be forwarded to the utility company.
7. 16 Del. C. § 7405B requires notification to and mutually agreeable measures from the public utility operating the electric line for any person intending to carry on any function, activity, work, or operation within dangerous proximity of any high voltage overhead electric lines. All contractors/other utilities must also maintain a minimum distance of 10'-0" from all energized lines. Additional clearance may be required from high voltage transmission lines.
8. Any existing facilities that are comprised of hazardous materials will be removed by the Utility Company unless otherwise outlined in the contract documents or language above. Any existing facilities containing hazardous materials will be purged by the Utility Company unless otherwise outlined in the contract documents or language above.
9. In conjunction with bid preparation and prior to starting work, the State's Contractor shall confirm with all respective Utility Companies noted in this Utility Statement to have advance utility relocations that the advance relocations have in fact been accomplished as summarized herein.

10. Contractors are not permitted to draw water from any hydrant for any use, without the written permission of the Municipality / Water Company having jurisdiction; and proper metering and backflow prevention equipment in place.


Prepared and Recommended by:



Zach Brander – Pennoni
(302) 351-5237; zbrander@pennoni.com

November 13, 2024
DATE

Approved as to form by



Utility Coordinator, DelDOT

November 25, 2024
DATE

**STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION
PO BOX 778
DOVER, DELAWARE 19903**

CERTIFICATE OF RIGHT-OF-WAY STATUS

STATE PROJECT NO. T202201102

F.A.P. NO. 5307-2022(08)

US 13 SOUTHBOUND BBRT LANE

NEW CASTLE COUNTY

Certificate of Right-of-Way Status – 100%

Status - LEVEL 1

As required by 23 CFR, Part 635, and other pertinent Federal and State regulations or laws, the following certifications are hereby made in reference to this highway project:

All necessary real property interests have been acquired in accordance with current FHWA/State directives covering the acquisition of real property; and,

All necessary rights-of-way, including control of access rights when pertinent, have been acquired including legal and physical possession; and,

All project rights of way are currently available in accordance with the project right-of-way plans; and,

Any residential displaced individuals or families have been relocated to decent, safe and sanitary housing, or adequate replacement housing has been made available in accordance with the provisions of the current Federal Highway Administration (FHWA) directive(s) covering the administration of the Highway Relocation Assistance Program; and,

All occupants have vacated the lands and improvements; and,

The State has physical possession and the right to remove, salvage, or demolish any improvements acquired as part of this project, and enter on all land.

RIGHT OF WAY SECTION



Monroe C. Hite, III
Chief of Right of Way

October 9, 2024



STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION
800 BAY ROAD
P.O. BOX 778
DOVER, DELAWARE 19903

NICOLE MAJESKI
SECRETARY

9/11/2024

ENVIRONMENTAL REQUIREMENTS
FOR

Contract Title: **US 13 Southbound BBRT Lane**

State Contract No. **T202201102**

Federal Aid No. **5307-2022(08)**

In accordance with the procedural provisions for implementing the National Environmental Policy Act of 1969, as amended, the referenced project has been processed through the Department's Environmental Review Procedures and has been classified as a Class II Action/Level D

Class II Action / Level C
CE action: **23 CFR 771.117 (c)(12)**

Environmental (NEPA) Approval Date: 12/7/2023

Due to the nature of the proposed construction activities, permits are not required for this project. However, the following construction requirements and special provisions have been developed to minimize and mitigate impact to the surrounding environs. These requirements by DeDOT, not specified within the contract, are listed below. These requirements are the responsibility of the contractor and are subject to risk of shut down at the contractor's expense if not followed.

GENERAL REQUIREMENTS:

1. All construction debris, excavated material, brush, rocks, and refuse incidental to such work shall be placed either on shore above the influence of flood waters or on some suitable dumping ground.

2. That effort shall be made to keep construction debris from entering adjacent waterways or wetlands. Any debris that enters those areas shall be removed immediately.
3. The disposal of trees, brush, and other debris in any stream corridor, wetland, surface water, or drainage area is prohibited.
4. DelDOT Environmental Studies Section must be notified if there are any changes to the project methods, footprint, materials, or designs, to allow the Department to coordinate with the appropriate resource agencies (COE, DNREC, and SHPO), for approval at (DOT_EnvironmentalStudies@delaware.gov).

Van Adams

Natural Resource Supervisor

Environmental Stewardship

Delaware Department of Transportation



STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION
 800 BAY ROAD
 P.O. BOX 778
 DOVER, DELAWARE 19903

NICOLE MAJESKI
 SECRETARY

RAILROAD STATEMENT

For

State Contract No.: T202201102

Federal Aid No.: 5307-2022(08)

Project Title: US 13 Southbound BBRT Lane

The following railroad companies maintain facilities within the contract limits:

- | | |
|--|---|
| <input type="checkbox"/> Amtrak | <input type="checkbox"/> Maryland & Delaware |
| <input type="checkbox"/> CSX | <input type="checkbox"/> Norfolk Southern |
| <input type="checkbox"/> State of Delaware
Delmarva Central | <input type="checkbox"/> Wilmington & Western |
| <input type="checkbox"/> East Penn | <input type="checkbox"/> Delmarva Central |
| | <input checked="" type="checkbox"/> None |

DOT Inventory No.: N/A No. Trains/Day: N/A Passenger Trains (Y / N): N/A

In accordance with 23 CFR 635, herein is the railroad statement of coordination (check one):

- No Railroad involvement.

- Railroad Agreement unnecessary but railroad flagging required. The contractor shall follow requirements stated in the DelDOT Maintenance of Railroad Traffic Item in the Special Provisions. Contractor shall coordinate railroad flagging with DelDOT's Railroad Program Manager at (302) 760-4882.

- Railroad Agreement required. The Contractor cannot begin work until the Agreement is complete and fully executed. Railroad related work to be undertaken and completed as required for proper coordination with physical construction schedules. The Contractor shall follow requirements stated in the DelDOT Maintenance of Railroad Traffic Item in the Special Provisions. Contractor shall coordinate railroad flagging with DelDOT's Railroad Program Manager at (302) 760-4882.

Approved As To Form:

Lei Xu

 DelDOT Railroad Program Manager

9/12/23

 DATE



**Delaware Department of Transportation
Quantity Sheet Summary**

Proposal ID: T202201102

Project Descripton: US 13 Southbound BBRT Lane

NOT TO BE USED FOR BIDDING

Item Number	Description	Unit	Quantity
202000	EXCAVATION AND EMBANKMENTThis is a Fixed Quantity item	CY	500
209006	BORROW, TYPE F	CY	141
211000	REMOVAL OF STRUCTURES AND OBSTRUCTIONS	LS	1
211001	REMOVAL OF PORTLAND CEMENT CONCRETE PAVEMENT, CURB AND SIDEWALK	SY	635
301001	GABC	CY	175
301002	GABC, PATCHING	CY	29
401014	SUPERPAVE TYPE B, PG 64-22	TON	134
602130	ADJUSTING AND REPAIRING EXISTING DRAINAGE INLET	EACH	2
701026	PCC MONOLITHIC MEDIAN	LF	38
701511	PCC CURB, SPECIAL	LF	9
705528	TEMPORARY PEDESTRIAN CONNECTION	EACH	4
760010	PAVEMENT MILLING, BITUMINOUS CONCRETE PAVEMENT	SYIN	7894
802003	ARROW PANELS TYPE C	EADY	40
401016	SUPERPAVE TYPE B, PG 76-22	TON	80
817038	PERMANENT PAVEMENT STRIPING, ALKYD-THERMOPLASTIC, 6"	LF	22
831564	PROVIDE AND INSTALL 1-1/2" GALVANIZED STEEL CONDUIT (TRENCH)	LF	18

This page is for information only. Do not use this page to submit a Bid.



**Delaware Department of Transportation
Quantity Sheet Summary**

Proposal ID: T202201102

Project Descripton: US 13 Southbound BBRT Lane

NOT TO BE USED FOR BIDDING

Item Number	Description	Unit	Quantity
813001	TEMPORARY BARRICADES, TYPE III	LFDY	1600
813002	PEDESTRIAN CHANNELIZING BARRICADE SYSTEM	LFDY	12750
401029	SUPERPAVE TYPE C, PG 64-22, PATCHING	TON	15
401030	SUPERPAVE TYPE B, PG 64-22, PATCHING	TON	44
401046	SUPERPAVE TYPE C, PG 76-22 (NON-CARBONATE STONE)	TON	511
602132	ADJUSTING AND REPAIRING EXISTING MANHOLE	EACH	11
701022	I.PCC CURB AND GUTTER, TYPE 3-6	LF	239
702000	TRIANGULAR CHANNELIZING ISLANDS	SF	1821
705001	PCC SIDEWALK, 4"	SF	965
705013	TRUNCATED DOME DETECTABLE WARNING SURFACE	SF	193
705009	PEDESTRIAN CONNECTION, TYPE 2, 3, AND/OR 4	SF	436
705011	PEDESTRIAN CONNECTION, SPECIAL	SF	249
762000	SAW CUTTING, BITUMINOUS CONCRETE	LF	3798
762001	SAW CUTTING, CONCRETE, FULL DEPTH	LF	76
763000	INITIAL EXPENSE/DE-MOBILIZATION	LS	1
763501	CONSTRUCTION ENGINEERING	LS	1
801000	MAINTENANCE OF TRAFFIC	LS	1

This page is for information only. Do not use this page to submit a Bid.



**Delaware Department of Transportation
Quantity Sheet Summary**

Proposal ID: T202201102

Project Descripton: US 13 Southbound BBRT Lane

NOT TO BE USED FOR BIDDING

Item Number	Description	Unit	Quantity
803001	PROVIDE AND MAINTAIN PORTABLE CHANGEABLE MESSAGE SIGN	EADY	120
804001	PROVIDE AND MAINTAIN PORTABLE LIGHT ASSEMBLY (FLOOD LIGHTS)	EADY	80
805001	PLASTIC TRAFFIC CONTROL DRUMS	EADY	4000
808002	PROVIDE AND MAINTAIN TRUCK MOUNTED ATTENUATOR, TYPE II	EADY	40
810001	TEMPORARY WARNING SIGNS AND PLAQUES	EADY	1425
811001	FLAGGER, NEW CASTLE COUNTY	HOUR	350
811013	FLAGGER, NEW CASTLE COUNTY, OVERTIME	HOUR	88
817002	PERMANENT PAVEMENT STRIPING, SYMBOL/LEGEND, ALKYD-THERMOPLASTIC	SF	3222
817031	REMOVAL OF PAVEMENT STRIPING	SF	2591
817042	PERMANENT PAVEMENT STRIPING, EPOXY RESIN PAINT, WHITE/YELLOW, 6"	LF	6995
817043	PERMANENT PAVEMENT STRIPING, EPOXY RESIN PAINT, WHITE/YELLOW, 12"	LF	5467
818001	SUPPLY OF FLAT SHEET ALUMINUM SIGN PANEL, TYPE IV, RETROREFLECTIVE SHEETING	SF	228
818003	SUPPLY OF FLAT SHEET ALUMINUM SIGN PANEL, TYPE XI, RETROREFLECTIVE SHEETING	SF	9
819011	GALVANIZED TELESCOPING STEEL SIGN POSTS, 12' X 2", COMPLETE W/ BASEPOSTS AND HARDWARE	EACH	24
819018	INSTALLATION OR REMOVAL OF TRAFFIC SIGN(S) ON SINGLE SIGN POST	EACH	63
819019	INSTALLATION OR REMOVAL OF TRAFFIC SIGN(S) ON MULTIPLE SIGN POSTS	SF	105

This page is for information only. Do not use this page to submit a Bid.



**Delaware Department of Transportation
Quantity Sheet Summary**

Proposal ID: T202201102

Project Descripton: US 13 Southbound BBRT Lane

NOT TO BE USED FOR BIDDING

Item Number	Description	Unit	Quantity
830008	ADJUST OR REPAIR EXISTING CONDUIT JUNCTION WELL	EACH	7
830010	REMOVAL OF EXISTING JUNCTION WELL	EACH	2
831501	PROVIDE AND INSTALL 4" SCHEDULE 80 PVC CONDUIT (OPEN CUT)	LF	22
831514	PROVIDE AND INSTALL 2-1/2" SCHEDULE 80 PVC CONDUIT (TRENCH)	LF	60
831545	PROVIDE AND INSTALL 4" HDPE SDR-13.5 CONDUIT (BORE)	LF	214
834005	POLE BASE, TYPE 4A	EACH	3
846001	PROVIDE AND INSTALL LOOP WIRE 1-CONDUCTOR #14 AWG ENCASED IN 1/4" FLEXIBLE TUBING IN A LOOP SAWCUT	LF	600
905001	SILT FENCE	LF	126
905005	INLET SEDIMENT CONTROL, CURB INLET	EACH	2
908004	TOPSOIL, 6" DEPTH	SY	346
908014	PERMANENT GRASS SEEDING, DRY GROUND	SY	346
201000	CLEARING AND GRUBBING	LS	1
701021	I.PCC CURB AND GUTTER, TYPE 3-4	LF	22
806500	TRAFFIC OFFICERS	HOUR	200

This page is for information only. Do not use this page to submit a Bid.