

STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION



BID PROPOSAL

CONTRACT T202611302

US 301 MEDIAN BARRIER, SR 896 TO MD LINE

Advertisement Date: July 22, 2026

INCLUDED IN THIS DOCUMENT:

BID PROPOSAL:

*GENERAL DESCRIPTION
PROSPECTIVE BIDDER'S NOTES
GENERAL NOTICES
PREVAILING WAGES
SPECIAL PROVISIONS
STATEMENTS
SAMPLE AFFIDAVIT - CRAFT TRAINING
QUANTITY SHEET SUMMARY*

ADDITIONAL BID PROPOSAL ITEMS:

ATTACHED OR POSTED DOCUMENTS:

*PROJECT PLANS
QUESTIONS & ANSWERS (if posted)*

**PAPER BIDDERS CONTACT DELDOT
FOR BID SUBMITTAL DOCUMENTS:**

*DRUG TESTING AFFIDAVIT;
CERTIFICATION FORM;
BID BOND FORM;
CD FOR BID PRICE ENTRY & PRINTING*

This Bid Proposal and related documents can be viewed on bids.delaware.gov and, for subscribers bidx.com/de/

Internet Bids for Bidders with Bid Express® accounts can be submitted at [BIDX.com/de](https://bidx.com/de/); **OR**;

Paper Bids with CD will be received in the Bidder's Room at the DelDOT Administration Building, Dover, DE;

ALL BIDS DUE PRIOR TO 2:00 P.M. Local Time, AUGUST 18, 2026

DIGITAL ACCESSIBILITY NOTICE

The Delaware Department of Transportation (DelDOT) is committed to ensuring that its digital services, content, and documents are accessible to all users and is actively working to comply with applicable federal and state accessibility requirements. DelDOT continues to make improvements over time, with current efforts focused on programs, applications, content, and documents that are actively in use and available to the public.

Due to the nature and complexity of certain materials, including construction plans, technical drawings, historical documents, maps, and other graphic-intensive files, some documents may not currently be fully digitally accessible or compliant with current accessibility standards. In some cases, these documents are provided for historical, reference, informational, or procurement purposes only.

If you require an accessible version of a document or need assistance accessing any content, please contact DelDOT at (302) 760-2031 or DOT.Profservices@delaware.gov, and reasonable efforts will be made to provide the information in an accessible format upon request. DelDOT appreciates your patience and understanding as accessibility improvements continue to be implemented.

GENERAL DESCRIPTION

A. BIDS DUE: AUGUST 18, 2026 **PRIOR TO 2:00 P.M. Local Time** – unless changed via Addendum.

BIDS MUST BE SUBMITTED VIA:

(a) **Internet** - Bidders with DelDOT Bid Express® accounts can submit bids at bidx.com/de/.

OR:

(b) **Paper Bid Delivered To:** Delaware Department of Transportation, Administration Building
North Entrance, Bidders Room, 800 Bay Road, Dover, DE 19901

For paper bids, contact DelDOT at dot-ask@delaware.gov or (302) 760-2031 to request a CD for bidding, required forms, and instructions. Bidders enter their Bid Item prices onto the supplied CD then print the form and deliver in a sealed envelope; the Bid Form, completed CD, and required documents prior to the Bid due date and time.
(CD's cannot be used to submit bids to bidx.com)

Do not submit both Internet and Paper Bids. If so, the Internet bid and documents will be rejected.

BID OPENING: Bids will be publicly opened and read aloud at the Date and Time of the Bid Opening. The Bid Opening will be held at the 'Paper Bid Delivered To' address shown above. Bidder bears the risk of late delivery, bids received after the stated time will be returned unopened.

Attendance is not required. DelDOT offers a call-in number to hear the Bid Opening telephonically. The telephone number to call is (302) 504-8986.

When prompted, enter Meeting number (access code): 651 529 280#

It is anticipated the telephone access information will remain the same for all Bid Openings.

B. PRE-BID MEETING: No

C. LOCATION: New Castle County

These improvements are more specifically shown on the Location Map(s) of the attached Plans.

D. DESCRIPTION: The improvements consist of furnishing all labor and materials for the project which includes approximately 8 miles of high-tension cable barrier and type 3-31 guardrail with a minimum 4-ft wide maintenance strip along sections of US 301 between the Maryland state line and SR 896. Follow other incidental construction in accordance with the location, notes and details shown on the plans, and as directed by the Engineer.

E. COMPLETION TIME: All work on this contract must be complete within 241 Calendar Days.

Extensions of contract time due to weather are specified in the Standard Specifications Section 108.7F, weather days. It is estimated a Notice to Proceed is issued such that work starts on or about October 26, 2026.

F. SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, DELAWARE DEPARTMENT OF TRANSPORTATION, JANUARY 2026 apply to this Bid Proposal and Project. The Contractor shall make himself aware of any revisions and corrections and apply them to the applicable item(s) of this contract. The Standard Specifications can be viewed [here](#). Units of Measure can be found at 101.4.

G. ATTACHMENTS: Included as part of this Bid Proposal are; *Project Plans; Questions & Answers* (if posted); *Addenda* (if issued), *Referenced Documents, Documents Posted with this Bid Proposal*; and *Bid documents mailed to contractors*.

H. ADDENDA: All Addenda are posted on the internet at bids.delaware.gov, and bidx.com/de/ and are included as part of the Bid Proposal. The Bidder is responsible to check the Website as needed to ensure that the Bidder is aware of Addenda that are included in the Bid Proposal. If Addenda are issued, the final Addendum will be posted no later than the end of the day two business days prior to the bid date. Each Addendum number and issue date must be entered on the submitted Certification Form. This original Bid Proposal will not be updated, you must refer to each Addendum.

I. QUESTIONS: E-MAIL TO; dot-ask@delaware.gov

Questions regarding this project are to be e-mailed to the above address no less than **six business days** prior to the bid opening date in order to receive a posted response. Please include the Contract number in the subject line.

Questions and responses are posted at bids.delaware.gov, and bidx.com/de/. The date of the final posted Questions and Answers document must be entered on the submitted Certification Form.

J. FLAGGERS:

- A. Included in the Bid Proposal are the prevailing wages for highway construction as determined by the Department of Labor of the State of Delaware in accordance with [Title 29 Del. C. §6960](#), relating to wages and the regulations implementing that Section.
- B. Flaggers must be bid at a minimum equal to the Laborer wage rate and may be bid up to, but not to exceed, 3 times the Laborer wage rate in accordance with the County where the Work is being performed.
- C. The Department will adjust the bid to the minimum for prices bid below the minimum acceptable bid and to the maximum for prices bid above the maximum allowable bid prior to award of the Contract.
 - 1. Flagger overtime must be bid at minimum of 1.45 times and may be bid up to a maximum of 4.35 times, the Laborer wage rate in accordance with the County where the Work is being performed.
 - 2. When a Contract for a Project contains both Federal Davis-Bacon and State of Delaware prevailing wage standards, the employer's minimum wage obligations are determined by whichever standards are higher.
- D. Overtime:
 - 1. Payment for overtime will be considered on a weekly basis for time worked in excess of 40 hours for a continuous 7-day period beginning Monday and ending Sunday inclusive.
 - 2. Time worked on other Projects or Work activities other than flagging will not be counted in the normal 40 hours or the overtime.
- E. The cost of the flagging operation when performed by others who are not the Contractor's employees will not be included in the 50% subcontracting limit as outlined in Section 108.1.

K. PROSPECTIVE BIDDERS NOTES:

1. CRAFT TRAINING REQUIREMENT ([29 Del. C. §6960A](#))

- a) The awarded contractor must include a craft training program for each craft in the project if at the time the contractor executes the contract, all of the following apply:
 - 1. This project requires prevailing wages.
 - 2. The contractor employs 10 or more total employees.
 - 3. This project is not a federal highway project (except for the US 301 project from the MD-DE state line to SR1).
 - 4. There is an apprenticeship program for a craft in the project on the list provided by the [Delaware Department of Labor](#).
- b) The awarded contractor must commit that all subcontractors provide craft training if the above applies to the subcontractor.
- c) The contractor must satisfy the craft training requirement before the contract is executed. A contractor or subcontractor may satisfy the craft training requirement by doing any of the following for each craft required:
 - 1. Having at least 1 active apprentice in a craft training program for the craft.
 - 2. Having at least 1 active apprentice who completes a craft training program for the craft within the 6 months before the date the contract was executed.
 - 3. Being a member of a consortium that provides craft training for the craft and all of the following apply to the craft training program for the craft:
 - (a). The consortium requires a regular financial contribution.
 - (b). The contractor or subcontractor has access to the craft training program.
 - (c). There is at least 1 active apprentice in the craft training program.
- 4. Making a payment under paragraph (e) of this section.
- d) The craft training program under above paragraphs c)1. and c)2. may be provided by the contractor or subcontractor or through agreement with another entity.

The active apprentice under paragraphs c)1. and c)2. does not have to work on this project.

- e) A contractor or subcontractor may satisfy the craft training requirement by making a payment in the amount established under § 204 of Title 19, for the craft into the Apprenticeship and Training Fund of the Department Labor. For each calendar year, a contractor or subcontractor satisfies the craft training requirement for all contracts executed during that year when payments made after January 1 equal the following amounts:
1. For employers with 10 through 25 employees, payments that total \$10,000.
 2. For employers with more than 25 employees, payments that total \$20,000.
- f) **PENALTY:** If the successful bidder fails to comply with the Craft Training Requirements:
1. The contractor must pay the amount of the payment required under paragraph e) above to the Apprenticeship and Training Fund.
 2. An amount that does not exceed 10 percent of the payment under paragraph f)1. of this section.
 3. A penalty assessed under paragraph f)1. may be fully or partially remitted or refunded by the agency awarding the contract only if the contractor establishes compliance within 60 days of the notice of the penalty. A claim for remission or refund of a penalty may only be granted if an application for the remission or refund is filed within 1 year of the notice of the penalty.
 4. Any contractor or subcontractor who fails to provide required craft training under 29 Del. C. § 6960A may be subject to suspension or debarment.
- 2. BIDDERS MUST BE REGISTERED** with DelDOT in order to submit a bid. Registrations are now completed online through SimpliGov. To complete registration or for more information, click [here](#).
- 3. SURETY BOND** - Each proposal must be accompanied by a deposit of either surety bond or security for a sum equal to at least 10% of the amount bid.
- 4. DELAWARE'S CONTRACTOR REGISTRATION ACT** - 19 Del.C. §§ 3601 *et seq.*, requires all contractors and subcontractors to register with the Delaware Department of Labor before performing construction services or maintenance. Refer to the GENERAL NOTICES section for further information.
- 5. DRUG TESTING** - Regulation 4104; The state Office of Management and Budget has developed regulations that require Contractors and Subcontractors to implement a program of mandatory drug testing for Employees who work on Large Public Works Contracts funded all or in part with public funds pursuant to 29 Del.C. §6908(a)(6). **Refer to the full requirements at the following link:**
<http://regulations.delaware.gov/register/december2017/final/21%20DE%20Reg%20503%2012-01-17.htm>
Note a few of the requirements;
- * At bid submission - Each bidder must submit with the bid a single signed affidavit certifying that the bidder and its subcontractors has in place or will implement during the entire term of the contract a Mandatory Drug Testing Program that complies with the regulation (*a blank affidavit form is attached*);
 - * At least two business days prior to contract execution - The awarded Contractor shall provide to DelDOT copies of the Employee Drug Testing Program for the Contractor, each participating DBE firm, and all other listed Subcontractors;
 - * Subcontractors - Contractors that employ Subcontractors on the job site may do so only after submitting a copy of the Subcontractor's Employee Drug Testing Program along with the standard required subcontractor information. A Subcontractor shall not commence work until **DelDOT** has approved the program in writing.
- 6. PERFORMANCE-BASED RATING SYSTEM** - 29 Del.C. §6962 (c)(12)(a) requires DelDOT to include a performance-based rating system for contractors. The Performance Rating for each Contractor shall be used as a prequalification to bid at the time of bid. Refer to 'General Notices' for details.
- 7. NO RETAINAGE** will be withheld on this contract unless through the Performance-Based Rating System.
- 8. EXTERNAL COMPLAINT PROCEDURE** can be viewed on DelDOT's Website, [Contractor Compliance/EEO - Delaware Department of Transportation](#) or request a copy by calling (302) 760-2555.
- 9. DELAWARE BUSINESS LICENSE;** a copy of your firm's Business License must be submitted with your bid.

10. FLATWORK CONCRETE TECHNICIAN CERTIFICATION TRAINING:

Section 501.3, 503.3, 505.3, 610.3, 701.3 and 702.3 of the 2026 Standard Specifications require contractors to provide an American Concrete Institute (ACI) or National Ready-Mix Concrete Association (NRMCA) certified concrete flatwork technician to supervise all finishing of flatwork concrete.

11. SIGNAGE LANGUAGE:

In order to maintain effective communication with the traveling public, only place signs, banners, flags, or other displays within the projects limits that meet the requirements of the latest version of the Delaware Manual on Uniform Traffic Control Devices. Any signs or other materials which deviate from the MUTCD, must be preapproved by the Engineer. The only signage and materials which may be displayed upon vehicles and equipment within the Project area are signs denoting the name of the Contractor and any subcontractors and other signs and/or materials required and approved pursuant to the MUTCD and the Engineer. Contractor shall immediately remove any signs or materials within the Project that does not meet these requirements immediately upon notification by the Engineer. Failure to remove signs or other materials following notification from the Engineer will result in Liquidated Damages being assessed in the manner and amount specified in the Standard Specifications section 108.9.A.

12. REVISED SPEC LANGUAGE:

The Revised Inspection Framework – January 2026 ([2026 Inspection Framework](#)) shall apply to this contract.

Delete from Section 101.3

Primary inspection. The inspection (formerly referred to as Final Inspection) conducted by the engineer to determine if the contractor has satisfactorily completed the project, or a portion of the project, in accordance with the contract.

Insert within Section 101.3

Acceptance Inspection. The inspection (formerly referred to as Primary Inspection) conducted by the Administering Section, contractor, and accepting section confirming that primary inspection punch list items have been addressed.

Primary inspection. The inspection (formerly referred to as initial inspection) conducted by the Department to review all contract work has been completed in accordance with the Plans, Standard Specifications, Special Provisions, and Standard Construction Details. The inspection is confirmation of the work completed per the contract documents.

Project Acceptance. The Department's notification to the Contractor that the time charges will cease, and construction activities are completed, releasing the contractor from liability and repairs or maintenance to the completed work.

Revise Section 104.12.A as follows.

- A. Before **acceptance** inspection, clean rubbish, excess materials, temporary structures, and equipment from the project, from any publicly owned borrow source used to complete the work, and from areas affected by the contractor in connection with the work within the right-of-way. Cut all grass and weeds taller than 6-inches. The cost of the final cleanup is incidental to Item 763000, **Initial Expense, De-Mobilization**.

Revise Section 105.4.F as follows.

- F. Submit copies of manufacturer's catalog cuts, drawings, wiring diagrams, and other relevant documents with working drawings for electrical and mechanical equipment. After the Department has reviewed all items of a particular system, prepare an instruction book for the particular system. Fasten and bind the items listed below in a leather or heavy plastic cover book with a title clearly shown. Provide five copies of the book to the engineer before **acceptance** inspection. Make the books available

when connecting and energizing electrical and mechanical systems. Ensure that the final bound copies reflect changes or adjustments made during the work. Include the following in the instruction book:

1. An equipment list.
2. A complete description of the equipment.
3. The sequence of operation including inter-locking and protective features.
4. The use of by-pass switches.
5. A detailed description of all wiring circuits.
6. A recommended spare parts list.
7. Renewal parts bulletins.
8. Instruction bulletins for the provided equipment.
9. Diagrams and drawings of reduced size suitable for binding.
10. An index listing all items.

Revise Section 105.13.D as follows.

- D. Include the cost of maintenance work during construction and before completion of the acceptance inspection punch list in the proposal. The Department will pay the cost of maintenance work occurring after completion of the acceptance inspection punch list.

Revise Section 105.14.A as follows.

- A. The engineer may order opening of certain sections of the work to traffic or other use before the contractor completes the work or before the engineer accepts the work. The Department will not consider opening sections of the work as constituting acceptance of the work or a waiver of any contract provisions. The engineer will pay the cost of repairing damage to the work caused by opening work to vehicular traffic unless opening the roadway is due to the fault, or inactivity of, the contractor or the contractor caused the damage. All other maintenance costs including, but not limited to, mowing grass and general cleanup are the contractor's responsibility until completion of the acceptance inspection punch list to the Department's satisfaction. Maintenance costs for work involving landscaping and vegetative growth are the contractor's responsibility until final acceptance.

Revise Section 105.16 as follows.

- A. Partial Acceptance.
 1. The decision to partially accept a portion of the project is solely at the discretion of the engineer. The engineer may partially accept portions of the work. The Department will not consider partial acceptance as constituting acceptance of the work that has not been partially accepted or a waiver of any contract provisions. The Department will maintain the partially accepted portion of the project, including repairing damage caused by the public.
- B. Project Acceptance
 1. The Department will cease counting contract time when the project reaches substantial completion as defined in Section 101.3, Definitions.
 2. Substantial Completion Verification
 - a. Upon receiving the contractor's notice of substantial completion of the project, the Department will verify all contract items are complete as defined in Section 101.3, Definitions. Items not deemed complete shall be completed by contractor prior to Department issuance of Substantial Completion.
 - b. After issuance of Substantial Completion, request Primary Inspection from the Department.
 - c. The Department will schedule the Primary Inspection within 30 calendar days of the request.
 3. Primary Inspection
 - a. The Department/Administering Section will conduct a Primary Inspection with the completion of 105.16.2 Substantial Completion Verification. The Administering Section will note and provide a written punch list by stations and in detail identifying work or conditions requiring correction. The punch list will include ADA inspection deficiencies.

- b. Perform the corrective work noted on the punch list within 30 calendar days upon receipt of the punch list created by the Administering Section, unless the parties mutually agree to extend the time frame.
 - c. Upon completion of the primary inspection punch list, request an acceptance inspection from the Department. Prior to acceptance inspection scheduling, the Administering Section will confirm and annotate the primary inspection punch list and ensure ADA Inspection deficiencies have been addressed and documented.
 - d. The Administering Section will schedule Acceptance inspection with the Maintenance District within 30 days of confirmation of primary punch list item completion.
- 4. Acceptance (formerly primary) Inspection.
 - a. The Department will conduct an acceptance inspection with the completion of 105.16.B.3, primary inspection. The Administering Section will provide a written punch list identifying deficiencies not satisfactorily addressed from the primary inspection punch list within 7 calendar days of the acceptance inspection.
 - b. Perform the corrective work noted on the punch list within 15 calendar days upon receipt of the punch list created by the Administering Section, unless the parties mutually agree to extend the time frame.
 - c. The Administering Section will verify remediation work and will provide a list with dates that remedial activities were resolved to the Maintenance District when requesting Project Acceptance.
- C. Project Acceptance
 - 1. The Administering Section will notify the Maintenance District that acceptance inspection punch list items have been addressed.
 - 2. The Maintenance District and/or other accepting entities will verify acceptance inspection punch list items have been addressed within 30 calendar days of notice from the Administering Section.
- D. Final Acceptance
 - 1. The engineer will provide final acceptance in writing that will state the acceptance date as defined in Section 101.3, Definitions.
- E. Project Closeout
 - 1. Upon final acceptance, provide the exempted documents, certificates, or proofs of compliance within 90 calendar days.
 - 2. The Department will not issue the final payment until the contractor executes and delivers the required documents.

Revise Section 108.8.K as follows.

- K. Once the Department determines that the work is substantially complete, the Department will suspend time charges and the assessment of liquidated damages. Failure to complete all punch list work identified during the primary and acceptance inspections within the timeframes allotted, will result in the Department restarting liquidated damages in accordance with the chart specified in Section 108.9, Schedule of Liquidated Damages. The assessment of post-substantial-completion liquidated damages will continue until project completion.

Revise Section 610.3.9.A.2 as follows.

- 2. The engineer will measure the width, length, and depth of each crack and establish the precise location of the crack termination points relative to permanent reference points on the member. The engineer will monitor and document the growth of individual cracks at an inspection interval the engineer will choose to determine if cracks are active or dormant after acceptance inspection.

remainder of page is blank

Revise Section 722.3.2.A as follows.

- A. Provide on-site field instruction by the system manufacturer, at a location determined by the engineer. Provide a minimum of 2 training sessions consisting of installation training before beginning cable barrier construction and maintenance training before **acceptance** inspection. The manufacturer shall establish the training duration and shall provide field training on all aspects of the system. Coordinate the training schedule and location with the engineer. The engineer will advise the appropriate department staff, including construction inspectors and maintenance personnel regarding the training location and schedule. Provide all training materials in both hard copy and electronic PDF format.

Revise Section 722.3.2.C.1 as follows.

1. Hold the maintenance training a minimum of 7 calendar days before **acceptance** inspection of the system. Submit the proposed training date to the engineer a minimum of 14 calendar days prior to the training session date for review and approval. Include the following participants:
 - a. District Maintenance Engineer, or designated representative;
 - b. District Maintenance Superintendent, or designated representative;
 - c. Area Yard Supervisor, or designated representative; and
 - d. District maintenance personnel.

Revise Section 722.3.3.L as follows.

- L. Within 10 calendar days of the **primary** inspection, supply spare parts for the HTCB system. Deliver the parts to the DelDOT maintenance facility as directed by the engineer. Provide an extra supply of the following:
 1. Socketed-type line posts, including post hardware, caps, reflective sheeting, straps, spacers, and socket covers. Include 200 posts and accessories.
 2. Rigging screws and threaded terminals. Provide enough materials to complete 8 turnbuckle assemblies.
 3. Anchor posts including post hardware and caps, reflective sheeting, straps, fittings, spacers, and socket covers. Provide enough materials to complete 3 end anchor installations.
 4. Fitting gaskets or socket covers. Provide 100 socket covers.

Revise Section 843.3.5.C as follows.

- C. Repair defects identified by the Department during **periodic or primary** inspections in accordance with this specification, including all highway lighting systems and components within the project limits. Begin highway lighting system repairs immediately following notice of the lighting system defect unless weather limitations prevent the corrective work. Provide notification to the Department before beginning corrective work.

Revise Section 843.3.5.D as follows.

- D. The Department will not consider the highway lighting system as substantially complete until correction of the deficiencies noted during the primary and **acceptance** inspections. Provide a maintenance bond for item 843001 – Electrical Testing upon substantial completion. Provide a maintenance bond meeting the following requirements:
 1. A bond sum equal to 100 percent of the value of all highway lighting system items the Department paid to the contractor;
 2. With original signatures, in ink, and not mechanical reproductions or facsimiles of any kind, naming the contractor as the principle;
 3. term of 1-year beyond the completion of the highway lighting system work; and
 4. written by a surety or insurance company licensed to write surety bonds in the State of Delaware by the Delaware Department of Insurance.

remainder of page is blank

Revise 911.3.6.G as follows.

- G. Water bi-weekly during the period June 15 through October 1. Continue watering, without interruption, until completing watering of all the plants on the project. Use water in accordance with Section 911.2.9. The Department will allow use of tree watering bags as a part of the watering operation. Remove the tree watering bags before **acceptance** inspection.

- end -

remainder of page is blank

GENERAL NOTICES

CONTRACTOR REGISTRATION ACT

On July 1, 2021, the Contractor Registration Act, as codified in 19 Del.C. §§ 3601 *et seq*, took effect. This law requires all contractors to register with the Delaware Department of Labor before performing construction services or maintenance. The Contractor Registration Act applies to all contractors that engage in construction and maintenance within the State of Delaware. Additionally, it requires contractors to have Delaware workers' compensation insurance where required, compliance with labor laws, and proof of a state business license. The Delaware Department of Labor's Office of Contractor Registration is responsible for enforcement of the requirements of the Contractor Registration Act. If you have any questions about the contractor registration process, please call 302-430-7739 or email Contract.Registry@delaware.gov. Registration at <https://onestop.delaware.gov/>.

SPECIFICATIONS :

The Delaware specifications entitled "*Standard Specifications for Road and Bridge Construction "January, 2026"*", hereinafter referred to as the *Standard Specifications*; and *Revisions* to the Standard Specifications effective as of the advertisement date of this Bid Proposal and hereby included by reference; the *Special Provisions*; *Notes on the Plans*; this *Bid Proposal* including referenced documents; any *Addenda* thereto; and any posted *Questions and Answers*; shall govern the work to be performed under this contract. The Contractor shall make itself aware of these specifications, revisions and corrections, and apply them to the applicable item(s) of this contract.

CLARIFICATIONS :

Under any Section or Item included in the Contract, the Contractor shall be aware that when requirements, responsibilities, and furnishing of materials are outlined in the details and notes on the Plans and in the paragraphs preceding the "Basis of Payment" paragraph in the Standard Specifications or Special Provisions, no interpretation shall be made that such stipulations are excluded because reiteration is not made in the "Basis of Payment" paragraph.

The Department requires the use of various electronic applications for various documentation processes. These processes will be identified, and the Contractor's required use will be detailed during the Preconstruction Meeting. No additional payments will be made to the contractor to use or interface with the applications.

ATTESTING TO NON-COLLUSION :

The Department requires as a condition precedent to acceptance of bids a sworn statement executed by, or on behalf of, the person, firm, association, or corporation to whom such contract is to be awarded, certifying that such person, firm, association, or corporation has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free competitive bidding in connection with such contract. The form for this sworn statement is included in the proposal and must be properly executed in order to have the bid considered.

QUANTITIES :

The quantities shown are for comparison of bids only. The Department may increase or decrease any quantity or quantities without penalty or change in the bid price.

PERFORMANCE-BASED RATING SYSTEM

29 Del.C. §6962 (c)(12)(a) requires a Department of Transportation project, excluding a Community Transportation Fund or municipal street aid contract, to include a performance-based rating system. At the time of bid, the Performance Rating for each Contractor shall be used as a prequalification to bid.

Bidders with Performance Rating scores equal to or greater than 85% shall be permitted to bid. Bidders with scores of less than 85% who comply with the retainage requirements of 29 Del.C. §6962 shall be permitted to bid provided the *Agreement to Accept Retainage* (located on the Certification Page) is executed and submitted with the bid. Lack of an executed *Agreement to Accept Retainage* will result in the rejection of the bid by the Department. Successful bidders awarded

Department contracts who have no performance history within the last five (5) years will be assigned a provisional Performance Rating of 85% at the date of advertisement.

Notification of Performance Rating. The Department shall post publicly the Performance Rating for all Contractors on the Department's [website](#). DelDOT will complete performance-based evaluations on the construction company contracted by the Department to build the project (the "Contractor"). Provisions to appeal Performance Ratings are described in the regulations. The regulations are set forth in Section 2408 of Title 2, Delaware Administrative Code, found [here](#).

PREFERENCE FOR DELAWARE LABOR:

Delaware Code, Title 29, Chapter 69, Section 6962, Paragraph (d), Subsection (4)b: "In the construction of all public works for the State or any political subdivision thereof, or by firms contracting with the State or any political subdivision thereof, preference in employment of laborers, workmen or mechanics shall be given to bona fide legal citizens of the State who have established citizenship by residence of at least 90 days in the State. Each public works contract for the construction of public works for the State or any political subdivision thereof shall contain a stipulation that any person, company or corporation who violates this section shall pay a penalty to the Secretary of Finance equal to the amount of compensation paid to any person in violation of this section."

EQUALITY OF EMPLOYMENT OPPORTUNITY ON PUBLIC WORKS :

Delaware Code, Title 29, Chapter 69, Section 6962, Paragraph (d), Subsection (7) states;

- a. As a condition of the awarding of any contract for public works financed in whole or in part by State appropriation, such contracts shall include the following provisions:

During the performance of this contract, the contractor agrees as follows:

1. The contractor will not discriminate against any employee or applicant for employment because of race, creed, color, sex, sexual orientation, gender identity or national origin. The contractor will take positive steps to ensure that applicants are employed and that employees are treated during employment without regard to their race, creed, color, sex, sexual orientation, gender identity or national origin. Such action shall include, but not be limited to, the following: employment, upgrading, demotion or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship. The contractor agrees to post in conspicuous places available to employees and applicants for employment notices to be provided by the contracting agency setting forth this nondiscrimination clause.
2. The contractor will, in all solicitations or advertisements for employees placed by or on behalf of the contractor, state that all qualified applicants will receive consideration for employment without regard to race, creed, color, sex, sexual orientation, gender identity or national origin.
3. The contractor will ensure employees receive equal pay for equal work, without regard to sex. Employee pay differential is acceptable if pursuant to a seniority system, a merit system, a system which measures earnings by quantity or quality of production, or if the differential is based on any other factor other than sex.

TAX CLEARANCE :

As payments to each vendor or contractor aggregate \$2,000, the Division of Accounting will report such vendor or contractor to the Division of Revenue, who will then check the vendor or contractor's compliance with tax requirements and take such further action as may be necessary to ensure compliance.

LICENSE :

A person desiring to engage in business in this State as a contractor shall obtain a license upon making application to the Division of Revenue.

CONTRACTOR / SUBCONTRACTOR LICENSE: 29 DEL. C. §6967:

- (b) No agency shall accept a proposal for a public works contract unless such contractor has provided a proper and current copy of its occupational and/or business license, as required by Title 30, to such agency.
- (c) Any contractor that enters a public works contract must provide to the agency to which it is contracting, within 30 days of entering such public works contract, copies of all occupational and business licenses of subcontractors and/or independent contractors that will perform work for such public works contract. However, if a subcontractor or independent contractor is hired or contracted more than 20 days after the contractor entered the public works contract the occupational or business license of such subcontractor or independent contractor shall be provided to the agency within 10 days of being contracted or hired.

DIFFERING SITE CONDITIONS:

SUSPENSIONS OF WORK and SIGNIFICANT CHANGES IN THE CHARACTER OF WORK:

Differing site conditions: During the progress of the work, if subsurface or latent physical conditions are encountered at the site differing materially from those indicated in the contract or if unknown physical conditions of an unusual nature, differing materially from those ordinarily encountered and generally recognized as inherent in the work provided for in the contract are encountered at the site, the party discovering such conditions shall promptly notify the other party in writing of the specific differing conditions before they are disturbed and before the affected work is performed.

Upon written notification, the engineer will investigate the conditions, and if he/she determines that the conditions materially differ and cause an increase or decrease in the cost or time required for the performance of any work under the contract, an adjustment, excluding loss of anticipated profits, will be made and the contract modified in writing accordingly. The engineer will notify the contractor of his/her determination whether or not an adjustment of the contract is warranted.

No contract adjustment which results in a benefit to the contractor will be allowed unless the contractor has provided the required written notice. No contract adjustment will be allowed under their clause for any effects caused on unchanged work.

Suspensions of work ordered by the engineer: If the performance of all or any portion of the work is suspended or delayed by the engineer in writing for an unreasonable period of time (not originally anticipated, customary or inherent to the construction industry) and the contractor believes that additional compensation and/or contract time is due as a result of such suspension or delay, the contractor shall submit to the engineer in writing a request for adjustment within 7 calendar days of receipt of the notice to resume work. The request shall set forth the reasons and support for such adjustment.

Upon receipt, the engineer will evaluate the contractor's request. If the engineer agrees that the cost and/or time required for the performance of the contract has increased as a result of such suspension and the suspension was caused by conditions beyond the control of and not the fault of the contractor, its suppliers, or subcontractors at any approved tier, and not caused by weather, the engineer will make an adjustment (excluding profit) and modify the contract in writing accordingly. The engineer will notify the contractor of his/her determination whether or not an adjustment of the contract is warranted.

No contract adjustment will be allowed unless the contractor has submitted the request for adjustment within the time prescribed. No contract adjustment will be allowed under this clause to the extent that performance would have been suspended or delayed by any other cause, or for which an adjustment is provided for or excluded under any other term or condition of this contract.

Significant changes in the character of work: The engineer reserves the right to make, in writing, at any time during the work, such changes in quantities and such alterations in the work as are necessary to satisfactorily complete the project. Such changes in quantities and alterations shall not invalidate the contract nor release the surety, and the contractor agrees to perform the work as altered.

If the alterations or changes in quantities significantly change the character of the work under the contract, whether or not changed by any such different quantities or alterations, an adjustment, excluding loss of anticipated profits, will be made to the contract. The basis for the adjustment shall be agreed upon prior to the performance of the work.

If a basis cannot be agreed upon, then an adjustment will be made either for or against the contractor in such amount as the engineer may determine to be fair and equitable.

The term "significant change" shall be construed to apply only to the following circumstances:

- (A) When the character of the work as altered differs materially in kind or nature from that involved or included in the original proposed construction, or
- (B) When a major item of work, as defined elsewhere in the contract, is increased in excess of 125 percent or decreased below 75 percent of the original contract quantity. Any allowance for an increase in quantity shall apply only to that portion in excess of 125 percent of original contract item quantity, or in case of a decrease below 75 percent, to the actual amount of work performed.

RIGHT TO AUDIT

The Department shall have the right to audit the books and records of the contractor or any subcontractor under this contract or subcontract to the extent that the books and records relate to the performance of the contract or subcontract. The books and records shall be maintained by the contractor for a period of 3 years from the date of final payment under the prime contract and by the subcontractor for a period of 3 years from the date of final payment under the subcontract (29 Del.C. §6930)

PREVAILING WAGES

Included in this proposal are the minimum wages to be paid various classes of laborers and mechanics as determined by the Department of Labor of the State of Delaware in accordance with Title 29 Del.C. §6960, relating to wages and the regulations implementing that Section.

REQUIREMENT BY DELAWARE DEPARTMENT OF LABOR FOR SWORN PAYROLL INFORMATION

Title 29 Del.C. §6960 stipulates;

(b) Every contract based upon these specifications shall contain a stipulation that the employer shall pay all mechanics and laborers employed directly upon the site of the work, unconditionally and not less often than once a week and without subsequent deduction or rebate on any account, the full amounts accrued at time of payment, computed at wage rates not less than those stated in the specifications, regardless of any contractual relationship which may be alleged to exist between the employer and such laborers and mechanics. The specifications shall further stipulate that the scale of wages to be paid shall be posted by the employer in a prominent and easily accessible place at the site of the work, and that there may be withheld from the employer so much of accrued payments as may be considered necessary by the Department of Labor to pay to laborers and mechanics employed by the employer the difference between the rates of wages required by the contract to be paid laborers and mechanics on the work and rates of wages received by such laborers and mechanics to be remitted to the Department of Labor for distribution upon resolution of any claims.

(c) Every contract based upon these specifications shall contain a stipulation that sworn payroll information, as required by the [Delaware] Department of Labor, be furnished weekly. The Department of Labor shall keep and maintain the sworn payroll information for a period of 6 months from the last day of the work week covered by the payroll.

Bidders are specifically directed to note the Department of Labor's prevailing wage regulations implementing §6960 relating to the effective date of the wage rates, at Part VI., Section C., which in relevant part states:

"Public agencies (covered by the provisions of 29 Del.C. §6960) are required to use the rates which are in effect on the date of the publication of specifications for a given project. In the event that a contract is not executed within one hundred twenty (120) days from the date the specifications were published, the rates in effect at the time of the execution of the contract shall be the applicable rates for the project."

Contractors with questions may contact:

Department of Labor, Division of Industrial Affairs,
4425 N. Market Street, Wilmington, DE 19802
Telephone (302) 761-8200
<https://dia.delawareworks.com/labor-law/>

STATE OF DELAWARE
DEPARTMENT OF LABOR
DIVISION OF INDUSTRIAL AFFAIRS
OFFICE OF LABOR LAW ENFORCEMENT
PHONE: (302) 318-2769

Mailing Address:
252 Chapman Road
Suite 210
Newark, DE 19702

Located at:
252 Chapman Road
Suite 210
Newark, DE 19702

PREVAILING WAGES FOR HIGHWAY CONSTRUCTION EFFECTIVE MARCH 13, 2026

CLASSIFICATION	NEW CASTLE	KENT	SUSSEX
BRICKLAYERS	68.29	68.29	73.01
CARPENTERS	69.62	64.06	52.30
CEMENT FINISHERS	74.68	45.80	46.69
ELECTRICAL LINE WORKERS	37.71	60.93	29.82
ELECTRICIANS	86.87	86.87	86.87
IRON WORKERS	91.78	33.47	35.55
LABORERS	58.11	53.49	52.49
MILLWRIGHTS	22.60	21.94	18.96
PAINTERS	84.99	84.99	84.99
PILEDRIERS	100.98	33.34	93.69
POWER EQUIPMENT OPERATORS	87.03	55.57	50.91
SHEET METAL WORKERS	31.93	28.51	25.80
TRUCK DRIVERS	54.70	39.63	48.26

CERTIFIED: 4/17/2026

BY:

For Fran Chudzik
ADMINISTRATOR, OFFICE OF LABOR LAW ENFORCEMENT

NOTE: THESE RATES ARE PROMULGATED AND ENFORCED PURSUANT TO THE PREVAILING WAGE REGULATIONS ADOPTED BY THE DEPARTMENT OF LABOR ON APRIL 3, 1992.

CLASSIFICATIONS OF WORKERS ARE DETERMINED BY THE DEPARTMENT OF LABOR. FOR ASSISTANCE IN CLASSIFYING WORKERS, OR FOR A COPY OF THE REGULATIONS OR CLASSIFICATIONS, PHONE (302) 318-2769.

NON-REGISTERED APPRENTICES MUST BE PAID THE MECHANIC'S RATE.

PROJECT: T202611302 US 301 MEDIAN BARRIER SR 896 TO MD LINE NEW CASTLE COUNTY, New Castle County



Contract T202611302
US 301 Median Barrier, SR 896 to MD line

SPECIAL PROVISIONS

S.P. Code	SPECIAL PROVISION DESCRIPTION
401502-25	ASPHALT CEMENT COST ADJUSTMENT
401575-25	PERVIOUS ASPHALT PAVEMENT – 19.0 MM TYPE B
763501-25	CONSTRUCTION ENGINEERING
763520-25	ELECTRONIC TICKETING
806500-25	TRAFFIC OFFICERS

401502 - ASPHALT CEMENT COST ADJUSTMENT

For Sections 304, 401, 402, 403, 404, and 405, payments to the Contractor shall be adjusted to reflect increases or decreases in the Delaware Posted Asphalt Cement Price when compared to the Project Asphalt Cement Base Price, as defined in these Special Provisions.

The Delaware Posted Asphalt Cement Price will be issued monthly by the Department and will be the industry posted price for Asphalt Cement, F.O.B. Philadelphia, Pennsylvania. The link for the posting is https://deldot.gov/Business/bids/index.shtml?dc=asphalt_cement_english.

The Project Asphalt Cement Base Price will be the Delaware Posted Asphalt Cement Price in effect on the date of advertisement.

All deviations of the Delaware Posted Asphalt Cement Price from the Project Asphalt Cement Base Price are eligible for cost adjustment. No minimum increases or decreases or corresponding percentages are required to qualify for cost adjustment.

Actual quantity of asphalt cement qualifying for any Asphalt Cement Cost Adjustment will be computed using the weight of eligible asphalt that is shown on the QA/QC pay sheets as a percentage for the delivered material.

If the mix was not inspected and no QA/QC pay sheet was generated, then the asphalt percentage will be obtained from the job mix formula for that mix ID. The asphalt percentage eligible for cost adjustment shall only be the virgin asphalt cement added to the mix.

There shall be no separate payment per ton cost of asphalt cement. That cost shall be included in the various unit prices bid per ton for those bid items that contain asphalt cement (mentioned above).

The Asphalt cement cost adjustment will be calculated on grade PG 64-22 asphalt regardless of the actual grade of asphalt used.

If the Contractor exceeds the authorized allotted completion time, the price of asphalt cement on the last authorized allotted workday, shall be the prices used for cost adjustment during the time

liquidated damages are assessed. However, if the industry posted price for asphalt cement goes down, the asphalt-cement cost shall be adjusted downward accordingly.

NOTE:

Application of Asphalt Cement Cost Adjustment requirements as indicated above shall apply only to those contracts involving items related to bituminous base and pavements, and with bitumen, having a total of 1,000 tons or more of hot-mix bid quantity in case of Sections 401, 402 and 403; and 15,000 gallons or more in case of Sections 304, 404 and 405.

12/14/2020

401575 - PERVIOUS ASPHALT PAVEMENT – 19.0 MM TYPE B

401576 - PERVIOUS ASPHALT PAVEMENT – 9.5 MM TYPE C

401578 – PERVIOUS ASPHALT PAVEMENT – 12.5 MM TYPE C

Description:

This specification is intended to be used for pervious asphalt pavement. Lift thicknesses will be as shown on the plans.

All portions of Division 400 of the Standard Specifications shall be applicable except as modified herein.

Materials:

- A. Asphalt cement shall be PG 76-22 per AASHTO MP-1.
- B. Coarse aggregate shall consist of clean, tough, durable fragments of crushed stone, or crushed gravel of uniform quality throughout. In the mixture, at least 75 percent, by mass (weight), of the material coarser than the 4.75 mm (No. 4) sieve shall have at least two fractured faces, and 90 percent shall have one or more fractured faces (ASTM D5821). Coarse aggregate shall be free from clay balls, organic matter, deleterious substances, and not more than 8.0% of flat or elongated pieces as specified in ASTM D4791 with a value of 5:1.
- C. Fine aggregate shall consist of clean, sound, durable, angular shaped particles produced by crushing stone or gravel that meets the requirements for wear and soundness specified for coarse aggregate. The aggregate particles shall be free from coatings of clay, silt, or other objectionable matter and shall contain no clay balls. The fine aggregate, including any blended material for the fine aggregate, shall have a plasticity index of not more than 6 and a liquid limit of not more than 25 when tested in accordance with ASTM D 4318.
- D. Mix Design.
 - 1. Pervious asphalt pavement mix shall have a binder content of 5.75% to 6.50 % by weight of dry aggregate. In accordance with ASTM D6390, drain down of the asphalt binder shall be no greater than 0.3%. If more absorptive aggregates, such as limestone, are used in the mix, then the amount of binder shall be based on the testing procedures outlined in the National Asphalt Pavement Association's Information Series 131 – "Pervious Asphalt Pavements for Stormwater Management" (2008).
 - 2. Submit a mix design at least 10 working days prior to the beginning of production. Make available samples of coarse aggregate, fine aggregate, mineral filler, fibers and a sample of the Performance Graded Asphalt Binder (PGAB) that will be used in the design of the mixture. A certificate of analysis (COA) of the PGAB shall be submitted with the mix design. The COA shall be certified by a laboratory meeting the requirements of AASHTO R18. The Laboratory will be certified by the Delaware DOT or qualified under ASTM D3666. HMA Plant/Field Technicians shall be certified by the Mid- Atlantic Region Technician Certification Program (MARTCP) and the Delaware Technician Certification Program.
 - 3. Bulk specific gravity (SG) used in air void content calculations shall not be determined and results will not be accepted using AASHTO T166 (saturated surface dry), since it is not intended for open graded specimens (>10% AV). Bulk SG shall be calculated using AASHTO T275 (paraffin wax) or ASTM D6752 (automatic vacuum sealing). Air void

content shall be calculated from the bulk SG and maximum theoretical SG (AASHTO T209) using ASTM D3203.

4. The materials shall be combined and graded to meet the composition limits by mass (weight) as shown in Table 1 below.

Table 1. Pervious Asphalt Pavement Mix Design Criteria

Sieve Size	NMAS (% Passing)		
	19.0 mm	12.5 mm	9.5 mm
19 mm	90 - 100	100	100
12.5 mm	90 max	90-100	100
9.5 mm		90 max	90 - 100
4.75 mm			90 max
2.36 mm	5 – 15	5-15	5 - 15
0.075 mm	2 – 4	2-4	2 - 4

Property	Specification
Asphalt binder content	5.75 - 6.50%
Fiber Content by Total Mixture Mass	0.3% cellulose or 0.4% mineral
Air Void Content (ASTM D6752/AASHTO T275)	16.0 - 22.0%
Drain down (ASTM D6390)*	<0.3%
Tensile Strength Ratio (AASHTO 283)**	>80%
Cantabro abrasion test on unaged samples (ASTM D7064-04)	<20%
Cantabro abrasion test on 7 day aged samples	<30%

* Cellulose or mineral fibers may be used to reduce drain down.

** If the TSR (retained tensile strength) values fall below 80% when tested per NAPA IS131 (with a single freeze thaw cycle rather than 5), then employ an antistrip additive to raise the TSR value above 80%.

E. Mix Production.

1. The pervious asphalt mix production shall be per Section 1014 and plant manufacturer's recommendations.

Construction Methods:

- A. The construction methods shall be per Section 401 except as modified herein.
- B. Minimum surface temperature of 60° F at time of placement and minimum ambient temperature of 50° F.
- C. The pervious asphalt pavement mix shall be placed either in a single lift not to exceed 4 inches thick or in two lifts. If more than one lift is used, sufficient care shall be taken to insure that the pervious asphalt layers join completely by keeping the time between layer placements minimal, keeping the first layer clear from dust and moisture, and minimizing traffic on the first layer.
- D. No traffic shall be permitted on material placed until the material has been thoroughly compacted and has been permitted to cool to below 100 °F.

- E. Make two passes with a standard asphalt pavement roller (5 ton minimum) operated in static mode. Do not over compact the material in order that permeability can be maintained.
- F. Any mixture that becomes loose and broken, mixed with dirt, or is in any way defective shall be removed and replaced with fresh mix. The mix shall be compacted to conform to the surrounding area.
- G. Installed pervious pavement shall not be used for equipment or materials storage during construction, and under no circumstances shall equipment be allowed to deposit soil on paved pervious surfaces.
- H. The full permeability of the pavement surface shall be tested by application of clean water at the rate of at least 5 gpm over the surface, using a hose or other distribution devise. Water used for the test shall be clean, free of suspended solids and deleterious liquids. The test shall be observed by the engineer.

Method of Measurement:

The Department will measure pervious asphalt pavement in accordance with Section 401.4.

Basis of Payment:

The Department will pay for pervious asphalt pavement in accordance with Section 401.5.

09/08/2023

763501 - CONSTRUCTION ENGINEERING
763597 – UTILITY CONSTRUCTION ENGINEERING

DESCRIPTION:

- A. This work consists of construction lay out. Subsection 105.10 Construction Stakes, Lines and Grades will be replaced by this spec.
- B. The Department will only establish the following:
 - 1. Original and final cross-sections for borrow pits.
 - 2. Final cross-sections:
 - a. Top and bottom pay limit elevations for all excavation bid items that are not field measured by construction inspection personnel.
 - b. The contractor shall notify the engineer when these pay limit elevations are ready and allow for a minimum of two calendar days for the engineer to obtain the information.
 - 3. Line and grade for extra work added on to the Plans.
- C. When applicable, this work will also consist of providing construction and right-of-way/easement information to utility companies performing work (as defined in the Utility Statement) within the LOC.

MATERIALS:

Not applicable.

CONSTRUCTION METHODS:

- A. Equipment
 - 1. Use and provide written certification that the equipment/instrument has been calibrated and is within manufacturer's tolerance. The certification shall be dated a maximum of 9-months before the start of construction. Renew the certification a minimum of every 9-months. The equipment/instrument shall have a minimum measuring accuracy of [3mm+2ppmxD] and an angle accuracy of up to 2.0-arc-seconds or 0.6-milligons.
 - 2. If the use of GPS technology in construction stakeout is chosen, provide the engineer with a GPS rover and automatic level for the duration of the contract. The GPS rover must be in good working condition and of similar make and model. Provide formal training on the GPS system being used to a maximum of 4, of the engineer's appointees. The formal training must be up to 8-hours or to the satisfaction of the engineer. At the end of the contract, the engineer will return the GPS rover. If any of the equipment/instruments are found to be out of adjustment or inadequate to perform its function, they shall be immediately replaced to the satisfaction of the engineer.

3. Choosing to use GPS technology does not give the authority to use machine control. Construction Engineering (GPS) Machine Control Grading shall only be used if noted in the contract outlining the available files that will be provided and "the Release for delivery of documents in electronic form to a contractor" are signed by all parties prior to delivery of any electronic files. Only files designated in the contract shall be provided. If machine control grading is allowed on the project, see the machine control section of this specification. GPS technology and machine control technology shall not be used in the construction of bridges.

B. Engineering/Survey Staff

1. Provide and have available an adequate engineering staff that is competent and experienced to set lines, grades, and compatibility with the scope of the project. Additionally, employ an engineer or surveyor, licensed in the State of Delaware, to be responsible for the quality and accuracy of the work done by the engineering staff. When individuals or firms other than the contractor perform any professional services under this item, that work shall not be subject to the subcontracting requirements of Section 108.1. Assume full responsibility for any errors and/or omissions in the work of the engineering staff.

C. Performance Requirements

1. Construction Engineering shall include establishing:
 - a. the survey points and survey centerlines;
 - b. finding, referencing, offsetting the project control points;
 - c. running a horizontal and vertical circuit to verify the precision of given control points.
2. Establishing plan coordinates and elevation marks for:
 - a. culverts,
 - b. slopes,
 - c. subbase,
 - d. subsurface drains,
 - e. paving,
 - f. subgrade,
 - g. retaining walls,
 - h. any other stakes required for control lines and grades.
3. Setting vertical control elevations for:
 - a. footings,
 - b. caps,
 - c. bridge seats and deck screed.

4. Preserve the Department's project control points and benchmarks. Establish and preserve any temporary control points (traverse points or benchmarks) needed for construction. Any project control points (traverse points) or benchmarks conflicting with construction of the project shall be relocated. Replace any or all stakes that are destroyed at any time during the life of the contract as directed by the engineer. Re-establish centerline points and stationing prior to final cross-sections by the engineer. The vertical control error of closure shall not exceed 0.035-feet. The horizontal control precision ratio shall have a minimum precision of 1:20,000 feet of distance traversed prior to adjustment.
5. Perform construction centerline layout of all roadways, ramps, connections, and driveways from project control points set by the engineer. Use the profiles and typical sections provided in the plans shall calculate proposed grades at the edge of pavement or verify information shown on the Plans.
6. Advise the engineer of any horizontal or vertical alignment revisions needed to establish smooth transitions to existing facilities. Immediately bring to the attention of the engineer any potential drainage problem within the project limits. The engineer must approve any proposed variation in profile, width, or cross slope.
7. Establish the working points at centerlines of bearings on bridge abutments and on piers, mark the location of anchor bolts to be installed, check the elevation of bearing surfaces before and after they are ground, and set anchor bolts at their exact elevation and alignment in accordance with the contract. Before completion of the fabrication of beams for bridge superstructures, verify the locations, both vertically and horizontally, of all bearings and assume full responsibility for fabricated beams fitting and bearing as constructed. After beam erection and concurrently with the Department project surveyors or their designated representative, survey top of beam elevations at a maximum of 10-foot stations and compute screed grades. Submit the beam elevations to the engineer for review and approval before the stay-in-place forms are set. Construction stakes and other reference control marks shall be set at intervals as established by the engineer to assure that all components of the structure are constructed in accordance with the lines and grades shown on the plans. Take full responsibility for all structure alignment control, grade control and all necessary calculations to establish and set these controls.
8. Investigate proposed construction for possible conflicts with existing and proposed utilities. Report any conflicts to the engineer for resolution.

9. Stake all sidewalk and curb ramp grades in accordance with the contract. Review the stakeout with the engineer prior to construction. The engineer must approve any deviation from the Contract in writing.
10. Stake all drainage inlets in accordance with the Contract. The offsets and top of grate elevations need to be calculated for each type of drainage inlet specified in the contract in order to line up the drainage inlet's flow line with the specified curb or ditch flow line as shown in the contract. The engineer must approve any deviations from the Contract in writing.
11. If wetland areas are involved and specifically defined on the plans the following shall apply:
 - a. Do not enter, damage, or destroy wetland areas, which exist beyond the LOC. These provisions will be strictly enforced, and all personnel shall understand the importance of these provisions.
 - b. Delineate wetlands at the LOC throughout the entire project, before any clearing operations commence as shown on the plans to the satisfaction of the engineer.
 - c. Use orange vinyl flagging material with "Wetland Boundary" printed on the flagging. In wooded areas, tie the flagging on the trees, at approximate 20-foot intervals through wetland areas. In open field and yard areas that have been identified as wetlands, drive 6-foot posts into the ground at approximate 50-foot intervals and tie with the flagging. The flagging shall extend approximately 12-inches in length beyond the post. Use oak posts with cross sectional dimensions of 1 1/2-inches to 2-inches by 1 1/2-inches to 2-inches or 1/4-inch rebar.
 - d. If the flagging has been destroyed and the engineer determines that its use is still required, reflag the area. Flagging shall be replaced within 48-hours of notification that replacement is needed. After 48-hours the engineer may proceed to have the area reflagged.
 - e. Remove all posts and flagging at Project acceptance.
 - f. Assume any responsibility for any damages to wetlands located beyond the LOC, which occurs from his/her operations during the life of the contract. Restore all temporarily disturbed wetland areas to their preconstruction conditions.
12. Whenever the engineer will be recording data for establishment of pay limits, the Contractor will be invited to obtain the data jointly with the engineer's survey crew(s) in order to agree with the information. If the Contractor's representative is not able to obtain the same data, then the information obtained by the engineer shall be considered the information to be used in computing the quantities in question.

D. Submittals

1. All computations, survey notes, electronic files, and other records necessary to accomplish the work shall be preserved and made available to the Department in a neat and organized manner at any time as directed by the engineer. The engineer may check all or any portion of the stakeout survey work or notes and any necessary correction to the work shall be made as soon as possible. Provide the engineer with such assistance as may be required for checking all lines, grades, and measurements necessary for the execution of the work. Checking by the engineer shall not relieve responsibility for the accuracy or completeness of the work. Copies of all notes must be provided to the engineer at the completion of the Project.
2. Submit any of the following at the engineer's request:
 - a. Proposed method of recording information in field books to ensure clarity and adequacy.
 - b. A printout of horizontal control verification, as well as coordinates, differences, and error of closure for all reestablished or temporary control points.
 - c. A printout of vertical control verification, with benchmark location elevation and differences from plan elevation.
 - d. Sketch of location of newly referenced horizontal control, with text printout of coordinates, method of reference and field notes associated with referencing control - traverse closure report.
 - e. Description of newly established benchmarks with location, elevation, and closed loop survey field notes - bench closure report
 - f. All updated electronic and manuscript survey records.
 - g. Stakeout plan for each structure and culvert.
 - h. Computations for buildups over beams, screed grades, and overhang form elevations.
 - i. A report showing differences between supplied baseline coordinates and field obtained coordinates, including a list of preliminary input data.
 - j. Any proposed plan alteration to rectify a construction stakeout error, including design calculations, narrative and sealed drawings.
 - k. Baseline for each borrows pit location.
 - l. Detailed sketch of proposed overhead ground mounted signs or signals showing obstructions that may interfere with their installation.
 - m. Copies of cut sheets.

E. Machine Control Grading

1. Machine control grading to be used on the project if authorized by the engineer.
2. Use of this procedure and equipment is intended for grading the subgrade surface; it is not intended for the use in constructing final surface grades.
3. Materials:
 - a. Provide all equipment required to perform GPS machine control grading, including equipment needed by to verify the work to the engineer.
 - b. Use manufacturer's GPS machine control equipment and system to achieve the grading requirements in accordance with the Contract.
4. Construction
 - a. Convert the electronic data provided by the Department into the format required for the equipment.
 - b. The Department will provide no additional electronic data.
 - c. Perform at least one 500-foot test section with the selected GPS system to demonstrate the capabilities, knowledge, equipment, and experience to properly operate the system and meet acceptable tolerances. The engineer will evaluate and make the determination as to whether additional 500-foot test sections are required. Failure to demonstrate this ability to the satisfaction of the engineer, construct the project using conventional surveying and staking methods.
 - d. DelDOT Responsibilities:
 - i. The Department will set initial vertical and horizontal control points in the field for the project as indicated in the contract.
 - ii. The Department will provide the project specific localized coordinate system.
 - iii. The Department may provide data in an electronic format as indicated in the general notes.
 - (1.) The information provided shall not be considered a representation of actual conditions to be encountered during construction. Providing this information does not relieve the responsibility of making an investigation of conditions to be encountered. This includes site visits and basing the bid on information obtained from these investigations, and the professional interpretations and judgments of the Contractor.
 - (2.) The Department will develop and provide electronic data for use as part of the Contract in the format as indicated in the Plans.
 - iv. The Department will provide the following electronic files:

- (1.) ASCII data files with coordinates and elevations for proposed points as selected by the engineer.
- (2.) Existing digital terrain model in .dtm file format compatible with software currently used by the Department.
- (3.) Proposed digital terrain model in .dtm file format compatible with software currently used by the Department.
- (4.) Design file in .dgn file format, that contains 3D features lines for the proposed design, 3D feature lines are for the proposed top surface elevation only.
- v. The engineer will perform spot checks of the machine control grading results, surveying calculations, records, field procedures, and actual staking. If the work is not being performed in a manner that will assure accurate results, the engineer may order the work to be redone to the requirements of the contract. The engineer may also require the use of conventional surveying and staking.
- e. Contractor's responsibilities:
 - i. No less than 2-weeks before the scheduled preconstruction meeting, submit to the engineer for review a written machine control grading work plan which shall include the equipment type, control software manufacturer and version, and proposed location of the local GPS base station used for broadcasting differential correction data to rover units.
 - ii. If the need to establish new control points, traverse from existing control points and verify to be accurate by conventional surveying techniques.
 - iii. Assume all risks and liabilities of any assumptions or manipulations marked from the electronic information provided or if chosen to develop a separate digital terrain model.
 - iv. Ensure that the electronic data provided will function in their machine control grading system.
 - v. Provide the engineer with a GPS rover and Automatic Level, for use during the duration of the contract. At the end of the contract, the GPS rover and Automatic Level will be returned. Provide a total of 8-hours of formal training on the GPS machine control system to the engineer and up to 3 additional Department appointees per rover.
 - vi. Review and apply the data provided by the Department to perform GPS machine control grading.
 - vii. Convert the electronic data provided by the Department into a format compatible with their system.

- viii. At the beginning of each workday check and if necessary, recalibrate the GPS machine control system in accordance with the manufacturer's recommendations, or more frequently as needed to meet the requirements of the project.
- ix. Meet the accuracy requirements as detailed per the Department's standards.
- x. Establish secondary control points at appropriate intervals and at locations along the length of the project. These points shall be outside the project limits and/or where work is performed. These points shall not to exceed 1000-foot intervals. The horizontal position of these points shall be determined by conventional survey traverse and adjustments from the original baseline control points. The conventional traverse shall meet or exceed the Department's Standards. The elevation of these control points shall be established using differential leveling from the project benchmarks, forming a closed loop. A copy of all new control point information including closure report shall be provided and approved by the engineer prior to construction activities. Assume responsibility for all errors resulting from these efforts and correct deficiencies to the satisfaction of the engineer.
- xi. Provide stakes at all alignment control points, at every 500-foot stationing, and where required for coordination activities involving environmental agencies and utility companies.
- xii. Set hubs, at a minimum of 500-foot intervals, at the top of finished grade at all hinge points on the cross section on the main line and at least 4 cross sections on side roads and ramps as directed by the engineer or as shown on the plans. Placement of a minimum of 4 control points outside the limits of disturbance for the excavation of borrow pits, Stormwater Management Ponds, and wetland mitigation sites. These control points shall be established using conventional survey methods for use by the engineer to check the accuracy of the construction.
- xiii. Preserve all reference points and monuments that are identified and established by the engineer for the Project.
- xiv. Provide control points and conventional grades stakes at critical points such as, PC's, PT's, superelevation points, and other critical points required for the construction of drainage and roadway structures.
- xv. Follow the guidelines set forth in the "Geometric Geodetic Accuracy Standards and Specifications for Using GPS Relative Positioning Techniques" and follow a minimum of Second Order Class 1, (2-I) classification standards.

xvi. Automated equipment operations have a high reliance on accurate control networks from which to take measurements, establish positions, and verify locations and features. Therefore, a strong contract control network in the field which is the same or is strongly integrated with the project control used during the design of the contract is essential to the successful use of this technology with the proposed Digital Terrain Model (DTM). Consistent and well designed site calibration for all machine control operations are required to ensure the quality of the contract deliverables. The Contract Control Plan is intended to document which horizontal and vertical control will be held for these operations. Continued incorporation of the Base Station(s) as identified in the Contract Control Plan is essential to maintaining the integrity of positional locations and elevations of features. The Contract Control Plan shall be submitted to the Department for review and approval by the Departments Survey Section 3 weeks prior to the start of any machine control work. Operate and maintain all elements of the Machine Grade Control continuously once the operations begin until otherwise approved by the engineer.

5. Contract Control Plan:

- a. Develop and submit a Contract Control Plan for use of Machine Control Grading. Contract control includes all primary and secondary horizontal and vertical control which will be used for the construction contract. Upon the completion of the initial survey reconnaissance and control verification, but prior to beginning primary field operations, submit a Contract Control Plan document. The Contract Control plan shall be signed and sealed by a Delaware licensed Land Surveyor or Delaware Professional Engineer who oversees its preparation for acceptance by the engineer. The plan shall include the following:
 - i. A control network diagram of all existing horizontal and vertical control recovered in the field as contract control.
 - ii. Include a summary of the calculated closures of the existing control network, and which control has been determined to have been disturbed or out of tolerance from its original positioning.
 - iii. An explanation of which horizontal and vertical control points will be held for construction purposes. If necessary, include all adjustments which may have been made to achieve required closures.
 - iv. An explanation of what horizontal and vertical control (including base stations) was set to accomplish the required stakeout or automated machine operation. Include how the position of these new control points was determined.

- v. Describe the proposed method and technique (technology and quality control) for utilizing the control to establish the existing and/or proposed feature location and to verify the completed feature location and/or measured quantity.
- vi. A listing of the horizontal and vertical datums to be used and the combined factor to be used to account for ellipsoidal reduction factor and grid scale factor.
- vii. If chosen to use machine control as a method of measuring and controlling excavation, fill, material placement or grading operations as a method of measuring and controlling excavation, fill, material placement or grading operations, the Control Plan shall include the method by which the automated machine guidance system will initially be site calibrated to both the horizontal and vertical contract control, and shall describe the method and frequency of the calibration to ensure consistent positional results.

F. Utility construction methods:

- 1. The engineer must approve all requests for Utility Construction Engineering before the work begins.
- 2. Instruct utility companies to submit their requests to the engineer. The engineer will decide if the requested work meets the criteria for Utility Construction Engineering or is normal Construction Engineering and pass the requests along with the decision.
- 3. The survey crew size shall be adequate to efficiently perform the work required and must be approved by the engineer.
- 4. Work covered under Utility Construction Engineering will fall into two categories:
 - a. Engineering/surveying work that is not necessary for construction of the Project, staking the clear zone line, providing cut/fill grades at proposed utility pole locations, staking back of drainage structures, and staking right-of-way lines where construction of the Project (exclusive of utilities) is within the right-of-way.
 - b. Engineering/surveying work that is necessary for construction but must be provided for utility companies well in advance of the need and will likely need to be redone later, as determined by the engineer. This can be any of the Construction Engineering work that when done early cannot be expected to remain undisturbed until needed for construction of the Project (non-utility).

METHOD OF MEASUREMENT:

- A. The Department will not measure construction engineering.
- B. The Department will measure the quantity of utility construction engineering as the number of hours the survey crew is in the field actively engaged in utility construction engineering work.

BASIS OF PAYMENT:

- A. The Department will pay the lump sum unit bid price for this work. Price and payment constitute full compensation for:
 - 1. the work associated with construction engineering;
 - 2. providing all equipment and instruments;
 - 3. providing and placing stakes;
 - 4. flagging and any reflagging;
 - 5. reconstruction of work;
 - 6. all costs related to the development of separate digital terrain model;
 - 7. reestablishing reference points; and
 - 8. wetland restoration.
- B. The Department will pay for utility construction engineering at the contract unit price per hour actively engaged in performing the work. Price and payment will constitute full compensation for:
 - 1. Office work;
 - 2. providing all labor;
 - 3. equipment;
 - 4. instruments;
 - 5. stakes; and
 - 6. other materials necessary to complete the Work.
- C. The Department will make monthly payment in proportion to the amount of work done as determined by the engineer.
- D. The Department will not make any adjustment in payment for any issues with equipment to operate the GPS machine control system for any construction items or be justification for granting contract time extension.
- E. The Department will not make any consideration for any extension of Contract Time or additional compensation due to delays, corrective work, or additional work that may result from faulty and erroneous construction stakeout, surveying, and engineering required.
- F. The Department will not make any adjustments for all liability, costs, or delays if the Contractor chooses to develop a separate digital terrain model.

2/9/23

763520 - ELECTRONIC TICKETING**Description:**

This work consists of providing electronic data for material weight tickets delivered to the project. This work also consists of placing an identifying vehicle number on the driver side and the passenger or rear sides of the delivery vehicle. This does not preclude or dismiss any requirement for paper tickets required by the Standard Specifications or other rules and regulations.

General Requirements:

- A. Send electronic tickets (eTicket) to the Department's Electronic Ticketing Portal <https://tickets.delldot.gov> as they are generated. The Department will reject any load that does not have a corresponding eTicket unless the cause is beyond the contractor's control. In such circumstances paper tickets may be permitted at the discretion of the engineer.
- B. Payment for material weight delivered to the project will be based upon the eTickets marked "*Delivered*", less waste, excess material weight as noted in 105.12 of the Standard Specifications, and any audit corrections.
- C. Do not reissue or reprint tickets that have been marked "*Delivered*" or "*Rejected*" without first notifying the engineer. The engineer may reject a reissued or reprinted ticket at their discretion. When a reissued or reprinted ticket is rejected, payment will be based upon the original ticket.

Data Integration:

Request a list of the Department's naming nomenclature. Include in the request an identification of what system the supplier utilizes for its load read-out weighing system. If necessary, create an Application Programming Interface (API) to integrate with the Department's eTicketing Portal. Utilize the API to provide electronic data from the load read-out weighing system at the material source that is readable by the Department's eTicketing Portal. Update the load read-out weighing system and API as necessary to maintain connection the Department's eTicketing Portal.

The data shall be provided as follows:

Reference Field No.	Description	Examples	Data Type	Required
1	Ticket Number	5126349, 101R, 539-19	String	Yes
2	Contract Number	T202011001	String	Yes

3	Contract Name (Job)	Walnut Street Streetscape Improvements	String	Yes
4	Contractor Name (Customer)	Mumford & Miller, Inc.; A Del Construction	String	Yes
5	Supplier Name	River Asphalt; Allan Myers Materials	String	Yes
6	Supplier Plant	Plant #1 Dagsboro; Dover Asphalt	String	Yes
7	Job Number (Location)	Task 1; Location 5	String	Yes
8	Weigh Master Name	Johnny Scales	String	Yes
9	Weigh Master ID	1234567	String	Yes
10	Left Intentionally Blank			No
11	Mix Design ID (Product)	1628p; AM-WILM-29 76-22	String	Yes
12	Material Type (Product Description)	9.5mm top; 19MM 76-22 NON CARB	String	Yes
13	Item No. (Product Code)	401005; 401016	String	Yes
14	Load Number	75	Number	Yes
15	Identifying Vehicle Number	T-1	String	Yes
16	Hauler	John Doe Trucking	String	Yes
17	Legal Gross Vehicle Weight	73,280	Number	Yes
18	Loading Date & Time	2020-06-15T13:45:30	String	Yes
19	Gross Weight	72,980	Number	Yes
20	Net Weight	27,900	Number	Yes
21	Truck Tare Weight	45,080	Number	Yes
22	Void	280	Number	No
23	Daily Running Total	44.43	Number	Yes

All provided weights shall be accurate to 0.01 tons.

Loads which do not have the required data shall be rejected.

Setup and Calibration:

Conduct a test of each supplier's integration with the Department's eTicketing Portal prior to shipping material. Complete test at least 14 days prior to shipping material unless otherwise approved by the engineer. The test must involve at least four calibration eTickets from each supplier approved for use on the project. The calibration eTickets must accurately reflect the categories 1-7 shown above; all other categories shall be marked "TEST". After the engineer confirms the calibration eTickets have been entered into the Department's eTicket Portal, void the eTickets with the reason "Calibration Testing".

Uptime:

Uptime reliability of the material supplier's ticketing system must be 99.5% over any 30-day rolling period. Uptime is defined as the ability for the Department to receive electronic tickets within a maximum of 10 minutes from when the ticket was created.

Load Identification:

Ensure the identifying vehicle numbers on the delivery vehicle correspond to the ticket. Place the numbers on the delivery vehicles such that at least one can be safely read from within the work area. Delivery vehicles without identifying vehicle numbers shall be rejected.

Method of Measurement:

The Department will not measure electronic ticketing.

Basis of Payment:

- A. The cost associated with creating and maintaining an API, providing electronic ticketing data, and placing identifying vehicle numbers on the delivery vehicles is incidental to the item being placed.
- B. The Department will make no payment for material that is rejected.

01/18/2022

806500 – TRAFFIC OFFICERS

Description:

In accordance with Section 806.1.

Materials:

Not applicable.

Construction:

In accordance with Section 806.3.

Method of Measurement:

In accordance with Section 806.4.

Basis of Payment:

- A. The Department will pay for traffic officers at the contract unit price per hour. Price and payment constitute full compensation for providing traffic officers, vehicles, and equipment.
- B. For bidding purposes, the Department has fixed the unit price at \$180.00 per hour. The Department will pay for traffic officers based on a submitted invoice from the police department plus 10 percent.

STATEMENTS

Included on the following pages:

UTILITY STATEMENTS

RIGHT-OF-WAY STATEMENTS

ENVIRONMENTAL STATEMENTS

RAILROAD STATEMENTS



STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION
800 BAY ROAD
P.O. BOX 778
DOVER, DELAWARE 19903

SHANTÉ A. HASTINGS
SECRETARY

UTILITY STATEMENT

January 13, 2026

State Contract No.: T202611302

F.A.P. No.: N/A

Project I.D. No.: 2026-00061

**US 301 Median Barrier, SR 896 to MD Line
New Castle County**

Utility relocations and/or adjustments are not anticipated for the work associated with this project. All existing utility facilities will remain in place and active throughout the duration of the contract. No working/existing utility facilities can be taken out of service. Wherever the proposed construction will cross an existing underground utility facility, the State Contractor shall test hole via non-intrusive methods to verify the horizontal alignment and vertical depth of the existing utility facility. The test holes shall be incidental to the work being performed. All proposed improvements outlined in the contract documents shall be adjusted in the field to avoid any, and all, existing aerial and underground utility facilities, this includes private utility facilities. The contractor must take care when performing all temporary and permanent work to avoid impact on underground and overhead utilities.

Any adjustments and/or relocations of municipally or county owned sewer or water facilities shall be performed by the State's Contractor in accordance with the respective agency's standard specifications as directed by the District Engineer. The State contractor shall coordinate any potential conflicts of municipally or county owned sewer or water facilities with facility owners and provide adequate notice (not less than 30 calendar days) to the municipally or county and to the District Engineer prior to performing work.

The State's contractor shall adjust any at grade features such as valve boxes, manholes, and handholes to match the surface elevation and slope as outlined in the contract documents. The State contractor shall coordinate any potential adjustments with facility owners and provide adequate notice (not less than 30 calendar days) to the said owners and to the District Engineer prior to performing work. Under no circumstances shall any valve box, manhole, handhole, or other at grade structure be paved over, filled, or knocked out of alignment during construction.

Should any utility conflicts be encountered as a result of the State Contractor's means and methods during construction requiring adjustment and/or relocation, the necessary relocation work shall be accomplished by the respective utility company and funded by the State's Contractor as directed

by the District Engineer. Following contract award date, the State's Contractor shall coordinate any and all potential changes including, but not limited to, identification of potential field conflict; changes in project construction scope; changes in construction phasing; or changes in contractor means and methods of construction with required parties, including the District Engineer and Utility Companies, for approval prior to finalizing and performing work. The State's Contractor shall provide utility companies with adequate notice (not less than 30 calendar days) prior to performing work once approved.

Any potential utility conflicts shall be coordinated by the State Contractor once the conflict is recognized if the proposed improvements cannot be adjusted to avoid the proposed conflict. The time to complete any relocations/adjustments found to be necessary during construction of the highway project will depend on the nature of the work.

Once the State's contractor has given the Utility the advance notice required above, it is the responsibility of the State's contractor to have the work area prepared and accessible for the Utility to perform the tasks listed above. If the site conditions are not ready and the state contractor has given notice to the utility on when the work is to be accomplished, the State's Contractor shall be responsible for any extra cost incurred by the utility company and the State Contractor shall also be responsible for any time delays. Between when the required notice is given to the Utility and when the work is performed and completed, the coordination and scheduling of the Utility is the sole responsibility of the State's Contractor. All costs related to the coordination and scheduling of the utilities are incidental to the contract.

General Notes:

1. The Contractor's attention is directed to Section 105.9 of the DelDOT Standard Specifications (see the contract documents for applicable date/version to reference). The Contractor shall contact Delmarva811 (previously known as Miss Utility of Delmarva) at 1-800-282-8555 at least two working days prior to any excavation. The Contractor is responsible for the support and protection of all utilities when excavating. The Contractor is also responsible for ensuring proper clearances, including safety clearances, from overhead utilities for construction equipment. The Contractor is advised to check the site for access purposes for proposed equipment and, if necessary, make arrangements directly with the utility companies for field adjustments for adequate clearances.
2. The information shown in the Contract Documents, including the Utility Statement and the Utility Schedule contained herein, concerning the location, type and size of existing and proposed utilities, their locations, and construction timing has been compiled by the preparer based on information furnished by each of the involved Utility Companies. It shall be the responsibility of the State's Contractor to verify all information and coordinate with the Utility Companies prior to and during construction, as specified in Section 105.9 of the Standard Specifications.
3. It is understood and agreed that the Contractor has considered in his bid all permanent and temporary utility appurtenances in their present and relocated positions as shown on the plans or described in the Utility Statement or are readily discernible and that no additional compensation will be allowed for any delays,

inconvenience, or damage due to any interference from the utility facilities and appurtenances or the operation of moving them, except that the Contractor may be granted an equitable extension of time. The Contractor's means and method of construction are not taken into account when known utility conflicts are identified. If the Contractor's means and method of construction create a utility conflict the Utility Statement will prevail in discussions with the utility and the Contractor.

4. The State's Contractor shall be responsible for any costs associated with any temporary outages; holding, bracing, supporting, and shielding of utility facilities; temporary relocations; or permanent relocations that are not specifically identified in this Utility Statement or shown in the contract plan set. It is important to note that electric companies will not insulate or otherwise rubber up any power lines for any purposes.
5. The State's Contractor is responsible for rough grading as required by the roadway construction prior to the Utility Company's placing their proposed facilities, unless otherwise indicated on the plans and/or outlined elsewhere in the Contract Documents.
6. Coordination and cooperation among the Utility Companies and the State's Contractor are of prime importance. Therefore, the Contractor is directed to contact Utility Company representatives as outlined in the Delmarva811 ticket with any questions regarding this work prior to submitting bids and work schedules. Proposed work schedules should reflect the Utility Companies' proposed relocations. The Utility Companies and their contractors do not work on nights, weekends, or legal holidays.
7. As outlined in Chapter 4 of the DelDOT Utilities Manual, individual utility companies are responsible for obtaining all required permits from municipal, State and federal government agencies and railroads prior to performing their work. This includes but is not limited to water quality permits/DNREC Water Quality Certification, DNREC Subaqueous Lands/Wetlands permits, DNREC Coastal Zone Consistency Certification, County Floodplain permits (New Castle County only), U.S. Coast Guard permits, US Army Corps 404 permits, sediment and erosion permits, and railroad crossing permits.
8. Individual utility companies are required to restore any areas disturbed in conjunction with their relocation work. If an area is disturbed by a utility company and is not properly restored, the Department may have the State's Contractor perform the necessary restoration. Any additional costs incurred as a result will be forwarded to the utility company.
9. 16 Del. C., Chapter 74B, § 7405B requires notification to and mutually agreeable measures from the public utility operating the electric line for the any person intending to carry on any function, activity, work, or operation within dangerous proximity of any high voltage overhead electric lines. 16 Del. C., Chapter 74B, § 7402B defines "dangerous proximity" as "a distance up to and including 10 feet of high-voltage lines, or within such greater distances as may be set forth in the current editions and any subsequent revisions of the regulations of the United States

Occupational Safety and Health Administration (29 C.F.R. § 1902.1 et seq.) and the National Electrical Safety Code.” With that, all contractors/other utilities must maintain a minimum distance of 10 feet from all overhead energized lines unless otherwise required in OSHA or the NESC.

10. Any existing facilities that are comprised of hazardous materials will be removed by the Utility Company unless otherwise outlined in the contract documents or language above. Any existing facilities containing hazardous materials will be purged by the Utility Company unless otherwise outlined in the contract documents or language above.
11. In conjunction with bid preparation and prior to starting work, the State’s Contractor shall confirm with all respective Utility Companies noted in this Utility Statement to have advance utility relocations that the advance relocations have in fact been accomplished as summarized herein.
12. Contractors are not permitted to draw water from any hydrant for any use, without the written permission of the municipality/water company having jurisdiction and proper metering and backflow prevention equipment in place.
13. Under no circumstances shall any valve box, manhole, handhole, or other at grade structure be paved over, filled, or knocked out of alignment during construction.

DIVISION OF TRANSPORTATION SOLUTIONS



Assistant Director of Field Operations
DelDOT EDC
Eric C. Cimo, P.E.
eric.cimo@delaware.gov

3/10/26
Date



STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION
800 BAY ROAD
P.O. BOX 778
DOVER, DELAWARE 19903

SHANTÉ A. HASTINGS
SECRETARY

**RIGHT OF WAY CERTIFICATE
STATE PROJECT NO. T202611302
F.A.P. NO. N/A for R/W**

**US 301 MEDIAN BARRIER, SR 896 TO MD LINE
NEW CASTLE COUNTY**

Certificate of Right-of-Way Status – 100%

Level 1

As required by 23 CFR, Part 635, and other pertinent Federal and State regulations or laws, the following certifications are hereby made in reference to this highway project:

All necessary real property interests have been acquired in accordance with current FHWA/State directives covering the acquisition of real property; and,

All necessary rights-of-way, including control of access rights when pertinent, have been acquired including legal and physical possession; and,

All project rights of way are currently available in accordance with the project right-of-way plans; and,

Any residential displaced individuals or families have been relocated to decent, safe and sanitary housing, or adequate replacement housing has been made available in accordance with the provisions of the current Federal Highway Administration (FHWA) directive(s) covering the administration of the Highway Relocation Assistance Program; and,

All occupants have vacated the lands and improvements; and,

The State has physical possession and the right to remove, salvage, or demolish any improvements acquired as part of this project, and enter on all land.

RIGHT OF WAY SECTION

A handwritten signature in black ink, appearing to read 'Breanna Kovach'.

Breanna Kovach, P.E.
Chief of Right-of-Way

January 14, 2026



STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION
800 BAY ROAD
P.O. BOX 778
DOVER, DELAWARE 19903

SHANTÉ A. HASTINGS
SECRETARY

January 9, 2026

ENVIRONMENTAL REQUIREMENTS
FOR

Contract Title: **US 301 Median Barrier, SR 896 to MD Line**

State Contract No. **T202611302**

Federal Aid No. N/A

Due to the nature of the proposed construction activities, permits are not required for this project. However, the following construction requirements and special provisions have been developed to minimize and mitigate impact to the surrounding environs. These requirements by DelDOT, not specified within the contract, are listed below. These requirements are the responsibility of the contractor and are subject to risk of shut down at the contractor's expense if not followed.

GENERAL REQUIREMENTS:

1. As locations are identified they will be submitted to the Environmental Studies Office to determine if there is any historical significance associated with the location and what if any cultural compliance documentation and/or approvals are needed. Likewise, natural resource evaluations will be undertaken to determine permit requirements, RTE issues, time of year restrictions for bird and/or fisheries resources, etc. No work will take place until all permits and approvals have been acquired. Notes in the contract document will specify that no work could begin until written approval is received from the ESO.
2. All construction debris, excavated material, brush, rocks, and refuse incidental to such work shall be placed either on shore above the influence of flood waters or on some suitable dumping ground.

3. That effort shall be made to keep construction debris from entering adjacent waterways or wetlands. Any debris that enters those areas shall be removed immediately.
4. The disposal of trees, brush, and other debris in any stream corridor, wetland, surface water, or drainage area is prohibited.
5. DelDOT Environmental Studies Section must be notified if there are any changes to the project methods, footprint, materials, or designs, to allow the Department to coordinate with the appropriate resource agencies (COE, DNREC, and SHPO), for approval at DOT_EnvironmentalStudies@delaware.gov.



Maia Lee

Environmental Specialist II

Environmental Stewardship

Delaware Department of Transportation



STATE OF DELAWARE
DEPARTMENT OF TRANSPORTATION
800 BAY ROAD
P.O. Box 778
DOVER, DELAWARE 19903

SHANTÉ A. HASTINGS
SECRETARY

RAILROAD STATEMENT

For

State Contract No.: T202611302

Federal Aid No.: N/A

Project Title: US 301 Median Barrier, SR 896 to MD Line

The following railroad companies maintain facilities within the contract limits:


- | | |
|--|---|
| ☐ Amtrak | ☐ Maryland & Delaware |
| ☐ CSX | ☐ Norfolk Southern |
| ☐ State of Delaware
Delmarva Central | ☐ Wilmington & Western |
| ☐ East Penn | ☐ Delmarva Central |
| | ☒ None |

DOT Inventory No.: N/A No. Trains/Day: N/A Passenger Trains (Y / N): N/A

In accordance with 23 CFR 635, herein is the railroad statement of coordination (check one):

- ☒ No Railroad involvement.
- ☐ Railroad Agreement unnecessary but railroad flagging required. The contractor shall follow requirements stated in the DelDOT Maintenance of Railroad Traffic Item in the Special Provisions. Contractor shall coordinate railroad flagging with the DelDOT Railroad Coordinator at (302) 659-4087.
- ☐ Railroad Agreement required. The Contractor cannot begin work until the Agreement is complete and fully executed. Railroad related work to be undertaken and completed as required for proper coordination with physical construction schedules. The Contractor shall follow requirements stated in the DelDOT Maintenance of Railroad Traffic Item in the Special Provisions. Contractor shall coordinate railroad flagging with the DelDOT Railroad Coordinator at (302) 659-4087.

Approved As To Form:


DelDOT Railroad Coordinator

1/8/2026

DATE

SAMPLE AFFIDAVIT OF CRAFT TRAINING COMPLIANCE

(Actual form for signature will be provided to the awarded contractor)

(PROJECT NAME)
(CONTRACT NUMBER)

AFFIDAVIT OF CRAFT TRAINING COMPLIANCE

We, the contractor, hereby certify that we and all applicable subcontractors will abide by the contractor and subcontractor craft training requirements outlined below for the duration of the contract. Craft training must be provided by a contractor and/or subcontractor for each craft on a project for which there are Delaware Department of Labor approved and registered training programs or, if the contractor and/or subcontractor meets the requirements under Title 29, Chapter 69, Section 6960A.(b)(1)c.1.-3., payment may be made in accordance with Title 29, Chapter 69, Section 6960A.(b)(1)d. A list of crafts for which there are approved and registered training programs is maintained by the Delaware Department of Labor and can be found at:

<https://laborfiles.delaware.gov/main/det/apprenticeship/DE%20Craft%20Training%20Occupation%20List%20Effective%20March%20201%202022.pdf>. If you have questions regarding craft training programs, please submit all questions in writing to the Delaware Department of Labor at: apprenticeship@delaware.gov. *This Affidavit of Craft Training Compliance must be submitted prior to contract execution.*

In accordance with Title 29, Chapter 69, Section 6960A.(a)(1), a contract relating to a public works project under § 6962 of Title 29 must include a craft training program for each craft in the project if at the time the contractor executes a public works contract, all of the following apply:

- A project meets the prevailing wage requirement under Section 6960 of Title 29.
- The contractor employs 10 or more total employees.
- The project is not a federal highway project, except for the project under Section 6962(c)(11) of Title 29.
- There is an apprenticeship program for a craft in the project on the list of crafts under Section 204(b)(2) of Title 19.

Pursuant to Title 29, Chapter 69, Section 6960A.(a)(2), *a contractor must commit that all subcontractors provide craft training* if paragraph (a)(1) of this section applies to the subcontractor. Failure to provide required craft training or payment on the project may subject the successful contractor and/or subcontractor(s) to penalties as outlined in Title 29, Chapter 69, Section 6960A.(d)(1)-(3).

Craft(s):

Contractor Name:

Contractor Address:

Contractor Program

Registration Number(s)

On this line also indicate whether DE, Other State (identify) or US Registration Number

Or

☐ A payment has been made in the amount established under Section 204(b)(2)b.2. of Title 19, for the craft into the Delaware Department of Labor's Apprenticeship and Training Fund.

Or

☐ Craft Training requirements are not applicable because:

Authorized Representative (typed or printed): _____

Authorized Representative (signature): _____

Title: _____

State of Delaware)
County of _____) ss:

Before me, a notary public, in and for said county and state, personally appeared, _____, who acknowledged to me that she/he did execute the foregoing instrument on behalf of _____.

IN TESTIMONY WHEREOF, I have subscribed my name and affixed my official seal this _____ day of _____, 20____.

Notary Public
Commission Expires _____

THIS PAGE MUST BE SIGNED AND NOTARIZED TO BE CONSIDERED.



**Delaware Department of Transportation
Quantity Sheet Summary**

Proposal ID: T202611302

Project Descripton: US 301 Median Barrier, SR 896 to MD Line

NOT TO BE USED FOR BIDDING

Item Number	Description	Unit	Quantity
302003	DELAWARE NO. 8 STONE	TON	3469
401575	PERVIOUS ASPHALT PAVEMENT - 19.0mm TYPE B	TON	2066
720023	GALVANIZED STEEL BEAM GUARDRAIL, TYPE 3-31	LF	1685
721004	GUARDRAIL END TREATMENT, TYPE 3-31	EACH	2
722001	HIGH TENSION CABLE BARRIER	LF	31704
722002	HIGH TENSION CABLE BARRIER END TERMINAL	EACH	22
762000	SAW CUTTING, BITUMINOUS CONCRETE	LF	7
763000	INITIAL EXPENSE/DE-MOBILIZATION	LS	1
763501	CONSTRUCTION ENGINEERING	LS	1
801000	MAINTENANCE OF TRAFFIC	LS	1
802003	ARROW PANELS TYPE C	EADY	173
803001	PROVIDE AND MAINTAIN PORTABLE CHANGEABLE MESSAGE SIGN	EADY	60
804001	PROVIDE AND MAINTAIN PORTABLE LIGHT ASSEMBLY (FLOOD LIGHTS)	EADY	35
805001	PLASTIC TRAFFIC CONTROL DRUMS	EADY	12050
808002	PROVIDE AND MAINTAIN TRUCK MOUNTED ATTENUATOR, TYPE II	EADY	173
810001	TEMPORARY WARNING SIGNS AND PLAQUES	EADY	8058
819003	INSTALL OR REMOVE TRAFFIC SIGNS	EACH	6

This page is for information only. Do not use this page to submit a Bid.



**Delaware Department of Transportation
Quantity Sheet Summary**

Proposal ID: T202611302

Project Description: US 301 Median Barrier, SR 896 to MD Line

NOT TO BE USED FOR BIDDING

Item Number	Description	Unit	Quantity
819111	GALVANIZED TELESCOPING STEEL SIGN POSTS, 12' X 2", COMPLETE W/ BASEPOSTS AND HARDWARE	EACH	5
905004	INLET SEDIMENT CONTROL, DRAINAGE INLET	EACH	98
908004	TOPSOIL, 6" DEPTH	SY	16236
908010	TOPSOILING, 6" DEPTH	SY	64942
908014	PERMANENT GRASS SEEDING, DRY GROUND	SY	81178
201000	CLEARING AND GRUBBING	LS	1
202000	EXCAVATION AND EMBANKMENT	CY	3715
204000	TEST HOLE	CY	56
211002	REMOVAL OF GUARDRAIL AND FENCE	LF	150
806500	TRAFFIC OFFICERS	HOURL	221